



Instrumentos y Equipos C.A

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
 Caracas, Venezuela 1080
 Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
 Fax: 58-212-977.3613
 E-mail: sales@intech-ie.com
 RIF J-30615033-1

Quote # C-2024-0171, rev 1
Date: 19/07/24
Customer ID CHEVRON PETROPIAR

Bill to:
CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela Att: Maria Teresa Andres - Departamento de Procura MariaTeresa.Andres@chevron.com

Ship to:
CHEVRON PETROPIAR Warehouse Jose Complex, Edo Anzoategui, Venezuela

Sales Rep.	Your #	Our #	Destiny	Terms	Validity
L. Zuniga	VEN-RFX-PP-ISA24-68-053	IBI-2024-0171 / 15761-2/SQIO00020_2	Venezuela	DDP Jose complex	30 days

Item	Cant	Description	Unit Price US\$	Total US\$
1	3	BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications AREA: CRUDO Part Number 3809GAB08CFB3H4CDCO Tag-001 10-FI-941 Tag-002 10-FI-942 Tag-003 10-FI-943 Max Press @ Max Temp 148 PSIG 10.2 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size OVERSIZED 3/4-in Connection Type 150# RF Flange Inlet Down Outlet Up O-Ring Material No Valve On Outlet-Teflon-Sent Detached Valve Connection Visible Thd Flg Range 6900 - 49000 SCFD Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless Part Number International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1 Certificate off Origin	\$14,060.00	\$42,180.00

2	2	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications AREA: CRUDO</p> <p>Part Number 3809GAA10BFBB3H4CDC0 Tag-001 57-FI-016 Tag-002 57-FI-036 Max Press @ Max Temp 148 PSIG 10.2 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size 1-inch Connection Type 150# RF Flange Inlet Down Outlet Up O-Ring Material No Valve On Outlet-Teflon-Sent Detached Valve Connection Visible Thd Flg Range 14000 - 120000 SCFD Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1 Certificate of Origin</p>	\$14,220.00	\$28,440.00
3	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications AREA: HIDROPROCESOS</p> <p>Part Number 3809GAB08CGBB3H4CDC0 Tag-001 15-FI-783 Max Press @ Max Temp 458 PSIG 31.6 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size OVERSIZED 3/4-in Connection Type 300# RF Flange Inlet Down Outlet Up O-Ring Material No Valve On Outlet-Teflon-Sent Detached Valve Connection Visible Thd Flg Range 5800 - 41000 SCFD Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1</p>	\$15,240.00	\$15,240.00

		Certificate of Origin		
4	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications AREA: COKER</p> <p>Part Number 3809GAB13DGBB3H4C0C0 Tag-001 12-FI-425 Max Press @ Max Temp 458 PSIG 31.6 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size OVERSIZED 3-inch Connection Type 300# RF Flange Inlet Down Outlet Up O-Ring Material No Valve No Valve Range 74000 - 740000 SCFD Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1 Certificate of Origin</p>	\$17,900.00	\$17,900.00
5	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications AREA: COKER</p> <p>Part Number 3809GAA10DGCB3H4CBC0 Tag-001 12-FI-653 Max Press @ Max Temp 458 PSIG 31.6 BAR Accuracy 2% -Direct Scale-VISC Meter Material 316L SS Connection Size 1-inch Connection Type 300# RF Flange Inlet Down Outlet Up O-Ring Material No Valve On Inlet-Teflon-Sent Detached Valve Connection Visible Thd Flg Range 1.6 - 14 GPM Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1</p>	\$16,110.00	\$16,110.00

		Certificate of Origin		
6	2	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications AREA: COKER</p> <p>Part Number 3809GAA10DGAB3H4CBC0 Tag-001 12-FI-994 Tag-002 12-FI-995 Max Press @ Max Temp 458 PSIG 31.6 BAR Accuracy 2% -Direct Scale-Liquid Meter Material 316L SS Connection Size 1-inch Connection Type 300# RF Flange Inlet Down Outlet Up O-Ring Material No Valve On Inlet-Teflon-Sent Detached Valve Connection Visible Thd Flg Range 1.8 - 15 GPM Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1 Certificate of Origin</p>	\$15,000.00	\$30,000.00
7	3	<p>Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications AREA: COKER</p> <p>Part Number 3809GAA12BGAB3H4CBC0 Tag-001 12-FI-650A Tag-002 12-FI-650B Tag-003 12-FI-197 Max Press @ Max Temp 458 PSIG 31.6 BAR Accuracy 2% -Direct Scale-Liquid Meter Material 316L SS Connection Size 1.5-inch Connection Type 300# RF Flange Inlet Down Outlet Up O-Ring Material No Valve On Inlet-Teflon-Sent Detached Valve Connection Visible Thd Flg Range 2.6 - 26 GPM Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p>	14,150.00	42,450.00

		<p>Certification (1) [C] NACE & Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>		
8	5	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p> <p>AREA: HIDROPROCESOS</p> <p>Part Number 3809GBB08CGBB3H4CDC0</p> <p>Tag-001 15-FI-961</p> <p>Tag-002 15-FI-963</p> <p>Tag-003 15-FI-931</p> <p>Tag-004 15-FI-932</p> <p>Tag-005 15-FI-964</p> <p>Max Press @ Max Temp 458 PSIG 31.6 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS w/ Cert 3.1</p> <p>Connection Size OVERSIZED 3/4-in</p> <p>Connection Type 300# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve On Outlet-Teflon-Sent Detached</p> <p>Valve Connection Visible Thd Flg</p> <p>Range 6100 - 43000 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE & Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>	\$15,180.00	\$75,900.00
9	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p> <p>AREA: HIDROPROCESOS</p> <p>Part Number 3809GAB08CGBB3H4CDC0</p> <p>Tag-001 15-FI-783</p> <p>Max Press @ Max Temp 458 PSIG 31.6 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS</p> <p>Connection Size OVERSIZED 3/4-in</p> <p>Connection Type 300# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve On Outlet-Teflon-Sent Detached</p> <p>Valve Connection Visible Thd Flg</p>	\$15,240.00	\$15,240.00

		<p>Range 5800 - 41000 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE & Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>		
10	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p> <p>AREA: AZUFRE</p> <p>Part Number 3809GAA12CFAB3H4C0C0</p> <p>Tag-001 24-FI-002</p> <p>Max Press @ Max Temp 148 PSIG 10.2 BAR</p> <p>Accuracy 2% -Direct Scale-Liquid</p> <p>Meter Material 316L SS</p> <p>Connection Size 1.5-inch</p> <p>Connection Type 150# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve No Valve</p> <p>Range 3.5 - 35 GPM</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE & Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>	\$14,150.00	\$14,150.00
11	2	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p> <p>AREA: AZUFRE</p> <p>Part Number 3809GAB12CFAB3H4C0C0</p> <p>Tag-001 24-FI-025</p> <p>Tag-002 24-FI-145</p> <p>Max Press @ Max Temp 148 PSIG 10.2 BAR</p> <p>Accuracy 2% -Direct Scale-Liquid</p> <p>Meter Material 316L SS</p> <p>Connection Size OVERSIZED 2-inch</p> <p>Connection Type 150# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve No Valve</p>	\$14,710.00	\$29,420.00

		<p>Range 3.5 - 35 GPM Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20ma – HART, LOI DIGITAL DISPLAY Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1 Certificate of Origin</p>		
12	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications AREA: AZUFRE</p> <p>Part Number 3809GAA08BGBB3H4CBC0 Tag-001 26-FI-001 Max Press @ Max Temp 458 PSIG 31.6 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size 1/2-inch Connection Type 300# RF Flange Inlet Down Outlet Up O-Ring Material No Valve On Inlet-Teflon-Sent Detached Valve Connection Visible Thd Flg Range 1700 - 17000 SCFD Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1 Certificate of Origin</p>	\$14,460.00	\$14,460.00
13	3	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications AREA: AZUFRE</p> <p>Part Number 3809GAD07BABB3H4CCCO Tag-001 28-FI-084 Tag-002 28-FI-087 Tag-003 28-FI-088 Max Press @ Max Temp 1500 PSIG 103.4 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size 1/2-inch Connection Type F-NPT Inlet Down Outlet Up</p>	\$12,320.00	\$36,960.00

		<p>O-Ring Material Viton Valve On Outlet-Viton-Ship Attached Valve Connection Visible Thd FNPT Range 480 - 4800 SCFD Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1 Certificate of Origin</p>		
14	2	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of liquid and steam applications AREA: AZUFRE</p> <p>Part Number 3809GAD07BABB3H4CCCO Tag-001 28-FI-540 Tag-002 28-FI-740 Max Press @ Max Temp 1500 PSIG 103.4 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size 1/2-inch Connection Type F-NPT Inlet Down Outlet Up O-Ring Material Viton Valve On Outlet-Viton-Ship Attached Valve Connection Visible Thd FNPT Range 500 - 5000 SCFD Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1 Certificate of Origin</p>	\$12,320.00	\$24,640.00
15	2	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications AREA: AZUFRE</p> <p>Part Number 3809GAD07BABB3H4CCCO Tag-003 28-FI-545 Tag-005 28-FI-745 Max Press @ Max Temp 1500 PSIG 103.4 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size 1/2-inch</p>	\$12,320.00	\$24,640.00

		<p>Connection Type F-NPT Inlet Down Outlet Up O-Ring Material Viton Valve On Outlet-Viton-Ship Attached Valve Connection Visible Thd FNPT Range 490 - 4900 SCFD Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1</p>		
16	6	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications AREA: AZUFRE</p> <p>Part Number 3809GAD07BABB3H4CCCO Tag-001 30-FI-027 Tag-002 30-FI-028 Tag-003 30-FI-030 Tag-004 30-FI-032 Tag-005 28-FI-546 Tag-006 28-FI-746 Max Press @ Max Temp 1500 PSIG 103.4 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size 1/2-inch Connection Type F-NPT Inlet Down Outlet Up O-Ring Material Viton Valve On Outlet-Viton-Ship Attached Valve Connection Visible Thd FNPT Range 490 - 4900 SCFD Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1 Certificate of Origin</p>	\$12,210.00	\$73,260.00
17	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications AREA: AZUFRE</p> <p>Part Number 3809GAA12CFBB3H4C0C0</p>	\$13,040.00	\$39,120.00

		<p>Tag-001 28-FI-866</p> <p>Max Press @ Max Temp 148 PSIG 10.2 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS</p> <p>Connection Size 1.5-inch</p> <p>Connection Type 150# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve No Valve</p> <p>Range 19000 - 190000 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE & Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>		
18	3	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p> <p>AREA: AZUFRE</p> <p>Part Number 3809GAB08BGBB3H4CDC0</p> <p>Tag-001 28-FI-942</p> <p>Tag-002 28-FI-945</p> <p>Tag-003 28-FI-946</p> <p>Max Press @ Max Temp 458 PSIG 31.6 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS</p> <p>Connection Size OVERSIZED 3/4-in</p> <p>Connection Type 300# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve On Outlet-Teflon-Sent Detached</p> <p>Valve Connection Visible Thd Flg</p> <p>Range 3000 - 30000 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE & Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>	\$15,250.00	\$45,750.00
19	2	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p>	\$13,040.00	\$26,080.00

		<p>AREA: AZUFRE</p> <p>Part Number 3809GAB10DFBB3H4COCO</p> <p>Tag-001 30-FI-040</p> <p>Tag-002 30-FI-041</p> <p>Max Press @ Max Temp 148 PSIG 10.2 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS</p> <p>Connection Size OVERSIZED 1.5-inch</p> <p>Connection Type 150# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve No Valve</p> <p>Range 12000 - 100000 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE & Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>		
20	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p> <p>AREA: AZUFRE</p> <p>Part Number 3809GAC08AGBB3H4CDCO</p> <p>Tag-001 30-FI-066</p> <p>Max Press @ Max Temp 458 PSIG 31.6 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS</p> <p>Connection Size OVERSIZED 1-inch</p> <p>Connection Type 300# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve On Outlet-Teflon-Sent Detached</p> <p>Valve Connection Visible Thd Flg</p> <p>Range 4500 - 37000 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE & Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>	\$15,250.00	\$15,250.00

		<p>Technical Notes - BROOKS Products:</p> <ul style="list-style-type: none"> • The end user must check the Actual Process Conditions for checking dimensioning and Flow range of each Rotameter before start production • All armored Rotameters comes with Transmitter with HART Capability and Dual Digital Local Display • All Transmitters are Explosion Proof 												
		<p>Delivery Time 8 - 10 Weeks ARO and Advance Payment done</p> <p>Payment Terms</p> <ul style="list-style-type: none"> • 50% with Order (Net 30 days) – Requirements for Advance Payments <ul style="list-style-type: none"> ○ BROOKS: Dimensioning per items must be revised and accepted by end users (Flow Ranges, Certificates required, etc) for start Production • 50% Net 30 days delivery time <p>Packing Material will be Securely packed in wooden crates suitable for air freight and export.</p> <p>Volume & Weight (to be reconfirmed) To be advised – Aprox 6000 Lbs</p> <p>General Warranty: WIKA and BROOKS warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p>Project Cancellation charges:</p> <table> <tr> <td>15%</td> <td>Up to submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> <tr> <td>75%</td> <td>Within two weeks of production release</td> </tr> <tr> <td>100%</td> <td>Two weeks after production commences</td> </tr> </table>	15%	Up to submittal of Engineering & Design Drawings and Documents	25%	After submittal of Engineering & Design Drawings and Documents	50%	After material order placement and before production commences	75%	Within two weeks of production release	100%	Two weeks after production commences		
15%	Up to submittal of Engineering & Design Drawings and Documents													
25%	After submittal of Engineering & Design Drawings and Documents													
50%	After material order placement and before production commences													
75%	Within two weeks of production release													
100%	Two weeks after production commences													
		NOTAS:												
		<p>CONDICIONES DE PAGO</p> <p><u>COMPONENTE IMPORTADO</u></p> <p>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</p> <p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134</p>												

	<p>CUENTA NUMERO 8303790106 BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A. ABA 067010509 SWIFT MNBMUS33</p> <p><u>COMPONENTE NACIONAL (IVA)</u></p> <p>En BOLIVARES (Bs.) mediante transferencia bancaria</p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. – 0105-0011-73-1011-50499-5</p>		
	<p>OTRAS CONDICIONES</p> <p>1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos</p> <p>2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y deberá ser cancelado a la tasa oficial del día de pago o de la retención correspondiente</p> <p>3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.</p> <p>4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrará garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente</p> <p>5. Aporte SOCIAL 3%: Esta Incluido en los precios y forma parte de la Oferta</p> <p>6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22.</p> <p>7. En caso de requerirse algún Tipo de Fianza de Anticipo, los Gastos de dicha Fianza serán reembolsables (en la moneda de su contratación) y por cuenta del Cliente CHEVRON, una vez recibidos los materiales en su almacén.</p> <p>Cci: W. Brito – INTECH PLCRZ</p>		

Please Transfer to Account of:
Bank: Amerant Bank
Address: 220 Alhambra Circle, Coral Gables,
Florida 33134, USA
ABA: 067010509
Swift: MNBMUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS
C.A.
Account # 8303790106

Subtotal	US\$	601,110.00
Freight	US\$	Incluido
Insurance	US\$	--
IVA 16%	US\$	96,177.60
IGTF 3%	US\$	---
TOTAL	US\$	697,287.60