



### Instrumentos y Equipos C.A

#### INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,  
 Caracas, Venezuela 1080  
 Tel: 58-212-9784430, 9784433, 977.7654, 977.6346  
 Fax: 58-212-977.3613  
 E-mail: [sales@intech-ie.com](mailto:sales@intech-ie.com)  
 RIF J-30615033-1

**Quote #** C-2024-0171  
**Date:** 28/05/24  
**Customer ID** CHEVRON PETROPIAR

Bill to:
<b>CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY</b> Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela Att: Maria Teresa Andres - Departamento de Procura <a href="mailto:MariaTeresa.Andres@chevron.com">MariaTeresa.Andres@chevron.com</a>

Ship to:
<b>CHEVRON PETROPIAR Warehouse</b> Jose Complex, Edo Anzoategui, Venezuela

Sales Rep.	Your #	Our #	Destiny	Terms	Validity
L. Zuniga	VEN-RFX-PP-ISA24-68-053	IBI-2024-0171 / 15761-2/SQIO00020_2	Venezuela	DDP Jose complex	30 days

Item	Cant	Description	Unit Price US\$	Total US\$
1	3	BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications <b>AREA: CRUDO</b>  Part Number <b>3809GAB08CFBB3H4CDC0</b> Tag-001 <b>10-FI-941</b> Tag-002 <b>10-FI-942</b> Tag-003 <b>10-FI-943</b> Max Press @ Max Temp 148 PSIG 10.2 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size OVERSIZED 3/4-in Connection Type 150# RF Flange Inlet Down Outlet Up O-Ring Material No Valve On Outlet-Teflon-Sent Detached Valve Connection Visible Thd Flg Range 6900 - 49000 SCFD Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless Part Number International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1 Certificate off Origin	\$14,060.00	\$42,180.00

2	2	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications <b>AREA: CRUDO</b></p> <p>Part Number <b>3809GAA10BFBB3H4CDC0</b>            Tag-001 <b>57-FI-016</b>            Tag-002 <b>57-FI-036</b>            Max Press @ Max Temp 148 PSIG 10.2 BAR            Accuracy 2% -Direct Scale-Gas            Meter Material 316L SS            Connection Size 1-inch            Connection Type 150# RF Flange            Inlet Down            Outlet Up            O-Ring Material No            Valve On Outlet-Teflon-Sent Detached            Valve Connection Visible Thd Flg            Range 14000 - 120000 SCFD            Indicator Housing XP STAINLESS            Electrical Connection 3/4-in NPT-F            Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART            Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA            Certification (1) [C] NACE &amp; Mat Cert 3.1            TAG Type Stainless            International Calibration Certificate (ICC)            Certificate of Conformance (Compliance) 2.1            Certificate of Origin</p>	\$14,220.00	\$28,440.00
3	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications <b>AREA: HIDROPROCESOS</b></p> <p>Part Number <b>3809GAB08CGBB3H4CDC0</b>            Tag-001 <b>15-FI-783</b>            Max Press @ Max Temp 458 PSIG 31.6 BAR            Accuracy 2% -Direct Scale-Gas            Meter Material 316L SS            Connection Size OVERSIZED 3/4-in            Connection Type 300# RF Flange            Inlet Down            Outlet Up            O-Ring Material No            Valve On Outlet-Teflon-Sent Detached            Valve Connection Visible Thd Flg            Range 5800 - 41000 SCFD            Indicator Housing XP STAINLESS            Electrical Connection 3/4-in NPT-F            Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART            Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA            Certification (1) [C] NACE &amp; Mat Cert 3.1            TAG Type Stainless            International Calibration Certificate (ICC)            Certificate of Conformance (Compliance) 2.1</p>	\$15,240.00	\$15,240.00

		Certificate of Origin		
4	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications <b>AREA: COKER</b></p> <p>Part Number <b>3809GAB13DGBB3H4C0C0</b>            Tag-001 <b>12-FI-425</b>            Max Press @ Max Temp 458 PSIG 31.6 BAR            Accuracy 2% -Direct Scale-Gas            Meter Material 316L SS            Connection Size OVERSIZED 3-inch            Connection Type 300# RF Flange            Inlet Down            Outlet Up            O-Ring Material No            Valve No Valve            Range 74000 - 740000 SCFD            Indicator Housing XP STAINLESS            Electrical Connection 3/4-in NPT-F            Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART            Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA            Certification (1) [C] NACE &amp; Mat Cert 3.1            TAG Type Stainless            International Calibration Certificate (ICC)            Certificate of Conformance (Compliance) 2.1            Certificate of Origin</p>	\$17,900.00	\$17,900.00
5	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications <b>AREA: COKER</b></p> <p>Part Number <b>3809GAA10DGCB3H4CBC0</b>            Tag-001 <b>12-FI-653</b>            Max Press @ Max Temp 458 PSIG 31.6 BAR            Accuracy 2% -Direct Scale-VISC            Meter Material 316L SS            Connection Size 1-inch            Connection Type 300# RF Flange            Inlet Down            Outlet Up            O-Ring Material No            Valve On Inlet-Teflon-Sent Detached            Valve Connection Visible Thd Flg            Range 1.6 - 14 GPM            Indicator Housing XP STAINLESS            Electrical Connection 3/4-in NPT-F            Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART            Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA            Certification (1) [C] NACE &amp; Mat Cert 3.1            TAG Type Stainless            International Calibration Certificate (ICC)            Certificate of Conformance (Compliance) 2.1</p>	\$16,110.00	\$16,110.00

		Certificate of Origin		
6	2	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications <b>AREA: COKER</b></p> <p>Part Number <b>3809GAA10DGAB3H4CBC0</b>            Tag-001 <b>12-FI-994</b>            Tag-002 <b>12-FI-995</b>            Max Press @ Max Temp 458 PSIG 31.6 BAR            Accuracy 2% -Direct Scale-Liquid            Meter Material 316L SS            Connection Size 1-inch            Connection Type 300# RF Flange            Inlet Down            Outlet Up            O-Ring Material No            Valve On Inlet-Teflon-Sent Detached            Valve Connection Visible Thd Flg            Range 1.8 - 15 GPM            Indicator Housing XP STAINLESS            Electrical Connection 3/4-in NPT-F            Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI            APPROVALS: DIV 1-ZONE 1 XP-IIC-IECEX-CSA            Certification (1) [C] NACE &amp; Mat Cert 3.1            TAG Type Stainless            International Calibration Certificate (ICC)            Certificate of Conformance (Compliance) 2.1            Certificate of Origin</p>	\$15,000.00	\$30,000.00
7	3	<p>Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications <b>AREA: COKER</b></p> <p>Part Number <b>3809GAA12BGAB3H4CBC0</b>            Tag-001 <b>12-FI-650A</b>            Tag-002 <b>12-FI-650B</b>            Tag-003 <b>12-FI-197</b>            Max Press @ Max Temp 458 PSIG 31.6 BAR            Accuracy 2% -Direct Scale-Liquid            Meter Material 316L SS            Connection Size 1.5-inch            Connection Type 300# RF Flange            Inlet Down            Outlet Up            O-Ring Material No            Valve On Inlet-Teflon-Sent Detached            Valve Connection Visible Thd Flg            Range 2.6 - 26 GPM            Indicator Housing XP STAINLESS            Electrical Connection 3/4-in NPT-F            Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL            APPROVALS: DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p>	14,150.00	42,450.00

		<p>Certification (1) [C] NACE &amp; Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>		
8	5	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p> <p><b>AREA: HIDROPROCESOS</b></p> <p>Part Number <b>3809GBB08CGBB3H4CDC0</b></p> <p>Tag-001 <b>15-FI-961</b></p> <p>Tag-002 <b>15-FI-963</b></p> <p>Tag-003 <b>15-FI-931</b></p> <p>Tag-004 <b>15-FI-932</b></p> <p>Tag-005 <b>15-FI-964</b></p> <p>Max Press @ Max Temp 458 PSIG 31.6 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS w/ Cert 3.1</p> <p>Connection Size OVERSIZED 3/4-in</p> <p>Connection Type 300# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve On Outlet-Teflon-Sent Detached</p> <p>Valve Connection Visible Thd Flg</p> <p>Range 6100 - 43000 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE &amp; Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>	\$15,180.00	\$75,900.00
9	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p> <p><b>AREA: HIDROPROCESOS</b></p> <p>Part Number <b>3809GAB08CGBB3H4CDC0</b></p> <p>Tag-001 <b>15-FI-783</b></p> <p>Max Press @ Max Temp 458 PSIG 31.6 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS</p> <p>Connection Size OVERSIZED 3/4-in</p> <p>Connection Type 300# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve On Outlet-Teflon-Sent Detached</p> <p>Valve Connection Visible Thd Flg</p>	\$15,240.00	\$15,240.00

		<p>Range 5800 - 41000 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE &amp; Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>		
10	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p> <p><b>AREA: AZUFRE</b></p> <p>Part Number <b>3809GAA12CFAB3H4C0C0</b></p> <p>Tag-001 <b>24-FI-002</b></p> <p>Max Press @ Max Temp 148 PSIG 10.2 BAR</p> <p>Accuracy 2% -Direct Scale-Liquid</p> <p>Meter Material 316L SS</p> <p>Connection Size 1.5-inch</p> <p>Connection Type 150# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve No Valve</p> <p>Range 3.5 - 35 GPM</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE &amp; Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>	\$14,150.00	\$14,150.00
11	2	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p> <p><b>AREA: AZUFRE</b></p> <p>Part Number <b>3809GAB12CFAB3H4C0C0</b></p> <p>Tag-001 <b>24-FI-025</b></p> <p>Tag-002 <b>24-FI-145</b></p> <p>Max Press @ Max Temp 148 PSIG 10.2 BAR</p> <p>Accuracy 2% -Direct Scale-Liquid</p> <p>Meter Material 316L SS</p> <p>Connection Size OVERSIZED 2-inch</p> <p>Connection Type 150# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve No Valve</p>	\$14,710.00	\$29,420.00

		<p>Range 3.5 - 35 GPM  Indicator Housing XP STAINLESS  Electrical Connection 3/4-in NPT-F  Indicator/Alarm/Transmit XMTR 4-20ma – HART, LOI DIGITAL DISPLAY  Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA  Certification (1) [C] NACE &amp; Mat Cert 3.1  TAG Type Stainless  International Calibration Certificate (ICC)  Certificate of Conformance (Compliance) 2.1  Certificate of Origin</p>		
12	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications  <b>AREA: AZUFRE</b></p> <p>Part Number <b>3809GAA08BGBB3H4CBC0</b>  Tag-001 <b>26-FI-001</b>  Max Press @ Max Temp 458 PSIG 31.6 BAR  Accuracy 2% -Direct Scale-Gas  Meter Material 316L SS  Connection Size 1/2-inch  Connection Type 300# RF Flange  Inlet Down  Outlet Up  O-Ring Material No  Valve On Inlet-Teflon-Sent Detached  Valve Connection Visible Thd Flg  Range 1700 - 17000 SCFD  Indicator Housing XP STAINLESS  Electrical Connection 3/4-in NPT-F  Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY  HART  Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA  Certification (1) [C] NACE &amp; Mat Cert 3.1  TAG Type Stainless  International Calibration Certificate (ICC)  Certificate of Conformance (Compliance) 2.1  Certificate of Origin</p>	\$14,460.00	\$14,460.00
13	3	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications  <b>AREA: AZUFRE</b></p> <p>Part Number <b>3809GAD07BABB3H4CCCO</b>  Tag-001 <b>28-FI-084</b>  Tag-002 <b>28-FI-087</b>  Tag-003 <b>28-FI-088</b>  Max Press @ Max Temp 1500 PSIG 103.4 BAR  Accuracy 2% -Direct Scale-Gas  Meter Material 316L SS  Connection Size 1/2-inch  Connection Type F-NPT  Inlet Down  Outlet Up</p>	\$12,320.00	\$36,960.00

		<p>O-Ring Material Viton</p> <p>Valve On Outlet-Viton-Ship Attached</p> <p>Valve Connection Visible Thd FNPT</p> <p>Range 480 - 4800 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE &amp; Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>		
14	2	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of liquid and steam applications</p> <p><b>AREA: AZUFRE</b></p> <p>Part Number <b>3809GAD07BABB3H4CCCO</b></p> <p>Tag-001 <b>28-FI-540</b></p> <p>Tag-002 <b>28-FI-740</b></p> <p>Max Press @ Max Temp 1500 PSIG 103.4 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS</p> <p>Connection Size 1/2-inch</p> <p>Connection Type F-NPT</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material Viton</p> <p>Valve On Outlet-Viton-Ship Attached</p> <p>Valve Connection Visible Thd FNPT</p> <p>Range 500 - 5000 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE &amp; Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>	\$12,320.00	\$24,640.00
15	2	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p> <p><b>AREA: AZUFRE</b></p> <p>Part Number <b>3809GAD07BABB3H4CCCO</b></p> <p>Tag-003 <b>28-FI-545</b></p> <p>Tag-005 <b>28-FI-745</b></p> <p>Max Press @ Max Temp 1500 PSIG 103.4 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS</p> <p>Connection Size 1/2-inch</p>	\$12,320.00	\$24,640.00

		<p>Connection Type F-NPT Inlet Down Outlet Up O-Ring Material Viton Valve On Outlet-Viton-Ship Attached Valve Connection Visible Thd FNPT Range 490 - 4900 SCFD Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE &amp; Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1</p>		
16	6	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications <b>AREA: AZUFRE</b></p> <p>Part Number <b>3809GAD07BABB3H4CCCO</b> Tag-001 <b>30-FI-027</b> Tag-002 <b>30-FI-028</b> Tag-003 <b>30-FI-030</b> Tag-004 <b>30-FI-032</b> Tag-005 <b>28-FI-546</b> Tag-006 <b>28-FI-746</b> Max Press @ Max Temp 1500 PSIG 103.4 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size 1/2-inch Connection Type F-NPT Inlet Down Outlet Up O-Ring Material Viton Valve On Outlet-Viton-Ship Attached Valve Connection Visible Thd FNPT Range 490 - 4900 SCFD Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE &amp; Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1 Certificate of Origin</p>	\$12,210.00	\$73,260.00
17	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications <b>AREA: AZUFRE</b></p> <p>Part Number <b>3809GAA12CFBB3H4C0C0</b></p>	\$13,040.00	\$39,120.00

		<p>Tag-001 <b>28-FI-866</b></p> <p>Max Press @ Max Temp 148 PSIG 10.2 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS</p> <p>Connection Size 1.5-inch</p> <p>Connection Type 150# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve No Valve</p> <p>Range 19000 - 190000 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE &amp; Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>		
18	3	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p> <p><b>AREA: AZUFRE</b></p> <p>Part Number <b>3809GAB08BGBB3H4CDC0</b></p> <p>Tag-001 <b>28-FI-942</b></p> <p>Tag-002 <b>28-FI-945</b></p> <p>Tag-003 <b>28-FI-946</b></p> <p>Max Press @ Max Temp 458 PSIG 31.6 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS</p> <p>Connection Size OVERSIZED 3/4-in</p> <p>Connection Type 300# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve On Outlet-Teflon-Sent Detached</p> <p>Valve Connection Visible Thd Flg</p> <p>Range 3000 - 30000 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE &amp; Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>	\$15,250.00	\$45,750.00
19	2	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p>	\$13,040.00	\$26,080.00

		<p><b>AREA: AZUFRE</b></p> <p>Part Number <b>3809GAB10DFBB3H4COCO</b></p> <p>Tag-001 <b>30-FI-040</b></p> <p>Tag-002 <b>30-FI-041</b></p> <p>Max Press @ Max Temp 148 PSIG 10.2 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS</p> <p>Connection Size OVERSIZED 1.5-inch</p> <p>Connection Type 150# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve No Valve</p> <p>Range 12000 - 100000 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE &amp; Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>		
20	1	<p>BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications</p> <p><b>AREA: AZUFRE</b></p> <p>Part Number <b>3809GAC08AGBB3H4CDC0</b></p> <p>Tag-001 <b>30-FI-066</b></p> <p>Max Press @ Max Temp 458 PSIG 31.6 BAR</p> <p>Accuracy 2% -Direct Scale-Gas</p> <p>Meter Material 316L SS</p> <p>Connection Size OVERSIZED 1-inch</p> <p>Connection Type 300# RF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material No</p> <p>Valve On Outlet-Teflon-Sent Detached</p> <p>Valve Connection Visible Thd Flg</p> <p>Range 4500 - 37000 SCFD</p> <p>Indicator Housing XP STAINLESS</p> <p>Electrical Connection 3/4-in NPT-F</p> <p>Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART</p> <p>Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA</p> <p>Certification (1) [C] NACE &amp; Mat Cert 3.1</p> <p>TAG Type Stainless</p> <p>International Calibration Certificate (ICC)</p> <p>Certificate of Conformance (Compliance) 2.1</p> <p>Certificate of Origin</p>	\$15,250.00	\$15,250.00

		<p><b>Technical Notes - BROOKS Products:</b></p> <ul style="list-style-type: none"> <li>• The end user must check the Actual Process Conditions for checking dimensioning and Flow range of each Rotameter before start production</li> <li>• All armored Rotameters comes with Transmitter with HART Capability and Dual Digital Local Display</li> <li>• All Transmitters are Explosion Proof</li> </ul>												
		<p><b>Delivery Time</b> <b>8 - 10 Weeks ARO and Advance Payment done</b></p> <p><b>Payment Terms</b></p> <ul style="list-style-type: none"> <li>• <b>50% with Order (Net 30 days) – Requirements for Advance Payments</b> <ul style="list-style-type: none"> <li>○ BROOKS: Dimensioning per items must be revised and accepted by end users (Flow Ranges, Certificates required, etc) for start Production</li> </ul> </li> <li>• <b>50% Net 30 days delivery time</b></li> </ul> <p><b>Packing</b> Material will be Securely packed in wooden crates suitable for air freight and export.</p> <p><b>Volume &amp; Weight (to be reconfirmed)</b> <b>To be advised – Aprox 6000 Lbs</b></p> <p><b>General Warranty:</b> WIKA and BROOKS warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p><b>Project Cancellation charges:</b></p> <table> <tr> <td>15%</td> <td>Up to submittal of Engineering &amp; Design Drawings and Documents</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering &amp; Design Drawings and Documents</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> <tr> <td>75%</td> <td>Within two weeks of production release</td> </tr> <tr> <td>100%</td> <td>Two weeks after production commences</td> </tr> </table>	15%	Up to submittal of Engineering & Design Drawings and Documents	25%	After submittal of Engineering & Design Drawings and Documents	50%	After material order placement and before production commences	75%	Within two weeks of production release	100%	Two weeks after production commences		
15%	Up to submittal of Engineering & Design Drawings and Documents													
25%	After submittal of Engineering & Design Drawings and Documents													
50%	After material order placement and before production commences													
75%	Within two weeks of production release													
100%	Two weeks after production commences													
		<b>NOTAS:</b>												
		<p><b>CONDICIONES DE PAGO</b></p> <p><b><u>COMPONENTE IMPORTADO</u></b></p> <p><i>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</i></p> <p><i>AMERANT BANK (in US\$)</i> <i>220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134</i></p>												

	<p><b>CUENTA NUMERO 8303790106</b> <b>BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A.</b> ABA 067010509 SWIFT MNBMUS33</p> <p><b><u>COMPONENTE NACIONAL (IVA)</u></b></p> <p>En BOLIVARES (Bs.) mediante transferencia bancaria</p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. – <b>0105-0011-73-1011-50499-5</b></p>		
	<p><b>OTRAS CONDICIONES</b></p> <ol style="list-style-type: none"> <li>1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos</li> <li>2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web <a href="http://www.bcv.org.ve">www.bcv.org.ve</a> y deberá ser cancelado a la tasa oficial del día de pago o de la retención correspondiente</li> <li>3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.</li> <li>4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrará garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente</li> <li>5. Aporte SOCIAL 3%: Esta Incluido en los precios y forma parte de la Oferta</li> <li>6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22.</li> <li>7. En caso de requerirse algún Tipo de Fianza de Anticipo, los Gastos de dicha Fianza serán reembolsables (en la moneda de su contratación) y por cuenta del Cliente CHEVRON, una vez recibidos los materiales en su almacén.</li> </ol> <p>Cci: W. Brito – INTECH PLCRZ</p>		

Please Transfer to Account of:  
Bank: Amerant Bank  
Address: 220 Alhambra Circle, Coral Gables,  
Florida 33134, USA  
ABA: 067010509  
Swift: MNBMUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS  
C.A.  
Account # 8303790106

<b>Subtotal</b>	<b>US\$</b>	<b>601,110.00</b>
<b>Freight</b>	<b>US\$</b>	<b>Incluido</b>
<b>Insurance</b>	<b>US\$</b>	<b>--</b>
<b>IVA 16%</b>	<b>US\$</b>	<b>96,177.60</b>
<b>IGTF 3%</b>	<b>US\$</b>	<b>---</b>
<b>TOTAL</b>	<b>US\$</b>	<b>697,287.60</b>