



Instrumentos y Equipos C.A

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
 Caracas, Venezuela 1080
 Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
 Fax: 58-212-977.3613
 E-mail: sales@intech-ie.com
 RIF J-30615033-1

Quote # **C-2024-0169**
 Date: **28/05/2024**
 Customer ID **CHEVRON PETROPIAR**

Bill to:
CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela Att: Jorgelis Rincon - Depto de Procura Jorgelis.Rincon1@chevron.com

Ship to:
CHEVRON PETROPIAR Warehouse Jose Complex, Edo Anzoategui, Venezuela

Sales Rep.	Your #	Our #	Destiny	Terms	Validity
L. Zuniga N. Carricatti	VEN-RFQ-PP152-DENSITOMETRO & PROBADOR	C-2024-0169/PL	Venezuela	DDP Jose complex	30 days

Item	Cant	Description	Unit Price US\$	Total US\$
1	4	<p>API / DENSITY PROCESS ANALYZER MODEL L-DENS 7400 SST NPT EXd, ANTON PAAR Tag # 61-AIT-003</p> <p><u>NOTE: The Micro Motion sensor is a fork type sensor similar to our L-Dens that has a u-tube.</u></p> <p><u>A direct mechanical replacement of this instrument with the L-Dens won't be possible because of the different mechanical design. It means that there are anyhow modifications on the line required. Similar by-passed connection is offered and a remote display is included.</u></p> <p>Each system Includes:</p> <ul style="list-style-type: none"> L-Dens 7400 VERSION SST NPT Ex d <p>Highly accurate process sensor for density and concentration measurement. The compact design enables inline or bypass installation with minimal integration effort. The robust oscillating U-tube measuring principle has no moving parts and is maintenance-free, with low operating costs.</p> <p>Scope of delivery</p> <p>1 Pcs. Process density sensor L-Dens 7400 SST NPT Ex d 1 Pcs. Instruction Manual 1 Pcs. Adjustment Report 1 Pcs. Ex-Safety Instructions</p> <p>For hazardous areas</p> <p>- ATEX: Ex II 2G Ex db IIB T4/T5 Gb - IECEx: Ex db IIB T4/T5 Gb - cQPSus certified: Class I Division 1 Gr CD T4/T5 Ex db IIB T4/T5 Gb Class I Zone 1, AEx db IIB T4/T5 Gb</p>	\$25.330,00	\$101.320,00

	<p>Technical specifications</p> <ul style="list-style-type: none"> - Process density: max. 3000 kg/m³ - Process temperature: -40 to 125 °C (T4) / -40 to 95 °C (T5) - Process pressure absolute: max. 50 bar - Flow rate: 100 to 500 L/h - Measurement uncertainty: 0.1 kg/m³ - Wetted part: stainless steel 1.4404 - Inner diameter of tube: 6.3 mm - Ambient temperature: <ul style="list-style-type: none"> -40 °C to +70 °C -40 °C to +70 °C with Pico 3000 -20 °C to +60 °C with Pico 3000 and HMI - Degree of protection: IP 66 / NEMA 4X - Threads for cable glands: 1/2" NPT <ul style="list-style-type: none"> • Process Transmitter Pico 3000 VERSION HART <p>High-performance transmitter for Anton Paar process sensors. Integrated into the sensor or as remote unit. Easy configuration by a USB interface and an optional human machine interface.</p> <p>Scope of delivery</p> <ul style="list-style-type: none"> 1 Pcs. transmitter Pico 3000 HART 1 Pcs. Instruction Manual 1 Pcs. USB cable 1.8 m black <p>Technical specifications</p> <ul style="list-style-type: none"> - interfaces: 1 x AO 4 -20 mA, 1 x HART <ul style="list-style-type: none"> • L-Dens 7400 F-ADAPTER SET ANSI B16.5 1/2" CL 300, SST, FKM-LT <p>AN 1/2" adapter set for easy installation of an L-Dens 7400 process density sensor into a pipeline.</p> <p>Scope of delivery</p> <ul style="list-style-type: none"> 1 Pcs. adapter stainless steel ANSI 1/2" 4 Pcs. screw M8x25 DIN 912 A4-70 4 Pcs. ripped washer M8 2 Pcs. O-ring 7x2 FKM-LT <p>Technical specifications</p> <ul style="list-style-type: none"> - Flange type: Class 300 ANSI B16.5 RF - Connection Diameter: AN 1/2" - Wetted parts: AISI 316L, FKM-LT - Process temperature: -29°C to 145 °C - Process pressure absolute: min. 1 bar; max. acc. to Class 300 <ul style="list-style-type: none"> • Pico 3000 RC NPT Ex d WALL MOUNTING REMOTE CONTROL HOUSING WITH HMI <p>Remote housing for the high-performance transmitter Pico 3000 for Anton Paar process sensors, incl. human machine interface.</p> <p>Scope of delivery</p> <ul style="list-style-type: none"> 1 Pcs. Pico 3000 RC housing NPT Ex d for wall-mount. + TFT-display Ex d 1 Pcs. Ex-Safety Instructions <p>For hazardous areas</p> <ul style="list-style-type: none"> - ATEX: Ex II 2G Ex db IIB T4/T5 Gb - IECEx: Ex db IIB T4/T5 Gb - CSA/UL/FM: Class I Division 1 Gr CD T4/T5 		
--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	--

	<p>Ex db IIB T4/T5 Gb Class I Zone 1, AEx db IIB T4/T5 Gb</p> <p>Technical specifications - electronics housing made of aluminium, anodised - TFT-display with capacitive keys - ambient temperature: - 20 to 60 °C - degree of protection: IP 66 / NEMA 4X - threads for cable glands: 1/2" NPT</p> <ul style="list-style-type: none"> • SET OF CABLE GLANDS 1/2" NPT Ex d FOR NON-ARMORED CABLES <p>Set of two cable glands for shielded EMC-cables without armoring and four blind plugs for use in hazardous areas.</p> <p>Scope of delivery 2 Pcs. NPT 1/2" Ex cable gland for non-armored cables 4 Pcs. NPT 1/2" Ex blind plug</p> <p>For hazardous areas ATEX: Ex II 2GD Ex db IIC Gb IECEX: Ex db IIC Gb</p> <p>Technical Specifications cable gland -Type: Cable gland for non-armored shielded EMC cable -Material: nickel-plated brass -Gasket: aramid fibers bonded with NBR -O-ring & sealing inserts: chloroprene / neoprene -Thread: NPT 1/2" -Inner jacket: 4 to 12 mm -Ambient temperature: -40 to 80 °C -Protection class: IP66 / IP68 , UL type 4X</p> <p>Technical specifications blind plug -Material: nickel plated brass -Thread: NPT 1/2" -Ambient temperature: -60 to 200 °C -Protection class: IP66</p> <ul style="list-style-type: none"> • SET OF CABLE GLANDS NPT 1/2" Ex d FOR ARMORED CABLES <p>Set of two NPT 1/2" cable glands for armored cables (steel wire armored or aluminum wire armored) and four blind plugs for use in hazardous areas.</p> <p>Scope of delivery 2 Pcs. Ex cable gland for armored cables 4 Pcs. Ex blind plugs</p> <p>For hazardous areas IECEX: Ex db IIC Gb ATEX: Ex II 2G Ex db IIC Gb cCSAus: Class I, Division 2, Groups A, B, C & D</p> <p>Technical specifications cable glands -Type: cable gland for SWA and AWA cables (steel and aluminum) -Material: brass nickel-plated -Thread: NPT 1/2" -Inner sheath: 3.1 to 8.6 mm -Outer sheath: 6.1 to 13.1 mm -Braid thickness: 0.80 to 1.25 mm -Ambient temperature: -60 to 130 °C</p>		
--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	--

	<p>-Degree of protection: IP66</p> <p>Technical specifications blind plugs</p> <p>-Material: brass nickel-plated</p> <p>-Thread: NPT 1/2"</p> <p>-Ambient temperature: -60 bis 200 °C</p> <p>-Degree of protection: IP66</p>		
	<p>Delivery Time 8 – 12 Weeks ARAD</p> <p>Payment Terms 100% Net 30 days delivery time</p> <p>Packing Material will be Securely packed in wooden crates suitable for air freight and export.</p> <p>Volume & Weight (to be reconfirmed) To be advised – Aprox 240 Lbs</p> <p>General Warranty: Anton Paar warrants its products to be free from defects in material and/or workmanship for a period of thirtysix (36) months following shipment or twelve (24) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p>Project Cancellation charges:</p> <p>15% Up to submittal of Engineering & Design Drawings and Documents</p> <p>25% After submittal of Engineering & Design Drawings and Documents</p> <p>50% After material order placement and before production commences</p> <p>75% Within two weeks of production release</p> <p>100% Two weeks after production commences</p>		
	<p>NOTAS:</p> <p>Technical Note: COMMISSIONING and TRAINING SUPPORT (1 day) - Included On-site startup, commissioning ad training. This option assumes that the purchaser has installed the AP-supplied systems and that all site utilities are tested and connected prior to the commencement of Commissioning Support</p>		
	<p>CONDICIONES DE PAGO</p> <p><u>COMPONENTE IMPORTADO</u></p> <p><i>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</i></p> <p><i>AMERANT BANK (in US\$)</i> <i>220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134</i> <i>CUENTA NUMERO 8303790106</i></p>		

	<p>BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A. ABA 067010509 SWIFT MNBMUS33</p> <p><u>COMPONENTE NACIONAL (IVA)</u></p> <p>En BOLIVARES (Bs.) mediante transferencia bancaria</p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. – 0105-0011-73-1011-50499-5</p>		
	<p>OTRAS CONDICIONES</p> <ol style="list-style-type: none"> 1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos 2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y deberá ser cancelado a la tasa oficial del día de pago o de la retención correspondiente 3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes. 4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente 5. Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta 6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22. <div style="display: flex; justify-content: space-between; align-items: center; margin-top: 20px;"> <div data-bbox="279 1354 542 1461" style="text-align: center;"> <p>In Tech Instrumentos y Equipos, C.A. RIF: J-30615033-1 NIT: 0096996004</p> </div> <div data-bbox="574 1339 847 1499" style="text-align: center;">  </div> </div> <p>Cci: W. Brito – INTECH PLCRZ</p>		

Please Transfer to Account of:
Bank: Amerant Bank
Address: 220 Alhambra Circle, Coral Gables,
Florida 33134, USA
ABA: 067010509
Swift: MNBMUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS
C.A.
Account # 8303790106

Subtotal	US\$	101,320.00
Freight	US\$	Incluido
Insurance	US\$	--
IVA 16%	US\$	16,211.20

IGTF 3%	US\$	---
TOTAL	US\$	117,531.20