

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
Caracas, Venezuela 1080
Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
Fax: 58-212-977.3613
E-mail: sales@intech-ie.com
RIF J-30615033-1

Quote # C-2024-0105
Date: 21/03/2024
Customer ID CHEVRON PETROPIAR

| Bill to: |
|---|
| <p>CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela Att: Maria Teresa Andres - Depto de Procura MariaTeresa.Andres@chevron.com</p> |

| Ship to: |
|---|
| <p>CHEVRON PETROPIAR Warehouse Jose Complex, Edo Anzoategui, Venezuela</p> |


| Sales Rep. | Your # | Our # | Destiny | Terms | Validity |
|----------------------------|--|---------------------------------------|-----------|------------------|----------|
| L. Zuniga N. Carricatti | VEN-PP- RFQ-ADQ. MANOMETR OS (PARTE I) | IBI-2024-0105/C-2024- 0055A-I1*1.2 | Venezuela | DDP Jose complex | 30 days |

| Item | Cant | Description | Unit Price US\$ | Total US\$ |
|------|------|--|--------------------|---------------|
| 1 | 14 | Pressure Gauge Range 0-100 PSIG, dial 4 ½ " Thermoplastic Case, WIKA PN 80052056 | \$360,00 | \$5.040,00 |
| | | <p>Model 232.34</p> <p>Case Black fiberglass reinforced thermoplastic (Ponca B4225)</p> <p>Bezel ring Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)</p> <p>Measuring system Stainless Steel</p> <p>Case filling Without</p> <p>Nominal size 4.5"</p> <p>Range 0 – 100 psig</p> <p>Process connection ½ NPT</p> <p>Connector location Lower mount</p> <p>Window Acrylic (PMMA)</p> <p>Restrictor Stainless Steel, D 0.6</p> <p>Pointer Adjustable Pointer</p> <p>Accuracy class +/- 0.5% (ASME B40.100 2A)</p> <p>Material pressure element Measuring system 316L</p> <p>Case filling fluid None</p> <p>Ingress protection IP65</p> <p>Pressure Gauge Standard US-Standard</p> <p>Color for scale Black</p> <p>Dial background White</p> <p>Stop pin on dial At 6 o'clock</p> | | |
| 2 | 4 | Pressure Gauge Range 0-200 PSIG, dial 4 ½ " Thermoplastic Case, WIKA PN 80052068 | \$360,00 | \$1.440,00 |
| | | <p>Model 232.34</p> | | |

| | | | | |
|---|----|--|----------|-------------|
| | | <p>Case Black fiberglass reinforced thermoplastic (Ponca B4225)</p> <p>Bezel ring Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)</p> <p>Measuring system Stainless Steel</p> <p>Case filling Without</p> <p>Nominal size 4.5"</p> <p>Range 0 – 200 psig</p> <p>Process connection ½ NPT</p> <p>Connector location Lower mount</p> <p>Window Acrylic (PMMA)</p> <p>Restrictor Stainless Steel, D 0.6</p> <p>Pointer Adjustable Pointer</p> <p>Accuracy class +/- 0.5% (ASME B40.100 2A)</p> <p>Material pressure element Measuring system 316L</p> <p>Case filling fluid None</p> <p>Ingress protection IP65</p> <p>Pressure Gauge Standard US-Standard</p> <p>Color for scale Black</p> <p>Dial background White</p> <p>Stop pin on dial At 6 o'clock</p> | | |
| 3 | 47 | <p>Pressure Gauge Range 0-300 PSIG, dial 4 ½ " Thermoplastic Case, WIKA PN 9834869</p> <p>Model 232.34</p> <p>Case Black fiberglass reinforced thermoplastic (Ponca B4225)</p> <p>Bezel ring Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)</p> <p>Measuring system Stainless Steel</p> <p>Case filling Without</p> <p>Nominal size 4.5"</p> <p>Range 0 – 300 psig</p> <p>Process connection ½ NPT</p> <p>Connector location Lower mount</p> <p>Window Acrylic (PMMA)</p> <p>Restrictor Stainless Steel, D 0.6</p> <p>Pointer Adjustable Pointer</p> <p>Accuracy class +/- 0.5% (ASME B40.100 2A)</p> <p>Material pressure element Measuring system 316L</p> <p>Case filling fluid None</p> <p>Ingress protection IP65</p> <p>Pressure Gauge Standard US-Standard</p> <p>Color for scale Black</p> <p>Dial background White</p> <p>Stop pin on dial At 6 o'clock</p> | \$360,00 | \$16.920,00 |
| 4 | 7 | <p>Pressure Gauge Range 0-400 PSIG, dial 4 ½ " Thermoplastic Case, WIKA PN 80052069</p> <p>Model 232.34</p> <p>Case Black fiberglass reinforced thermoplastic (Ponca B4225)</p> <p>Bezel ring Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)</p> <p>Measuring system Stainless Steel</p> | \$360,00 | \$2.520,00 |

| | | | | |
|---|----|--|----------|-------------|
| | | <p>Case filling Without</p> <p>Nominal size 4.5"</p> <p>Range 0 – 400 psig</p> <p>Process connection ½ NPT</p> <p>Connector location Lower mount</p> <p>Window Acrylic (PMMA)</p> <p>Restrictor Stainless Steel, D 0.6</p> <p>Pointer Adjustable Pointer</p> <p>Accuracy class +/- 0.5% (ASME B40.100 2A)</p> <p>Material pressure element Measuring system 316L</p> <p>Case filling fluid None</p> <p>Ingress protection IP65</p> <p>Pressure Gauge Standard US-Standard</p> <p>Color for scale Black</p> <p>Dial background White</p> <p>Stop pin on dial At 6 o'clock</p> | | |
| 5 | 8 | <p>Pressure Gauge Range 0-600 PSIG, dial 4 ½ " Thermoplastic Case, WIKA PN 9834885</p> <p>Model 232.34</p> <p>Case Black fiberglass reinforced thermoplastic (Ponca B4225)</p> <p>Bezel ring Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)</p> <p>Measuring system Stainless Steel</p> <p>Case filling Without</p> <p>Nominal size 4.5"</p> <p>Range 0 – 600 psig</p> <p>Process connection ½ NPT</p> <p>Connector location Lower mount</p> <p>Window Acrylic (PMMA)</p> <p>Restrictor Stainless Steel, D 0.6</p> <p>Pointer Adjustable Pointer</p> <p>Accuracy class +/- 0.5% (ASME B40.100 2A)</p> <p>Material pressure element Measuring system 316L</p> <p>Case filling fluid None</p> <p>Ingress protection IP65</p> <p>Pressure Gauge Standard US-Standard</p> <p>Color for scale Black</p> <p>Dial background White</p> <p>Stop pin on dial At 6 o'clock</p> | \$360,00 | \$2.880,00 |
| 6 | 60 | <p>MINIATURE COOLING ADAPTOR WITH MICRO-SIPHON 700°F (370°C) TYPE 910.32.250, WIKA PN 52873114</p> <p>Material 316L stainless steel</p> <p>Connection 1/2"NPT female x 1/2"NPT male</p> <p>Pressure Rating Max. 6000 psi (400 bar) at a temperature of 500°F (260°C)</p> | \$400,00 | \$24.000,00 |

| | | | | | | | | | | | | | |
|------|--|-----|--|-----|--|-----|--|-----|--|------|--------------------------------------|--|--|
| | <p>Delivery Time Item 1-5: 2 – 3 Weeks ARAD (MATERIAL ON STOCK, WIKA USA) Item 6: 4-5 Weeks ARAD</p> <p>Payment Terms • 100% with Order (Net 30 days)</p> <p>Packing Material will be Securely packed in wooden crates suitable for air freight and export. Volume & Weight To be advised</p> <p>General Warranty: WIKA warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p>Project Cancellation charges:</p> <table border="0"> <tr> <td>15%</td> <td>Up to submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> <tr> <td>75%</td> <td>Within two weeks of production release</td> </tr> <tr> <td>100%</td> <td>Two weeks after production commences</td> </tr> </table> | 15% | Up to submittal of Engineering & Design Drawings and Documents | 25% | After submittal of Engineering & Design Drawings and Documents | 50% | After material order placement and before production commences | 75% | Within two weeks of production release | 100% | Two weeks after production commences | | |
| 15% | Up to submittal of Engineering & Design Drawings and Documents | | | | | | | | | | | | |
| 25% | After submittal of Engineering & Design Drawings and Documents | | | | | | | | | | | | |
| 50% | After material order placement and before production commences | | | | | | | | | | | | |
| 75% | Within two weeks of production release | | | | | | | | | | | | |
| 100% | Two weeks after production commences | | | | | | | | | | | | |
| | <p>NOTAS:</p> <p>SE CONSIDERAN 60 ACCESORIOS (ITEM 6) PARA TEMPERATURA PARA LOS SIGUIENTES MANOMETROS CONSIDERANDO QUE SUS TEMPERATURAS MAXIMAS DE OPERACION ESTAN POR ENCIMA DE 220 °F. ESTA ES LA ALTERNATIVA OFRECIDA MAS RAPIDA Y ECONOMICA.</p> <p>RANGO 0-300 PSI – 47 UNIDADES RANGO 0-400 PSI – 5 UNIDADES RANGO 0-600 PSI – 8 UNIDADES</p> | | | | | | | | | | | | |
| | <p>CONDICIONES DE PAGO</p> <p><u>COMPONENTE IMPORTADO</u></p> <p><i>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</i></p> <p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134 CUENTA NUMERO 8303790106 BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A. ABA 067010509 SWIFT MNBMUS33</p> <p><u>COMPONENTE NACIONAL (IVA)</u></p> <p><i>En BOLIVARES (Bs.) mediante transferencia bancaria</i></p> | | | | | | | | | | | | |

| | | | |
|--|--|--|--|
| | <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. - 0105-0011-73-1011-50499-5</p> | | |
| | <p>OTRAS CONDICIONES</p> <ol style="list-style-type: none"> 1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos 2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y debera ser cancelado a la tasa oficial del día de pago o de la retención correspondiente 3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes. 4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente 5. Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta 6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22. <div style="display: flex; justify-content: space-between; align-items: center; margin-top: 20px;"> <div data-bbox="277 1150 542 1260" style="text-align: center;"> <p>In Tech Instrumentos y Equipos, C.A. RIF: J-30615033-1 NIT: 0096996004</p> </div> <div data-bbox="574 1136 846 1297" style="text-align: center;">  </div> </div> <p style="margin-top: 20px;">Cci: W. Brito – INTECH PLCRZ</p> | | |

Please Transfer to Account of:
Bank: Amerant Bank
Address: 220 Alhambra Circle, Coral Gables,
Florida 33134, USA
ABA: 067010509
Swift: MNB MUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS
C.A.
Account # 8303790106

| | | |
|------------------|-------------|------------------|
| Subtotal | US\$ | 52,800.00 |
| Freight | US\$ | Incluido |
| Insurance | US\$ | -- |
| IVA 16% | US\$ | 8,448.00 |
| IGTF 3% | US\$ | --- |
| TOTAL | US\$ | 61,248.00 |