



Instrumentos y Equipos C.A

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
 Caracas, Venezuela 1080
 Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
 Fax: 58-212-977.3613
 E-mail: sales@intech-ie.com
 RIF J-30615033-1

Quote # **C-2024-0062Rev2**
 Date: **07/03/2024**
 Customer ID **CHEVRON PETROPIAR**

Bill to:
CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela Att: Sofia Elena Camejo - Depto de Procura SofiaElena.Camejo@chevron.com

Ship to:
CHEVRON PETROPIAR Warehouse Jose Complex, Edo Anzoategui, Venezuela

Sales Rep.	Your #	Our #	Destiny	Terms	Validity
L. Zuniga N. Carricatti	20Feb2024- VEN-PP- RFX-PP- 2024-085	IBI-2024-0044 WIKA-PL	Venezuela	DDP Jose complex	30 days

Item	Cant	Description	Unit Price US\$	Total US\$
1	2	PRESSURE GAUGE SERIE 233.34 WITH GLYCERINE 0-15 PSI, WIKA PN 233.34.45-P015PX-N4BK/LSG Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0... 15 psi 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower back mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock	\$460,00	\$920,00

2	3	<p>ASSEMBLY PRESSURE GAUGE SERIE 233.34 WITH GLYCERINE 0-30 PSI WITH DIAPHRAGM SEAL 990.10, WIKA PN 233.34.45-P030PX-N4BK/LSG L990.10-N4FN4-MOMO-0SSMO-VI-100</p> <p>Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/30 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 69.8°F (room temperature) Process temperature max.: + 212°F Ambient temperature pressure meas. min: + 69.8°F (room temperature) Ambient temperature pressure meas. max: + 69.8°F (room temperature) Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 1/2" NPT male Nominal pressure rating: PN 100 Upper housing material / housing material: Monel 400 (2.4360) Diaphragm material: MONEL 400 (2.4360) Lower housing material: in MONEL 400 (2.4360) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Label: WIKA standard without / with Tag-number</p>	\$4.420,00	\$13.260,00
3	1	<p>PRESSURE GAUGE SERIE 233.34 WITH GLYCERINE 0-60 PSI, WIKA PN 233.34.45-P060PX-N4BK/LSG</p> <p>Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)</p>	\$460,00	\$460,00

		<p>Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0... 60 psi 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower back mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock</p>		
4	2	<p>ASSEMBLY PRESSURE GAUGE SERIE 233.34 WITH GLYCERINE 0-100 PSI WITH DIAPHRAGM SEAL 990.10, WIKA PN 233.34.45-P100PX-N4BK/LSG L990.10-N4FN4-MOMO-OSSMO-VI-100</p> <p>Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/100 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 69.8°F (room temperature) Process temperature max.: + 212°F Ambient temperature pressure meas. min: + 69.8°F (room temperature)</p>	\$4.420,00	\$8.840,00

		<p>Ambient temperature pressure meas. max: + 69.8°F (room temperature) Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 1/2" NPT male Nominal pressure rating: PN 100 Upper housing material / housing material: Monel 400 (2.4360) Diaphragm material: MONEL 400 (2.4360) Lower housing material: in MONEL 400 (2.4360) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Label: WIKA standard without / with Tag-number</p>		
5	1	<p>PRESSURE GAUGE SERIE 233.34 WITH GLYCERINE 0-160 PSI, WIKA PN 233.34.45-P160PX-N4BK/LSG</p> <p>Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0... 160 psi 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower back mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock</p>	\$460,00	\$460,00
6	1	<p>PRESSURE GAUGE SERIE 233.34 WITH GLYCERINE 0-2000 PSI, WIKA PN 233.34.45-P20CPX-N4BK/LSG</p> <p>Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0... 2000 psi 2nd Scale / Special Scale: none</p>	\$460,00	\$460,00

		<p>Process Connection: 1/2 NPT Connector location: lower back mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock</p>		
7	2	<p>BROOKS Rotameters Model 3809GSA10AGBC3H3S0001</p> <p>Metal Tube VA Flow Meter</p> <p>Line Description MT3809G Stainless Meter GAS 1.8 - 18 NCFM</p> <p>Base Model MT3809 SS</p> <p>Max Press@TMin 720 PSIG (49.6 BAR)</p> <p>Max Press@TMax 458 PSIG (31.6 BAR)</p> <p>CRN Province N/A</p> <p>Max Temp 572F (300C)</p> <p>Min Temp -325F (-198C)</p> <p>Accuracy 1% Direct Scale-Gas</p> <p>Meter Material 316/316L SS w\ TTM Float – Cert 3.1-Material</p> <p>Connection Size 1-in</p> <p>Connection Type 300# WNRF Flange</p> <p>Inlet Down</p> <p>Outlet Up</p> <p>O-Ring Material None</p> <p>Lay Length 250 mm</p> <p>Valve Type No Valve</p> <p>Valve Conn No Valve</p> <p>Tube Size 10-A 1.17/V</p> <p>Float 10-V-222</p> <p>Float Material Titanium</p> <p>Range 1.8 - 18 NCFM</p> <p>Ref Conditions 0C @ 1 atm</p> <p>Primary Scale Direct Read</p> <p>Secondary Scale N/A</p> <p>Scale Type White Face Metal Scale</p> <p>Fluid SEAL GAS COMPRESSOR</p> <p>Density 0.67 S.G</p> <p>Viscosity 0.01 cP</p> <p>Operating Temp 68F</p> <p>Operating Press 14.5 psfg</p> <p>Amb Temp Limit -20C to 70C</p> <p>Ind. Housing XP Stainless</p> <p>Electrical Conn 1/2" NPT-F</p> <p>Ind/Alarm/Xmtr Transmitter w\ Digital Display</p> <p>Approvals UL- DIV 1 -ZONE 1 -IS</p> <p>Remote Relay None</p> <p>Power Supply None</p>	\$15.410,00	\$30.820,00

	<p>Cert1 N/A Cert2 N/A Additional Services Decl 2.1 - Compliance (CoC) Cert 3.1 - Material Hazardous Location Cert Stainless Steel Tags Certified Prints Required</p> <p>Tags # 14-FIT-080, 14-FIT-081</p> <p>Equivalent to Old Brooks MT3809E-13ABC3ALA1 Grupo Alvica – Fluor Daniel – Data Sheet N.SOS 0350212 1/4</p>												
	<p>Delivery Time 8 – 10 Weeks ARAD Partial Shipments allowed (WIKA) (BROOKS)</p> <p>Payment Terms</p> <ul style="list-style-type: none"> • 50% with Order (Net 30 days) • 50% Net 30 days delivery time <p>Packing Material will be Securely packed in wooden crates suitable for air freight and export.</p> <p>Volume & Weight (to be reconfirmed) To be advised – Aprox 180 Lbs</p> <p>General Warranty: WIKA and BROOKS warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p>Project Cancellation charges:</p> <table border="0"> <tr> <td>15%</td> <td>Up to submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> <tr> <td>75%</td> <td>Within two weeks of production release</td> </tr> <tr> <td>100%</td> <td>Two weeks after production commences</td> </tr> </table>	15%	Up to submittal of Engineering & Design Drawings and Documents	25%	After submittal of Engineering & Design Drawings and Documents	50%	After material order placement and before production commences	75%	Within two weeks of production release	100%	Two weeks after production commences		
15%	Up to submittal of Engineering & Design Drawings and Documents												
25%	After submittal of Engineering & Design Drawings and Documents												
50%	After material order placement and before production commences												
75%	Within two weeks of production release												
100%	Two weeks after production commences												
	<p>NOTAS:</p>												
	<p>CONDICIONES DE PAGO</p> <p><u>COMPONENTE IMPORTADO</u></p> <p>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</p>												

	<p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134 CUENTA NUMERO 8303790106 BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A. ABA 067010509 SWIFT MNBMUS33</p> <p><u>COMPONENTE NACIONAL (IVA)</u></p> <p>En BOLIVARES (Bs.) mediante transferencia bancaria</p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. - 0105-0011-73-1011-50499-5</p>		
	<p>OTRAS CONDICIONES</p> <ol style="list-style-type: none"> 1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos 2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y deberá ser cancelado a la tasa oficial del día de pago o de la retención correspondiente 3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes. 4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente 5. Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta 6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22. <div style="display: flex; justify-content: space-between; align-items: center; margin-top: 20px;"> <div data-bbox="277 1430 542 1539" style="text-align: center;"> <p>In Tech Instrumentos y Equipos, C.A. RIF: J-30615033-1 NIT: 0096996004</p> </div> <div data-bbox="573 1415 846 1577" style="text-align: center;">  </div> </div> <p>Cci: W. Brito – INTECH PLCRZ</p>		

Please Transfer to Account of:
Bank: Amerant Bank
Address: 220 Alhambra Circle, Coral Gables,
Florida 33134, USA
ABA: 067010509
Swift: MNB MUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS
C.A.
Account # 8303790106

Subtotal	US\$	55,220.00
Freight	US\$	Incluido
Insurance	US\$	--
IVA 16%	US\$	8,835.20
IGTF 3%	US\$	---
TOTAL	US\$	64,055.20