

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
Caracas, Venezuela 1080
Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
Fax: 58-212-977.3613
E-mail: sales@intech-ie.com
RIF J-30615033-1

Oferta #

C-2024-0053Rev 2

Fecha:

21/02/2024

Su referencia

VEN-PP-ISA24-68-007 ADQ.
MATERIALES DE INSTRUMENTACION
PARA FLARE / P. PLANTA (II)

Facturar a:

Chevron Global Technology Services Company
RIF: N/D
Telf: 0281-4204140
Attn: Maria Teresa Andres (SCM – Business Analyst)
Correo: MariaTeresa.Andres@chevron.com

Despachar a:

Chevron Global Technology Services Company
Barcelona, Edo. Anzoategui – Venezuela

Vendedor	Condiciones	Referencia	Destino	Términos Pago	Validez
N. Carricatti L. Zuniga	DDP	C-2024-0056/PL22/WIDN- 01022024/1.25*I-22-54- NAC	Jose, ANZ	Ver terminos	30 días

Item	Cant	Descripción	Unitario US\$	Total US\$
67	1	<p>WIKA DUAL CHAMBER LEVEL SYSTEM – Redundant BNA/DU-2"/300/RF-M1753-L/CS 60x2.77/60x2,77-MRF-ZTSS50x225mm, SS TAG 57-LIT-021</p> <p>Magnetic Level Gauge Type BNA-SD00 Pressure: 11.7 psi ; Temp.: 14°F...230 °F; Fluid density: 850 kg/m³ Design code: ASME B31.3 Chamber dimensions: OD 60.3 x 2.77 mm (2" Sch. 10S) Duo stainless steel 316/316L (EN 1.4401/1.4404) Process connection: CS Flange ASME B16.5 2" 300# Form RF Distance C-to-C: 1753 mm Measuring range: 1753 mm Chamber end top: Flat Cap w/ 3/4" NPT Vent & Plug Chamber end bottom: 300# Slip on Flange and Blind Mating Flange w/ 3/4" NPT Drain & Plug Vent connection: Butt weld end 3/4" Drain connection: Butt weld end 3/4" Float: 50 x 225mm, SS Dampening element: Dampening spring, bottom, with cover Gasket(s): Spiral wound type, SS 316L/Graphite Bolting: UNC series, carbon steel A193 Gr. B7 HDG / A194 Gr. 2H HDG Top stand-off (T): 100 mm Bottom stand-off (U): 250 mm Nameplate: Stainless steel laser printed Includes Bottom: Mag Trap -316ss/ CS construction -316SS 2" x 2" Tee with 2" CS 300# RFWN Flange -Bottom: CS 2" 300# RFWN with blind mating flange & 1/2" NPT Drain and Plug</p> <p>Dual Chamber (DUplus) Side chamber: OD 60.3 x 2,77 mm (2" Sch. 10S) Location of secondary chamber: 3 o'clock (right side of MLG chamber) Process connection GT: CS Flange ASME B16.5 2" 300# Form RF Distance between chambers center lines: 200 mm Radar connection stand-off: 254 mm Side chamber bottom stand-off: 254 mm</p>	43,080.00	43,080.00

		<p>Insertion external sensor: With MRF-M1753 Level Indicator for Magnetic Level Gauge Type BMD-FA Measuring range: 1753 mm Housing material: Aluminum anodized Indicating elements: Stainless steel flaps Red & white Graduated scale: Aluminum engraved Graduation unit: inch INSULATION BLANKET 1/2" Ceramic Fiber with Silicone Alpha Cloth Exterior and High Heat Interior</p> <p>W/RADAR Transmitter FX81.FADACDXANAM eID: US34478045 TDR sensor for continuous level and interface measurement of liquids Scope F : USA Approval A : FM (NI) CL I, II, III DIV2, GP ABCDFG Version / Material D : Exchangeable cable (ø2mm) with centering weight / 316 Probe : mounted Length (from seal surface) : 87.000 inch Length of rigid part : 3.937 inch Dimensions centering weight (diameter / height) 1.77in / 1.18in (for 2" Schedule 40/80 and 3" Schedule 80/160) Process fitting / Material AC : Flange 2" 300lb RF, ASME B16.5 / 316/316L Seal / Second line of defense / Process temperature D : FFKM (Kalrez 6375) / without / -20...+150°C Electronics H : Two-wire 4 ... 20 mA/HART Supplementary electronics X : with Overvoltage protection of the supply cable 24 VDC , Model USB63-48.N Housing / Protection A : Aluminum single chamber / IP66/IP68 (0.2bar) Cable entry / Connection N : ½NPT / Blind plug Display/Adjustment module PLICSCOM A : mounted Certificates M : Yes Certificate / Standard : (C) Material test report – traceable (EN 10204 type 3.1 + NACE MR0175 + NACE MR0103) PMI test : RFA (positive material identification) incl. 3.1 inspection certificate Supply certificates : with goods Operating instructions : EN - English Number of operating instructions : 2 Measurement loop identification label : of Stainless Steel Customer-specific adjustment : Yes - Unit : inch - 100 % (distance from seal surface) : 10.000 inch - 0 % (distance from seal surface) : 79.000 inch Linearization : No Min. process pressure in bar : -1.000 Max. process pressure in bar : 40.0</p>		
68	1	<p>WIKA DUAL CHAMBER LEVEL SYSTEM – Redundant BNA/DU-2"/300/RF-M1727-L/CS 60x2.77/60x2,77-MRF-ZTSS50x225mm, SS TAG 57-LIT-032</p> <p>Magnetic Level Gauge Type BNA-SD00 Pressure: 8.9 psi ; Temp.: 14°F...230 °F; Fluid density: 850 kg/m³ Design code: ASME B31.3 Chamber dimensions: OD 60.3 x 2.77 mm (2" Sch. 10S) Duo stainless steel 316/316L (EN 1.4401/1.4404) Process connection: CS Flange ASME B16.5 2" 300# Form RF Distance C-to-C: 1727 mm Measuring range: 1727 mm Chamber end top: Flat Cap w/ 3/4" NPT Vent & Plug Chamber end bottom: 300# Slip on Flange and Blind Mating Flange w/ 3/4" NPT</p>	42,710.00	42,710.00

	<p>Drain & Plug Vent connection: Butt weld end 3/4" Drain connection: Butt weld end 3/4" Float: 50 x 225mm, SS Dampening element: Dampening spring, bottom, with cover Gasket(s): Spiral wound type, SS 316L/Graphite Bolting: UNC series, carbon steel A193 Gr. B7 HDG / A194 Gr. 2H HDG Top stand-off (T): 100 mm Bottom stand-off (U): 250 mm Nameplate: Stainless steel laser printed Includes Bottom: Mag Trap -316ss/ CS construction -316SS 2" x 2" Tee with 2" CS 300# RFWN Flange -Bottom: CS 2" 300# RFWN w/ 1" blind mating flange & 1/2" NPT Drain and Plug</p> <p>Dual Chamber (DUplus) Side chamber: OD 60.3 x 2,77 mm (2" Sch. 10S) Location of secondary chamber: 3 o'clock (right side of MLG chamber) Process connection GT: CS Flange ASME B16.5 2" 300# Form RF Distance between chambers center lines: 200 mm Radar connection stand-off: 254 mm Side chamber bottom stand-off: 254 mm Insertion external sensor: With MRF-M1727 Level Indicator for Magnetic Level Gauge Type BMD-FA Measuring range: 1727 mm Housing material: Aluminum anodized Indicating elements: Stainless steel flaps Red & white Graduated scale: Aluminum engraved Graduation unit: inch INSULATION BLANKET 1/2" Ceramic Fiber with Silicone Alpha Cloth Exterior and High Heat Interior</p> <p>w/RADAR Transmitter FX81.FADACDHXANAM eID: US34482216 TDR sensor for continuous level and interface measurement of liquids Scope F : USA Approval A : FM (NI) CL I, II, III DIV2, GP ABCDFG Version / Material D : Exchangeable cable (ø2mm) with centering weight / 316 Probe : mounted Length (from seal surface) : 86.000 inch Length of rigid part : 3.937 inch Dimensions centering weight (diameter / height) 1.77in / 1.18in (for 2" Schedule 40/80 and 3" Schedule 80/160) Process fitting / Material AC : Flange 2" 300lb RF, ASME B16.5 / 316/316L Seal / Second line of defense / Process temperature D : FFKM (Kalrez 6375) / without / -20...+150°C Electronics H : Two-wire 4 ... 20 mA/HART Supplementary electronics X : with Overvoltage protection of the supply cable 24 VDC , Model USB63-48.N Housing / Protection A : Aluminum single chamber / IP66/IP68 (0.2bar) Cable entry / Connection N : ½NPT / Blind plug Display/Adjustment module PLICSCOM A : mounted Certificates M : Yes Certificate / Standard : (C) Material test report – traceable (EN 10204 type 3.1 + NACE MR0175 + NACE MR0103) PMI test : RFA (positive material identification) incl. 3.1 inspection certificate Supply certificates : with goods Operating instructions : EN - English Number of operating instructions : 2 Measurement loop identification label : of Stainless Steel Customer-specific adjustment : Yes - Unit : inch</p>		
--	--	--	--

		<p>- 100 % (distance from seal surface) : 10.000 inch - 0 % (distance from seal surface) : 78.000 inch Linearization : No Min. process pressure in bar : -1.000 Max. process pressure in bar : 40.0</p>		
69	1	<p>WIKA DUAL CHAMBER LEVEL SYSTEM – Redundant BNA/DU-2"/300/RF-M0356-L/CS 60x2.77/60x2,77-MRF-ZTSS50x225mm, SS TAG 57-LIT-031</p> <p>Magnetic Level Gauge Type BNA-SD00 Pressure: 8.9 psi ; Temp.: 14°F...230 °F; Fluid density: 850 kg/m³ Design code: ASME B31.3 Chamber dimensions: OD 60.3 x 2.77 mm (2" Sch. 10S) Duo stainless steel 316/316L (EN 1.4401/1.4404) Process connection: CS Flange ASME B16.5 2" 300# Form RF Distance C-to-C: 356 mm Measuring range: 356 mm Chamber end top: Flat Cap w/ 3/4" NPT Vent & Plug Chamber end bottom: 300# Slip on Flange and Blind Mating Flange w/ 3/4" NPT Drain & Plug Vent connection: Butt weld end 3/4" Drain connection: Butt weld end 3/4" Float:50 x 225mm, SS Dampening element: Dampening spring, bottom, with cover Gasket(s): Spiral wound type, SS 316L/Graphite Bolting: UNC series, carbon steel A193 Gr. B7 HDG / A194 Gr. 2H HDG Top stand-off (T): 100 mm Bottom stand-off (U): 250 mm Nameplate: Stainless steel laser printed Includes Bottom: Mag Trap -316ss/ CS construction -316SS 2" x 2" Tee with 2" CS 300# RFWN Flange -Bottom: CS 2" 300# RFWN with blind mating flange & 1/2" NPT Drain and Plug</p> <p>Dual Chamber (DUplus) Side chamber: OD 60.3 x 2,77 mm (2" Sch. 10S) Location of secondary chamber: 3 o'clock (right side of MLG chamber) Process connection GT: CS Flange ASME B16.5 2" 300# Form RF Distance between chambers center lines: 200 mm Radar connection stand-off: 254 mm Side chamber bottom stand-off: 254 mm Insertion external sensor: With MRF-M0356 Level Indicator for Magnetic Level Gauge Type BMD-FA Measuring range: 356 mm Housing material: Aluminum anodized Indicating elements: Stainless steel flaps Red & white Graduated scale: Aluminum engraved Graduation unit: inch INSULATION BLANKET 1/2" Ceramic Fiber with Silicone Alpha Cloth Exterior and High Heat Interior</p> <p>W/RADAR Transmitter FX81.FADACDHXANAM eID: US34482410 TDR sensor for continuous level and interface measurement of liquids Scope F : USA Approval A : FM (NI) CL I, II, III DIV2, GP ABCDFG Version / Material D : Exchangeable cable (ø2mm) with centering weight / 316 Probe : mounted Length (from seal surface) : 32.000 inch Length of rigid part : 3.937 inch</p>	33,490.00	33,490.00

	<p>Dimensions centering weight (diameter / height) 1.77in / 1.18in (for 2" Schedule 40/80 and 3" Schedule 80/160) Process fitting / Material AC : Flange 2" 300lb RF, ASME B16.5 / 316/316L Seal / Second line of defense / Process temperature D : FFKM (Kalrez 6375) / without / -20...+150°C Electronics H : Two-wire 4 ... 20 mA/HART Supplementary electronics X : with Overvoltage protection of the supply cable 24 VDC , Model USB63-48.N Housing / Protection A : Aluminum single chamber / IP66/IP68 (0.2bar) Cable entry / Connection N : ½NPT / Blind plug Display/Adjustment module PLICSCOM A : mounted Certificates M : Yes Certificate / Standard : (C) Material test report – traceable (EN 10204 type 3.1 + NACE MR0175 + NACE MR0103) PMI test : RFA (positive material identification) incl. 3.1 inspection certificate Supply certificates : with goods Operating instructions : EN - English Number of operating instructions : 2 Measurement loop identification label : of Stainless Steel Customer-specific adjustment : Yes - Unit : inch - 100 % (distance from seal surface) : 10.000 inch - 0 % (distance from seal surface) : 24.000 inch Linearization : No Min. process pressure in bar : -1.000 Max. process pressure in bar : 40.0</p>		
	<p>Included on each System: Approval Drawings Hydrostatic Pressure Test 1.5x Flange Rating for 10 min @ ambient NACE MR0175 Certificate Material Test Reports with Tagging Information on each Positive Material Identification w/o Carbon Content (10) shots per unit 100% Xray Liquid Dye Penetrant Package/ Handling (per Lot)</p>		

		<p>Tiempo de entrega Luego de recibir orden de compra y pago hito, Items: 12-18 semanas aprox.</p> <p>El tiempo de entrega de los elementos ofertados queda sujeto a cambios generados por eventos fuera de manejo de la compañía como:</p> <ol style="list-style-type: none"> 1. Fenómenos climáticos que no permitan el transporte de materia prima a la fábrica, transporte local en el extranjero del material manufacturado y/o transporte internacional del producto. 2. Normal funcionamiento de aduana Venezolana y/o extranjeras. 3. Alteración del orden público en el país de origen, país en tránsito y/o país final. 4. Actos delictivos y/o terroristas. 5. Cualquier otro evento considerado de fuerza mayor. <p>Términos de pago 50% con su Orden de Compra (neto a 30 días) 50% Balance a 30 días fecha de entrega su almacen</p> <p>Volumen y Peso Peso y volumen por confirmar</p>		
		<p>OTRAS CONDICIONES</p> <ol style="list-style-type: none"> 1. <i>Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos</i> 2. <i>El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y debera ser cancelado a la tasa oficial del día de pago o de la retención correspondiente</i> 3. <i>Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.</i> 4. <i>INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente</i> 5. <i>Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta</i> 6. <i>Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas,</i> 		

no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22.

In Tech
Instrumentos y Equipos, C.A.
RIF: J-30615033-1
NIT: 0096996004



Subtotal	US\$	119,280.00
Flete	US\$	Incluido
Seguro	US\$	Incluido
IVA 16 %	US\$	19,084.80
IGTF	US\$	N.A.
TOTAL	US\$	138,364.80

CONDICIONES DE PAGO
COMPONENTE IMPORTADO

1. En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a cualquiera de las siguientes cuentas

AMERANT BANK (in US\$)
220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134
CUENTA NUMERO 8303790106
BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A.
ABA 067010509
SWIFT MNBMUS33

COMPONENTE NACIONAL

1. En BOLIVARES (Bs.) mediante transferencia bancaria

Banco Mercantil
Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A.
– 0105-0011-73-1011-50499-5