

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
Caracas, Venezuela 1080
Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
Fax: 58-212-977.3613
E-mail: sales@intech-ie.com
RIF J-30615033-1

Oferta # C-2024-0038 Rev 1
Fecha: 15/02/2024
Su referencia VEN-PP-ISA24-68-007 ADQ.
TRANSMISORES / P. PLANTA
(IV)

Facturar a:

**Chevron Global Technology Services
Company**
RIF: N/D
Telf: 0281-4204140
Attn: Maria Teresa Andres (SCM – Business
Analyst)
Correo: MariaTeresa.Andres@chevron.com

Despachar a:

Chevron Global Technology Services Company
Barcelona, Edo. Anzoategui – Venezuela

Vendedor	Condiciones	Referencia	Destino	Términos Pago	Validez
N. Carricatti	DDP	C-2024-0037/PL&RFQ- 202401-02/QUO00015554 Ve-4156720/0	Jose Complex, ANZ	Ver Terminos	30 días

Item	Cant	Descripción	Unitario US\$	Total US\$
1	2	<p>TRANSMISOR FLUJO TRANSMISOR DE PRESION DIFERENCIAL MODELO DPT-20, WIKA PN 80064243</p> <p>Differential Pressure Transmitter DPT-20 Specifications according to data sheet: PE 86.22 Electrical approval: ATEX Ignition protection type: Ex d - explosion proof Zone: Zone 1 attached to zone 0 gas [II 1/2G Ex db ia IIC T6...T1 Ga/Gb] Housing material: Aluminum single chamber Case version: compact / IP66/IP68 (0.2bar); NEMA 6P Digital Display: with integrated indicating/adjustment module (top) Output signal: 4...20 mA, 2-wire, HART Electrical connection: 1/2" NPT female conduit / plug Unit: bar Maximal working pressure: 160 bar (16 MPa / 2400 psi) Measuring range: -500 ... +500 mbar Process connection/mounting/material/venting: for diaphragm seals (accuracy for complete assembly 0.1 % at reference conditions) Diaphragm material: 316L Sealing (temperature range): copper seal ring (-40 ... +85 °C) Accuracy: 0.1 % of span Filling of sensor: Silicone oil for regular applications (KN2) Operating modes: Pressure measurement Scaling unit DP-measurement: inH2O Lower scaling value DP: 0 inH2O Upper scaling value DP: 150,0 Density value: 1 Density unit: kg/dm³ Linearization curve: linear Damping [s]: 1 s (default setting) Output signal low level in %: 0%</p>	\$12,390.00	\$24,780.00

		<p>output signal high level in %: 100% Displayed value: differential pressure (acc. scaling) Diaphragm seal system with 2 diaphragm seals Assembly specification High-Side: 20 feet capillary; stainless steel Height difference high side: no height difference Assembly specification Low-Side: 20 feet capillary; stainless steel System fill fluid: KN 2 Silicone oil for general applications Height difference low side: no height difference Servicecategory: Basic Service according to Technical Information IN 00.25 Process temperature min.: + 32°F Process temperature max.: + 752°F Ambient temperature pressure meas. min: + 69,8°F (room temperature) Ambient temperature pressure meas. max: + 104°F Capillary inner diameter: ID 2mm (3x0.5 mm) Diaphragm seal, flange type, flush diaphragm Specifications according to data sheet: DS 99.27 Diaphragm seal: Model 990.27 High-/Low-Side: High-Side Diaphragm seal: Model 990.27 Process connection standard: following ASME B16.5 Process connection: 3" Nominal pressure rating: Class 600 Sealing face: RF 125...250 AA Upper body material / main body material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Sealing face material: Stainless steel 1.4435 (316L); UNS S31603 Diaphragm seal, flange type, flush diaphragm Specifications according to data sheet: DS 99.27 High-/Low-Side: Low-Side Diaphragm seal: Model 990.27 Process connection standard: following ASME B16.5 Process connection: 3" Nominal pressure rating: Class 600 Sealing face: RF 125...250 AA Upper body material / main body material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Sealing face material: Stainless steel 1.4404 (316L); UNS S31603 Label: WIKA standard without / with Tag-number language of the label: English Link to product details https://en-co.wika.de/990_27_en_co.WIKA https://en-co.wika.de/dpt_20_en_co.WIKA</p>		
2	1	<p>MEDIDOR DE NIVEL MODELO SOLITRAC 31, VEGA PN ST31.UG1ADNBX120-eID: US59482414</p> <p>Radiation-based sensor for continuous level and interface measurement Application area The SOLITRAC 31 is a radiation-based sensor with PVT rod detector for continuous measurement of liquids and bulk solids. It is suitable for level and interface measurement under extreme process temperatures, with critical product features or in aggressive products. The SOLITRAC 31 is ideal for use in cylindrical vessels, reactors, autoclaves, separators and mixing vessels.</p> <p>Your benefit - High plant availability through non-contact measurement - Best measurement performance through PVT detector with maximum sensitivity</p>	\$59,430.00	\$59,430.00

		<p>- Simple mounting through supplied accessory</p> <p>Approval directive / Scope : FM / USA Approval UG : FM (XP-IS) CL I, II, III, DIV1, GP ABCDEFG Version / Ambient temperature 1 : Standard / -40...+60°C Electronics A : Four-wire 4 ... 20 mA/HART (Ex-d output) Housing / Protection D : Aluminium double chamber / IP66/IP67 Cable entry / Cable gland / Plug connection N : ½ NPT / without / without Display/adjustment module PLICSCOM B : mounted Additional equipment X : Without Shipment cooling option : without, no cooling required Length 120 : 120" / 3048 mm Menu language : EN - English Mounting accessory : with Operating instructions : EN - English Number of operating instructions : 1 Type label / Measurement loop identification label : of foil / of stainless steel Test certificate : without Certificate / Standard : (D) 3.1-Inspection certificate for instrument with test data (EN 10204) Supply certificates : with goods Customs tariff number (HS code) : 90301000 Software Version : 3.0.0 device revision 3</p>		
3	1	<p>MEDIDOR DE NIVEL MODELO SOLITRAC 31, VEGA PN ST31.UG1ADNBX048-eID: US50320376</p> <p>Radiation-based sensor for continuous level and interface measurement</p> <p>Application area The SOLITRAC 31 is a radiation-based sensor with PVT rod detector for continuous measurement of liquids and bulk solids. It is suitable for level and interface measurement under extreme process temperatures, with critical product features or in aggressive products. The SOLITRAC 31 is ideal for use in cylindrical vessels, reactors, autoclaves, separators and mixing vessels.</p> <p>Your benefit - High plant availability through non-contact measurement - Best measurement performance through PVT detector with maximum sensitivity - Simple mounting through supplied accessory</p> <p>Approval directive / Scope : FM / USA Approval UG : FM (XP-IS) CL I, II, III, DIV1, GP ABCDEFG Version / Ambient temperature 1 : Standard / -40...+60°C Electronics A : Four-wire 4 ... 20 mA/HART (Ex-d output) Housing / Protection D : Aluminium double chamber / IP66/IP67 Cable entry / Cable gland / Plug connection N : ½ NPT / without / without Display/adjustment module PLICSCOM B : mounted Additional equipment X : Without Shipment cooling option : without, no cooling required Length 048 : 48" / 1219 mm Menu language : EN - English Mounting accessory : with Operating instructions : EN - English Number of operating instructions : 1 Type label / Measurement loop identification label : of foil / of stainless steel Test certificate : without Certificate / Standard : (D) 3.1-Inspection certificate for instrument with test data (EN 10204)</p>	\$47,510.00	\$47,510.00

	<p>Supply certificates : with goods Customs tariff number (HS code) : 90301000 Software Version : 3.0.0 device revision 3</p>		
	<p>Terminos de Pago: 50% con la Orden de Compra (30 dias) 50% a 30 dias fecha de entrega</p> <p>Tiempo de entrega Luego de recibir orden de compra., Items 1: 16-20 semanas aprox. Items 2, 3: 10-14 semanas aprox.</p> <p>El tiempo de entrega de los elementos ofertados queda sujeto a cambios generados por eventos fuera de manejo de la compañía como:</p> <ol style="list-style-type: none"> 1. Fenómenos climáticos que no permitan el transporte de materia prima a la fábrica, transporte local en el extranjero del material manufacturado y/o transporte internacional del producto. 2. Normal funcionamiento de aduana Venezolana y/o extranjeras. 3. Alteración del orden público en el país de origen, país en tránsito y/o país final. 4. Actos delictivos y/o terroristas. 5. Cualquier otro evento considerado de fuerza mayor. <p>Volumen y Peso Peso y volumen serán reconfirmados antes del despacho</p>		
	<p>OTRAS CONDICIONES</p> <ol style="list-style-type: none"> 1. <i>Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos</i> 2. <i>El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y debera ser cancelado a la tasa oficial del día de pago o de la retención correspondiente</i> 3. <i>Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.</i> 4. <i>INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente</i> 5. <i>Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta</i> 6. <i>Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo</i> 		

9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22.

In Tech

Instrumentos y Equipos, C.A.

RIF: J-30615033-1

NIT: 0096996004

Subtotal	US\$	131,720.00
Flete	US\$	Incluido
Seguro	US\$	-
IVA 16 %	US\$	21,075.20
IGTF	US\$	-
TOTAL	US\$	152,795.20

CONDICIONES DE PAGO
COMPONENTE IMPORTADO

1. En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a cualquiera de las siguientes cuentas

AMERANT BANK (in US\$)
220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134
CUENTA NUMERO 8303790106
BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A.
ABA 067010509
SWIFT MNBMUS33

COMPONENTE NACIONAL

1. En BOLIVARES (Bs.) mediante transferencia bancaria

Banco Mercantil
Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A.
– 0105-0011-73-1011-50499-5