

Instrumentos y Equipos C.A

Visít us at <http://www.intech-ie.com>

**INTECH Instrumentos y Equipos C.A.**

Av. Río Caura, Torre Humboldt, Ofic 04-04,  
Caracas, Venezuela 1080  
Tel: 58-212-9784430, 9784433, 977.7654, 977.6346  
Fax: 58-212-977.3613  
E-mail: sales@intech-ie.com  
RIF J-30615033-1

**Quote #** C-2026-0137  
**Date:** 30/04/2026  
**Customer ID** GUYSUCO

**Bill to:**  
**Guyana Sugar Corporation Inc.**  
La Bonne Intention, East Coast Demerara  
P: +592-2202891/4  
Att: Guysuco Procurement and Contract Management Department.  
E-mail: pcmd@guysuco.com

**Ship to:**  
CIF Georgetown Airport. Custom Agent to be advised.

Sales Rep.	Your #	Our #	Destiny	Terms	Validity
S. Mendez	5202600216/FO	C-2026-0137/PL	Guyana	See below	90 days

Item	Cant	Description	Unit Price US\$	Total US\$
1	6	<p><b>DIFFERENTIAL PRESSURE TRANSMITTER MODEL DPT-20, WIKA PN DPT-20-ZZZ-ADZZZ-AR-BBD330-DSVL-ZZZA-ZZ</b></p> <p>Differential Pressure Transmitter DPT-20 Housing material: Aluminum single chamber enclosure execution: compact / IP66/IP68 (0.2bar); NEMA 6P Output signal: 4...20 mA, 2-wire Electrical connection: M20x1,5 / cable gland PA black (ø5-9mm), standard Unit: bar Maximal working pressure: 160 bar (16 MPa / 2400 psi) Pressure range: -3 ... +3 bar Process connection/mounting/material/venting: 1/4-18 NPT IEC 61518 / 7/16-20 UNF / 316L / dorsal, incl. 2 valves Diaphragm material: 316L Sealing (temperature range): FKM (-20 ... +85 °C) Accuracy: 0.065 % of span Filling of sensor: Silicone oil for regular applications (KN2) Operating modes: Pressure measurement Density value: 1 Density unit: kg/dm<sup>3</sup> Linearization curve: linear Damping [s]: 1 s (default setting) Output signal low level in %: 0% Output signal low level in %: 100% Displayed value: differential pressure (acc. scaling)</p>	\$2,935.00	\$17,610.00
2	3	<p><b>DIFFERENTIAL PRESSURE TRANSMITTER MODEL DPT-20, WIKA PN DPT-20-ZZZ-ADZZZ-AN-BBD250-7SVL-ZZZA-4Z // CERT31-EGPT-AB- - - - - - - - - - -</b></p> <p>Differential Pressure Transmitter DPT-20 Housing material: Aluminum single chamber enclosure execution: compact / IP66/IP68 (0.2bar); NEMA 6P</p>	\$3,226.00	\$9,678.00

		<p>Output signal: 4...20 mA, 2-wire Electrical connection: 1/2" NPT female conduit Unit: bar Maximal working pressure: 160 bar (16 MPa / 2400 psi) Pressure range: -500 ... +500 mbar Process connection/mounting/material/venting: 1/4-18 NPT IEC 61518 / PN160 M10 / 316L / dorsal incl. 2 valves Diaphragm material: 316L Sealing (temperature range): FKM (-20 ... +85 °C) Accuracy: 0.065 % of span Filling of sensor: Silicone oil for regular applications (KN2) Certificates/Approvals: Certificate 3.1 Accuracy with inspection values listed Operating modes: Pressure measurement Density value: 1 Density unit: kg/dm<sup>3</sup> Linearization curve: linear Damping [s]: 1 s (default setting) Output signal low level in %: 0% Output signal low level in %: 100% Displayed value: differential pressure (acc. scaling) Inspection certificate 3.1 per EN 10204 Certificate type: Inspection certificate acc. to EN 10204 3.1 Certificate Language: English and German Certificate for: process pressure transmitter Accuracy: Calibration values listed (traceable to national standards)</p>		
3	3	<p><b>DIFFERENTIAL PRESSURE TRANSMITTER MODEL DPT-20, WIKA PN DPT-20-ZZZ-ADZZZ-AN-BBD250-7SVL-ZZZZA-4Z // CERT31- EGPT-AB- - - - - - - - - - -</b></p> <p>Differential Pressure Transmitter DPT-20 Housing material: Aluminum single chamber enclosure execution: compact / IP66/IP68 (0.2bar); NEMA 6P Output signal: 4...20 mA, 2-wire Electrical connection: 1/2" NPT female conduit Unit: bar Maximal working pressure: 160 bar (16 MPa / 2400 psi) Pressure range: -500 ... +500 mbar Process connection/mounting/material/venting: 1/4-18 NPT IEC 61518 / PN160 M10 / 316L / dorsal incl. 2 valves Diaphragm material: 316L Sealing (temperature range): FKM (-20 ... +85 °C) Accuracy: 0.065 % of span Filling of sensor: Silicone oil for regular applications (KN2) Certificates/Approvals: Certificate 3.1 Accuracy with inspection values listed Operating modes: Pressure measurement Density value: 1 Density unit: kg/dm<sup>3</sup> Linearization curve: linear Damping [s]: 1 s (default setting) Output signal low level in %: 0% Output signal low level in %: 100% Displayed value: differential pressure (acc. scaling) Inspection certificate 3.1 per EN 10204</p>	\$3,226.00	\$9,678.00

	<p>Certificate type: Inspection certificate acc. to EN 10204 3.1 Certificate Language: English and German Certificate for: process pressure transmitter Accuracy: Calibration values listed (traceable to national standards)</p>		
	<p><b>Delivery time</b> Item 1-3: 18-20 weeks after receiving your order and payment</p> <p>The delivery time of the items offered is subject to changes generated by events outside the company's control, such as:</p> <ol style="list-style-type: none"> <li>1. Climatic phenomena that do not allow the transport of raw material to the factory, local transport abroad of the manufactured material and/or international transport of the product.</li> <li>2. Normal functioning of Venezuelan and/or foreign customs.</li> <li>3. Disruption of public order in the country of origin, country of transit and/or final country.</li> <li>4. Criminal and/or terrorist acts.</li> <li>5. Any other event considered a major force.</li> </ol> <p><b>INCOTERMS</b> CIF - Georgetown Airport</p> <p><b>Warranty &amp; Country of Origin</b> 12 months, Germany</p> <p><b>Payment terms</b> *40% Pre-payment with PO *60% 30 days after receiving the invoice and instruments.</p> <p><b>Volume &amp; Weight</b> Weight and Volume to be advised</p>		

Please Transfer to Account of:  
Bank: Amerant Bank  
Address: 220 Alhambra Circle, Coral Gables,  
Florida 33134, USA  
ABA: 067010509  
Swift: MNB MUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS  
C.A.  
Account # 8303790106

<b>Subtotal</b>	<b>US\$</b>	<b>36,966.00</b>
<b>Freight</b>	<b>US\$</b>	<b>Included</b>
<b>Insurance</b>	<b>US\$</b>	<b>Included</b>
<b>Docs</b>	<b>US\$</b>	<b>Included</b>
<b>TOTAL</b>	<b>US\$</b>	<b>36,966.00</b>