



## Instrumentos y Equipos C.A

### INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,

Caracas, Venezuela 1080

Tel: 58-212-9784430, 9784433, 977.7654, 977.6346

Fax: 58-212-977.3613

E-mail: [sales@intech-ie.com](mailto:sales@intech-ie.com)

RIF J-30615033-1

Quote #

C-2026-0146

Date:

05/05/2026

Customer ID

CHEVRON PETROBOSCAN

#### Bill to:

#### CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY

Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela

Att: Rafael Azuaje - Depto de Procura

[Rafael.Azuaje@chevron.com](mailto:Rafael.Azuaje@chevron.com)

#### Ship to:

#### CHEVRON PETROBOSCAN Warehouse

Edo Anzoategui, Venezuela


Sales Rep.	Your #	Our #	Destiny	Terms	Validity
N. Carricatti	VEN-RFQ-PB-2026-207	C-2026-0146/PL @Justrite 04/05/2026	Venezuela	DDP Jose complex	30 days

Item	Cant	Description	Unit Price US\$	Total US\$
1	40	<p><b>30 Gallon, Portable Hughes Self-Contained Safety Shower with Eye/Face Wash, Mobile, Justrite - Hughes PN 40K45G</b></p> <p><u>The eye/face wash with high, ANSI-compliant flow rate features an integral lid connected to the water valve for automatic operation—activate by simply pulling down the lid. Easy-to-reach flow regulator valve positioned on the side of the bowl adjusts to suit the severity of the accident. Suitable for Class 1 Division 2 hazardous areas, as well as non-hazardous areas.</u></p> <p>Mobile eye/face wash and shower provides a continuous flow of water for 1-1/2 minutes High-performance quarter-turn ball valves made of 316L stainless steel endure the harshest environments and site conditions Covered, durable acrylic-capped ABS eye/face wash protects the bowl and eyewash diffusers from dust and debris Twin diffusers provide a gentle flow of aerated water and prevent further injury to the eyes</p> <p>Color White UPC 805042001738 Brand Justrite Capacity 30 gallon Net Weight, lbs 176 Net Weight, kg 80 Dimensions, Exterior 91" H x 29" W x 57.5" D Dimensions, Exterior 2315mm H x 734mm W x 1462mm D Water Inlet Size NPT 1/2 in quick release hose connector Minimum Operating Pressure 3 bar g, 43 PSI Maximum Operating Pressure 5.5 bar g, 79 PSI Water Flow Shower/Body Liters/min 75.7 Water Flow Shower/Body US Gal/min 20 Water Flow Eye/Face Liters/min 12</p>	\$18.010,00	\$720.400,00

		<p>Water Flow Eye/Face US Gal/min 3          Operating Valve Material Stainless steel, full bore, stay open ball valve          Eye/Face Wash Bowl Material Acrylic-Capped ABS Plastic          Mounting Type Portable          Pipework Material Stainless Steel          Activation Method Shower: Push down lever, Eye/Face: Pull lid down          Minimum Ambient Temperature, °F 41          Minimum Ambient Temperature, °C 5          Maximum Ambient Temperature, °F 95          Maximum Ambient Temperature, °C 35          Operation Duration, min 1.5</p>		
2	10	<p><b>Floor Mount, Open Stainless Steel Bowl, Self-Draining Hughes Combination Shower, Stainless Steel Pipe, Justrite - Hughes PN SD18GS85G</b></p> <p>Use outdoors, in warm climates with a maximum ambient operating temperature of 113°F (45°C) or below          Self-draining valve allows standing water to drain away from the standpipe ensuring the delivery of tepid water          Includes a universal safety shower sign for enhanced visibility  <u><b>Meets ANSI Z358.1 2014 and EN 15154 standards, supports OSHA requirements</b></u></p> <p>Brand Justrite          Net Weight, lbs 35.3          Net Weight, kg 16          Dimensions, Exterior 101.7" H x 25.8" W x 29.5" D          Dimensions, Exterior 2584mm H x 654mm W x 654mm D          Height Without Sign, inches 89.7          Height Without Sign, mm 2277          UL Classified to ANSI Z358.1-2014 Yes          Water Inlet Size NPT 1-1/4 in (F)          Minimum Operating Pressure 2 bar g, 29 PSI          Maximum Operating Pressure 6 bar g, 87 PSI          Water Flow Shower/Body Liters/min 76          Water Flow Shower/Body US Gal/min 20          Water Flow Eye/Face Liters/min 11.4          Water Flow Eye/Face US Gal/min 3          Material Specifications Nozzle: Nylon 6, Eye/facewash diffusers: Chrome plated brass with stainless steel mesh.          Operating Valve Material 316L Stainless          Eye/Face Wash Bowl Material Stainless Steel          Mounting Type Floor          Pipework Material Stainless Steel          Activation Method Shower: Hand lever, Eye/Face wash: Hand lever          Eye/Face Wash Bowl Interior          Dimensions          10" W x 10" D          254mm W x 254mm D          Minimum Ambient Temperature, °F 41          Minimum Ambient Temperature, °C 5          Maximum Ambient Temperature, °F 113          Maximum Ambient Temperature, °C 4</p>	\$4.430,00	\$44.300,00
3	20	<p><b>Block and bleed valve, 2-valve manifold, Single Stage, Model IV20, WIKA PN 47442334BR</b></p> <p>IV202 1/2 NPT M - 1/2 NPT F 316/316L VENT 1/4NPT F PTFE 6k          Block and bleed valve, 2-valve manifold</p>	\$490,00	\$9.800,00

		<p>Specifications according to data sheet: AC 09.19  Design: square, in-line  1/2 NPT male - 1/2 NPT female  Stainless steel 316/316L - 1.4401/1.4404 - S31600/S31603  without bracket hole  Vent connection: 1/4" NPT female with plug  Nominal pressure: 6000 psi / 420 bar  Material packing: PTFE  NACE MR0175 Sour Gas Service &amp; Inspection certificate 3.1, EN 10204, all wetted parts material</p>		
4	10	<p><b>IBC Outdoor Shed With Pallet, Forklift Pockets, Rolltop Doors, EcoPolyBlend™, Justrite - Hughes  PN 28677</b></p> <p>Reliable spill protection and safe storage for indoor IBCs  Complies with EPA SPCC regulations and meets fire codes  Ships fully assembled</p> <p><b><u>EPA, SPCC compliant and meets fire codes.</u></b>  (UDL) Uniformly Distributed Load - 1250 Lbs/567 Kgs. per drum, for DrumSheds™ and Pallets  Safe allowable uniform distributed load of 9000 lbs (4082 kg) based on a service temperature range of -30°F to 120°F (-39°C to 49°C)</p> <p>Brand Justrite  Pallet Quantity 1  Color Yellow  Material Specifications Recycled Polyethylene  UL Approval Yes  UL Environmental Approval Yes  OSHA Compliance Yes  EPA Compliance Yes  SPCC Compliance Yes  Percent Recycled 40  Sump Capacity - Gallons 372  Sump Capacity - liters 1408  Load Bearing Capacity, lbs 9000  Load Bearing Capacity, kg 4082  Dimensions, Exterior 103.75" H x 60.75" W x 68.5" D  Dimensions, Exterior 1543mm W x 2635mm H x 1740mm D  Net Weight, lbs 322.3  Net Weight, kg 146.2</p>	\$15.900,00	\$159.000,00
5	12	<p><b>Floor Mount, Open Stainless Steel Bowl, Self-Draining Hughes Combination Shower, Stainless Steel Pipe, Justrite - Hughes  PN SD18GS85G</b></p> <p>Use outdoors, in warm climates with a maximum ambient operating temperature of 113°F (45°C) or below  Self-draining valve allows standing water to drain away from the standpipe ensuring the delivery of tepid water  Includes a universal safety shower sign for enhanced visibility  <b><u>Meets ANSI Z358.1 2014 and EN 15154 standards, supports OSHA requirements</u></b></p> <p>Brand Justrite  Net Weight, lbs 35.3  Net Weight, kg 16  Dimensions, Exterior 101.7" H x 25.8" W x 29.5" D</p>	\$4.580,00	\$54.960,00

	<p>Dimensions, Exterior 2584mm H x 654mm W x 654mm D          Height Without Sign, inches 89.7          Height Without Sign, mm 2277          UL Classified to ANSI Z358.1-2014 Yes          Water Inlet Size NPT 1-1/4 in (F)          Minimum Operating Pressure 2 bar g, 29 PSI          Maximum Operating Pressure 6 bar g, 87 PSI          Water Flow Shower/Body Liters/min 76          Water Flow Shower/Body US Gal/min 20          Water Flow Eye/Face Liters/min 11.4          Water Flow Eye/Face US Gal/min 3          Material Specifications Nozzle: Nylon 6, Eye/facewash diffusers: Chrome plated brass with stainless steel mesh.          Operating Valve Material 316L Stainless          Eye/Face Wash Bowl Material Stainless Steel          Mounting Type Floor          Pipework Material Stainless Steel          Activation Method Shower: Hand lever, Eye/Face wash: Hand lever          Eye/Face Wash Bowl Interior          Dimensions          10" W x 10" D          254mm W x 254mm D          Minimum Ambient Temperature, °F 41          Minimum Ambient Temperature, °C 5          Maximum Ambient Temperature, °F 113          Maximum Ambient Temperature, °C 4</p>												
	<p><b>Delivery Time</b>  <b>ARAD/AROC,</b>  <b>Items: 2 – 4 weeks</b></p> <p><b>Payment Terms</b>  <b>50% Prepayment with Order</b>  <b>50% Payment 30 days DUE NET</b></p> <p><b>Packing</b>          Material will be Securely packed in wooden crates suitable for air freight and export.          Volume &amp; Weight (to be reconfirmed)  <b>To be advised – Aprox 13308 Lbs</b></p> <p><b>General Warranty:</b>          Our brands warrants its products to be free from defects in material and/or workmanship for a period of 18 months after delivery or 12 months from installation, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer’s obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall manufacturer’s be liable for damages in excess of the amount paid by the purchaser.</p> <p><b>Project Cancellation charges:</b></p> <table data-bbox="251 1690 901 1990"> <tr> <td>15%</td> <td>Up to submittal of Engineering &amp; Design Drawings and Documents (when applicable)</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering &amp; Design Drawings and Documents (when applicable)</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> <tr> <td>75%</td> <td>Within two weeks of production release</td> </tr> <tr> <td>100%</td> <td>Two weeks after production commences</td> </tr> </table>	15%	Up to submittal of Engineering & Design Drawings and Documents (when applicable)	25%	After submittal of Engineering & Design Drawings and Documents (when applicable)	50%	After material order placement and before production commences	75%	Within two weeks of production release	100%	Two weeks after production commences		
15%	Up to submittal of Engineering & Design Drawings and Documents (when applicable)												
25%	After submittal of Engineering & Design Drawings and Documents (when applicable)												
50%	After material order placement and before production commences												
75%	Within two weeks of production release												
100%	Two weeks after production commences												

		<b>NOTAS:</b>		
		<p><b>CONDICIONES DE PAGO</b></p> <p><b><u>COMPONENTE IMPORTADO</u></b></p> <p><i>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</i></p> <p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134 CUENTA NUMERO <b>8303790106</b> BENEFICIARIO <b>INTECH INSTRUMENTOS Y EQUIPOS C.A.</b> ABA 067010509 SWIFT MNBMUS33</p> <p><b><u>COMPONENTE NACIONAL (IVA)</u></b></p> <p><i>En BOLIVARES (Bs.) mediante transferencia bancaria</i></p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. - <b>0105-0011-73-1011-50499-5</b></p>		
		<p><b>OTRAS CONDICIONES</b></p> <ol style="list-style-type: none"> <li>1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos</li> <li>2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web <a href="http://www.bcv.org.ve">www.bcv.org.ve</a> y debera ser cancelado a la tasa oficial del día de pago o de la retención correspondiente</li> <li>3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.</li> <li>4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente</li> <li>5. Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta</li> <li>6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22.</li> <li>7. En caso de requerirse algún Tipo de Fianza de Anticipo, los Gastos de dicha Fianza serán reembolsables (en la moneda de su contratación) y por cuenta del Cliente CHEVRON, una vez recibidos los materiales en su almacén.</li> </ol> <p><b>In Tech</b> Instrumentos y Equipos, C.A. RIF: J-30615033-1 NIT: 0096996004</p> 		

Please Transfer to Account of:  
Bank: Amerant Bank  
Address: 220 Alhambra Circle, Coral Gables,  
Florida 33134, USA  
ABA: 067010509  
Swift: MNBMUS33  
  
Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS  
C.A.  
Account # 8303790106

<b>Subtotal</b>	<b>US\$</b>	<b>988,460.00</b>
<b>Freight</b>	<b>US\$</b>	<b>Incluido</b>
<b>Insurance</b>	<b>US\$</b>	<b>--</b>
<b>IVA 16%</b>	<b>US\$</b>	<b>158,153.60</b>
<b>IGTF 3%</b>	<b>US\$</b>	<b>---</b>
<b>TOTAL</b>	<b>US\$</b>	<b>1,146,613.60</b>