



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
 Suite 130, Sunrise, FL 33323
 Tel: 954-302-3187, 315-4781
 Fax: 954-838-7746
 E-mail: ibicorp@intech-ie.com
 Tax Certificate No. 16-8012998465-1

Quote # IBI-2026-0013
Date: Jan 28th, 2026
Customer ID PETROPIAR - VEN

Bill To:
INNOVATECH SUPPLY C.A.
 Av. Principal de Lecheria, Centro Empresarial Lecheria,
 Piso 5, Oficina 501, Edo Anzoategui
 Venezuela
 Tlf: +58-281-285.04.83
 Attn: Jose Triana
Jose.triana@innovatechsupply.com

Ship To:
 Custom Agent to be informed at La Guaira port,
 Venezuela

Your #	Our #	Sales Rep	CIF	SHIP VIA	Terms	Validity
Email	IBI-2026-0013 / ELZ	L. Zuñiga W. Brito	Maiquetia Port	BWPPD	See below	60 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	1	Eqp	<p>WIKA DUAL CHAMBER LEVEL SYSTEM - Redundant BNA/DU-2"/300/RF-M508-L/CS 60x2.77/60x2,77-MRF-ZVSS185/PN25/R48H Tags # 41-LIT-101; SAP 1119265</p> <p>Magnetic Level Gauge Type BNA-SD00 Pressure: 100 psi ; Temp.: 14°F...357 °F; Fluid density: 898 -914 kg/m³ Service: TOTAL Level Design code: ASME B31.3 Chamber dimensions: OD 60.3 x 2.77 mm (2" Sch. 10S) Duo stainless steel 316/316L (EN 1.4401/1.4404) Process connection: CS Flange ASME B16.5 2" 300# Form RF Distance C-to-C: 1219 mm Measuring range: 1219 mm Chamber end top: Pipe cap Chamber end bottom: CS Flange ASME B16.5 2" 300# Form RF Vent connection: Butt weld end 3/4" Drain connection: Butt weld end 3/4" Float: ZVSS185/PN25/R48H Dampening element: Dampening spring, bottom, with cover Gasket(s): Spiral wound type, SS 316L/Graphite Bolting: UNC series, carbon steel A193 Gr. B7 HDG / A194 Gr. 2H HDG Top stand-off (T): 100 mm Bottom stand-off (U): 250 mm Nameplate: Stainless steel laser printed Includes Bottom: Mag Trap -316ss/ CS construction -316SS 2" x 2" Tee with 2" CS 300# RFWN Flange -Bottom: CS 2" 300# RFWN with blind mating flange & 1/2" NPT Drain and Plug</p> <p>Dual Chamber (DUplus) Sidechamber: OD 60.3 x 2,77 mm (2" Sch. 10S) Location of secondary chamber: 3 o'clock (right side of MLG chamber) Process connection GT: CS Flange ASME B16.5 2" 300# Form RF Distance between chambers center lines: 200 mm</p>	\$37,800.00	\$37,800.00



		<p>Radar connection stand-off: 254 mm Side chamber bottom stand-off: 254 mm Insertion external sensor: With MRF-M1219 Level Indicator for Magnetic Level Gauge Type BMD-FA Measuring range: 1219 mm Housing material: Aluminum anodized Indicating elements: Stainless steel flaps Red & white Graduated scale: Aluminum engraved Graduation unit: inch <u>INCLUDES INSULATION JACKET</u> SS Tag Plate</p> <p>w/ RADAR Transmitter FX81.FADACKHXANAM eID: US34262802 Scope F : USA Approval A : FM (NI) CL I, II, III DIV2, GP ABCDFG Version / Material D : Exchangeable cable (ø2mm) with centering weight / 316 Probe : mounted Length (from seal surface) : 66.000 inch Length of rigid part : 3.937 inch Dimensions centering weight (diameter / height) : 1.77in / 1.18in (for 2" Schedule 40/80 and 3" Schedule 80/160) Process fitting / Material AC : Flange 2" 300lb RF, ASME B16.5 / 316/316L Seal / Second line of defense / Process temperature K : FFKM (Kalrez 6375) / without / -20...+200°C Electronics H : Two-wire 4 ... 20 mA/HART Supplementary electronics X : with Overvoltage protection of the supply cable 24 VDC , Model USB63-48.N Housing / Protection A : Aluminum single chamber / IP66/IP68 (0.2bar) Cable entry / Connection N : ½NPT / Blind plug Display/Adjustment module PLICSCOM A : mounted Certificates M : Yes Certificate / Standard : (C) Material test report – traceable (EN 10204 type 3.1 + NACE MR0175 + NACE MR0103) PMI test : RFA (positive material identification) incl. 3.1 inspection certificate Supply certificates : with goods Measurement loop identification label : of Stainless Steel Customer-specific adjustment : Yes - Unit : inch - 100 % (distance from seal surface) : 10.000 inch - 0 % (distance from seal surface) : 58.000 inch Linearization : No Min. process pressure in bar : -1.000 Max. process pressure in bar : 40.0</p>		
			Discount 10%	(\$ 3,780.00)
		<p>Technical Notes Included on each System:</p> <ul style="list-style-type: none"> - Approval Drawings - Hydrostatic Pressure Test 1.5x Flange Rating for 10 min @ ambient - NACE MR0175 Certificate - Material Test Reports with Tagging Information on each - Positive Material Identification w/o Carbon Content (10) shots per unit - 100% Xray - Liquid Dye Penetrant - Package/ Handling (per Lot) 		
		<p>Delivery Time 14 – 18 weeks ARAD</p> <p>Payment Terms Prepayment 100% with Order</p>		



INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
 Suite 130, Sunrise, FL 33323
 Tel: 954-302-3187, 315-4781
 Fax: 954-838-7746
 E-mail: ibicorp@intech-ie.com

		<p>Volume & Weight Weight and Volume to be advised IPPC Stamped Sea Freight Export Wood Crate</p> <p>Cci: Williams Brito – INTECH Lecherias</p>		
--	--	---	--	--

PLEASE TRANSFER TO OUR ACCOUNT AT:
 Branch Banking & Trust Co.
 450 North Pine Island
 Plantation, FL 33324
 Account #: 0140953040
 ABA# 053-101-121
 Routing/Transit Number: 2631-9138-7
 Swift Code: BRBTUS33

Subtotal	US \$	\$34,020.00
Freight	US \$	-
Insurance	US \$	-
Docs.	US \$	-
TOTAL	US \$	\$34,020.00

THANK YOU FOR YOUR BUSINESS