



# Sales Quote

**INDUSTRIAL BUSINESS INTL CORP**

1580 Sawgrass Corporate Parkway  
 Suite 130, Sunrise, FL 33323  
 Tel: 954-302-3187, 315-4781  
 Fax: 954-838-7746  
 E-mail: ibicorp@intech-ie.com  
 Tax Certificate No. 16-8012998465-1

**Quote #** IBI-2026-0017  
**Date:** Feb 06<sup>th</sup>, 2026  
**Customer ID** TEKNOMAQ CENTRO

<b>Bill To:</b>
<b>TEKNOMAQ CENTRO, S.A.</b> <b>RIF: J-31507069-3</b> Av. Henry Ford Zona Ind. Municipal Sur C.C. Boulevard Industrial Nave B local BC-19 Attn: Application and Purchase Department Tlfn: +58 241-8223162 / 414-4323577 Correo: compra@teknomaqcentro.com

<b>Ship To:</b>
El material se enviará al almacén/broker del cliente en Valencia, Carabobo.

Your #	Our #	Sales Rep	Incoterms - DDP	SHIP VIA	Terms	Validity
Budgetary	IBI-2026-0017	S. Méndez	CBB	Pick up	See below	30 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	20	Pc	<b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 1/2" RANGO 0 A 2000 PSI CONEXIÓN INFERIOR 1/2 NPT SIN RELLENO, WIKA PN 45849400</b>  Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0/2000 psi Process Connection: 1/2 NPT Connector location: lower mount Window: acrylic (PMMA) Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65	\$210.00	\$4,200.00
2	4	Pc	<b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 1/2" RANGO 0 A 100 PSI/BAR CONEXIÓN INFERIOR 1/4 NPT CON RELLENO, WIKA PN 80077030</b>  Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/100 psi 2nd Scale / Special Scale: 2nd scale bar Process Connection: 1/4 NPT Connector location: lower mount Window: acrylic (PMMA) Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L	\$218.00	\$872.00



			Case filling fluid: Glycerine Ingress Protection: IP 65		
3	4	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 21X.34 DIAL 4 1/2" RANGO 0 A 30 PSI CONEXIÓN INFERIOR 1/4 NPT SIN RELLENO, WIKA PN 80077031</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Copper Alloy          Case filling: without          Nominal size: 4.5"          Scale range: 0/30 psi          Process Connection: 1/4 NPT          Connector location: lower mount          Window: acrylic (PMMA)          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System CU-Alloy          Case filling fluid: prepared for filling          Ingress Protection: IP 65          Movement: Copper alloy</p>	\$191.00	\$764.00
4	5	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 1/2" RANGO 0 A 60 PSI/BAR CONEXIÓN INFERIOR 1/2 NPT SIN RELLENO, WIKA PN 80077033</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: with          Nominal size: 4.5"          Scale range: 0/60 psi          2nd Scale / Special Scale: 2nd scale bar          Process Connection: 1/2 NPT          Connector location: lower mount          Window: acrylic (PMMA)          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: Glycerine          Ingress Protection: IP 65</p>	\$218.00	\$1,090.00
5	6	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR 1/4 NPT, WIKA PN 80063019</b></p> <p>Explosion protection: without          Pressure range: 0...5000 psig          Process Connection: 1/4 NPT          wetted parts: stainless steel, Elgiloy Sensor          Accuracy: 0.05 % FS          Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204 (factory calibration)          incl. protective housing cap</p>	\$1,776.00	\$10,656.00



6	4	Pc	<p><b>MANOMETRO EN ACERO INOXIDABLE DIAL 2 1/2" RANGO 0 A 15 PSI/BAR CONEXIÓN INFERIOR 1/4 NPT CON RELLENO, WIKA PN 80077034</b></p> <p>Measuring System: Stainless Steel          Case filling: with          Nominal size: 2.5"          Scale range: 0/15 psi          2nd Scale / Special Scale: 2nd scale bar          Process Connection: 1/4 NPT          Connector location: lower mount          Window: Flat Instrument Glass          Pointer: standard pointer          IIoT: without          Accuracy Class: class 1.0          Material pressure element: Measuring System 316 SS          Case filling fluid: glycerine-water-mixture          Ingress Protection: IP 65</p>	\$187.00	\$748.00
7	32	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 1/2" RANGO 0 A 500 PSI/BAR CONEXIÓN INFERIOR 1/2 NPT CON RELLENO, WIKA PN 80077035</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: without          Nominal size: 4.5"          Scale range: 0/500 psi          2nd Scale / Special Scale: 2nd scale bar          Process Connection: 1/2 NPT          Connector location: lower mount          Window: acrylic (PMMA)          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- 1% (ASME B40.100 Grade 1A)          Material pressure element: Measuring System 316L          Case filling fluid: prepared for filling          Ingress Protection: IP 65</p>	\$202.00	\$6,464.00
8	2	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR 1/4 NPT, WIKA PN 80063019</b></p> <p>Explosion protection: without          Pressure range: 0...5000 psig          Process Connection: 1/4 NPT          wetted parts: stainless steel, Elgiloy Sensor          Accuracy: 0.05 % FS          Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204 (factory calibration)          incl. protective housing cap</p>	\$1,776.00	\$3,552.00
9	4	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR 1/4 NPT, WIKA PN 80063019</b></p>	\$1,776.00	\$7,104.00



			<p>Explosion protection: without Pressure range: 0...5000 psig Process Connection: 1/4 NPT wetted parts: stainless steel, Elgiloy Sensor Accuracy: 0.05 % FS Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204 (factory calibration) incl. protective housing cap</p>		
10	4	Pc	<p><b>MANOMETRO EN ACERO INOXIDABLE DIAL 4" RANGO 0 A 100 PSI CONEXIÓN TRASERA 1/2 NPT CON RELLENO, WIKA PN 70312195</b></p> <p>Measuring System: Stainless Steel Case filling: with Nominal size: 4" Scale range: 0/100 psi Process Connection: 1/2 NPT Connector location: lower back mount Mounting Flange/Bracket: Panel mount with Stainless steel U-clamp Window: laminated safety glass Pointer: standard pointer IIoT: without Accuracy Class: class 1.0 Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65</p>	\$209.00	\$836.00
11	4	Pc	<p><b>MANOMETRO EN ACERO INOXIDABLE DIAL 4" RANGO 0 A 400 PSI CONEXIÓN TRASERA 1/2 NPT CON RELLENO, WIKA PN 80077047</b></p> <p>Measuring System: Stainless Steel Case filling: with Nominal size: 4" Scale range: 0/400 psi Process Connection: 1/2 NPT Connector location: lower back mount Mounting Flange/Bracket: Panel mount with Stainless steel U-clamp Window: laminated safety glass Pointer: standard pointer IIoT: without Accuracy Class: class 1.0 Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65</p>	\$209.00	\$836.00
12	4	Pc	<p><b>MANOMETRO EN ACERO INOXIDABLE DIAL 4" RANGO 0 A 1000 PSI CONEXIÓN TRASERA 1/2 NPT CON RELLENO, WIKA PN 46634878</b></p> <p>Measuring System: Stainless Steel Case filling: with Nominal size: 4" Scale range: 0/1000 psi</p>	\$225.00	\$900.00



			<p>Process Connection: 1/2 NPT          Connector location: lower back mount          Mounting Flange/Bracket: Panel mount with Stainless steel U-clamp          Window: laminated safety glass          Pointer: standard pointer          IIoT: without          Accuracy Class: class 1.0          Material pressure element: Measuring System 316L          Case filling fluid: Glycerine          Ingress Protection: IP 65</p>		
13	4	Pc	<p><b>MANOMETRO EN ACERO INOXIDABLE DIAL 4" RANGO 0 A 1500 PSI          CONEXIÓN TRASERA 1/2 NPT CON RELLENO, WIKA          PN 80077048</b></p> <p>Measuring System: Stainless Steel          Case filling: with          Nominal size: 4"          Scale range: 0/1500 psi          Process Connection: 1/2 NPT          Connector location: lower back mount          Mounting Flange/Bracket: Panel mount with Stainless steel U-clamp          Window: laminated safety glass          Pointer: standard pointer          IIoT: without          Accuracy Class: class 1.0          Material pressure element: Measuring System 316L          Case filling fluid: Glycerine          Ingress Protection: IP 65</p>	\$225.00	\$900.00
14	4	Pc	<p><b>MANOMETRO EN ACERO INOXIDABLE DIAL 4 1/2" RANGO 0 A 200 PSI          CONEXIÓN TRASERA 1/2 NPT SIN RELLENO, WIKA          PN 80077051</b></p> <p>Nominal size: 4.5"          Measuring System: Stainless Steel          Case: With Pressure Blowout Disk          Scale range: 0/200 psi          Process Connection: 1/2 NPT          Connector location: lower back mount          Mounting Flange/Bracket: Front Flange, Stainless Steel          Accuracy Class: +/- .5% (ASME B40.100 2A)          Case surface: bare          Material pressure element: Measuring System 316L          Case filling fluid: prepared for filling          Window: laminated safety glass          Ingress Protection: IP 65</p>	\$336.00	\$1,344.00
15	4	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 1/2" RANGO          0 A 400 PSI CONEXIÓN INFERIOR 1/2 NPT CON RELLENO, WIKA          PN 9834057</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: with          Nominal size: 4.5"</p>	\$215.00	\$860.00



			<p>Scale range: 0/400 psi          Process Connection: 1/2 NPT          Connector location: lower mount          Window: acrylic (PMMA)          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: Glycerine          Ingress Protection: IP 65</p>		
16	4	Pc	<p><b>MANOMETRO EN ACERO INOXIDABLE DIAL 2 1/2" RANGO 0 A 1500 PSI CON SELLO DIAFRAGMA CON RELLENO, WIKA PN 80077062</b></p> <p>Case filling: with          Nominal size: 2.5"          Scale range: 0/1500 psi          Process Connection: Diaphragm Seal          Connector location: lower mount          Window: Polycarbonate          Pointer: adjustable pointer          IIoT: without          Accuracy Class: class 1.6          Material pressure element: Measuring System 316 SS          Case filling fluid: Glycerine          Ingress Protection: IP 65</p> <p>Diaphragm seal with threaded process connection          Diaphragm seal: Model 990.10          System fill fluid: KN 2 Silicone oil for general applications          Threaded connection: 1/4" NPT female          Flushing connection: 1 x 1/4 NPT female          Nominal pressure rating: PN 100          Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603          Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603          Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)</p>	\$1,138.00	\$4,552.00
17	4	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR 1/4 NPT, WIKA PN 80063019</b></p> <p>Explosion protection: without          Pressure range: 0...5000 psig          Process Connection: 1/4 NPT          wetted parts: stainless steel, Elgiloy Sensor          Accuracy: 0.05 % FS          Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204 (factory calibration)          incl. protective housing cap</p>	\$1,776.00	\$7,104.00
18	4	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 1/2" RANGO 0 A 600 PSI CONEXIÓN INFERIOR 1/4 NPT CON RELLENO, WIKA PN 9833884</b></p>	\$215.00	\$860.00



			<p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/600 psi Process Connection: 1/4 NPT Connector location: lower mount Window: acrylic (PMMA) Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.1 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65</p>		
19	2	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR 1/4 NPT, WIKA PN 80063019</b></p> <p>Explosion protection: without Pressure range: 0...5000 psig Process Connection: 1/4 NPT wetted parts: stainless steel, Elgiloy Sensor Accuracy: 0.05 % FS Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204 (factory calibration) incl. protective housing cap</p>	\$1,776.00	\$3,552.00
20	5	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR 1/4 NPT, WIKA PN 52821338</b></p> <p>Explosion protection: without Pressure range: 0...5000 psig Process Connection: 1/4 NPT Wetted parts: stainless steel, Elgiloy Sensor Accuracy: 0.05 % FS Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204 Communication: Bluetooth® with Bluetooth®-USB-Stick integrated data logger incl. protective housing cap</p>	\$1,996.00	\$9,980.00
21	20	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 1/2" RANGO 0 A 100 PSI/BAR CONEXIÓN INFERIOR 1/4 NPT CON RELLENO, WIKA PN 80077030</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/100 psi 2nd Scale / Special Scale: 2nd scale bar Process Connection: 1/4 NPT Connector location: lower mount Window: acrylic (PMMA)</p>	\$218.00	\$4,360.00



			<p>Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: Glycerine          Ingress Protection: IP 65</p>		
22	20	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 1/2" RANGO 0 A 100 PSI/BAR CONEXIÓN INFERIOR 1/4 NPT CON RELLENO, WIKA PN 80077030</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: with          Nominal size: 4.5"          Scale range: 0/100 psi          2nd Scale / Special Scale: 2nd scale bar          Process Connection: 1/4 NPT          Connector location: lower mount          Window: acrylic (PMMA)          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: Glycerine          Ingress Protection: IP 65</p>	\$218.00	\$4,360.00
23	20	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 1/2" RANGO 0 A 30 PSI CONEXIÓN INFERIOR 1/4 NPT SIN RELLENO, WIKA PN 9834567</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: without          Nominal size: 4.5"          Scale range: 0/30 psi          Process Connection: 1/4 NPT          Connector location: lower mount          Window: acrylic (PMMA)          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: prepared for filling          Ingress Protection: IP 65</p>	\$198.00	\$3,960.00
24	30	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 1/2" RANGO 0 A 30 PSI CONEXIÓN INFERIOR 1/4 NPT SIN RELLENO, WIKA PN 9834567</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: without          Nominal size: 4.5"          Scale range: 0/30 psi          Process Connection: 1/4 NPT          Connector location: lower mount</p>	\$251.00	\$7,530.00



			<p>Window: acrylic (PMMA)          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: prepared for filling          Ingress Protection: IP 65</p>		
25	20	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 63X.34 DIAL 4 ½" RANGO 0 A 30 INH2O CONEXIÓN INFERIOR ¼ NPT, WIKA PN 80077053</b></p> <p>Case: Black Plastic          Accuracy Class: +/- 2/1/2% (ASME B40.100 Grade A)          Measuring System: Stainless Steel          Case filling: without          Nominal size: 4.5"          Unit: inH2O          Scale range: 0 inH2O...30 inH2O          Second dial scale: mbar          Process Connection: 1/4 NPT          Connector location: lower mount          Movement: stainless steel          Package: Single packing          Window: flat instrument glass</p>	\$873.00	\$17,460.00
26	30	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 63X.34 DIAL 4 ½" RANGO 0 A 30 INH2O CONEXIÓN INFERIOR ¼ NPT, WIKA PN 80077053</b></p> <p>Case: Black Plastic          Accuracy Class: +/- 2/1/2% (ASME B40.100 Grade A)          Measuring System: Stainless Steel          Case filling: without          Nominal size: 4.5"          Unit: inH2O          Scale range: 0 inH2O...30 inH2O          Second dial scale: mbar          Process Connection: 1/4 NPT          Connector location: lower mount          Movement: stainless steel          Package: Single packing          Window: flat instrument glass</p>	\$873.00	\$26,190.00
27	299	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 400 PSI CONEXIÓN INFERIOR ¼ NPT SIN RELLENO, WIKA PN 50291831</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: without          Nominal size: 4.5"          Scale range: 0/400 psi          Process Connection: 1/4 NPT          Connector location: lower mount          Window: acrylic (PMMA)</p>	\$198.00	\$59,202.00



			<p>Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: prepared for filling          Ingress Protection: IP 65</p>		
28	386	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 200 PSI CONEXIÓN INFERIOR ¼ NPT SIN RELLENO, WIKA PN 50982096</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: without          Nominal size: 4.5"          Scale range: 0/200 psi          Process Connection: 1/4 NPT          Connector location: lower mount          Window: acrylic (PMMA)          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: prepared for filling          Ingress Protection: IP 65</p>	\$198.00	\$76,428.00
29	117	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 21X.34 DIAL 4 ½" RANGO 0 A 600 PSI CONEXIÓN INFERIOR ¼ NPT SIN RELLENO, WIKA PN 80077054</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Copper Alloy          Case filling: without          Nominal size: 4.5"          Scale range: 0/600 psi          Process Connection: 1/4 NPT          Connector location: lower mount          Window: Flat Instrument Glass          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System CU-Alloy          Case filling fluid: prepared for filling          Ingress Protection: IP 65          Movement: Copper alloy</p>	\$197.00	\$23,049.00
30	80	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 26X.34 DIAL 4 ½" RANGO 0 A 1000 PSI CONEXIÓN INFERIOR ¼ NPT SIN RELLENO, WIKA PN 80077055</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Monel          Case filling: without          Nominal size: 4.5"          Scale range: 0/1000 psi          Process Connection: 1/4 NPT</p>	\$507.00	\$40,560.00



			<p>Connector location: lower mount          Window: Flat Instrument Glass          Restrictor: Monel, Threaded, Orifice 0.6mm(0.024 inches)          Pointer: adjustable pointer          Material pressure element: Measuring System MONEL          Case filling fluid: prepared for filling          Ingress Protection: IP 65</p>		
31	10	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 600 PSI/BAR CONEXIÓN INFERIOR ½ NPT SIN RELLENO, WIKA PN 80077056</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: without          Nominal size: 4.5"          Scale range: 0/600 psi          2nd Scale / Special Scale: 2nd scale bar          Process Connection: 1/2 NPT          Connector location: lower mount          Window: acrylic (PMMA)          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- 1% (ASME B40.100 Grade 1A)          Material pressure element: Measuring System 316L          Case filling fluid: prepared for filling          Ingress Protection: IP 65</p>	\$202.00	\$2,020.00
32	50	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 2000 PSI CONEXIÓN CON SELLO DIAFRAGMA SIN RELLENO, WIKA PN 80077059</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: without          Nominal size: 4.5"          Scale range: 0/2000 psi          Process Connection: Diaphragm Seal          Connector location: lower mount          Window: Flat Instrument Glass          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          IIoT: without          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: prepared for filling          Ingress Protection: IP 65</p> <p>Diaphragm seal with threaded process connection          Diaphragm seal: Model 990.10          System fill fluid: KN 2 Silicone oil for general applications          Threaded connection: 1/2" NPT female          Flushing connection: 1 x 1/4 NPT female          Nominal pressure rating: PN 250          Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS</p>	\$2,947.00	\$147,350.00



			<p>S31603 Diaphragm material: Inconel 625 2.4856; UNS N06625 Lower housing material: in (Inconel 625 2.4856; UNS N06625) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Inconel 625 2.4856; UNS N06625)</p>		
33	11	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR ¼ NPT, WIKA PN 80063019</b></p> <p>Explosion protection: without Pressure range: 0...5000 psig Process Connection: 1/4 NPT wetted parts: stainless steel, Elgiloy Sensor Accuracy: 0.05 % FS Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204 (factory calibration) incl. protective housing cap</p>	\$1,776.00	\$19,536.00
34	2	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 400 PSI CONEXIÓN INFERIOR ½ NPT CON RELLENO, WIKA PN 9834057</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/400 psi Process Connection: 1/2 NPT Connector location: lower mount Window: acrylic (PMMA) Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65</p>	\$215.00	\$430.00
35	2	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 200 PSI CONEXIÓN INFERIOR ½ NPT CON RELLENO, WIKA PN 80077060</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/200 psi Process Connection: 1/2 NPT Connector location: lower mount Window: Flat Instrument Glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- 1% (ASME B40.100 Grade 1A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine</p>	\$220.00	\$440.00



			Ingress Protection: IP 65		
36	2	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 100 PSI CONEXIÓN INFERIOR ½ NPT CON RELLENO, WIKA PN 80077061</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/100 psi Process Connection: 1/2 NPT Connector location: lower mount Window: Flat Instrument Glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- 1% (ASME B40.100 Grade 1A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65</p>	\$220.00	\$440.00
37	2	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 600 PSI CONEXIÓN INFERIOR ½ NPT CON RELLENO, WIKA PN 80069373</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/600 psi Process Connection: 1/2 NPT Connector location: lower mount Window: Flat Instrument Glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65</p>	\$220.00	\$440.00
38	3	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR ¼ NPT, WIKA PN 80063019</b></p> <p>Explosion protection: without Pressure range: 0...5000 psig Process Connection: 1/4 NPT wetted parts: stainless steel, Elgiloy Sensor Accuracy: 0.05 % FS Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204 (factory calibration) incl. protective housing cap</p>	\$1,776.00	\$5,328.00
39	10	Pc	<p><b>MANOMETRO EN ACERO INOXIDABLE DIAL 2 ½" RANGO 0 A 1500 PSI CON SELLO DIAFRAGMA CON RELLENO, WIKA PN 80077062</b></p>	\$1,138.00	\$11,380.00



			<p>Case filling: with          Nominal size: 2.5"          Scale range: 0/1500 psi          Process Connection: Diaphragm Seal          Connector location: lower mount          Window: Polycarbonate          Pointer: adjustable pointer          IIoT: without          Accuracy Class: class 1.6          Material pressure element: Measuring System 316 SS          Case filling fluid: Glycerine          Ingress Protection: IP 65</p> <p>Diaphragm seal with threaded process connection          Diaphragm seal: Model 990.10          System fill fluid: KN 2 Silicone oil for general applications          Threaded connection: 1/4" NPT female          Flushing connection: 1 x 1/4 NPT female          Nominal pressure rating: PN 100          Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603          Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603          Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)</p>		
40	10	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR ¼ NPT, WIKA PN 80063019</b></p> <p>Explosion protection: without          Pressure range: 0...5000 psig          Process Connection: 1/4 NPT          wetted parts: stainless steel, Elgiloy Sensor          Accuracy: 0.05 % FS          Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204 (factory calibration)          incl. protective housing cap</p>	\$1,776.00	\$17,760.00
41	5	Pc	<p><b>MANOMETRO EN ACERO INOXIDABLE DIAL 2 ½" RANGO 0 A 1500 PSI CON SELLO DIAFRAGMA CON RELLENO, WIKA PN 80077062</b></p> <p>Case filling: with          Nominal size: 2.5"          Scale range: 0/1500 psi          Process Connection: Diaphragm Seal          Connector location: lower mount          Window: Polycarbonate          Pointer: adjustable pointer          IIoT: without          Accuracy Class: class 1.6          Material pressure element: Measuring System 316 SS          Case filling fluid: Glycerine          Ingress Protection: IP 65</p>	\$1,138.00	\$5,690.00



			<p>Diaphragm seal with threaded process connection          Diaphragm seal: Model 990.10          System fill fluid: KN 2 Silicone oil for general applications          Threaded connection: 1/4" NPT female          Flushing connection: 1 x 1/4 NPT female          Nominal pressure rating: PN 100          Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603          Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603          Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)</p>		
42	20	Pc	<p><b>MANOMETRO EN ACERO INOXIDABLE DIAL 4" RANGO 0 A 300 PSI CONEXIÓN INFERIOR 1/2 NPT CON RELLENO, WIKA PN 80069368</b></p> <p>Measuring System: Stainless Steel          Case filling: with          Nominal size: 4"          Scale range: 0/300 psi          Process Connection: 1/2 NPT          Connector location: lower mount          Window: Polycarbonate          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: glycerine-water-mixture          Ingress Protection: IP 65</p>	\$208.00	\$4,160.00
43	12	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 1/2" RANGO 0 A 1000 PSI CONEXIÓN INFERIOR 1/2 NPT CON RELLENO, WIKA PN 52954484</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: with          Nominal size: 4.5"          Scale range: 0/1000 psi          Process Connection: 1/2 NPT          Connector location: lower mount          Window: acrylic (PMMA)          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: Glycerine          Ingress Protection: IP 65</p>	\$226.00	\$2,712.00
44	12	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 1/2" RANGO 0 A 600 PSI CONEXIÓN INFERIOR 1/2 NPT CON RELLENO, WIKA PN 80076271</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: with          Nominal size: 4.5"          Scale range: 0/600 psi</p>	\$253.00	\$3,036.00



			<p>Process Connection: 1/2 NPT          Connector location: lower mount          Window: laminated safety glass          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: Silicone, 1000 cSt          Ingress Protection: IP 65</p>		
45	10	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR 1/4 NPT, WIKA PN 52821338</b></p> <p>Explosion protection: without          Pressure range: 0...5000 psig          Process Connection: 1/4 NPT          Wetted parts: stainless steel, Elgiloy Sensor          Accuracy: 0.05 % FS          Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204          Communication: Bluetooth® with Bluetooth®-USB-Stick          integrated data logger          incl. protective housing cap</p>	\$1,996.00	\$19,960.00
46	24	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 1/2" RANGO 0 A 600 PSI CONEXIÓN CON SELLO DIAFRAGMA CON RELLENO, WIKA PN 80077074</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: with          Nominal size: 4.5"          Scale range: 0/600 psi          Process Connection: Diaphragm Seal          Connector location: lower mount          Window: acrylic (PMMA)          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: Glycerine          Ingress Protection: IP 65</p> <p>Diaphragm seal with threaded process connection          Diaphragm seal: Model 990.10          System fill fluid: KN 2 Silicone oil for general applications          Threaded connection: 1" NPT male          Flushing connection: 1 x 1/4 NPT female          Nominal pressure rating: PN 100          Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603          Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603          Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)          Gasket: FPM max. 200°C          Fastening parts: Retainer flange and bolts in stainless steel</p>	\$1,229.00	\$29,496.00



			Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)		
47	12	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 600 PSI CONEXIÓN INFERIOR ½ NPT SIN RELLENO, WIKA PN 50255657</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: without          Nominal size: 4.5"          Scale range: 0/600 psi          Process Connection: 1/2 NPT          Connector location: lower mount          Window: laminated safety glass          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Material pressure element: Measuring System 316L          Case filling fluid: prepared for filling          Ingress Protection: IP 65</p>	\$211.00	\$2,532.00
48	40	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 100 PSI CONEXIÓN INFERIOR ¼ NPT SIN RELLENO, WIKA PN 76203509</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: without          Nominal size: 4.5"          Scale range: 0/100 psi          Process Connection: 1/4 NPT          Connector location: lower mount          Window: Flat Instrument Glass          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: prepared for filling          Ingress Protection: IP 65</p>	\$204.00	\$8,160.00
49	12	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 100 PSI CONEXIÓN INFERIOR ¼ NPT SIN RELLENO, WIKA PN 76203509</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: without          Nominal size: 4.5"          Scale range: 0/100 psi          Process Connection: 1/4 NPT          Connector location: lower mount          Window: Flat Instrument Glass          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          IIoT: without          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: prepared for filling</p>	\$204.00	\$2,040.00



			Ingress Protection: IP 65		
50	2	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR 1/4 NPT, WIKA PN 52821338</b></p> <p>Explosion protection: without Pressure range: 0...5000 psig Process Connection: 1/4 NPT Wetted parts: stainless steel, Elgiloy Sensor Accuracy: 0.05 % FS Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204 Communication: Bluetooth® with Bluetooth®-USB-Stick integrated data logger incl. protective housing cap</p>	\$1,996.00	\$3,992.00
51	3	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR 1/4 NPT, WIKA PN 52821338</b></p> <p>Explosion protection: without Pressure range: 0...5000 psig Process Connection: 1/4 NPT Wetted parts: stainless steel, Elgiloy Sensor Accuracy: 0.05 % FS Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204 Communication: Bluetooth® with Bluetooth®-USB-Stick integrated data logger incl. protective housing cap</p>	\$1,996.00	\$5,988.00
52	2	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR 1/4 NPT, WIKA PN 52821338</b></p> <p>Explosion protection: without Pressure range: 0...5000 psig Process Connection: 1/4 NPT Wetted parts: stainless steel, Elgiloy Sensor Accuracy: 0.05 % FS Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204 Communication: Bluetooth® with Bluetooth®-USB-Stick integrated data logger incl. protective housing cap</p>	\$1,996.00	\$3,992.00
53	3	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR 1/4 NPT, WIKA PN 52821338</b></p> <p>Explosion protection: without Pressure range: 0...5000 psig Process Connection: 1/4 NPT Wetted parts: stainless steel, Elgiloy Sensor</p>	\$1,996.00	\$5,988.00



			<p>Accuracy: 0.05 % FS          Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204          Communication: Bluetooth® with Bluetooth®-USB-Stick          integrated data logger          incl. protective housing cap</p>		
54	2	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR ¼ NPT, WIKA PN 52821338</b></p> <p>Explosion protection: without          Pressure range: 0...5000 psig          Process Connection: 1/4 NPT          Wetted parts: stainless steel, Elgiloy Sensor          Accuracy: 0.05 % FS          Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204          Communication: Bluetooth® with Bluetooth®-USB-Stick          integrated data logger          incl. protective housing cap</p>	\$1,996.00	\$3,992.00
55	25	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 200 PSI/BAR CONEXIÓN INFERIOR ½ NPT CON RELLENO, WIKA PN 80077077</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: with          Nominal size: 4.5"          Scale range: 0/200 psi          2nd Scale / Special Scale: 2nd scale bar          Process Connection: 1/2 NPT          Connector location: lower mount          Window: Flat Instrument Glass          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: Glycerine          Ingress Protection: IP 65</p>	\$223.00	\$5,575.00
56	10	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 400 PSI CONEXIÓN INFERIOR ½ NPT CON RELLENO, WIKA PN 9834057</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: with          Nominal size: 4.5"          Scale range: 0/400 psi          Process Connection: 1/2 NPT          Connector location: lower mount          Window: acrylic (PMMA)          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer</p>	\$215.00	\$2,150.00



			<p>Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: Glycerine          Ingress Protection: IP 65</p>		
57	10	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 200 PSI CONEXIÓN INFERIOR ½ NPT CON RELLENO, WIKA PN 80077060</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: with          Nominal size: 4.5"          Scale range: 0/200 psi          Process Connection: 1/2 NPT          Connector location: lower mount          Window: Flat Instrument Glass          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- 1% (ASME B40.100 Grade 1A)          Material pressure element: Measuring System 316L          Case filling fluid: Glycerine          Ingress Protection: IP 65</p>	\$220.00	\$2,200.00
58	10	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 100 PSI CONEXIÓN INFERIOR ½ NPT CON RELLENO, WIKA PN 80077061</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: with          Nominal size: 4.5"          Scale range: 0/100 psi          Process Connection: 1/2 NPT          Connector location: lower mount          Window: Flat Instrument Glass          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- 1% (ASME B40.100 Grade 1A)          Material pressure element: Measuring System 316L          Case filling fluid: Glycerine          Ingress Protection: IP 65</p>	\$220.00	\$2,200.00
59	20	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 600 PSI CONEXIÓN INFERIOR ½ NPT CON RELLENO, WIKA PN 80077082</b></p> <p>Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: with          Nominal size: 4.5"          Scale range: 0/600 psi          Process Connection: 1/2 NPT          Connector location: lower mount          Window: Flat Instrument Glass          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer</p>	\$247.00	\$4,940.00



			<p>Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: Silicone, 1000 cSt          Ingress Protection: IP 65</p>		
60	8	Pc	<p><b>MANOMETRO CAJA TERMOPLASTICA MODELO 23X.34 DIAL 4 ½" RANGO 0 A 600 PSI CONEXIÓN CON SELLO DIAFRAGMA CON RELLENO, WIKA PN 80077074</b></p> <p>Specifications according to data sheet: APM 02.10          Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: with          Nominal size: 4.5"          Scale range: 0/600 psi          Process Connection: Diaphragm Seal          Connector location: lower mount          Window: acrylic (PMMA)          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Accuracy Class: +/- .5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: Glycerine          Ingress Protection: IP 65</p> <p>Diaphragm seal with threaded process connection          Diaphragm seal: Model 990.10          System fill fluid: KN 2 Silicone oil for general applications          Threaded connection: 1" NPT male          Flushing connection: 1 x 1/4 NPT female          Nominal pressure rating: PN 100          Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603          Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603          Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)          Gasket: FPM max. 200°C          Fastening parts: Retainer flange and bolts in stainless steel          Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)</p>	\$1,229.00	\$9,832.00
61	2	Pc	<p><b>MANOMETRO DIGITAL EN ACERO INOXIDABLE DIAL 5" RANGO 0 A 5000 PSI CONEXIÓN INFERIOR ¼ NPT, WIKA PN 80063019</b></p> <p>Explosion protection: without          Pressure range: 0...5000 psig          Process Connection: 1/4 NPT          wetted parts: stainless steel, Elgiloy Sensor          Accuracy: 0.05 % FS          Type of certificate: Acceptance test certificate 3.1 in accordance with DIN EN 10204 (factory calibration)          incl. protective housing cap</p>	\$1,776.00	\$3,552.00
			<p><b>Delivery Time</b>          Items 1-26,30-61: 12-14 weeks after receipt of order and payment (subject to changes)          Items 27-29: 14-16 weeks after receipt of order and payment (subject to changes)</p>		



**INDUSTRIAL BUSINESS INTL CORP**

1580 Sawgrass Corporate Parkway  
 Suite 130, Sunrise, FL 33323  
 Tel: 954-302-3187, 315-4781  
 Fax: 954-838-7746  
 E-mail: ibicorp@intech-ie.com

		<p>The delivery time of the items offered is subject to changes generated by events outside the company's control, such as:</p> <ol style="list-style-type: none"> <li>1. Climatic phenomena that do not allow the transport of raw material to the factory, local transport abroad of the manufactured material and/or international transport of the product.</li> <li>2. Normal functioning of Venezuelan and/or foreign customs.</li> <li>3. Disruption of public order in the country of origin, country of transit and/or final country.</li> <li>4. Criminal and/or terrorist acts.</li> <li>5. Any other event considered major force.</li> </ol> <p><b>Payment terms</b>          100% with purchase order</p> <p><b>Volume &amp; Weight</b>          Weight / Volume to be advised</p>		
--	--	--	--	--

**PLEASE TRANSFER TO OUR ACCOUNT AT:**  
 Branch Banking & Trust Co.  
 450 North Pine Island  
 Plantation, FL 33324  
 Account #: 0140953040  
 ABA# 053-101-121  
 Routing/Transit Number: 2631-9138-7  
 Swift Code: BRBTUS33

**THANK YOU FOR YOUR BUSINESS**

<b>Subtotal</b>	<i>US \$</i>	667,584.00
<b>Freight</b>	<i>US \$</i>	Included
<b>Insurance</b>	<i>US \$</i>	Included
<b>Docs.</b>	<i>US \$</i>	Included
<b>TOTAL</b>	<i>US \$</i>	<b>667,584.00</b>