



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
 Suite 130, Sunrise, FL 33323
 Tel: 954-302-3187, 315-4781
 Fax: 954-838-7746
 E-mail: ibicorp@intech-ie.com
 Tax Certificate No. 16-8012998465-1

Quote # IBI-2026-0037
Date: 03/17/26
Customer ID PDVSA - CRP

Bill To:
PDVSA CRP Complejo Refinacion AMUAY, Punto Fijo, Edo Falcon, Venezuela Attn: Biangreg Barrera – Ing. De Instrum.y Control Gerencia Confiabilidad de Instrumentos ingbiangregbarrera@gmail.com

Ship To:
Custom Agent in Venezuela to be advised

Your #	Our #	Sales Rep	Incoterms -CIF	SHIP VIA	Terms	Validity
Budgetary	IBI-2026-0037 225244	L. Zuniga G.Novoa	Maiquetia Airport	BWPPD	Prepayment	60 days

Item	Qty	Units	Description	Unit Pr (EUR)	Total (EUR)
1	1	Sys	ENOTEC Oxygen and Coe Analyzer System COMTEC 6000 Gas EX to be used on Unit DCAy, Exit of Regenerator R-2402 of FCC Tag # :A-401 Each System Includes: 1 Pcs KEX6A023E2AS COMTEC In situ probe O2/COe w. solenoid valve sintered metal filter & protect. tube Probe Probe type: KEX-6A02 Insertion depth: 863 mm Filter unit: sintered metal filter incl. flame arrestor Test gas shut-off: stainless steel solenoid valve, U~ = 115 VAC ATEX marking: II 2G Ex db IIC T3 Gb IP code terminal box: IP66 (color: RAL 6029) Probe material: stainless steel (SS316) Protection tube material: stainless steel (SS316) Protection tube flange: ANSI 3" 150 lbsr RF Flue gas temp. continuous: 500 °C limit due to T3-certificate Ambient temperature: -40 °C to +70 °C Flue gas pressure: ±50 mbar (atmospheric pressure) Flue velocity: 0-10 m/s MXP-COe-Sensor Measuring range COe: 1 range, min.: 0-1000 ppm / max.: 0-5000 ppm (factory adjustable, other ranges on request) Measurement accuracy COe: < 5.0 % of range end Measuring principle: MXP sensor for COe/Combustibles MLT O2 sensor Response time: < 1 s (with test gas) T-90-time: < 5 s (with test gas) Measurement accuracy O2: < 0.5 % of measured value or 0.02 Vol. % O2 (higher value valid) Measuring principle: Zirconium oxide Sensor temperature: 800 °C The multi-layer MLT protective coatings extend the life of the oxygen sensor, especially in flue gases containing SO2 and CO. Dust particles which pass through the probe's diffusion filter to the O2 sensor are largely kept away from the active platinum electrode of the O2 sensor by these protective layers. Notice	52,170.00	52,170.00

		<p>ENOTEC InSitu analyzers measure O2 molecules direct in the flue gas of combustion plants or in comparable inert gas mixtures. If oxidizable gas components are contained in this gas mixture, contact ENOTEC. Other specifications on request!</p> <p>1 Pc SME-5D1F7M00 COMTEC electronic with HART interface ATEX II 2G Ex d IIC T6 Gb (2 housings)</p> <p>Unit housing SME-5D: 2 cast aluminum field housings with windows, mounted on rails; RAL 6029 Protection: IP66 ATEX marking: ATEX II 2GD Ex d IIC T6 Gb IECEX marking: Ex db IIC T6 Gb Dimensions: approx. 356x700x249 mm (HxWxD) Weight: approx. 35 kg, depending on options up to 36 kg Line voltage: 115 V AC \pm 10 %, f = 50/60Hz Heater voltage: 115 V AC Ambient temperature: -20 °C to +55 °C Sensor signal value memory: on and off switchable, active during calibration O2 output: configurable 0/4-20 mA, active (source), galvanically isolated, 500 Ω max. COe output: 4-20 mA, active (source), galvanically isolated, 500 Ω max. Relays output: system failure, maintenance, solenoid valve probe, measuring ranges: 1 limit value each for O2 and Coe (alternatively assignable by factory on request) Digital input: calibration release, O2 measuring range selection (alternatively assignable by factory on request) LED status indicators: alarm, error and maintenance Calibration: 1-point with instrument air or 2-point with air and test gas bottle by external supply and piping Automatic calibration*: execution by time interval (1-90 days) or by external release signal Pneumatic integrated (option): flow monitoring for test gas and reference air, automatic apply of test air and test gas on calibration, requires on-site instrument air and test gas supply of the electronics Interface: ENOTEC REMOTE, HART Operation: keypad, soft keys, menu-driven, self-explanatory LC-display Language: English/German <u>Failsafe heater control (HCU-0001)</u> ATEX approved failsafe heater shut down, if the sensor temperature exceeds the set point for the internal probe heater to guarantee the probe temperature class T3. <u>COMTEC MXP sensor board</u> Upgrade of the SME-5D electronic unit for the measurement of the signals from the InSitu COe sensor. The COe output signal is a trend signal for the plausibility check of the O2 signal. An increase of O2 signals will cause a decrease of the COe signal and vice versa. The COe sensor response test can be done with a test gas, which does contain CO. Depending on the flue gas composition the test gas must contain SO2 as well for cross sensitivity compensation. * Pneumatic unit required. Other specifications on request!</p> <p>1 Pcs SME-5000060 SME-5D test gas and reference air supply for instrument air, EEx d ACAL</p> <p>The pneumatic unit in a separate field case can be installed beside the electronic unit and is suitable for customers instrument air. The installed flow meters, for reference air and test air (test gas), allow the gas flow control visual during fully automatic calibration. With installed EExd solenoid valve test gas/test air is supplied to the probe. Supplied with 3,5 m cable and one compound cable gland (pre-installed) included. Technical data: Protection: IP 66 Color: green (RAL 6029) Material: steel sheet case Dimensions: approx. 400x300x210 mm (HxWxD) Weight: approx. 10 kg Connection: 1/4" clamping ring</p>		
--	--	---	--	--



		<p>Electric con.: M20 Power supply solenoid valve: 115 V AC (from electronic unit SME-5D) Solenoid valve certificate: II 2G Ex eb mb IIC T4 Gb Air pressure: 2-10 bar Air quality: dry and oil-free, -40 °C dew point Air volume: 30 l/h (measuring), 150-180 l/h (calibration) Test gas pressure: 0.5 to 3.0 bar</p> <p>1 pcs 1-140955-01 Mounting plate and frame for SME-5D and pneumatic unit</p> <p>1 pcs WSK-0002 Weather protection roof for SME-5D.... DxWxH:1000x500x600mm; SS316 2mm</p> <p>1 pc ADP-6000 Counter flange ANSI 4" 150 lbs S235JR tube: without, inner diameter: 90,0 mm</p> <p>50 mts FEP-0007 Probe cable COMTEC, OXITEC / COMTEC ATEX connection probe <> electronic unit The probe signal cable is a special cable supplied by ENOTEC to transmit the sensor signals, the signals of the thermocouple and the probe heater voltages between probe and electronic unit. Cable insulation is ultra violet resistant and flame resistant.</p> <p>1 Set (2 pcs) FEP-0007-CC2 . COMTEC cable gland resin 3/4" NPT, cable: FEP-0007</p> <p>50 Mts FEP-0002 ENOTEC probe pneumatic cable connection probe <> electronic unit The ENOTEC pneumatic cable is a special double pneumatic hose (2x6x1 mm) to transport the reference air and, if required the test gas to the probe. Max. distance between probe and electronic 150 m for pneumatic units using customer instrument air supply, or max. 50 m for internal pump versions. Cable insulation is flame retardant and UV-resistant.</p> <p>50 Mts FEP-0011 ENOTEC solenoid valve control cable connection ATEX probe <> electronic unit The solenoid control cable between the electronic unit and the probe transmits power to the optional testgas solenoid valve. Max. distance standard between probe and electronic unit is 150 meter. Cable insulation flame resistant and ultra violet resistant.</p> <p>1 pcs FEP-0011-CG1 1 pcs. cable gland resin 1/2"NPT, cable type: FEP-0011</p> <p>1 pcs VKS5D1 Packing costs for 1 ENOTEC analyzer 2 boxes: probe, electronic & accessories</p> <p>1pcs VKPNEU Packing costs for PNEUMATIC UNIT</p> <p>1 SERV001 On-site Assistance on Commissioning, Start-up & Training on ENOTEC Systems to be done on PDVSA CRP, Amuay Refinery Jobsite, Venezuela, by One (1) Certified ENOTEC Technician</p>		
--	--	--	--	--



		<p>Delivery Time 8 – 9 wks after receiving your PO and payment</p> <p>Commissioning Services must be scheduled in advance (see Service Notes) Equipment must be installed on site before technician arrival</p> <p>Payment terms 100% Prepayment with Order</p> <p>Volume & Weight To be notified</p>		
		<p>Manufacturer Terms & Conditions</p> <p>Export controls This offer is subject to rules and regulations of the EU for Foreign Trade department which are valid at the time of quotation. <i>ENOTEC</i> is obliged to examine all export transactions in regard to restrictions and export bans. Exporting to so-called embargo countries may be subject to certain limitations by EU law and by that of the Foreign Trade Act (AWG) and the Foreign Trade Ordinance (AWV). These rules and regulations may change at any time during the period between that of the order placement and that of the shipping date and result in the export not being carried out or being subject to an ACFA export permit. <i>ENOTEC</i> has no influence on the processing time of the ACFA and the associated delay. This applies to the material as well as to the receiver of the goods or the end-user. If the customer or end user is in a country subject to the embargo, they are the obligated to notify <i>ENOTEC</i> immediately. In this case <i>ENOTEC</i> may cancel the contract or a delivery commitment at any time which will not constitute a claim for damages whatsoever.</p> <p>Delivery terms The specified delivery time is only valid after the final technical and commercial clarification.</p> <p>Warranty terms The Place of warranty is Marienheide, Germany. Unless otherwise agreed separately in writing, the warranty condition which occurs first in time applies. Tear and wear parts are generally excluded from warranty, including:</p> <ul style="list-style-type: none"> • filter elements and seals for sample probes as well as fine dust filters • hoses of the peristaltic pump as well as hoses for disposal of the condensate • diaphragms and valves of the sample gas pumps • filter mats from cabinet fans and air inlet or outlet gratings • parts that come into contact with flue gas or other process gases <p>Important: Mechanical destruction is generally excluded from warranty.</p> <p>Documentation costs Should there be costs for the legalization or certification of documents, these are not included in the order value and will be charged extra according to expenditure.</p> <p>Reservation of ownership Merchandise shall remain property of <i>ENOTEC</i> until full payment has been made. Transfer of the ownership will be effective after 100% payment.</p> <p>Delay in acceptance of delivery Should a delay in acceptance of delivery on the part of the customer arise or should the customer not accept delivery although a valid supply contract exists, or the customer does not provide adequate delivery instructions after being informed of readiness for dispatch of the products, <i>ENOTEC</i> may place the products in storage at the expense of the customer. Upon placing the products in storage, the delivery is deemed complete and any risk concerning the delivery is transferred to the customer and any arising costs thereof will be carried by the customer.</p>		



		<p>Limitation of liability ENOTEC is not liable for normal wear and tear of the supplied equipment, for damages caused by the customer when further processing ENOTEC products, for improper storage, for damage resulting from improper installation and operation, or through lack of maintenance and damage caused by an alteration or repair not previously approved in writing by ENOTEC. ENOTEC shall not be liable for any damage or malfunction caused by the use of unauthorized software or unauthorized spare or replacement parts. Should costs arise from testing and addressing such deficiencies, these are to be paid by the customer at ENOTEC's request.</p> <p>General In case there are technical problems relevant to the ENOTEC scope of supply, the customer must report this in writing within 24 hours after the disturbance with a detailed error description to ENOTEC. Furthermore ENOTEC must be granted the right to correct the deficiencies notified by the end customer within one week after receipt of the notice, when that communication about at side trouble does result in a failure in the ENOTEC scope of supply. All wear and tear parts, as specified by ENOTEC must be at side with the end user and all required maintenance, as specified in the ENOTEC documentation, must have been done and recorded by the customer or the end user accordingly. Delivery and services are carried out according to ENOTEC's specifications and conditions unless otherwise specified in written form in a supply contract. ENOTEC reserves the right to review the price and technical details of orders and to adapt them accordingly. The customer will be informed of any changes in writing by ENOTEC. All additional services provided, such as a commissioning by our service personnel will be invoiced separately. ENOTEC will not disclose or release the internal software source code or other intellectual properties to the customer or the end user. In the event of delay of the delivery ENOTEC is exempt of any type of penalties and claims for subsequent measures or subsequent damages. Customer-supplied general conditions of purchase are generally excluded. ENOTEC reserves the right to make technical changes to individual offered positions. Due to the currently unpredictable global market situation, we reserve the right to adjust prices and/or delivery times at short notice. Please note the details provided by ENOTEC in the order confirmation.</p> <p>Place of jurisdiction/arbitration Gummersbach, Germany The contract and any order issued there under shall be subject to the substantive of the law of the Federal Republic of Germany.</p>		
		<p>Service Notes:</p> <ol style="list-style-type: none"> 1. The dates of service will be fix and scheduled with at least four (4) weeks in advance of acceptance of installation by customer. 2. Personnel of affiliated company in Venezuela, SERVITECH ORIENTE will do local support on these services. 3. Partial Invoicing will be done with successful comply of milestones described on payment terms. In case of any advance payments it will be deducted accordingly on each Invoice. 4. PDVSA CRP - AMUAY must supply all support on site including services of electricity and air (if required) to Working Teams at Refineries and Control Room. A list of necessities regarding power supply, air & water will be supplied at time of order reception and programming Job 5. Security induction procedures for allowing personnel to access the Plant will be done during working hours of service 6. Our personnel should be allowed to use bathroom and food area under PDVSA CRP - AMUAY's conditions. 7. If Installation is halt or delayed because major force or Internal PDVSA CRP - AMUAY's Situations, partial invoices regarding labor and expenses will be done for paying at status of job at that moment. Also a standby 		



		<p>charge @ EUR 1,450.00 per day will be generated until work could be reinitiated when PDVSA CRP - AMUAY will authorize these activities again and the conditions of site will allow to continue them safely and efficiently</p> <ol style="list-style-type: none"> 8. A complete Report of final working hours, extra hours, standby days, extra flat rate expenses day, etc, will be issued at the end of the Job done. This Report must be signed by customer for supporting any Labor difference between original estimates and final Job done 9. Any Tax discount or charge which must be paid for our Intl services in your country will be PDVSA CRP - AMUAY's responsibility and will be charged it on Final Invoice. 10. Any special safety equipment and/or accessory must be supplied by PDVSA CRP - AMUAY at site for all personnel involved. 11. PDVSA CRP - AMUAY is responsible to have a record of working hours inside their installations of this technical personnel 12. All above conditions must be part of final Purchase Order and/or contract <p>Cc: German Novoa – NOVOA SERVICES</p>		
--	--	---	--	--

PLEASE TRANSFER TO OUR ACCOUNT AT:
 TRUIST Bank
 450 North Pine Island
 Plantation, FL 33324
 Account #: 0140953040
 ABA# 053-101-121
 Routing/Transit Number: 2631-9138-7
 Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	EUR	52,170.00
Freight	EUR	Included
Insurance	EUR	Included
Docs.	EUR	Included
TOTAL	EUR	52,170.00