



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway

Suite 130, Sunrise, FL 33323

Tel: 954-302-3187, 315-4781

Fax: 954-838-7746

E-mail: ibicorp@intech-ie.com

Tax Certificate No. 16-8012998465-1

Quote #**IBI-2026-0076****Date:**Jun 10th, 2026**Customer ID****PETROBOSCAN****Bill To:****CHEVRON PETROBOSCAN**

Maracaibo, Edo. Zulia

Atn: Elizabeth Luzardo

Telf.: 0424-6314997 / 0261-7304615

E-mail: luzardoem@pdvsa.com.ve

Ship To:Material will be sent to customer broker at
Maracaibo Airport

<i>Your #</i>	<i>Our #</i>	<i>Sales Rep</i>	<i>Incoterms - CIF</i>	<i>SHIP VIA</i>	<i>Terms</i>	<i>Validity</i>
PB-2026-207-III	C-2026-0153/PL0.8	N. Carricatti	Maracaibo Airport	Pick up	See below	30 days

<i>Item</i>	<i>Qty</i>	<i>Units</i>	<i>Description</i>	<i>Unit Pr (US\$)</i>	<i>Total (US\$)</i>
1	7	Set	OIL WATER DETECTOR RANGE 0-100 % WITH INSERTABLE/RETRACTABLE INCLUDING LCD DISPLAY AND INSERTION TOOL, KAM Controls 3 Units: Oil Water Detector SKU: OWD_0-100%_INSXX_2"150RF TYPE/MODEL: Insertable / Retractable CONNECTION: 2" ANSI 150 RF RANGE: 0-100% ACCURACY: +/- 1% of range (100%) SHAFT LENGTH: TBD. Standard Lengths are 24", 30", 36" and 48". MATERIAL (WETTED PARTS): SS316L MATERIAL (ENCLOSURE): Copper-free Aluminum CERTIFICATIONS: ATEX (II 2 G Ex db IIB T6 Gb) and IECEx (Ex db IIB T6 Gb). Wetted Parts NACE MR0175/ISO 15156 ELEC. CONDUIT PORT: (2) 3/4" NPT DRAWING: 152-XXX-XX2-001 LCD Display SPECIFICATIONS: .4-20 mA Input, 3.5 Digit, 1" High LCD, NEMA 4X and Explosion Proof Enclosure DRAWING: 213-003-000 4 Units: Oil Water Detector SKU: OWD_0-100%_INSXX_2"300RF TYPE/MODEL: Insertable / Retractable CONNECTION: 2" ANSI 300 RF RANGE: 0-100% ACCURACY: +/- 1% of range (100%) SHAFT LENGTH: TBD. Standard Lengths are 24", 30", 36" and 48".	\$73.384,00	\$513.688,00



			MATERIAL (WETTED PARTS): SS316L MATERIAL (ENCLOSURE): Copper-free Aluminum CERTIFICATIONS: ATEX (II 2 G Ex db IIB T6 Gb) and IECEEx (Ex db IIB T6 Gb). Wetted Parts NACE MR0175/ISO 15156 ELEC. CONDUIT PORT: (2) 3/4" NPT DRAWING: 152-XXX-XX2-001 LCD Display SPECIFICATIONS: .4-20 mA Input, 3.5 Digit, 1" High LCD, NEMA 4X and Explosion Proof Enclosure DRAWING: 213-003-000 Includes: KAM IT Insertion Tool FUNCTION: For all installations over 110 PSI DRAWING: 233-001-000 Note: one unit for the 7 analyzers * The offer includes local technical staff for installation and commissioning.		
2	4	Set	LOW RANGE (0-10% / 0-5%) WATERCUT METER WITH INSERTABLE/RETRACTABLE INCLUDING LCD DISPLAY AND INSERTION TOOL, KAM Controls 2 Units: SKU: LRW_0-5%_INS_2"300RF MODEL: Insertable/Retractable CONNECTION: 2" ANSI 300 RF RANGE: 0-5% ACCURACY: +/- 0.05% from 3-5% Water SHAFT LENGTH: TBD. Standard Shaft lengths are 24" and 30". MATERIAL (WETTED PARTS): SS316 MATERIAL (ENCLOSURE): Copper-free Aluminum CERTIFICATIONS: ATEX (II 2 G Ex db IIB T6 Gb) and IECEEx (Ex db IIB T6 Gb). NACE MR0175/ISO 15156 INPUTS REQUIRED: Density ELEC. CONDUIT PORT: (2) 3/4" NPT DRAWING: 152-XXX-XX0-000 LCD Display SPECIFICATIONS: .4-20 mA Input, 3.5 Digit, 1" High LCD, NEMA 4X and Explosion Proof Enclosure DRAWING: 213-003-000 2 Units: SKU: LRW_0-10%_INS_2"150RF MODEL: Insertable/Retractable CONNECTION: 2" ANSI 150 RF RANGE: 0-10% ACCURACY: +/- 0.1% from 5-10% Water SHAFT LENGTH: TBD. Standard Shaft lengths are 24" and 30". MATERIAL (WETTED PARTS): SS316 MATERIAL (ENCLOSURE): Copper-free Aluminum CERTIFICATIONS: ATEX (II 2 G Ex db IIB T6 Gb) and IECEEx (Ex db IIB T6 Gb). NACE MR0175/ISO 15156 INPUTS REQUIRED: Density ELEC. CONDUIT PORT: (2) 3/4" NPT DRAWING: 152-XXX-XX0-000 LCD Display SPECIFICATIONS: .4-20 mA Input, 3.5 Digit, 1" High LCD, NEMA 4X and Explosion	\$49.304,00	\$197.216,00

			Proof Enclosure DRAWING: 213-003-000 Includes: KAM IT Insertion Tool FUNCTION: For all installations over 110 PSI DRAWING: 233-001-000 Note: one unit for the 4 analyzers * The offer includes local technical staff for installation and commissioning.		
3	2	Set	MULTIPARAMETER MEASUREMENT SYSTEM (PH, CONDUCTIVITY OR TDS, DO), KNICK Complete measuring system for pH, conductivity and DO Digital basic unit, multiparameter, 2-channel, HART communication E401N.030 Digital basic unit, multiparameter A402N HART communication SW-A001 2 sensors (pH + COND) connected to the Stratos Multi. The Multi can calculate the TDS from conductivity. The DO sensor will be connected to the Stratos EVO. PH: SE571 Memosens 120 mm SE571X/1-NMSN-B1 5 m CA/MS-005NAA COND: G 1" SE670/G1 Cable with M12 plug (e.g. for SE670, SE680) 5 m CA/M12-005NA DO: SE740 optical oxygen sensor, digital 120 mm SE740/1 5 m CA/M12-005N485 Note: valves, bypasses, piping, etc., not included.	\$14.192,00	\$28.384,00
			Delivery Time Luego de recibir orden de compra y pago, Items: 10-12 semanas aprox. El tiempo de entrega de los elementos ofertados queda sujeto a cambios generados por eventos fuera de manejo de la compañía como: 1. Fenómenos climáticos que no permitan el transporte de materia prima a la fábrica, transporte local en el extranjero del material manufacturado y/o transporte internacional del producto. 2. Normal funcionamiento de aduana Venezolana y/o extranjeras. 3. Alteración del orden público en el país de origen, país en tránsito y/o país final. 4. Actos delictivos y/o terroristas. 5. Cualquier otro evento considerado de fuerza mayor. Payment terms 100% prepago con orden de compra Volume & Weight Peso y volumen por notificar		

**INDUSTRIAL BUSINESS INTL CORP**

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com

***PLEASE TRANSFER TO OUR
ACCOUNT AT:***

Branch Banking & Trust Co.
450 North Pine Island
Plantation, FL 33324
Account #: 0140953040
ABA# 053-101-121
Routing/Transit Number: 2631-9138-7
Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

<i>Subtotal</i>	<i>US \$</i>	739,288.00
<i>Freight</i>	<i>US \$</i>	<i>Included</i>
<i>Insurance</i>	<i>US \$</i>	<i>Included</i>
<i>Docs.</i>	<i>US \$</i>	<i>Included</i>
<i>TOTAL</i>	<i>US \$</i>	739,288.00