



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com
Tax Certificate No. 16-8012998465-1

Quote #

IBI-2026-0095

Date:

Jul 17th, 2026

Customer ID

ARCO SERVICES

Bill To:

Arco Services, C.A

RIF: J-30644633-8

Av. Raul Leoni Boulevard del Sur Edif. Arco Piso PB
Local Anexo a Sector Juanico Maturin. Edo
Monagas. Zona Postal 6201.
Telf: +58 414-8752084
Attn: Teresita Milano
Correo: tmlano@arcoservices.net /
tmlano1605@gmail.com

Ship To:

El material se enviará al almacén/broker del
cliente en Maturin, Edo. Monagas

Your #	Our #	Sales Rep	Incoterms - DDP	SHIP VIA	Terms	Validity
Budgetary	IBI-2026-0095	S. Méndez	MON	Pick up	See below	30 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	1	Pc	CENTRIFUGE MODEL 6-16HS INCLUDING ACCESSORIES SET FOR ASTM D91/96 PETROLEUM TUBES, SIGMA-ZENTRIFUGEN PN 841TM846A9WQ Universal benchtop centrifuge Speed range up to 13,500 rpm Maximum capacity: 4 x 1,000 ml User-friendly Spincontrol S controller Extra-large TFT display 60 programs Compact, space-saving unit Low noise level Automatic rotor identification Zero-maintenance induction motor Motorised lid lock Automatic imbalance monitoring Rotor life monitoring for high safety Easily cleaned stainless steel chamber Window in lid for external speed monitoring Manufactured according to the latest national and international standards (e.g. EN 61010-2-020) Heated, unrefrigerated centrifuge Temperature setting range: 0 °C to +70 °C Optimised for measuring the moisture content of crude oil and products made from crude oil (in accordance with ASTM standards) Includes: *Swing-out rotor with Comfort coating for 4 x 100 ml petroleum tube buckets no. 13113, 13114, 13116 *2 SETS - Round bucket for 100 ml, 8" petroleum glass tube no. 15130 according to ASTM D 91/96 (max. 700 x g), incl. adapter no. 16103 and rubber cushion no. 16021, sealable with non-included cap no. 17107, 1 set = 2 pcs. *2 SETS - Round aluminium sealing cap for bucket no. 13113 with thread, 1 set = 2 pcs. *2 SETS - Adapter for 100 ml/8" petroleum glass tube no. 15130, incl. rubber	\$30,671.00	\$30,671.00

			cushion no. 16021, 1 set = 2 pcs.		
2	10	Pc	Glass tube, 100 ml, 8" for petroleum, according to ASTM D 91/96 PN 15RG13AA0	\$235.00	\$2,350.00
3	1	Pc	PS500 LONG DURATION NiMH + PUMP + DATALOGGING, O2, H2S, CO2 SENSOR FITTED, INCLUDES: USER CD, QUICK OP GUIDE, BELT CLIP, CALIBRATION CERTIFICATE, 3M TUBING (PUMPED ONLY), CHARGER (LONG DURATION AND FAST CHARGE ONLY, TELEDYNE PN 61368-BCP	\$3,573.00	\$3,573.00
4	1	Pc	MANOMETRO ACERO INOXIDABLE DIAL 4" RANGO 0 A 200 PSI CONEXIÓN INFERIOR ½ NPT CON GLICERINA, WIKA PN 233.50-E-PG414Z-ND-UZHCCZZ-ZZZZZZZZ Measuring System: Stainless Steel Case filling: with Nominal size: 4" Scale range: 0/200 psi Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Pointer: standard pointer Smart.Link (Digitalization): without Accuracy Class: class 1.0 Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65	\$185.00	\$185.00
5	1	Pc	MANOMETRO ACERO INOXIDABLE DIAL 4" RANGO 0 A 500 PSI CONEXIÓN INFERIOR ½ NPT CON GLICERINA, WIKA PN 233.50-E-PG434Z-ND-UZHCCZZ-ZZZZZZZZ Measuring System: Stainless Steel Case filling: with Nominal size: 4" Scale range: 0/500 psi Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Pointer: standard pointer Smart.Link (Digitalization): without Accuracy Class: class 1.0 Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65	\$200.00	\$200.00
6	1	Pc	MANOMETRO ACERO INOXIDABLE DIAL 4" RANGO 0 A 1000 PSI CONEXIÓN INFERIOR ½ NPT CON GLICERINA, WIKA PN 233.50-E-PG469Z-ND-UZHCCZZ-ZZZZZZZZ Measuring System: Stainless Steel Case filling: with Nominal size: 4" Scale range: 0/1000 psi	\$199.00	\$199.00

			Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Pointer: standard pointer Smart.Link (Digitalization): without Accuracy Class: class 1.0 Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65		
7	1	Pc	MANOMETRO ACERO INOXIDABLE DIAL 4" RANGO 0 A 2000 PSI CONEXIÓN INFERIOR ½ NPT CON GLICERINA, WIKA PN 233.50-E-PG514Z-ND-UZH2CZZ-ZZZZZZZZ Measuring System: Stainless Steel Case filling: with Nominal size: 4" Scale range: 0/2000 psi Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Pointer: standard pointer Smart.Link (Digitalization): without Accuracy Class: class 1.0 Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65	\$199.00	\$199.00
8	1	Pc	MANOMETRO ACERO INOXIDABLE DIAL 4" RANGO 0 A 10000 PSI CONEXIÓN INFERIOR ½ NPT CON GLICERINA, WIKA PN 233.50-E-PG569Z-ND-UZH2CZZ-ZZZZZZZZ Measuring System: Stainless Steel Case filling: with Nominal size: 4" Scale range: 0/10000 psi Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Pointer: standard pointer Smart.Link (Digitalization): without Accuracy Class: class 1.0 Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65	\$199.00	\$199.00
9	1	Pc	TERMOMETRO BIMETALICO DIAL 3" RANGO 0 A 250 °F CONEXIÓN MULTIANGULAR ½ NPT LONGITUD 3", WIKA PN TG53.3ZDS-S-FBFZ-ND-W030GZ-ZZZZZZZZ Model: TG53.3Z Specifications according to data sheet: ATM 53.02 Accuracy Class: +/- 1% of Full Scale (ASME B40.3) Nominal size: 3" Connector position: back mount, adjustable	\$373.00	\$373.00

			Design of Connection: standard, male thread Process Connection: 1/2" NPT Scale Range: 0 °F ... 250 °F Stem Diameter: 1/4" Insertion length L1: 3" Window: Flat Instrument Glass Ingress Protection: IP 66 / NEMA 4X		
10	1	Pc	TERMOMETRO BIMETALICO DIAL 3" RANGO 0 A 250 °F CONEXIÓN MULTIANGULAR ½ NPT LONGITUD 4", WIKA PN TG53.3ZDS-S-FBFZ-ND-W040GZ-ZZZZZZ Model: TG53.3Z Specifications according to data sheet: ATM 53.02 Accuracy Class: +/- 1% of Full Scale (ASME B40.3) Nominal size: 3" Connector position: back mount, adjustable Design of Connection: standard, male thread Process Connection: 1/2" NPT Scale Range: 0 °F ... 250 °F Stem Diameter: 1/4" Insertion length L1: 4" Window: Flat Instrument Glass Ingress Protection: IP 66 / NEMA 4X	\$373.00	\$373.00
11	1	Pc	TERMOPOZO EN ACERO INOXIDABLE CONICO CONEXIÓN ROSCADO HEXAGONAL ½ NPT LONGITUD DE INSERCIÓN 2.5", WIKA PN Threaded Thermowell TW15, solid machined Head Design: Hexagon Thermowell Style: Tapered Unit of Measure: Imperial (inch) Process thread [P or E]: 1/2" NPT Instrument connection [N]: 1/2 NPT female Insertion length [U]: 2.5 inch Head Length: 1.75" Bar Material: Stainless steel 316/316L Bore size [B or d1]: 0.335 inch (8.5 mm) Root diameter [Q]: 0.625 inch Tip diameter [V or F3]: 0.625 inch Bore depth / stem length (US): 4.000 inch Tip thickness [Tt]: 0.250 inch (6.4 mm)	\$332.00	\$332.00
12	1	Pc	MANOMETRO MODELO 213.53 DIAL 2" RANGO 0 A 30 PSI CONEXIÓN TRASERA 1/8 NPT, WIKA PN 213.53-B-PG321Z-NH-AZZZ-ZZZ Measuring System: Copper Alloy Case: 304 Stainless Steel Case: Non-removable crimp ring Nominal size: 2" Scale range: 0/30 psi Process Connection: 1/8 NPT Connector location: back mount	\$93.00	\$93.00

			Accuracy Class: class 1.6 Case filling fluid: Glycerine Window: Plastic, clear		
13	1	Pc	MANOMETRO MODELO 213.53 DIAL 2" RANGO 0 A 60 PSI CONEXIÓN TRASERA 1/8 NPT, WIKA PN 213.53-B-PG341Z-NH-AZZZ-ZZZ Measuring System: Copper Alloy Case: 304 Stainless Steel Case: Non-removable crimp ring Nominal size: 2" Scale range: 0/60 psi Process Connection: 1/8 NPT Connector location: back mount Accuracy Class: class 1.6 Case filling fluid: Glycerine Window: Plastic, clear	\$93.00	\$93.00
14	1	Pc	MANOMETRO MODELO 213.53 DIAL 2" RANGO 0 A 100 PSI CONEXIÓN TRASERA 1/8 NPT, WIKA PN 213.53-B-PG369Z-NH-AZZZ-ZZZ Measuring System: Copper Alloy Case: 304 Stainless Steel Case: Non-removable crimp ring Nominal size: 2" Scale range: 0/100 psi Process Connection: 1/8 NPT Connector location: back mount Accuracy Class: class 1.6 Case filling fluid: Glycerine Window: Plastic, clear	\$93.00	\$93.00
			Delivery Time Items 1-3: 5-8 weeks after receipt of order and payment (subject to changes) Items 4-14: 10-15 weeks after receipt of order and payment (subject to changes) The delivery time of the items offered is subject to changes generated by events outside the company's control, such as: 1. Climatic phenomena that do not allow the transport of raw material to the factory, local transport abroad of the manufactured material and/or international transport of the product. 2. Normal functioning of Venezuelan and/or foreign customs. 3. Disruption of public order in the country of origin, country of transit and/or final country. 4. Criminal and/or terrorist acts. 5. Any other event considered major force. Payment terms 100% with purchase order Volume & Weight Weight / Volume to be advised		

**INDUSTRIAL BUSINESS INTL CORP**

1580 Sawgrass Corporate Parkway

Suite 130, Sunrise, FL 33323

Tel: 954-302-3187, 315-4781

Fax: 954-838-7746

E-mail: ibicorp@intech-ie.com

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

Branch Banking & Trust Co.

450 North Pine Island

Plantation, FL 33324

Account #: 0140953040

ABA# 053-101-121

Routing/Transit Number: 2631-9138-7

Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	38,933.00
Freight	US \$	Included
Insurance	US \$	Included
Docs.	US \$	Included
TOTAL	US \$	38,933.00