



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com
Tax Certificate No. 16-8012998465-1

Quote #

IBI-2025-0042

Date:

Feb 28th, 2025

Customer ID

PETROPIAR - VEN

Bill To:

Chevron PetroPiar

Complejo Petrolero y Petroquimico Jose, Edo
Anzoategui, Venezuela
Att: Nancy Cordero – Ing. Costos
corderonj@petropiar.pdvsa.com

Ship To:

Custom Agent to be informed at La Guaira port,
Venezuela

Your #	Our #	Sales Rep	CIF	SHIP VIA	Terms	Validity
Budgetary	IBI-2025-0042/	L. Zuñiga	Maiquetia Airport, VEN	BWPPD	See below	60 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	1	Eqp	BROOKS INSTRUMENTS Armored Rotameter , Model 3809GAD07AABB3H4CCCO Tag-001 28-FI-346 Max Press @ Max Temp 1500 PSIG 103.4 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size 1/2-inch Connection Type F-NPT Inlet Down Outlet Up O-Ring Material Viton Valve On Outlet-Viton-Ship Attached Valve Connection Visible Thd FNPT Range 180 - 1800 SCFD Indicator Housing XP STAINLESS STEEL Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL Approvals DISPLAY - HART Certification (1) DIV 1-ZONE 1 XP-IIC-IECEX-CSA TAG Type [C] NACE & Mat Cert 3.1 International Calibration Certificate (ICC) Stainless Certificate of Conformance (Compliance) 2.1	9,890.00	
2	1	Eqp	BROOKS INSTRUMENTS Armored Rotameter , Modell 3809GAD07BABB3H4CCCO Tag-001 28-FI-340 Max Press @ Max Temp 1500 PSIG 103.4 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size 1/2-inch Connection Type F-NPT Inlet Down Outlet Up	9,890.00	



			O-Ring Material Valve Valve Connection Range Indicator Housing Electrical Connection Indicator/Alarm/Transmit Approvals Certification (1) TAG Type International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	Viton On Outlet-Viton-Ship Attached Visible Thd FNPT 500 - 5000 SCFD XP STAINLESS STEEL 3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1 Stainless		
3	4	Eqp	BROOKS INSTRUMENTS Armored , Model 3809GAD07BAB3H4CCCO Tag-001 Tag-002 Tag-003 Tag-004 Max Press @ Max Temp Accuracy Meter Material Connection Size Connection Type Inlet Outlet O-Ring Material Valve Valve Connection Range Indicator Housing Electrical Connection Indicator/Alarm/Transmit Approvals Certification (1) TAG Type International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	28-FI-345 28-FI-350 28-FI-550 28-FI-750 1500 PSIG 103.4 BAR 2% -Direct Scale-Gas 316L SS 1/2-inch F-NPT Down Up Viton On Outlet-Viton-Ship Attached Visible Thd FNPT 490 - 4900 SCFD XP STAINLESS STEEL 3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1 Stainless	9,875.00	
4	1	Eqp	BROOKS INSTRUMENTS Armored Rotameter , Model 3809GAD07BAB3H4CCCO Tag-001 Max Press @ Max Temp Accuracy Meter Material Connection Size Connection Type Inlet Outlet O-Ring Material Valve Valve Connection Range Indicator Housing	30-FI-029 1500 PSIG 103.4 BAR 2% -Direct Scale-Gas 316L SS 1/2-inch F-NPT Down Up Viton On Outlet-Viton-Ship Attached Visible Thd FNPT 490 - 4900 SCFD XP STAINLESS STEEL	11,375.00	



INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com

			Electrical Connection Indicator/Alarm/Transmit Approvals Certification (1) TAG Type International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1 Stainless		
5	1	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAA12CFBB3H4C0C0 Tag-001 Max Press @ Max Temp Accuracy Meter Material Connection Size Connection Type Inlet Outlet O-Ring Material Valve Range Indicator Housing Electrical Connection Indicator/Alarm/Transmit Approvals Certification (1) TAG Type International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	28-FI-666 148 PSIG 10.2 BAR 2% -Direct Scale-Gas 316L SS 1.5-inch 150# RF Flange Down Up No No Valve 19000 - 190000 SCFD XP STAINLESS STEEL 3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1 Stainless	10,905.00	
6	3	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAB08BGBB3H4CDC0 Tag-001 Tag-002 Tag-003 Max Press @ Max Temp Accuracy Meter Material Connection Size Connection Type Inlet Outlet O-Ring Material Valve Valve Connection Range Indicator Housing Electrical Connection Indicator/Alarm/Transmit Approvals Certification (1) TAG Type International Calibration Certificate (ICC)	28-FI-942 28-FI-945 28-FI-946 458 PSIG 31.6 BAR 2% -Direct Scale-Gas 316L SS OVERSIZED 3/4-in 300# RF Flange Down Up No On Outlet-Teflon-Sent Detached Visible Thd Flg 3000 - 30000 SCFD XP STAINLESS STEEL 3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1 Stainless	11,845.00	



			Certificate of Conformance (Compliance) 2.1		
7	2	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAA13CFBB3H4C0C0 Tag-001 30-FI-080 Tag-002 30-FI-081 Max Press @ Max Temp 148 PSIG 10.2 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size 2-inch Connection Type 150# RF Flange Inlet Down Outlet Up O-Ring Material No Valve No Valve Range 30000 - 300000 SCFD Indicator Housing XP STAINLESS STEEL Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	11,925.00	
8	9	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAA13BFBB3H4C0C0 Tag-001 28-FI-462 Tag-002 28-FI-463 Tag-003 28-FI-464 Tag-004 28-FI-662 Tag-005 28-FI-663 Tag-006 28-FI-664 Tag-007 28-FI-862 Tag-008 28-FI-863 Tag-009 28-FI-864 Max Press @ Max Temp 148 PSIG 10.2 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size 2-inch Connection Type 150# RF Flange Inlet Down Outlet Up O-Ring Material No Valve No Valve Range 24000 - 240000 SCFD Indicator Housing XP STAINLESS STEEL Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	11,845.00	



9	1	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAB07BFBB3H4CCCO Tag-001 30-FI-031 Max Press @ Max Temp 148 PSIG 10.2 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size OVERSIZED 3/4-in Connection Type 150# RF Flange Inlet Down Outlet Up O-Ring Material No Valve On Outlet-Viton-Sent Detached Valve Connection Visible Thd Flg Range 490 - 4900 SCFD Indicator Housing XP STAINLESS STEEL Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	11,445.00	
10	2	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAA12AGAB3H4CBCO Tag-001 12-FI-654 Tag-002 12-FI-655 Max Press @ Max Temp 458 PSIG 31.6 BAR Accuracy 2% -Direct Scale-Liquid Meter Material 316L SS Connection Size 1.5-inch Connection Type 300# RF Flange Inlet Down Outlet Up O-Ring Material No Valve On Inlet-Teflon-Sent Detached Valve Connection Visible Thd Flg Range 1.8 - 18 GPM Indicator Housing XP STAINLESS STEEL Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	15,250.00	
11	3	Eqp	BROOKS INSTRUMENTS Armored, Model 3809GAB12AFBB3H4COCO Tag-001 30-FI-001 Tag-002 30-FI-003 Tag-003 30-FI-005 Max Press @ Max Temp 148 PSIG 10.2 BAR Accuracy 2% -Direct Scale-Gas	11,615.00	



			Meter Material 316L SS Connection Size OVERSIZED 2-inch Connection Type 150# RF Flange Inlet Down Outlet Up O-Ring Material No Valve No Valve Range 12000 - 110000 SCFD Indicator Housing XP STAINLESS STEEL Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1		
12	1	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAA10AGAC3H4C0C0 Tag-001 12-FI-116 Max Press @ Max Temp 458 PSIG 31.6 BAR Accuracy 1% -Direct Scale-Liquid Meter Material 316L SS Connection Size 1-inch Connection Type 300# RF Flange Inlet Down Outlet Up O-Ring Material No Valve No Valve Range 0.52 - 5.2 GPM Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless Certificate of Conformance (Compliance) 2.1 International Calibration Certificate (ICC)	10,835.00	
13	1	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAC07AGBB3H4C0C0 Tag-001 12-FI-357 Max Press @ Max Temp 458 PSIG 31.6 BAR Accuracy 2% -Direct Scale-Gas Meter Material 316L SS Connection Size OVERSIZED 1-inch Connection Type 300# RF Flange Inlet Down Outlet Up O-Ring Material No Valve No Valve Range 200 - 2000 SCFD Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F	10,465.00	



			Indicator/Alarm/Transmit Approvals Certification (1) TAG Type International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX- CSA [C] NACE & Mat Cert 3.1 Stainless		
14	4	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAA12BGAB3H4CBC0 Tag-001 Tag-002 Tag-003 Tag-004 Max Press @ Max Temp Accuracy Meter Material Connection Size Connection Type Inlet Outlet O-Ring Material Valve Valve Connection Range Indicator Housing Electrical Connection Indicator/Alarm/Transmit Approvals Certification (1) TAG Type International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	12-FI-651A 12-FI-652A 12-FI-651B 12-FI-652B 458 PSIG 31.6 BAR 2% -Direct Scale-Liquid 316L SS 1.5-inch 300# RF Flange Down Up No On Inlet-Teflon-Sent Detached Visible Thd Flg 2.6 - 26 GPM XP STAINLESS 3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1 Stainless	15,205.00	
15	3	Eqp	BROOKS INSTRUMENTS Armored Rotameter, 3809GAB08CGB3H4CDC0 Tag-001 Tag-002 Tag-003 Max Press @ Max Temp Accuracy Meter Material Connection Size Connection Type Inlet Outlet O-Ring Material Valve Valve Connection Range Indicator Housing Electrical Connection Indicator/Alarm/Transmit Approvals	18-FI-940 18-FI-941 18-FI-939 458 PSIG 31.6 BAR 1% -Direct Scale-Gas 316L SS OVERSIZED 3/4-in 300# RF Flange Down Up No On Outlet-Teflon-Sent Detached Visible Thd Flg 6400 - 46000 SCFD XP STAINLESS STEEL 3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA	12,385.00	



			Certification (1) TAG Type International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	[C] NACE & Mat Cert 3.1 Stainless		
16	1	Eqp	BROOKS INSTRUMENTS Armored, Model 3809GAA15AFBB3H4C0C0 Tag-001 Max Press @ Max Temp Accuracy Meter Material Connection Size Connection Type Inlet Outlet O-Ring Material Valve Range Indicator Housing Electrical Connection Indicator/Alarm/Transmit Approvals Certification (1) TAG Type Certificate of Conformance (Compliance) 2.1 International Calibration Certificate (ICC)	65-FI-068 148 PSIG 10.2 BAR 2% -Direct Scale-Gas 316L SS 3-inch 150# RF Flange Down Up No No Valve 50 - 390 SCFM XP STAINLESS STEEL 3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1 Stainless	15,080.00	
17	1	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAB08CGBB3H4CDC0 Part Number Tag-001 Max Press @ Max Temp Accuracy Meter Material Connection Size Connection Type Inlet Outlet O-Ring Material Valve Valve Connection Range Indicator Housing Electrical Connection Indicator/Alarm/Transmit Approvals Certification (1) TAG Type International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	63-FI-931 458 PSIG 31.6 BAR 2% -Direct Scale-Gas 316L SS OVERSIZED 3/4-in 300# RF Flange Down Up No On Outlet-Teflon-Sent Detached Visible Thd Flg 6400 - 46000 SCFD XP STAINLESS STEEL 3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1 Stainless	11,925.00	
18	1	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAB08CGBB3H4CDC0 Tag-001 Max Press @ Max Temp	22-FI-931 458 PSIG 31.6 BAR	11,925.00	11,925.00



			Accuracy Meter Material Connection Size Connection Type Inlet Outlet O-Ring Material Valve Valve Connection Range Indicator Housing Electrical Connection Indicator/Alarm/Transmit Approvals Certification (1) TAG Type International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	2% -Direct Scale-Gas 316L SS OVERSIZED 3/4-in 300# RF Flange Down Up No On Outlet-Teflon-Sent Detached Visible Thd Flg 6400 - 46000 SCFD XP STAINLESS STEEL 3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1 Stainless		
19	2	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAA10AGBC3H4C0C0 Tag-001 Tag-002 Max Press @ Max Temp Accuracy Meter Material Connection Size Connection Type Inlet Outlet O-Ring Material Valve Range Indicator Housing Electrical Connection Indicator/Alarm/Transmit Approvals Certification (1) TAG Type Certificate of Conformance (Compliance) 2.1 International Calibration Certificate (ICC)	12-FI-042 12-FI-043 458 PSIG 31.6 BAR 1% -Direct Scale-Gas 316L SS 1-inch 300# RF Flange Down Up No No Valve 1.9 - 19 SCFM XP STAINLESS 3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1 Stainless	10,765.00	
20	2	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAB08CGBB3H4CDC0 Tag-001 Tag-002 Max Press @ Max Temp Accuracy Meter Material Connection Size Connection Type Inlet Outlet O-Ring Material Valve	15-FI-965 15-FI-966 458 PSIG 31.6 BAR 2% -Direct Scale-Gas 316L SS OVERSIZED 3/4-in 300# RF Flange Down Up No On Outlet-Teflon-Sent Detached	11,865.00	



			Valve Connection Range Indicator Housing Electrical Connection Indicator/Alarm/Transmit Approvals Certification (1) TAG Type International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	Visible Thd Flg 6300 - 45000 SCFD XP STAINLESS STEEL 3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1 Stainless		
21	1	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAB08CGBC3H4CDC0 Tag-001 Max Press @ Max Temp Accuracy Meter Material Connection Size Connection Type Inlet Outlet O-Ring Material Valve Valve Connection Range Indicator Housing Electrical Connection Indicator/Alarm/Transmit Approvals Certification (1) TAG Type International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	41-FI-931 458 PSIG 31.6 BAR 1% -Direct Scale-Gas 316L SS OVERSIZED 3/4-in 300# RF Flange Down Up No On Outlet-Teflon-Sent Detached Visible Thd Flg 6400 - 46000 SCFD XP STAINLESS 3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1 Stainless	12,480.00	
22	1	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GAB08CGBC3H4CDC0 Tag-001 Max Press @ Max Temp Accuracy Meter Material Connection Size Connection Type Inlet Outlet O-Ring Material Valve Valve Connection Range Indicator Housing Electrical Connection Indicator/Alarm/Transmit Approvals Certification (1)	18-FI-942 458 PSIG 31.6 BAR 1% -Direct Scale-Gas 316L SS OVERSIZED 3/4-in 300# RF Flange Down Up No On Outlet-Teflon-Sent Detached Visible Thd Flg 6400 - 46000 SCFD XP STAINLESS STEEL 3/4-in NPT-F XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1	12,385.00	



			TAG Type International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1	Stainless		
23	2	Eqp	BROOKS INSTRUMENTS Armored Rotameter, Model 3809GBD08DAAC3K30000 Tag-001 12-FISL-742 Tag-002 12-FISL-743 Max Press @ Max Temp 2567 PSIG 177 BAR Accuracy 1% -Direct Scale-Liquid Meter Material 316L SS Connection Size ½- in Connection Type F_NPT Inlet Down Outlet Up O-Ring Material No Valve No Valve Valve Connection No valve Range 0.46 – 4.4 GPM Indicator Housing XP STAINLESS STEEL Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART Relays 24 VDC Relay, 2 Channel Approvals DIV 1-ZONE 1 XP-IIC-IECEX-CSA Certification (1) [C] NACE & Mat Cert 3.1 TAG Type Stainless International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1		12,385.00	
			Payment Terms 50 % with Order and Approval Dimensioning 50 % with Advise of Shipment to Venezuela CIF Delivery Time 16-18 weeks ARO and payment Volume & Weight Weight and Volume to be advised (aprox 1,000 Lbs Gross Weight) Recommended shipping <u>by Air Freight to final destination</u> Cci: W. Brito – INTECH PLCRZ			

**INDUSTRIAL BUSINESS INTL CORP**

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com

--	--	--	--	--	--

***PLEASE TRANSFER TO OUR
ACCOUNT AT:***

Branch Banking & Trust Co.
450 North Pine Island
Plantation, FL 33324
Account #: 0140953040
ABA# 053-101-121
Routing/Transit Number: 2631-9138-7
Swift Code: BRBTUS33

<i>Subtotal</i>	<i>US \$</i>	1,271,180.00
<i>Freight</i>	<i>US \$</i>	1,750.00
<i>Insurance</i>	<i>US \$</i>	-
<i>Docs.</i>	<i>US \$</i>	-
<i>TOTAL</i>	<i>US \$</i>	1,272,930.00

THANK YOU FOR YOUR BUSINESS