



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com
Tax Certificate No. 16-8012998465-1

Quote #

IBI-2025-0134

Date:

Aug 25th, 2025

Customer ID

PETROPIAR - VEN

Bill To:

Chevron PetroPiar

Complejo Petrolero y Petroquimico Jose, Edo
Anzoategui, Venezuela
Att: Jean Laya - Confiabilidad
colayajj@pdvsa.com

Ship To:

Custom Agent to be informed at La Guaira port,
Venezuela

Your #	Our #	Sales Rep	CIF	SHIP VIA	Terms	Validity
Budgetary	IBI-2025-0134 / ELZ	L. Zuñiga W. Brito	La Guaira Port	BWPPD	See below	90 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	2	Eqp	WIKA DUAL CHAMBER LEVEL SYSTEM – Redundant BNA/DU-2"/300/RF-M5943-L/CS 60x2.77/60x2,77-MRF/SAP-ZVSS185/PN25/R48H Tag: 14-LIT-006, 14-LIT-007 Magnetic Level Gauge Type BNA-SD00 Pressure: 160 psi ; Temp.: 14°F...350 °F; SG 0.76 Design code: ASME B31.3 Chamber dimensions: OD 60.3 x 2.77 mm (2" Sch. 10S) Duo stainless steel 316/316L (EN 1.4401/1.4404) Process connection: CS Flange ASME B16.5 2" 300# Form RF Distance C-to-C: 234.0 inch Measuring range: 234.0 inch Chamber end top: Pipe cap Chamber end bottom: CS Flange ASME B16.5 2" 300# Form RF Vent connection: MNPT Nipple 3/4" for valve (by others) Drain connection: MNPT Nipple 3/4" for valve (by others) Float: ZVSS185/PN25/R48H Dampening element: Dampening spring, bottom & top, with cover Gasket(s): Spiral wound type, SS 316L/Graphite Bolting: UNC series, carbon steel A193 Gr. B7 HDG / A194 Gr. 2H HDG Top stand-off (T): 3.9 inch Bottom stand-off (U): 21.0 inch Nameplate: Stainless steel laser printed TOTAL INDICATION Stability Bracket: 1 Dual Chamber (DUplus) Sidechamber: OD 60.3 x 2,77 mm (2" Sch. 10S) Location of secondary chamber: 3 o'clock (right side of MLG chamber) Process connection GT: CS Flange ASME B16.5 2" 300# Form RF Distance between chambers center lines: 7,9 inch Radar connection stand-off: 10.0 inch Side chamber bottom stand-off: 10.0 inch Includes Bottom: Mag Trap -316ss/ CS construction -316SS 2" x 2" Tee with 2" CS 300# RFWN Flange -Bottom: CS 2" 300# RFWN with blind mating flange & 1/2" NPT Drain and Plug MRF/SAP-M4572 Level Indicator for Magnetic Level Gauge Type BMD-FA Measuring range: 234 inch	\$43,860.00	\$87,720.00

			Housing material: Aluminum anodized Indicating elements: Stainless steel flaps Red & white Graduated scale: Aluminum engraved Graduation unit: % Includes Insulation Jacket 1" Ceramic Fiber with Silicone Alpha Cloth Exterior and High Heat Interior w/RADAR Transmitter FX81.FADACDHXANAM eID: US34258534 Scope F : USA Approval A : FM (NI) CL I, II, III DIV2, GP ABCDFG Version / Material D : Exchangeable cable (ø2mm) with centering weight / 316 Probe : mounted Length (from seal surface) : 240.000 inch Length of rigid part : 3.937 inch Dimensions centering weight (diameter / height) 1.77in / 1.18in (for 2" Schedule 40/80 and 3" Schedule 80/160) Process fitting / Material AC : Flange 2" 300lb RF, ASME B16.5 / 316/316L Seal / Second line of defense / Process temperature K : FFKM (Kalrez 6375) / without / -20...+200°C Electronics H : Two-wire 4 ... 20 mA/HART Housing / Protection A : Aluminum single chamber / IP66/IP68 (0.2bar) Cable entry / Connection N : ½NPT / Blind plug Display/Adjustment module PLICSCOM A : mounted Certificates M : Yes Certificate / Standard : (C) Material test report – traceable (EN 10204 type 3.1 + NACE MR0175 + NACE MR0103) PMI test : RFA (positive material identification) incl. 3.1 inspection certificate Supply certificates : with goods Measurement loop identification label : of Stainless Steel Customer-specific adjustment : Yes - Unit : inch - 100 % (distance from seal surface) : 10.000 inch - 0 % (distance from seal surface) : 240.000 inch Linearization : No Min. process pressure in bar : -1.000 Max. process pressure in bar : 40.0		
2	1	Eqp	WIKA BYPASS CHAMBER BZG-2"/900/rf-M914-CS60.3x5.54 Tag : 14-LIT-024 External Chamber Type BZG-K00 Pressure: 1610 psi , Temp: 14°F – 300°F Design code: ASME B31.3 Test Pressure: 188 bar Chamber dimensions: OD 60.3 x 5.54 mm (2" Sch 80S) Chamber material: Steel A105/106 Gr. B Joint design: Slip on welds not permitted. Only welding-neck flanges allowed Corrosion allowance: min 1.6 mm included Process connection: Flange ASME B16.5 2" 900# Form RF Process connection orientation: Side-Side Connection technology: Pipe on Pipe Distance C-to-C: 36" Chamber end top: Flange ASME B16.5 2" 900# Form RF Chamber end bottom: Pipe cap Vent connection: male thread ¾" NPT Vent connection orientation: 6 o'clock / 180° Drain connection: Male thread ¾" Gasket(s): Spiral wound type, SS 316L/Graphite Bolting: UNC Series, carbon steel A320 Gr. L7 / HDG / A194 Gr. 7 HDG Top stand-off (T): 254 mm Bottom stand-off (U) 254 mm Side distance (X) 150 mm Nameplate: Stainless steel laser printed TOTAL INDICATION Insertion external sensor: with w/RADAR Transmitter FX86.FADCZ1HXANAM	\$64,450.00	\$64,450.00

			eID: US34260183 Scope F : USA Approval A : FM (NI) CL I, II, III DIV2, GP ABCDFG Version / Material D : Exchangeable cable (ø2mm) with centering weight / 316 Probe : mounted Length (from seal surface) : 42.000 inch Length of rigid part : 3.937 inch Dimensions centering weight (diameter/height) 1.77in / 1.18in (for 2" Schedule 40/80 and 3" Schedule 80/160) Process fitting / Material CZ : Flange 2" 900lb RF, ASME B16.5 / 316/316L Seal / Second line of defense / Process temperature: Ceramic graphite / with / -196...+280°C Electronics H : Two-wire 4 ... 20 mA/HART Housing / Protection A : Aluminum single chamber / IP66/IP68 (0.2bar) Cable entry / Connection N : ½NPT / Blind plug Display/Adjustment module PLICSCOM A : mounted Certificates M : Yes Certificate / Standard : (C) Material test report – traceable (EN 10204 type 3.1 + NACE MR0175 + NACE MR0103) PMI test : RFA (positive material identification) incl. 3.1 inspection certificate Supply certificates : with goods Measurement loop identification label : of Stainless Steel Customer-specific adjustment : Yes - Unit : inch - 100 % (distance from seal surface) : 10.000 inch - 0 % (distance from seal surface) : 29.000 inch Linearization : No Min. process pressure in bar : -1.000 Max. process pressure in bar : 148		
3	1	Eqp	WIKA BYPASS CHAMBER BZG-2"/900/rf-M2133-CS60.3x5.54 Tag : 14-LIT-025 External Chamber Type BZG-K00 Pressure: 1610 psi , Temp: 14°F – 300°F Design code: ASME B31 3 Test Pressure: 188 bar Chamber dimensions: OD 60.3 x 5.54 mm (2" Sch 80S) Chamber material: Steel A105/106 Gr. B Joint design: Slip on welds not permitted. Only welding-neck flanges allowed Corrosion allowance: min 1.6 mm included Process connection: Flange ASME B16.5 2" 900# Form RF Process connection orientation: Side-Side Connection technology: Pipe on Pipe Distance C-to-C: 84" Chamber end top: Flange ASME B16.5 2" 900# Form RF Chamber end bottom: Pipe cap Vent connection: male thread ¾" NPT Vent connection orientation: 6 o'clock / 180° Drain connection: Male thread ¾" Gasket(s): Spiral wound type, SS 316L/Graphite Bolting: UNC Series, carbon steel A320 Gr. L7 / HDG / A194 Gr. 7 HDG Top stand-off (T): 254 mm Bottom stand-off (U) 254 mm Side distance (X) 150 mm Nameplate: Stainless steel laser printed TOTAL INDICATION Insertion external sensor: with w/RADAR Transmitter FX86.FADCZ1HXANAM eID: US34260183 Scope F : USA Approval A : FM (NI) CL I, II, III DIV2, GP ABCDFG Version / Material D : Exchangeable cable (ø2mm) with centering weight / 316 Probe : mounted Length (from seal surface) : 90.000 inch Length of rigid part : 3.937 inch	\$96,675.00	\$96,675.00



INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com

			Dimensions centering weight (diameter/height) 1.77in / 1.18in (for 2" Schedule 40/80 and 3" Schedule 80/160) Process fitting / Material CZ : Flange 2" 900lb RF, ASME B16.5 / 316/316L Seal / Second line of defense / Process temperature: Ceramic graphite / with / -196...+280°C Electronics H : Two-wire 4 ... 20 mA/HART Housing / Protection A : Aluminum single chamber / IP66/IP68 (0.2bar) Cable entry / Connection N : ½NPT / Blind plug Display/Adjustment module PLICSCOM A : mounted Certificates M : Yes Certificate / Standard : (C) Material test report – traceable (EN 10204 type 3.1 + NACE MR0175 + NACE MR0103) PMI test : RFA (positive material identification) incl. 3.1 inspection certificate Supply certificates : with goods Measurement loop identification label : of Stainless Steel Customer-specific adjustment : Yes - Unit : inch - 100 % (distance from seal surface) : 10.000 inch - 0 % (distance from seal surface) : 29.000 inch Linearization : No Min. process pressure in bar : -1.000 Max. process pressure in bar : 148		
			Technical Notes Included on each System: - Approval Drawings - Material Certificate 3.1, According EN 10201 3.1 (wetted parts) - Hydrostatic Pressure Test 1.5x Flange Rating for 10 min @ ambient - NACE MR0175 Certificate - Material Test Reports with Tagging Information on each - Positive Material Identification w/o Carbon Content (PMI) - Package/ Handling (per Lot)		
			Delivery Time 18 - 20 weeks ARAD and payment Payment Terms 50 % with Purchase Order 50% Net 30 days Shipping to your custom agent in Vzla Volume & Weight Weight and Volume to be advised IPPC Stamped Sea Freight Export Wood Crate Cci: Williams Brito – INTECH Lecherias		

PLEASE TRANSFER TO OUR ACCOUNT AT:

TRUIST Bank
450 North Pine Island
Plantation, FL 33324
Account #: 0140953040
ABA# 053-101-121
Routing/Transit Number: 2631-9138-7
Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	\$248,845.00
Freight	US \$	-
Insurance	US \$	-
Docs.	US \$	-
TOTAL	US \$	\$248,845.00