



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com
Tax Certificate No. 16-8012998465-1

Quote #**IBI-2025-0136****Date:****Aug 29th, 2025****Customer ID****PETROPIAR - VEN****Bill To:**

Chevron PetroPiar
Complejo Petrolero y Petroquimico Jose, Edo
Anzoategui, Venezuela
Att: Hector Santaella – Estimacion costos
santaellahj@pdvsa.com,
zabaladh@petropiar.pdvsa.com

Ship To:

*Custom Agent to be informed at La Guaira port,
Venezuela*

Your #	Our #	Sales Rep	CIF	SHIP VIA	Terms	Validity
25-0427	IBI-2025-0136/PL &RFQ-202508-03/ QUO00021427-1	N. Carricatti	Maiquetia Airport, VEN	BWPPD	See below	60 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	5	Pz.	PRESSURE GAUGE SERIE 232.34, WIKA PN 232.34.45-PXXX0PX-N4LM/LSG/LOGO Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX psi - TAGREF 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock TAG - REF: 41-PI-001A: 0 - 1,200 PSIG 41-PI-010: 0 - 1,200 PSIG 41-PI-007: 0 - 1,200 PSIG 41-PI-024: 0 - 1,200 PSIG	\$289,00	\$1.445,00

			41-PI-025: 0 - 1,200 PSIG		
2	1	Pz.	PRESSURE GAUGE SERIE 232.34, WIKA PN 232.34.45-PXXX0PX-N4LM/LSG/LOGO Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX psi - TAGREF 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number * ... * stop pin on dial: at 6 o'clock TAG - REF: 41-PI-006B: 0 - 2,000 PSIG	\$289,00	\$289,00
3	2	Pz.	PRESSURE GAUGE CAPSULE SERIE 6X2.34, WIKA PN 80NG07CV46IN49 Type 6X2.34 - Capsule Process Gauges Specifications according to data sheet: PM 06.07 Case: Black Plastic Bezel ring: Threaded Retainer Ring, Plastic, Black Accuracy Class: +/- 2/1/2% (ASME 840.100 Grade A) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Unit: inH2O Scale range: 0 inH2O ... 80 inH2O Process Connection: 1/2 NPT Connector location: lower mount Movement: stainless steel Ingress Protection: IP 65 Case filling fluid: Silicon oil, 50 cSt Package: Single packing Window: laminated safety glass Dial description: Pressure Gauge Standard: International (standard Europe) color for 1.scale (outside): black dial background: White	\$1.085,00	\$2.170,00

			Manufacturer logo: *WIKA* Serial number *...* stop pin on dial: at 6 o'clock norm-mark on dial: *EN 837-3* inner packages label: Standard (with Wika Logo) outside packages label: Standard (with Wika Logo)		
4	1	Pz.	PRESSURE GAUGE SERIE 232.34, WIKA PN 232.34.45-PXXX0PX-N4LM/LSG/LOGO Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX psi - TAGREF 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock TAG - REF: 41-PI-0026: 0 - 20 PSIG	\$289,00	\$289,00
5	2	Pz.	PRESSURE GAUGE SERIE 232.34, WIKA PN 232.34.45-PXXX0PX-N4LM/LSG/LOGO Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX psi - TAGREF 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard	\$289,00	\$578,00

			color for 1.scale (outside): black dial background: White Manufacturer logo: *WIKA* Serial number * ... * stop pin on dial: at 6 o'clock norm-mark on dial: *EN 837-3* inner packages label: Standard (with Wika Logo) outside packages label: Standard (with Wika Logo) TAG-1 (SS Tag Plate) 41 PI-004A; 41 PI-027		
6	1	Pz.	PRESSURE GAUGE SERIE 232.34, WIKA PN 232.34.45-PXXX0PX-N4LM/LSG/LOGO Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX psi - TAGREF 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number * ... * stop pin on dial: at 6 o'clock TAG - REF: 41-PI-032: 0 - 300 PSIG	\$289,00	\$289,00
7	1	Pz.	PRESSURE GAUGE SERIE 232.34, WIKA PN 232.34.45-BXXX0PX-N4LM/LSG/LOGO Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX bar - TAGREF 2nd Scale / Special Scale: none Process Connection: 1/2 NPT	\$289,00	\$289,00

			Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock TAG - REF: 41-PI-036A: 0 – 3 bar		
8	2	Pz.	PRESSURE GAUGE SERIE 232.34, WIKA PN 232.34.45-PXXX0PX-N4LM/LSG/LOGO Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX psi - TAGREF 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock TAG - REF: 41-PI-038: 0 - 60 PSIG 41-PI-039: 0 - 60 PSIG	\$289,00	\$578,00
9	1	Pc	BIMETAL THERMOMETER, PROEESS GRADE, MODEL TG53.5Z WITH THERMOWELL TW15, WIKA PN 56NG05CV00IN88- 39TE119CH06CA8 Bimetal thermometer, Proeess grade aeeording to ASME B40.200 Model: TG53.5Z Speifieations aeeording to data sheet: ATM 53.02	\$705,00	\$705,00

			Accuracy Class: +/-1% of Full Scale (ASME B40.3) Nominal size: 5" Connector position: back mount, adjustable Design of Connection: standard, male thread Process Connection: 1/2" NPT Seal Range: 0 °C ... 150 °C Stem Diameter: 1/4" Insertion length L 1: 9" Window: laminated safety glass Ingress Protection: IP 66 / NEMA 4X Permissible ambient temperature: -40 ... +70 °C with Serial number Manufacturer logo: *WIKA** Threaded Thermowell TW15, solid machined Specifications according to data sheet: TW 95.15 Head Design: Hexagon Thermowell Style: Tapered Unit of Measure: Imperial (inch) Process thread [P or E]: 1" NPT Instrument connection [N]: 1/2 NPT female Insertion length [U]: 7.5 inch Head Length: 1.75" Material: Stainless steel 316/316L Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 1.063 inch Tip diameter [V or F3]: 0.750 inch Bore depth / stem length (US): 9.000 inch Tip thickness [Tt]: 0.250 inch (6.4 mm) TAG-1 (SS Tag Plate) 41-TI-006		
10	1	Pc	GAS ACTUATED THERMOMETER, MODEL S73.100 WITH THERMOWELL TW15, WIKA PN 80NG07CV46IN48- 39TE10CH80CA40 Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem Material: stainless steel Model: S73.100, nominal size 100, adjustable stem and dial Unit: °F Seal Range: 400 a 1200 °F Design of Connection: 4, compression fitting, sliding on stem Process Connection: 1/2" NPT Stem Diameter: 6 mm Insertion length L 1: 152 Ignition protection type: without Zone: without Accuracy Class: class 1 per EN 13190 Window: laminated safety glass Connector location: axial Manufacturer logo: *WIKA* with Serial number QR code with extended serial number on dial Threaded Thermowell TW15, solid machined Specifications according to data sheet: TW 95.15 Head Design: Hexagon Thermowell Style: Tapered	\$1.224,00	\$1.224,00

			Unit of Measure: Imperial (inch) Process thread [P or E]: 1" NPT Instrument connection [N]: 1/2 NPT female Insertion length [U]: 4.5 inch Head Length: 1.75" Material: Stainless steel 316/316L Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 1.063 inch Tip diameter [V or F3]: 0.750 inch Bore depth / stem length (US): 6.000 inch Tip thickness [Tt]: 0.250 inch (6.4 mm) TAG-1 (SS Tag Plate) 41-TI-007		
11	4	Pc	BIMETAL THERMOMETER, PROEESS GRADE, MODEL TG53.5Z WITH THERMOWELL TW15, WIKA PN 80NG05CV11IN79-39TE119CH06CA8 Bimetal thermometer, Proeess grade aeecording to ASME B40.200 Model: TG53.5Z Speeifications aeecording to data sheet: ATM 53.02 Aeeuraey Class: +/-1% of Full Seale (ASME B40.3) Nominal size: 5" Conneetor position: baek mount, adjustable Design of Conneetion: standard, male thread Proeess Conneetion: 1/2" NPT Seale Range: 50 °F ... 550 °F Stem Diameter: 1/4" Insertion length L 1: 9" Window: laminated safety glass Ingress Proteetion: IP 66 / NEMA 4X Permissible ambient temperature: -40 ... +70 °C with Serial number Manufaeturer logo: *WIKA®* Threaded Thermowell TW15, solid machined Specifications according to data sheet: TW 95.15 Head Design: Hexagon Thermowell Style: Tapered Unit of Measure: Imperial (inch) Process thread [P or E]: 1" NPT Instrument connection [N]: 1/2 NPT female Insertion length [U]: 7.5 inch Head Length: 1.75" Material: Stainless steel 316/316L Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 1.063 inch Tip diameter [V or F3]: 0.750 inch Bore depth / stem length (US): 9.000 inch Tip thickness [Tt]: 0.250 inch (6.4 mm) TAG-1 (SS Tag Plate) 41-TI-025; 41-TI-026; 41-TI-030; 41-TI-031	\$709,00	\$2.836,00
			Payment Terms Net 30 days delivery date, with Advise of Shipment to Venezuela CIF		

**INDUSTRIAL BUSINESS INTL CORP**

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com

			Delivery Time ARO and payment Items 1, 2, 4-8: 6-10 weeks Items 3: 18-20 weeks Items 9-11: 9-10 weeks Volume & Weight Weight and Volume to be advised Recommended shipping <u>by Air Freight to final destination</u> Cci: W. Brito – INTECH PLCRZ		

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

Branch Banking & Trust Co.
450 North Pine Island
Plantation, FL 33324
Account #: 0140953040
ABA# 053-101-121
Routing/Transit Number: 2631-9138-7
Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	10,692.00
Freight	US \$	included
Insurance	US \$	included
Docs.	US \$	included
TOTAL	US \$	10,692.00