



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com
Tax Certificate No. 16-8012998465-1

Quote #

IBI-2025-0150

Date:

Oct 9th, 2025

Customer ID

PETROPIAR - VEN

Bill To:

Chevron PetroPiar

Complejo Petrolero y Petroquimico Jose, Edo
Anzoategui, Venezuela
Att: Hector Santaella – Ing. Costos
santaellahj@pdvsa.com

Ship To:

Custom Agent to be informed at La Guaira port,
Venezuela

Your #	Our #	Sales Rep	CIF	SHIP VIA	Terms	Validity
25-0497	IBI-2025-0147 / LE	L. Zuñiga	Maiquetia Airport, VEN	BWPPD	See below	60 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	6	Pcs	BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications AREA: COKER Part Number 3809GAA12BGAB3H4CBC0 Tag-001 12-FI-650A Tag-002 12-FI-651A Tag-003 12-FI-652A Tag-004 12-FI-650B Tag-005 12-FI-651B Tag-006 12-FI-652B Max Press @ Max Temp 720 PSIG 49.6 BAR Accuracy 2% -Direct Scale-Liquid Meter Material 316L SS w/ Cert 3.1 Connection Size 1 ½ - in Connection Type 300# WNRF Flange Inlet Down Outlet Up O-Ring Material No Valve On Inlet-Teflon-Sent Detached Valve Connection Visible Thd Flg Range 2.6 – 26 GPM Indicator Housing XP STAINLESS Electrical Connection 3/4-in NPT-F Indicator/Alarm/Transmit XMTR 4-20MA – HART, LOI DIGITAL DISPLAY - HART DIV 1-ZONE 1 XP-IIC-IECEX-CSA [C] NACE & Mat Cert 3.1 Approvals Certification (1) Stainless TAG Type International Calibration Certificate (ICC) Certificate of Conformance (Compliance) 2.1 Certificate of Origin	14,760.00	88,560.00

2	100	Pcs	WIKA PRESSURE GAUGES SERIES 233.XX with Diaphragm Seal LOWER MOUNT Process gauge 233.50, SS Case, 100 mm (4") Scale Range: 0-100 psi Measuring System 316L Ingress protection: IP 65 Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIC T85 °C ... T450 °C Db X) class 1.0 Window: laminated safety glass adjustable pointer Case filling fluid: Silicone Oil Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number with QR Code Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21 °C (room temperature) Process temperature max.: + 21°C (room temperature) Ambient temperature pressure meas. min: + 10 °C Ambient temperature pressure meas. max: + 40 °C Diaphragm seal with threaded process connection Model 990.10 Threaded connection: 1/2" NPT male PN 100 Upper body material / main body material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower part material: Stainless steel 1.4404 (316L); UNS S31603 Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Test certificate acc. to EN 10204 2.2 Certificate Language: English and German Certificate for: Diaphragm seal system with pressure measuring instrument Formal certificate: Manufactured according to state-of-the-art Label: WIKA standard without / with Tag-number	\$1,550.00	\$155,000.00
3	3	Pcs	WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0/160 psi Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling	\$295.00	\$885.00

			Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial		
4	6	Pcs	WIKA PRESSURE GAUGE Serie 233.XX Process Gauge 233.50., SS316 Case, 100 mm (4") Scale Range 0-20 psi Connection 1/2 NPT lower mount Measuring System 316L Ingress protection: IP 65 Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C ... T450 °C Db X) class 1.0 Window: laminated safety glass Case filling fluid: Silicone Oil Permissible ambient temperature: -20 ... +60 °C Permissible medium temperature: + 100 °C Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number with QR Code Label: WIKA standard without / with Tag-number Add to shopping cart	\$160.00	\$960.00
5	50	Pcs	WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure with DIAPHRAGM SEAL Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0/200 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications	\$1,495.00	\$74,750.00

			Process temperature min.: + 21°C (room temperature) Process temperature max.: + 40°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 3/4" NPT female Nominal pressure rating: 1500 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)		
6	40	Pcs	WIKA PRESSURE GAUGE Serie 233.XX Process Gauge 233.50., SS316 Case, 63 mm (2 1/2") Scale Range 0-30 psi Connection 1/2 NPT lower mount Measuring System 316L Ingress protection: IP 65 Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C ... T450 °C Db X) class 1.0 Window: laminated safety glass Case filling fluid: Silicone Oil Permissible ambient temperature: -20 ... +60 °C Permissible medium temperature: + 100 °C Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number with QR Code Label: WIKA standard without / with Tag-number Add to shopping cart	\$155.00	\$6,200.00
7	75	Pcs	WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure with DIAPHRAGM SEAL Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0/400 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65	\$1,490.00	\$111,750.00

			Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21°C (room temperature) Process temperature max.: + 40°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 3/4" NPT female Nominal pressure rating: 1500 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)		
8	1	Pcs	WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure with DIAPHRAGM SEAL Process gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0 - 50 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Silicone, 1000 cSt Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial	\$1,530.00	\$1,530.00

			Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21°C (room temperature) Process temperature max.: + 40°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 3/4" NPT female Flushing connection: 1 x 1/4 NPT female Nominal pressure rating: 1500 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)		
9	30	Pcs	WIKA PRESSURE GAUGE Serie 232.XX Process Gauge 233.50., S316 Case, 63 mm (2 1/2") Scale Range 0-30 psi Connection 1/4 NPT lower mount Measuring System 316L Ingress protection: IP 65 Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIC T85 °C ... T450 °C Db X) class 1.0 Window: laminated safety glass Case filling fluid: DRY Permissible ambient temperature: -20 ... +60 °C Permissible medium temperature: + 100 °C Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number with QR Code Label: WIKA standard without / with Tag-number Add to shopping cart	\$135.00	\$4,050.00
10	18	Pcs	WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: Silicone Oil Nominal size: 4.5" Scale range: 0/1500 psi Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling	\$345.00	\$6,210.00

			Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial		
11	5	Pcs	WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: Silicone Oil Nominal size: 4.5" Scale range: 0/300 psi Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial	\$370.00	\$1,850.00
12	5	Pcs	WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0/600 psi Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock	\$345.00	\$1,725.00

			QR code with extended serial number on dial		
13	16	Pcs	WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure with DIAPHRAGM SEAL Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0/800 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21°C (room temperature) Process temperature max.: + 40°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 1" NPT female Nominal pressure rating: 1500 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)	\$1,490.00	\$23,840.00
14	1	Pcs	WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel	\$320.00	\$320.00



			Case filling: Silicone Oil Nominal size: 4.5" Scale range: 0/300 psi Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIK®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial		
15	7	Pcs	WIK® PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: Silicone Oil Nominal size: 4.5" Scale range: 0/3000 psi Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: WIK® Dial background: Reflective Fluorescent Yellow *WIK®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial	\$335.00	\$2,345.00
16	7	Pcs	WIK® PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: Silicone Oil Nominal size: 4.5" Scale range: 0/5000 psi Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer	\$335.00	\$2,345.00

		Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial												
		Item 1: 6 -8 Weeks ARO Item 12: 1 – 2 Weeks ARO Others: 12 - 16 Weeks ARO Partial Shipments allowed (WIKA) Payment Terms • 50% advance payment with Order and ARAD • 50% Balance Net 30 days delivery DDP Volume & Weight (to be reconfirmed) To be advised – Aprox 3,100 Lbs General Warranty: WIKA warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser. Project Cancellation charges: <table><tr><td>15%</td><td>Up to submittal of Engineering & Design Drawings and Documents</td></tr><tr><td>25%</td><td>After submittal of Engineering & Design Drawings and Documents</td></tr><tr><td>50%</td><td>After material order placement and before production commences</td></tr><tr><td>75%</td><td>Within two weeks of production release</td></tr><tr><td>100%</td><td>Two weeks after production commences</td></tr></table> Cci: W. Brito – INTECH PLCRZ	15%	Up to submittal of Engineering & Design Drawings and Documents	25%	After submittal of Engineering & Design Drawings and Documents	50%	After material order placement and before production commences	75%	Within two weeks of production release	100%	Two weeks after production commences		
15%	Up to submittal of Engineering & Design Drawings and Documents													
25%	After submittal of Engineering & Design Drawings and Documents													
50%	After material order placement and before production commences													
75%	Within two weeks of production release													
100%	Two weeks after production commences													

**INDUSTRIAL BUSINESS INTL CORP**

1580 Sawgrass Corporate Parkway

Suite 130, Sunrise, FL 33323

Tel: 954-302-3187, 315-4781

Fax: 954-838-7746

E-mail: ibicorp@intech-ie.com

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

TRUIST Bank.

450 North Pine Island

Plantation, FL 33324

Account #: 0140953040

ABA# 053-101-121

Routing/Transit Number: 2631-9138-7

Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	482,320.00
Freight	US \$	Included
Insurance	US \$	Included
Docs.	US \$	Included
TOTAL	US \$	482,320.00