



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com
Tax Certificate No. 16-8012998465-1

Quote #

IBI-2025-0166

Date:

Nov 14th, 2025

Customer ID

Bill To:

ALDYL ENERGIA, C.A.

RIF: J-50552371-6

Av Francisco De Miranda, C/C Tamanaco Edif Easo
Piso Mezzanina Of 1 Urb El Rosal Caracas (Chacao)
Miranda Zona Postal 1060
Telf: 0424-6421805
Attn: Yanitza Martinez
Correo: Puedes enviarme la cotización por aquí y
por mi correo corporativo
y.martinez@aldyl.com.ar

Ship To:

El material se enviará al almacén/broker del
cliente en Venezuela.

Your #	Our #	Sales Rep	Incoterms - DDP	SHIP VIA	Terms	Validity
@06/11/2025	IBI-2025-0166/PL	N. Carricatti	CCS	Pick up	Ver abajo	30 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	1	Pc	Barometric Smart Manometer HHP360-A Replacement, Omega Accuracy Class < 0.1% Accuracy Detail Pressure Accuracy: $\pm 0.020\%$ Full Scale + 0.005% of Reading; Temperature Probe Accuracy : IEC 60751 PT100 class A ,Tolerance = $\pm (0.15 + 0.002$ Additional Features 1 Selectable Engineering Units, MIN/MAX, Datalogging Altitude Up to 36,000 ft Applications Filter Monitoring, Leak testing, Pressure Calibration Battery Size and Type Alkaline AA Data Interface USB Dimensions Note Length 9.8 in (248.9 mm) from manifold to end of boot Width 5.2 in (132.1 mm) at widest point with boot Height 2.3 in (58.4 mm) Connections Display Measuring Units Min/Max Display Resolution Up to 6 digit depending on pressure unit selected Height 2.3 in Indicated Air Speed 0 Knots to 660 Knots, 0 to 760 mph, 0 Km/h to 1223 Km/h Length 9.8 in Materials 316 Stainless Steel Measurement Pressure Type Barometric Measurement Pressure, Max 15 psi Measurement Pressure, Min 0 psi Number of Batteries 4 Number of Digits 6 Operating Temperature, Max 50 °C Operating Temperature, Min -10 °C Pressure Accuracy $\pm 0.025\%$ Probe Temperature, Max 250 °C	\$6.800,00	\$6.800,00



		Probe Temperature, Min -50 °C Process Connection Note 1/8" Female NPT 316SS USB, Omega Tethered Sensor (OTS) Port,USB Power Process Connection Size 1/8 in Process Connection Type NPT Female RTD Accuracy Class A Storage Temperature, Max 70 °C Storage Temperature, Min -20 °C Supply Power Note 4 AA batteries Tolerance $\pm (0.15 + 0.002)$ Width 5.2 in		
		Delivery Time Luego de recibir orden de compra y pago, Items: 8-10 semanas aprox. El tiempo de entrega de los elementos ofertados queda sujeto a cambios generados por eventos fuera de manejo de la compañía como: 1. Fenómenos climáticos que no permitan el transporte de materia prima a la fábrica, transporte local en el extranjero del material manufacturado y/o transporte internacional del producto. 2. Normal funcionamiento de aduana Venezolana y/o extranjeras. 3. Alteración del orden público en el país de origen, país en tránsito y/o país final. 4. Actos delictivos y/o terroristas. 5. Cualquier otro evento considerado de fuerza mayor. Payment terms 100 % con orden de compra Volume & Weight Peso y volumen por notificar		

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

Branch Banking & Trust Co.
450 North Pine Island
Plantation, FL 33324
Account #: 0140953040
ABA# 053-101-121
Routing/Transit Number: 2631-9138-7
Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	\$6.800,00
Freight	US \$	Included
Docs.	US \$	Included
TOTAL	US \$	\$6.800,00