



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway

Suite 130, Sunrise, FL 33323

Tel: 954-302-3187, 315-4781

Fax: 954-838-7746

E-mail: ibicorp@intech-ie.com

Tax Certificate No. 16-8012998465-1

Quote #**IBI-2025-0184****Date:**Dec 11th, 2025**Customer ID****Cerveceria Polar - BCNA****Bill To:****Cerveceria Polar, C.A.****RIF: J-00006372-9**

Av. 2da De Los Cortijos De Lourdes, Local Planta Polar, Urb. Los Cortijos De Lourdes. Caracas 1071.

Atn: Pedro Ancheta

Telf.: 0414-8282262

Correo: Pedro.ancheta@empresaspolar.com

Ship To:

El material se enviará al almacén / broker del cliente en el Aeropuerto de Maiquetía - Venezuela

Your #	Our #	Sales Rep	Incoterms - CPT	SHIP VIA	Terms	Validity
Budgetary	IBI-2025-0183/PL	N. Carricatti	Maiquetia Airport	Pick up	See below	60 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
			SISTEMA REEMPLAZO ACM, LR.11- VARIVENT		
1	1	Pc	SISTEMA ANALIZADOR DE BRIX 5100 CON PACK DE INSTALACION TUBERIA DN50, ANTON PAAR PN 65427650 Highly accurate process sensor for refractive index and sugar measurement. Includes: VARINLINE ACCESS UNIT SET DN 50 WITH DEFLECTOR FOR BRIX METER Technical specification - Accuracy: ± 0.0002 nD (equivalent to ± 0.1 % mass) - Repeatability: ± 0.0001 nD (equivalent to ± 0.05 % mass) - Refractive index range: 1.31 to 1.54 nD - Sugar range: 0 to 100 % - Process temperature: -20 bis 120 °C (145 °C for 30 min) - Process pressure: 100 mbara to 16 bara (10 bara > 120 °C) - Ambient temperature: -20 to 60 °C - Wetted parts: Stainless steel 1.4404, PEEK, Sapphire - Protection rating: IP65, IP67 / Nema 6P - Certificates: EHEDG	\$11.616,00	\$11.616,00
2	1	Pc	SISTEMA UNIDAD DE EVALUACION EDGE 7000 CONTROLADOR HMI IP65 Y HOUSING INTEGRADO Y BOARD ANALOGICA/DIGITAL DE COMUNICACION, ANTON PAAR PN 49897298 Technical specifications - Dimensions Controller (WxDxH): 240 x 150 x 70 mm - Dimensions HMI (WxDxH): 290 x 210 x 6 mm	\$8.971,00	\$8.971,00

			- Dimensions panel cutout (WxH): 260 x 183 mm - Touch screen: 10.1" TFT, 1280 x 800 px - Power supply: DC 24 V -15 % / +20 % - Power consumption: - without sensors: 30 W* - with CAN sensors: 105W* - with CAN sensors and L-Col 6100: 130 W* * USB periphery max. 0.5 A per port - Ambient temperature: -20 °C bis 55 °C - Air humidity: 0 to 90 % relative humidity, non-condensing - Interfaces - Analog output: 2x 4 to 20 mA active - Analog input: 1x 4 to 20 mA active and passive - Digital output: 4x - Digital input: 6x - Fieldbus interfaces: PROFIBUS DP, PROFINET IO, EtherNet/IP - Sensor input: CAN - Service and communication interfaces: 1x USB 2.0 and 2x USB 3.0 2x Ethernet IEEE 802.3, 10/100/1000 MBit - Protection rating: IP65 (HMI front), IP20 (controller back) - Weight: 1.5 kg		
3	30	m	CABLE 2x2x0.22 D7.1 mm PER m FOR CAN BUS PN 94268	\$14,00	\$420,00
			Delivery Time 8-10 weeks after receipt of order and payment (subject to changes) The delivery time of the items offered is subject to changes generated by events outside the company's control, such as: 1. Climatic phenomena that do not allow the transport of raw material to the factory, local transport abroad of the manufactured material and/or international transport of the product. 2. Normal functioning of Venezuelan and/or foreign customs. 3. Disruption of public order in the country of origin, country of transit and/or final country. 4. Criminal and/or terrorist acts. 5. Any other event considered major force. Payment terms 100% with purchase order Volume & Weight Weight / Volume to be advised		

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

Branch Banking & Trust Co.
450 North Pine Island
Plantation, FL 33324
Account #: 0140953040
ABA# 053-101-121
Routing/Transit Number: 2631-9138-7
Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	21,007.00
Freight	US \$	1,500.00
Insurance	US \$	Included
Docs.	US \$	Included
TOTAL	US \$	22,507.00