



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com
Tax Certificate No. 16-8012998465-1

Quote #

IBI-2025-0185Rev1

Date:

Feb 19th, 2026

Customer ID

PETROPIAR - VEN

Bill To:

CHEVRON – PDVSA PETROPIAR

Complejo Petrolero y Petroquimico Jose, Edo
Anzoategui, Venezuela
P: +58-414-9829407
Att: Ing. Audrey Villarroel- Estimacion costos
villarroeladr@petropiar.pdvs.com

Ship To:

Custom Agent to be informed at La Guaira port,
Venezuela

Your #	Our #	Sales Rep	CIF	SHIP VIA	Terms	Validity
25-0283	IBI-2025-0185/PL WIDN-202512-01 QUO00022390 IBI-2026-0050	N. Carricatti	Maiquetia Airport, VEN	BWPPD	See below	60 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	4	Pz.	DIAPHRAGM PRESSURE SWITCH MODEL MW-TXUS, WIKA PN 80077422 Diaphragm pressure switch, Stainless steel case, Model MW measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection A electric contacts: 2 x SPDT or 1 x DPDT silver contact, hermetically sealed, argon gas filling setting range: -15...25 psi Standard, working range = -15...25 PSI, proof pressure 30 PSI process connection: Adaptor 1/2 NPT-M electrical connection: 3/4 -14 NPT-F Enclosure with plate for wall or direct mounting Ingress Protection: IP66 Diaphragm: Stainless Steel AISI 316/O-Ring: FPM/Connection: Stainless steel AISI 316L brand: WIKA Instruments Italia Specifications according to data sheet: PV 31.10 Repeatability of set point: ≤ 1% of span set point definition: Set Point to be defined Approvals / Certificates IECEx-ATEX Ex ia	\$1.548,00	\$6.192,00
2	2	Pc	INDUSTRIAL PROCESS TRANSMITTER MODEL IPT-20, WIKA PN 80076377 Industrial process transmitter IPT-2x with metallic sensor element Model: IPT-20 Specifications according to data sheet: PE 86.06 Pressure Range: adjustable with turn down up to 100 : 1 Process connection type: Standard connection with pressure port Electrical approval: ATEX, IECEx,	\$6.840,00	\$12.960,00

		Ignition protection type: Ex d - explosion proof Zone: Zone 1 attached to zone 0 gas [Ex d IIC T1...T6 Ga/Gb] Housing material: Aluminum single chamber enclosure execution: compact/ IP66/IP67; NEMA 4X Digital Display: with integrated indicating/adjustment module (top) Output signal: 4...20 mA, 2-wire, HART Electrical connection: ½NPT / plug Pressure range: -1 ... +5 bar gauge Accuracy: 0.1 % of span process connection form: Gauge connection open Process connection / wetted parts: Diaphragm seal Sealing: without Clean specification: without Filling of sensor: Silicone oil Certification sterile processes: without wetted parts: stainless steel Unit of outer Scale: without Density unit: kg/dm³ Mounting accessories: Mounting bracket for wall and pipe mounting (stainless steel) (for 2" pipe) Sensor principle: piezoresistiv Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: 4 meter capillary; stainless steel System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: - 40°F Process temperature max.: + 266°F Ambient temperature pressure meas. min: + 69.8°F (room temperature) Ambient temperature pressure meas. max: + 86°F diameter of capillary: ID 2mm (3x0.5 mm) Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 1/2" NPT male Flushing connection: 1 x 1/4 NPT female Nominal pressure rating: PN 250 Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: PTFE max. 500°F Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Label: WIKA standard without / with Tag-number		
		Payment Terms Net 30 days delivery date, with Advise of Shipment to Venezuela CIF Delivery Time ARO and payment Items 1, 2: 10-14 weeks Volume & Weight Weight and Volume to be advised Recommended shipping <u>by Air Freight to final destination</u>		
		Cci: W. Brito – INTECH PLCR		

**INDUSTRIAL BUSINESS INTL CORP**

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com

--	--	--	--	--	--

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

Branch Banking & Trust Co.
450 North Pine Island
Plantation, FL 33324
Account #: 0140953040
ABA# 053-101-121
Routing/Transit Number: 2631-9138-7
Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	19,152.00
Freight	US \$	included
Insurance	US \$	included
Docs.	US \$	included
TOTAL	US \$	19,152.00