



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com
Tax Certificate No. 16-8012998465-1

Quote #

IBI-2024-0006

Date:

Jan 24th, 2024

Customer ID

Cerveceria Regional

Bill To:

C.A. Cervecería Regional

RIF: J-07000344-8

Av. Principal Norte, Zona Industrial Santa Rosalia,
Cagua, Edo. Aragua - Venezuela

Telf: 0244-4003160 / 0412-4791553

Attn: Pedro Beomont

Correo: pedro.beomont@cerveceriaregional.com

Ship To:

Material will be sent to customer's warehouse at
Cagua, Edo. Aragua - Venezuela.

Your #	Our #	Sales Rep	Incoterms – DDP	SHIP VIA	Terms	Validity
Budgetary	IBI-2024-0006/PL	N. Carricatti	Cagua, VEN	Pick up	See below	60 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	1	Pc	BEER MONITOR 5600, ANTON PAAR PN 183483 High precision beverage measuring system for determination of alcohol, real, original extract, CO2 and other parameters in beer. Inline installation using both ports of a single VARINLINE® housing. Scope of delivery 1 Pcs. Carbo 6300 Sensor with Cable glands 1 Pcs. mPDS 5 with CPU 1 Pcs. L-Com 5500 incl. Sample pump, with Cable glands 2 Pcs. Varivent clamp 1 Pcs. DSUB CANopen 9BU Plug 35° Technical specifications Accuracy Real Extract: 0.02 % w/w Accuracy Original Extract: 0.04 % w/w Range Real Extract: 0 to 12 °Plato Range Original Extract: 0 to 35 °Plato Accuracy CO2: 0.05 g/L (0.025 Vol) CO2 Range: 0 to 12 g/L (0 to 6 Vol) Accuracy Alcohol: 0.02 % v/v Range Alcohol: 0 to 12 % w/w (0 to 15 % v/v at 20 °C) Process temperature: -3 °C to 25 °C (130 °C for max. 30 min CIP/SIP) Process pressure: up to 10 bar (145 psi) Ambient temperature: 5 to 40 °C Wetted parts: Stainless steel 1.4404, PEEK, Sapphire, EPDM, SSiC, tungsten carbide Protection rating: IP66 (Sensors), IP54 (Evaluation unit) Process connection: Tuchenhausen Varivent Type N, DN 65	43,760.00	43,760.00
2	1	Pc	I/O BOARD mPDS 5, ANTON PAAR PN 23961 Interface board with digital inputs/outputs and 0/4-20 mA inputs and 4-20 mA outputs.	1,458.00	1,458.00

			In addition the board provides 2 relay outputs. Technical specifications 2 Stk. Relays 12 Pcs. digital inputs and outputs (active/passive/configurable) 4 Pcs. analog 4-20 mA outputs (active) 3 Pcs. analog 0/4-20 mA inputs (active or passive)		
3	20	Pc	CABLE 2x0.5 mm2 D5.5 mm SHIELDED PER m PN 50654 Nota: la distancia debe ser confirmada. Cable para alimentación electrica y comunicación a PLC	6.00	120.00
4	20	Pc	CABLE 2x1.5 mm2 D7.1 mm SHIELDED PER m PN 99389 Nota: la distancia debe ser confirmada. Cable para alimentación electrica y comunicación a PLC	7.00	140.00
			RECOMMENDED OPTIONALS		
5	1	Pc	POWER SUPPLY 100-240 VAC 24 VDC 20 A PN 93074	1,163.00	1,163.00
6	1	Pc	Davis 5 SOFTWARE INCL. 1 LICENSE mPDS 5, ANTON PAAR PN 89816 Software for data acquisition and visualization for mPDS 5 evaluation units Technical specifications Up to 10x mPDS 5 on one Davis 5 Server Up to 10x Davis 5 Clients on one Davis 5 Server Graphical and numerical online windows Remote product management for the mPDS 5 Product selection, alarms, alarm reset Graphical, statistical and histogram reports Automatic reports to e-mail addresses and file shares LIMS interface Client/Server application Microsoft SQL Database Server Compatible with most common Windows OS versions	3,521.00	3,521.00
7	1	Pc	VARINLINE ACCESS UNIT SET DN 40 POCKET-FREE INSTALLATION, ANTON PAAR PN 101119 Consisting of: 1 Pcs. VARINLINE Access Unit DN 40 2 Pcs. Hinged clamp Varivent N with nut 2 Pcs. O-Ring 60x3 EPDM 70 FDA compliant 1 Pcs. Blanking plate Type N	843.00	843.00
8	1	Pc	STAINLESS STEEL HOUSING mPDS 5 COMPLETE, MOUNTED, ANTON PAAR PN 86824 Includes: 1 Pcs. Stainless steel housing for mPDS 1000/1100/2000/5 hinged 1 Pcs. Front panel for mPDS 5	4,040.00	4,040.00

**INDUSTRIAL BUSINESS INTL CORP**

1580 Sawgrass Corporate Parkway

Suite 130, Sunrise, FL 33323

Tel: 954-302-3187, 315-4781

Fax: 954-838-7746

E-mail: ibicorp@intech-ie.com

		1 Set Ground wire for stainless steel housing 1 Set Mounting - mPDS 1 Set Mounting rail installed in stainless steel housing hinged 1 Blind plug set for stainless steel housing 2x PG13.5, 4x PG11, 4x PG9, seal ring nuts 2 Pcs. Cable gland PG13.5 D6-12 IP68 2 Pcs. Cable gland PG11 D5-10 IP68 2 Pcs. Cable gland PG9 D2-6 IP68		
		Delivery Time 7-10 weeks after receipt of order and payment (subject to changes) The delivery time of the items offered is subject to changes generated by events outside the company's control, such as: 1. Climatic phenomena that do not allow the transport of raw material to the factory, local transport abroad of the manufactured material and/or international transport of the product. 2. Normal functioning of Venezuelan and/or foreign customs. 3. Disruption of public order in the country of origin, country of transit and/or final country. 4. Criminal and/or terrorist acts. 5. Any other event considered major force. Payment terms Prepayment with PO Volume & Weight Weight / Volume to be advised		

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

Branch Banking & Trust Co.

450 North Pine Island

Plantation, FL 33324

Account #: 0140953040

ABA# 053-101-121

Routing/Transit Number: 2631-9138-7

Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	55,045.00
Freight	US \$	1,360.00
Insurance	US \$	Included
Docs.	US \$	Included
TOTAL	US \$	56,405.00