



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com

Quote #**IBI-2024-0010****Date:****Feb 5th, 2024****Customer ID****PDVSA PETROPIAR****Bill To:**

CONTROVAL
Barcelona, Edo Anzoategui, Venezuela
Attn: Francisco Bessa
Cel: +584242187056
fbessa@controval.com

Ship To:

Customer's warehouse in Barcelona, Venezuela

Your #	Our #	Sales Rep	Incoterms - DDP	SHIP VIA	Terms	Validity
Email	IBI-2024-0010/PL	S. Mendez	VEN	Pick up	Prepayment with Order	30 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	2	Pcs	PRESSURE GAUGE, MATERIAL STAINLESS STEEL, Series 233.50 Dial 4" Range 0 – 15 PSI, WIKA PN 80049729 Type 23X.50 - SS Case - Pressure Gauges Series Model: 233.50 Specifications according to data sheet: PM 02.02 Measuring System: Stainless Steel Case filling: with Nominal size: 4" Scale range: 0/15 psi Process Connection: 1/2 NPT Connector location: lower back mount Window: laminated safety glass Pointer: standard pointer Accuracy Class: class 1.0 Material pressure element: Measuring System 316L Case filling fluid: glycerine-water-mixture Ingress Protection: IP 65 Permissible medium temperature: + 100 °C Permissible ambient temperature: -20 ... +60 °C Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIK*A* with Serial number	165.00	330.00
2	3	Pcs	PRESSURE GAUGE WITH MOUNTED DIAPHRAGM SEALS, MATERIAL STAINLESS STEEL, Series DSS10M Dial 4" Range 0-2.5 BAR, WIKA PN 14213345 pressure gauge with mounted diaphragm seals, with threaded connection Model: DSS10M Specifications according to data sheet: DS 95.01 Pressure measuring instrument: Manometer according to EN 837-1 nominal size 100 mm Case filling: with Unit of outer Scale: bar Scale range: 0...2.5 bar	785.00	2,355.00

			Assembly: direct assembly System fill fluid: KN 2 Silicone oil for general applications Unit of temperature: Celsius Process temperature min.: - 10°C Process temperature max.: + 150°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Process connection standard: following ANSI B 1.20.1 (e.g. 1/2" NPT) Threaded connection: 1/2" NPT male Nominal pressure rating: PN 100 Wetted parts: Stainless steel 1.4404/1.4435 (316L); UNS S31603 Gasket: PTFE max. 260°C Fastening parts: Retainer flange and bolts in stainless steel		
3	1	Pcs	PRESSURE GAUGE TYPE BOURDON TUBE, MATERIAL SS, Series 233.50 Dial 4" Range 0 – 60 PSI, WIKA PN 80049733 Type 23X.50 - SS Case - Pressure Gauges Series Model: 233.50 Specifications according to data sheet: PM 02.02 Measuring System: Stainless Steel Case filling: with Nominal size: 4" Scale range: 0/60 psi Process Connection: 1/2 NPT Connector location: lower back mount Window: laminated safety glass Pointer: standard pointer Accuracy Class: class 1.0 Material pressure element: Measuring System 316L Case filling fluid: glycerine-water-mixture Ingress Protection: IP 65 Permissible medium temperature: + 100 °C Permissible ambient temperature: -20 ... +60 °C Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIK*A* with Serial number	165.00	165.00
4	2	Pcs	PRESSURE GAUGE WITH MOUNTED DIAPHRAGM SEALS, MATERIAL STAINLESS STEEL, Series DSS10M Dial 4" Range 0-10 BAR, WIKA PN pressure gauge with mounted diaphragm seals, with threaded connection Model: DSS10M Specifications according to data sheet: DS 95.01 Pressure measuring instrument: Manometer according to EN 837-1 nominal size 100 mm Case filling: with Unit of outer Scale: bar Scale range: 0...10 bar Assembly: direct assembly System fill fluid: KN 2 Silicone oil for general applications Unit of temperature: Celsius Process temperature min.: - 10°C Process temperature max.: + 150°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Process connection standard: following ANSI B 1.20.1 (e.g. 1/2" NPT)	760.00	1,520.00

			Threaded connection: 1/2" NPT male Nominal pressure rating: PN 100 Wetted parts: Stainless steel 1.4404/1.4435 (316L); UNS S31603 Gasket: PTFE max. 260°C Fastening parts: Retainer flange and bolts in stainless steel		
5	1	Pcs	PRESSURE GAUGE TYPE BOURDON TUBE, MATERIAL SS, Series 233.50 Dial 4" Range 0 – 160 PSI, WIKA PN 14387486 Type 23X.50 - SS Case - Pressure Gauges Series Model: 233.50 Specifications according to data sheet: PM 02.02 Measuring System: Stainless Steel Case filling: with Nominal size: 4" Scale range: 0/160 psi Process Connection: 1/2 NPT Connector location: lower back mount Window: laminated safety glass Pointer: standard pointer Accuracy Class: class 1.0 Material pressure element: Measuring System 316L Case filling fluid: glycerine-water-mixture Ingress Protection: IP 65 Permissible medium temperature: + 100 °C Permissible ambient temperature: -20 ... +60 °C Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIK*A* with Serial number	165.00	165.00
6	1	Pcs	PRESSURE GAUGE TYPE BOURDON TUBE, MATERIAL SS, Series 233.50 Dial 4" Range 0 – 2000 PSI, WIKA PN 80064373 Type 23X.50 - SS Case - Pressure Gauges Series Model: 233.50 Specifications according to data sheet: PM 02.02 Measuring System: Stainless Steel Case filling: with Nominal size: 4" Scale range: 0/2000 psi Process Connection: 1/2 NPT Connector location: lower back mount Window: laminated safety glass Pointer: standard pointer Accuracy Class: class 1.0 Material pressure element: Measuring System 316L Case filling fluid: glycerine-water-mixture Ingress Protection: IP 65 Permissible medium temperature: + 100 °C Permissible ambient temperature: -20 ... +60 °C Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIK*A* with Serial number	180.00	180.00



INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com

		Delivery Time 12-16 weeks after receipt of order and payment (subject to changes) The delivery time of the items offered is subject to changes generated by events outside the company's control, such as: 1. Climatic phenomena that do not allow the transport of raw material to the factory, local transport abroad of the manufactured material and/or international transport of the product. 2. Normal functioning of Venezuelan and/or foreign customs. 3. Disruption of public order in the country of origin, country of transit and/or final country. 4. Criminal and/or terrorist acts. 5. Any other event considered major force. Payment terms Prepayment with PO Volume & Weight Weight / Volume to be advised Cci: W. Brito – INTECH PLCRZ		
--	--	---	--	--

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

TRUIST Bank
450 North Pine Island
Plantation, FL 33324
Account #: 0140953040
ABA# 053-101-121
Routing/Transit Number: 2631-9138-7
Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US\$	4,715.00
Freight	US\$	Included
Insurance	US\$	-
Docs.	US\$	-
TOTAL	US\$	4,715.00