



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com

Quote #**IBI-2024-0043****Date:****May 6th, 2024****Customer ID****PDVSA PETROPIAR****Bill To:**

**CHEVRON GLOBAL TECHNOLOGY SERVICES
COMPANY**
**Av. Ppal La Estancia, Centro Banaven, Torre
D, Piso 7, Chuao, Caracas 1060, Venezuela**
Att: Orlimary Zabala - Procurement
duranos@pdvsa.com

Ship To:

Customer's forwarder in Miami, FL to be advised

Your #	Our #	Sales Rep	CPT	SHIP VIA	Terms	Validity
Email	2024-0043 / SQIO-0029_1	L. Zuñiga W. Brito	Miami, FL USA	BWPPD	Prepayment with Order	30 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	2	Pcs	PRESSURE GAUGE SERIE 233.34 WITH GLYCERINE 0-15 PSI, WIKA PN 233.34.45-P015PX-N4BK/LSG Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0... 15 psi 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower back mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock	330.00	660.00
2	3	Pcs	ASSEMBLY PRESSURE GAUGE SERIE 233.34 WITH GLYCERINE 0-30 PSI WITH DIAPHRAGM SEAL 990.10, WIKA PN 233.34.45-P030PX-N4BK/LSG L990.10-N4FN4-MOMO-0SSMO-VI-100	2,265.00	6,795.00

			Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/30 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 69.8°F (room temperature) Process temperature max.: + 212°F Ambient temperature pressure meas. min: + 69.8°F (room temperature) Ambient temperature pressure meas. max: + 69.8°F (room temperature) Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 1/2" NPT male Nominal pressure rating: PN 100 Upper housing material / housing material: Monel 400 (2.4360) Diaphragm material: MONEL 400 (2.4360) Lower housing material: in MONEL 400 (2.4360) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Label: WIKA standard without / with Tag-number		
3	1	Pcs	PRESSURE GAUGE SERIE 233.34 WITH GLYCERINE 0-60 PSI, WIKA PN 233.34.45-P060PX-N4BK/LSG Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5"	330.00	330.00

			Scale range: 0... 60 psi 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower back mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock		
4	2	Pcs	ASSEMBLY PRESSURE GAUGE SERIE 233.34 WITH GLYCERINE 0-100 PSI WITH DIAPHRAGM SEAL 990.10, WIKA PN 233.34.45-P100PX-N4BK/LSG L990.10-N4FN4-MOMO-OSSMO-VI-100 Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/100 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 69.8°F (room temperature) Process temperature max.: + 212°F Ambient temperature pressure meas. min: + 69.8°F (room temperature) Ambient temperature pressure meas. max: + 69.8°F (room temperature) Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01	2,265.00	4,530.00

			Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 1/2" NPT male Nominal pressure rating: PN 100 Upper housing material / housing material: Monel 400 (2.4360) Diaphragm material: MONEL 400 (2.4360) Lower housing material: in MONEL 400 (2.4360) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Label: WIKA standard without / with Tag-number		
5	1	Pcs	PRESSURE GAUGE SERIE 233.34 WITH GLYCERINE 0-160 PSI, WIKA PN 233.34.45-P160PX-N4BK/LSG Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0... 160 psi 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower back mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock	330.00	330.00
6	1	Pcs	PRESSURE GAUGE SERIE 233.34 WITH GLYCERINE 0-2000 PSI, WIKA PN 233.34.45-P20CPX-N4BK/LSG Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0... 2000 psi 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower back mount Window: laminated safety glass	330.00	330.00



			Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock		
7	2	Pcs	BROOKS Rotameters Model 3809GSA10AGBC3H3S000I Metal Tube VA Flow Meter Line Description MT3809G Stainless Meter GAS 1.8 - 18 NCFM Base Model MT3809 SS Max Press@TMin 720 PSIG (49.6 BAR) Max Press@TMax 458 PSIG (31.6 BAR) CRN Province N/A Max Temp 572F (300C) Min Temp -325F (-198C) Accuracy 1% Direct Scale-Gas Meter Material 316/316L SS w\ TTM Float – Cert 3.1-Material Connection Size 1-in Connection Type 300# WNRF Flange Inlet Down Outlet Up O-Ring Material None Lay Length 250 mm Valve Type No Valve Valve Conn No Valve Tube Size 10-A 1.17/V Float 10-V-222 Float Material Titanium Range 1.8 - 18 NCFM Ref Conditions 0C @ 1 atm Primary Scale Direct Read Secondary Scale N/A Scale Type White Face Metal Scale Fluid SEAL GAS COMPRESSOR Density 0.67 S.G Viscosity 0.01 cP Operating Temp 68F Operating Press 14.5 psfg Amb Temp Limit -20C to 70C Ind. Housing XP Stainless Electrical Conn 1/2" NPT-F Ind/Alarm/Xmtr Transmitter w\ Digital Display Approvals UL- DIV 1 -ZONE 1 -IS Remote Relay None Power Supply None Cert1 N/A Cert2 N/A Additional Services Decl 2.1 - Compliance (CoC) Cert 3.1 - Material	9,580.00	19,160.00

			Hazardous Location Cert Stainless Steel Tags Certified Prints Required Tags # 14-FIT-080, 14-FIT-081		
			Equivalent to Old Brooks MT3809E-13ABC3ALA1 Grupo Alvica – Fluor Daniel – Data Sheet N.SOS 0350212 1/4		
			Delivery Time 8 – 10 Weeks ARO Payment Terms • 100 % Prepayment with Order (Net 30 days) Volume & Weight (to be reconfirmed)		
			Cci: W. Brito – INTECH PLCRZ		

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

TRUIST Bank
450 North Pine Island
Plantation, FL 33324
Account #: 0140953040
ABA# 053-101-121
Routing/Transit Number: 2631-9138-7
Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US\$	32,135.00
Freight	US\$	Included
Insurance	US\$	-
Docs.	US\$	-
TOTAL	US\$	32,135.00