



Instrumentos y Equipos C.A

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
Caracas, Venezuela 1080
Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
Fax: 58-212-977.3613
E-mail:sales@intech-ie.com
RIF J-30615033-1

Quote # C-2025-0354
Date: 10/10/2025
Customer ID CHEVRON PETROPIAR

Table with 1 column: Bill to. Content: CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY, Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela, Att: Allen Michael Gamboa, Depto de Procura, AllenMichael.Gamboa@chevron.com

Table with 1 column: Ship to. Content: CHEVRON PETROPIAR Warehouse, Edo Anzoategui, Venezuela

Summary table with 6 columns: Sales Rep., Your #, Our #, Destiny, Terms, Validity. Row 1: L. Zuñiga, VEN-PP-2025-463-I, C-2025-0354/ LE, Venezuela, DDP Jose complex, 60 days

Main item table with 5 columns: Item, Cant, Description, Unit Price US\$, Total US\$. Row 1: 1, 6, BROOKS Rotameters, Rugged all metal variable area flow meter ideal for a variety of gas liquid and steam applications, 18,450.00, 110,700.00. Includes detailed specifications and certifications.

2	100	<p><b>WIKA PRESSURE GAUGES SERIES 233.XX with Diaphragm Seal LOWER MOUNT</b> Process gauge 233.50, SS Case, 100 mm (4") <b>Scale Range: 0-100 psi</b> Measuring System 316L Ingress protection: IP 65 Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C ... T450 °C Db X) class 1.0 <b>Window: laminated safety glass</b> adjustable pointer <b>Case filling fluid: Silicone Oil</b> Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number with QR Code</p> <p>Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21 °C (room temperature) Process temperature max.: + 21°C (room temperature) Ambient temperature pressure meas. min: + 10 °C Ambient temperature pressure meas. max: + 40 °C</p> <p>Diaphragm seal with threaded process connection Model 990.10 <b>Threaded connection: 1/2" NPT male PN 100</b> Upper body material / main body material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower part material: Stainless steel 1.4404 (316L); UNS S31603 Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel</p> <p>Test certificate acc. to EN 10204 2.2 Certificate Language: English and German Certificate for: Diaphragm seal system with pressure measuring instrument Formal certificate: Manufactured according to state-of-the-art</p> <p>Label: WIKA standard without / with Tag-number</p>	\$1,940.00	\$194,000.00
3	3	<p><b>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure</b> Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" <b>Scale range: 0/160 psi</b> Connector location: lower mount <b>Window: laminated safety glass</b> Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service <b>Accuracy Class: +/- 0.5% (ASME B40.100 2A)</b> Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65</p>	\$370.00	\$1,110.00

		<p>Dial description:  <b>WIKA Dial background: Reflective Fluorescent Yellow</b>            *WIKA®*  <b>CHEVRON Logo (2 colors)</b>            serial number on dial: Serial number *...*            stop pin on dial: at 6 o'clock  <b>QR code with extended serial number on dial</b></p>		
4	6	<p><b>WIKA PRESSURE GAUGE Serie 233.XX</b>            Process Gauge 233.50., SS316 Case, 100 mm (4")  <b>Scale Range 0-20 psi</b>            Connection 1/2 NPT lower mount            Measuring System 316L            Ingress protection: IP 65            Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C ... T450 °C Db X)            class 1.0  <b>Window: laminated safety glass</b>  <b>Case filling fluid: Silicone Oil</b>            Permissible ambient temperature: -20 ... +60 °C            Permissible medium temperature: + 100 °C            Pressure Gauge Standard: International (standard Europe)            *WIKA*            with Serial number            with QR Code            Label: WIKA standard without / with Tag-number            Add to shopping cart</p>	\$200.00	\$1,200.00
5	50	<p><b>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure with DIAPHRAGM SEAL</b>            Process Gauge Model: 232.34            Specifications according to data sheet: APM 02.10            Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)            Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)            Measuring System: Stainless Steel            Case filling: without            Nominal size: 4.5"  <b>Scale range: 0/200 psi</b>  <b>Process Connection: Diaphragm Seal</b>            Connector location: lower mount  <b>Window: laminated safety glass</b>            Restrictor: stainless steel, D 0.6            Pointer: adjustable pointer            Special design features: NACE Sour Gas Service            Accuracy Class: +/- 0.5% (ASME B40.100 2A)            Material pressure element: Measuring System 316L            Case filling fluid: prepared for filling            Ingress Protection: IP 65            Dial description:  <b>WIKA Dial background: Reflective Fluorescent Yellow</b>            *WIKA®*  <b>CHEVRON Logo (2 colors)</b>            serial number on dial: Serial number *...*            stop pin on dial: at 6 o'clock  <b>QR code with extended serial number on dial</b></p> <p>Diaphragm seal system with 1 diaphragm seal            Assembly specification High-Side: Direct assembly            System fill fluid: KN 2 Silicone oil for general applications</p>	\$1,870.00	\$93,500.00

		<p>Process temperature min.: + 21°C (room temperature) Process temperature max.: + 40°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14)</p> <p>Diaphragm seal: Model 990.10 <b>Threaded connection: 3/4" NPT female</b> Nominal pressure rating: 1500 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)</p>		
6	40	<p><b>WIKA PRESSURE GAUGE Serie 233.XX</b> Process Gauge 233.50., SS316 Case, 63 mm (2 1/2") <b>Scale Range 0-30 psi</b> Connection 1/2 NPT lower mount Measuring System 316L Ingress protection: IP 65 Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C ... T450 °C Db X) class 1.0 <b>Window: laminated safety glass</b> <b>Case filling fluid: Silicone Oil</b> Permissible ambient temperature: -20 ... +60 °C Permissible medium temperature: + 100 °C Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number with QR Code Label: WIKA standard without / with Tag-number Add to shopping cart</p>	\$190.00	\$7,600.00
7	75	<p><b>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure with DIAPHRAGM SEAL</b> Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" <b>Scale range: 0/400 psi</b> <b>Process Connection: Diaphragm Seal</b> Connector location: lower mount <b>Window: laminated safety glass</b> Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65</p>	\$1,860.00	\$139,500.00

		<p>Dial description:  <b>WIKA Dial background: Reflective Fluorescent Yellow</b>          *WIKA®*  <b>CHEVRON Logo (2 colors)</b>          serial number on dial: Serial number *...*          stop pin on dial: at 6 o'clock  <b>QR code with extended serial number on dial</b></p> <p>Diaphragm seal system with 1 diaphragm seal          Assembly specification High-Side: Direct assembly          System fill fluid: KN 2 Silicone oil for general applications          Process temperature min.: + 21°C (room temperature)          Process temperature max.: + 40°C          Ambient temperature pressure meas. min: + 10°C          Ambient temperature pressure meas. max: + 40°C          Diaphragm seal with threaded process connection          Specifications according to data sheet: ACS 99.01          Specifications according to data sheet: ACS 99.03          Specifications according to data sheet: in preparation (Typ 990.14)</p> <p>Diaphragm seal: Model 990.10  <b>Threaded connection: 3/4" NPT female</b>          Nominal pressure rating: 1500 PSI          Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603          Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603          Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)          Gasket: FPM max. 200°C          Fastening parts: Retainer flange and bolts in stainless steel          Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)</p>		
8	1	<p><b>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure with DIAPHRAGM SEAL</b>          Process gauge Model: 233.34          Specifications according to data sheet: APM 02.10          Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: with          Nominal size: 4.5"  <b>Scale range: 0 - 50 psi</b>  <b>Process Connection: Diaphragm Seal</b>          Connector location: lower mount  <b>Window: laminated safety glass</b>          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Special design features: NACE Sour Gas Service          Accuracy Class: +/- 0.5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L  <b>Case filling fluid: Silicone, 1000 cSt</b>          Ingress Protection: IP 65          Dial description:  <b>WIKA Dial background: Reflective Fluorescent Yellow</b>          *WIKA®*  <b>CHEVRON Logo (2 colors)</b>          serial number on dial: Serial number *...*          stop pin on dial: at 6 o'clock  <b>QR code with extended serial number on dial</b></p> <p>Diaphragm seal system with 1 diaphragm seal</p>	\$1,910.00	\$1,910.00

		<p>Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21°C (room temperature) Process temperature max.: + 40°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) <b>Diaphragm seal: Model 990.10</b> <b>Threaded connection: 3/4" NPT female</b> Flushing connection: 1 x 1/4 NPT female Nominal pressure rating: 1500 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)</p>		
9	30	<p><b>WIKA PRESSURE GAUGE Serie 232.XX</b> Process Gauge 233.50., SS316 Case, 63 mm (2 1/2") <b>Scale Range 0-30 psi</b> Connection 1/4 NPT lower mount Measuring System 316L Ingress protection: IP 65 Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C ... T450 °C Db X) class 1.0 <b>Window: laminated safety glass</b> <b>Case filling fluid: DRY</b> Permissible ambient temperature: -20 ... +60 °C Permissible medium temperature: + 100 °C Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number with QR Code Label: WIKA standard without / with Tag-number Add to shopping cart</p>	\$170.00	\$5,100.00
10	18	<p><b>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure</b> Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel <b>Case filling: Silicone Oil</b> Nominal size: 4.5" <b>Scale range: 0/1500 psi</b> Connector location: lower mount <b>Window: laminated safety glass</b> Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service <b>Accuracy Class: +/- 0.5% (ASME B40.100 2A)</b> Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65</p>	\$430.00	\$7,740.00

		<p>Dial description:  <b>WIKA Dial background: Reflective Fluorescent Yellow</b>            *WIKA®*  <b>CHEVRON Logo (2 colors)</b>            serial number on dial: Serial number *...*            stop pin on dial: at 6 o'clock  <b>QR code with extended serial number on dial</b></p>		
11	05	<p><b>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure</b>            Process Gauge Model: 233.34            Specifications according to data sheet: APM 02.10            Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)            Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)            Measuring System: Stainless Steel  <b>Case filling: Silicone Oil</b>            Nominal size: 4.5"  <b>Scale range: 0/300 psi</b>            Connector location: lower mount  <b>Window: laminated safety glass</b>            Restrictor: stainless steel, D 0.6            Pointer: adjustable pointer            Special design features: NACE Sour Gas Service  <b>Accuracy Class: +/- 0.5% (ASME B40.100 2A)</b>            Material pressure element: Measuring System 316L            Case filling fluid: prepared for filling            Ingress Protection: IP 65            Dial description:  <b>WIKA Dial background: Reflective Fluorescent Yellow</b>            *WIKA®*  <b>CHEVRON Logo (2 colors)</b>            serial number on dial: Serial number *...*            stop pin on dial: at 6 o'clock  <b>QR code with extended serial number on dial</b></p>	\$460.00	\$2,300.00
12	5	<p><b>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure</b>            Process Gauge Model: 232.34            Specifications according to data sheet: APM 02.10            Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)            Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)            Measuring System: Stainless Steel            Case filling: without            Nominal size: 4.5"  <b>Scale range: 0/600 psi</b>            Connector location: lower mount  <b>Window: laminated safety glass</b>            Restrictor: stainless steel, D 0.6            Pointer: adjustable pointer            Special design features: NACE Sour Gas Service  <b>Accuracy Class: +/- 0.5% (ASME B40.100 2A)</b>            Material pressure element: Measuring System 316L            Case filling fluid: prepared for filling            Ingress Protection: IP 65            Dial description:  <b>WIKA Dial background: Reflective Fluorescent Yellow</b>            *WIKA®*  <b>CHEVRON Logo (2 colors)</b>            serial number on dial: Serial number *...*            stop pin on dial: at 6 o'clock  <b>QR code with extended serial number on dial</b></p>	\$430.00	\$2,150.00

13	16	<p><b>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure with DIAPHRAGM SEAL</b>          Process Gauge Model: 232.34          Specifications according to data sheet: APM 02.10          Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel          Case filling: without          Nominal size: 4.5"  <b>Scale range: 0/800 psi</b>  <b>Process Connection: Diaphragm Seal</b>          Connector location: lower mount  <b>Window: laminated safety glass</b>          Restrictor: stainless steel, D 0.6          Pointer: adjustable pointer          Special design features: NACE Sour Gas Service          Accuracy Class: +/- 0.5% (ASME B40.100 2A)          Material pressure element: Measuring System 316L          Case filling fluid: prepared for filling          Ingress Protection: IP 65          Dial description:  <b>WIKA Dial background: Reflective Fluorescent Yellow</b>          *WIKA®*  <b>CHEVRON Logo (2 colors)</b>          serial number on dial: Serial number *...*          stop pin on dial: at 6 o'clock  <b>QR code with extended serial number on dial</b></p> <p>Diaphragm seal system with 1 diaphragm seal          Assembly specification High-Side: Direct assembly          System fill fluid: KN 2 Silicone oil for general applications          Process temperature min.: + 21°C (room temperature)          Process temperature max.: + 40°C          Ambient temperature pressure meas. min: + 10°C          Ambient temperature pressure meas. max: + 40°C          Diaphragm seal with threaded process connection          Specifications according to data sheet: ACS 99.01          Specifications according to data sheet: ACS 99.03          Specifications according to data sheet: in preparation (Typ 990.14)</p> <p>Diaphragm seal: Model 990.10  <b>Threaded connection: 1" NPT female</b>          Nominal pressure rating: 1500 PSI          Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603          Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603          Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)          Gasket: FPM max. 200°C          Fastening parts: Retainer flange and bolts in stainless steel          Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)</p>	\$1,860.00	\$29,760.00
14	1	<p><b>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure</b>          Process Gauge Model: 233.34          Specifications according to data sheet: APM 02.10          Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)          Measuring System: Stainless Steel  <b>Case filling: Silicone Oil</b>          Nominal size: 4.5"</p>	\$400.00	\$400.00

		<p><b>Scale range: 0/300 psi</b> Connector location: lower mount <b>Window: laminated safety glass</b> Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service <b>Accuracy Class: +/- 0.5% (ASME B40.100 2A)</b> Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: <b>WIKA Dial background: Reflective Fluorescent Yellow</b> *WIKA®* <b>CHEVRON Logo (2 colors)</b> serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock <b>QR code with extended serial number on dial</b></p>		
15	7	<p><b>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure</b> Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel <b>Case filling: Silicone Oil</b> Nominal size: 4.5" <b>Scale range: 0/3000 psi</b> Connector location: lower mount <b>Window: laminated safety glass</b> Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service <b>Accuracy Class: +/- 0.5% (ASME B40.100 2A)</b> Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: <b>WIKA Dial background: Reflective Fluorescent Yellow</b> *WIKA®* <b>CHEVRON Logo (2 colors)</b> serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock <b>QR code with extended serial number on dial</b></p>	\$420.00	\$2,940.00
16	7	<p><b>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure</b> Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel <b>Case filling: Silicone Oil</b> Nominal size: 4.5" <b>Scale range: 0/5000 psi</b> Connector location: lower mount <b>Window: laminated safety glass</b> Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service <b>Accuracy Class: +/- 0.5% (ASME B40.100 2A)</b></p>	\$420.00	\$2,940.00

	<p>Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial</p>		
	<p><b>Delivery Time</b> <b>Item 1: 6 -8 Weeks ARO</b> <b>Item 12: 1 – 2 Weeks ARO</b> <b>Others: 12 - 16 Weeks ARO</b></p> <p><b>Partial Shipments allowed (WIKA )</b></p> <p><b>Payment Terms</b></p> <ul style="list-style-type: none"> <li>• Credit Net 30 days delivery DDP</li> </ul> <p><b>Volume &amp; Weight (to be reconfirmed)</b></p> <p><b>General Warranty:</b> WIKA warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p>		
	<p><b>NOTAS:</b></p>		
	<p><b>CONDICIONES DE PAGO</b></p> <p><b><u>COMPONENTE IMPORTADO</u></b></p> <p><i>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</i></p> <p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134 CUENTA NUMERO <b>8303790106</b> BENEFICIARIO <b>INTECH INSTRUMENTOS Y EQUIPOS C.A.</b> ABA 067010509 SWIFT MNB MUS33</p> <p><b><u>COMPONENTE NACIONAL (IVA)</u></b></p> <p><i>En BOLIVARES (Bs.) mediante transferencia bancaria</i></p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. – <b>0105-0011-73-1011-50499-5</b></p>		
	<p><b>OTRAS CONDICIONES</b></p>		

1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos
2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web [www.bcv.org.ve](http://www.bcv.org.ve) y deberá ser cancelado a la tasa oficial del día de pago o de la retención correspondiente
3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.
4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente
5. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22.

**In Tech**  
Instrumentos y Equipos, C.A.  
RIF: J-30615033-1  
NIT: 0096996004



Cci: W. Brito – INTECH PLCRZ

Please Transfer to Account of:  
Bank: Amerant Bank  
Address: 220 Alhambra Circle, Coral Gables,  
Florida 33134, USA  
ABA: 067010509  
Swift: MNB MUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS  
C.A.  
Account # 8303790106

<b>Subtotal</b>	<b>US\$</b>	<b>602,850.00</b>
<b>Freight</b>	<b>US\$</b>	<b>Incluido</b>
<b>Insurance</b>	<b>US\$</b>	<b>--</b>
<b>IVA 16%</b>	<b>US\$</b>	<b>96,456.00</b>
<b>IGTF 3%</b>	<b>US\$</b>	<b>---</b>
<b>TOTAL</b>	<b>US\$</b>	<b>699.306,00</b>