



### Instrumentos y Equipos C.A

#### INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,  
 Caracas, Venezuela 1080  
 Tel: 58-212-9784430, 9784433, 977.7654, 977.6346  
 Fax: 58-212-977.3613  
 E-mail:sales@intech-ie.com  
 RIF J-30615033-1

**Quote #** C-2025-0340  
**Date:** 03/10/2025  
**Customer ID** CHEVRON PETROPIAR

<b>Bill to:</b>
<b>CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY</b>
Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela Att: Diana Carolina Rocha - Depto de Procura Diana.Rocha@chevron.com

<b>Ship to:</b>
<b>CHEVRON PETROPIAR Warehouse</b> Edo Anzoategui, Venezuela


Sales Rep.	Your #	Our #	Destiny	Terms	Validity
N. Carricatti	VEN-PP-RFX-PP-2025-050	C-2025-0340/ WIKA@202509-03/QUO00021756-3	Venezuela	DDP Jose complex	30 days

Item	Cant	Description	Unit Price US\$	Total US\$
2	50	<p><b>PRESSURE TRANSMITTER MODEL UPT-20, WIKA PN 80075240</b></p> <p>Specifications according to data sheet: PE 86.05            power supply: DC 12...36 V / DC 14...30 V            Pressure Range: adjustable with turn down up to 100 : 1            Ingress Protection: IP 66/67 with internal pressure compensation            Process connection type: Standard connection with pressure port            Electrical approval: ATEX / IECEx            Ignition protection type: Ex i - intrinsically safe            Zone: Zone 1 attached to zone 0 gas [II 1/2G Ex ia IIC T6...T1 Ga/Gb]            Case design: stainless steel cast, IP66/IP67            Digital Display: With Integrated 4 Digit LCD-Display            window: plastic window PC            Output signal: 4 ... 20 mA with HART protocol, 2-wire            Electrical connection: 1/2" NPT female conduit            Pressure range: 0 ... 1500 psig            Process connection: Diaphragm Seal            Accuracy: 0.1 % of span            Unit of outer Scale: psi            Scaling lower value: 0 psi            Scaling high value: 1000,0            Sensor principle: Thin film            Diaphragm seal system with 1 diaphragm seal            Assembly specification High-Side: Direct assembly, vertical            System fill fluid: KN 2 Silicone oil for general applications            Process temperature min.: + 69.8°F (room temperature)            Process temperature max.: +176°F            Ambient temperature pressure meas. min: + 69.8°F (room temperature)            Ambient temperature pressure meas. max: + 69.8°F (room temperature)            Diaphragm seal with threaded process connection            Specifications according to data sheet: ACS 99.01            Specifications according to data sheet: ACS 99.03</p>	\$5.970,00	\$298.500,00

		<p>Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 3/4" NPT female Nominal pressure rating: PN 100 Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Label: WIKA standard without / with Tag-number TAG-1 (SS Tag Plate) PIT</p>		
3	350	<p><b>PRESSURE TRANSMITTER MODEL UPT-20, WIKA PN 80075244</b></p> <p>Specifications according to data sheet: PE 86.05 power supply: DC 12...36 V / DC 14...30 V Pressure Range: adjustable with turn down up to 100 : 1 Ingress Protection: IP 66/67 with internal pressure compensation Process connection type: Standard connection with pressure port Electrical approval: ATEX / IECEx Ignition protection type: Ex i - intrinsically safe Zone: Zone 1 attached to zone 0 gas [II 1/2G Ex ia IIC T6...T1 Ga/Gb] Case design: stainless steel cast, IP66/IP67 Digital Display: With Integrated 4 Digit LCD-Display window: plastic window PC Output signal: 4 ... 20 mA with HART protocol, 2-wire Electrical connection: 1/2" NPT female conduit Pressure range: 0 ... 1500 psig Process connection: Diaphragm Seal Accuracy: 0.1 % of span Sensor principle: Thin film Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: 10 feet capillary; stainless steel System fill fluid: KN 2 Silicone oil for general applications Vacuum service: Basic Service according to Technical Information IN 00.25 Process temperature min.: + 69.8°F (room temperature) Process temperature max.: + 212°F Ambient temperature pressure meas. min: + 69.8°F (room temperature) Ambient temperature pressure meas. max: + 69.8°F (room temperature) diameter of capillary: ID 2mm (3x0.5 mm) Diaphragm seal, flange type, flush diaphragm Specifications according to data sheet: DS 99.27 Diaphragm seal: Model 990.27 Diaphragm seal: Model 990.27 Process connection standard: following ASME B16.5 Process connection: 1 1/2" Nominal pressure rating: Class 300 Sealing face: RF 125...250 AA Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Sealing face material: Stainless steel 1.4404 (316L); UNS S31603 Accessories: Flushing ring Label: WIKA standard without / with Tag-number TAG-1 (SS Tag Plate) PIT</p>	\$6.140,00	\$2.149.000,00

5	6	<p><b>RADAR LEVEL TRANSMITTER SERIE VEGAPULS 6X, VEGA PN PS6X.2SWGFMFXAWDNAHFHXXXXXX</b></p> <p>Generation 2 Second generation Application S Standard Radar technology W 80 GHz technology Process fitting GM Flange ASME B16.5 NPS 3" Class 150 RF / 316/316L Antenna version F Flange with encapsulated antenna system Additional equipment X without Material / Seal / Process temperature AW PTFE / PTFE / -60...+150°C Housing / Protection D Aluminium double chamber / IP66/IP68 (0.2bar) Cable entry / Connection N ½NPT / Blind plug Display/adjustment module PLICSCOM A Display/adjustment module PLICSCOM Electronics H Two-wire 4 ... 20 mA/HART Explosion protection FH c-FM-us; gas, intrinsic safety; zone 0, 0/1, 1; Class I Div 1 + Dust, intrinsic safety; zone 20, 20/21, 21; Class II Div 1, Class III Type label of stainless steel Max. measuring range 393.7 ft Min. process pressure in bar -1 Max. process pressure in bar 19</p>	\$25.610,00	\$153.660,00
7	10	<p><b>CAPACITIVE LEVEL SWITCH MODEL VEGACAP 64, VEGA PN CP64.UXFNDRANX</b></p> <p>Measuring unit for lengths Metre / Millimetre Approval directive / Scope FM / USA Approval UX FM (NI) CL I, DIV2, GP ABCD, (DIP) CL II, III, DIV1, GP EFG Version / Process temperature F Rod (Ø12mm) 304 with PTFE insulation / -50...+150°C Process fitting / Material ND Thread 1½NPT PN64, ASME B1.20.1 / 316L Electronics R Relay (DPDT) 20 ... 72 V DC/20 ... 253 V AC (3A) Housing / Protection A Aluminium single chamber / IP66/IP67 Special colour none Cable entry / Cable gland / Plug connection N ½NPT / without / without Switching status display PLICSLED without Length (from seal surface) 150 mm Active rod length 50 mm</p>	\$7.960,00	\$79.600,00

14	6	<p><b>TEMPERATURE SWITCH MODEL TCA, WIKA PN 80075226</b></p> <p>TCA4BA - 90 ... 160°C - 1/2 NPT male - electrical connection: 1/2 -14 NPT-F compact temperature switch Model TCA switch enclosure: stainless steel 316L sensor: direct mounting contacts: 1xSPDT, silver contact setting range: 90 ... 160°C, working range -40 ... +170°C, proof temperature +180°C process connection: 1/2 NPT male electrical connection: 1/2 -14 NPT-F Mounting: standard direct or wall mounting, fixing bore on the case Stem length for direct mounting: standard 125 mm Sensor Dimensions: active length X = 55 mm, stem diameter D=9,5 mm brand: WIKA Instruments Italia Ingress Protection: IP66 Specifications according to data sheet: SP 08.65 (TCA) Repeatability of set point: ≤ 1% of span set point definition: Set Point not defined Approvals / Certificates IECEX-ATEX Ex d TAG-1 (SS Tag Plate) TS</p>	\$3.460,00	\$20.760,00						
		<p><b>Delivery Time</b> <b>Item 2, 3: 16 – 20 Weeks ARAD</b> <b>Item 5, 7: 4 – 8 Weeks ARAD</b> <b>Item 14: 14 – 18 Weeks ARAD</b></p> <p><b>Partial Shipments allowed (WIKA )</b></p> <p><b>Payment Terms</b></p> <ul style="list-style-type: none"> <li>• 50 % Prepayment with Order</li> <li>• 50% Net 30 days delivery time</li> </ul> <p><b>Packing</b> Material will be Securely packed in wooden crates suitable for air freight and export.</p> <p><b>Volume &amp; Weight (to be reconfirmed)</b> <b>To be advised – Aprox 10370 Lbs</b></p> <p><b>General Warranty:</b> Brand warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p><b>Project Cancellation charges:</b></p> <table border="0"> <tr> <td>15%</td> <td>Up to submittal of Engineering &amp; Design Drawings and Documents</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering &amp; Design Drawings and Documents</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> </table>	15%	Up to submittal of Engineering & Design Drawings and Documents	25%	After submittal of Engineering & Design Drawings and Documents	50%	After material order placement and before production commences		
15%	Up to submittal of Engineering & Design Drawings and Documents									
25%	After submittal of Engineering & Design Drawings and Documents									
50%	After material order placement and before production commences									

	75% Within two weeks of production release		
	100% Two weeks after production commences		
	<b>NOTAS:</b>		
	<p><b>CONDICIONES DE PAGO</b></p> <p><b><u>COMPONENTE IMPORTADO</u></b></p> <p>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</p> <p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134 CUENTA NUMERO <b>8303790106</b> BENEFICIARIO <b>INTECH INSTRUMENTOS Y EQUIPOS C.A.</b> ABA 067010509 SWIFT MNBMUS33</p> <p><b><u>COMPONENTE NACIONAL (IVA)</u></b></p> <p>En BOLIVARES (Bs.) mediante transferencia bancaria</p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. – <b>0105-0011-73-1011-50499-5</b></p>		
	<p><b>OTRAS CONDICIONES</b></p> <p>1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos</p> <p>2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web <a href="http://www.bcv.org.ve">www.bcv.org.ve</a> y debera ser cancelado a la tasa oficial del día de pago o de la retención correspondiente</p> <p>3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.</p> <p>4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente</p> <p>5. Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta</p> <p>6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22.</p> <p><b>In Tech</b> Instrumentos y Equipos, C.A. RIF: J-30615033-1 NIT: 0096996004</p>  <p>Cci: W. Brito – INTECH PLCRZ</p>		

--	--	--	--	--

Please Transfer to Account of:  
 Bank: Amerant Bank  
 Address: 220 Alhambra Circle, Coral Gables,  
 Florida 33134, USA  
 ABA: 067010509  
 Swift: MNBMUS33  
  
 Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS  
 C.A.  
 Account # 8303790106

<b>Subtotal</b>	<b>US\$</b>	<b>2,701,520.00</b>
<b>Freight</b>	<b>US\$</b>	<b>Incluido</b>
<b>Insurance</b>	<b>US\$</b>	<b>--</b>
<b>IVA 16%</b>	<b>US\$</b>	<b>432,243.20</b>
<b>IGTF 3%</b>	<b>US\$</b>	<b>---</b>
<b>TOTAL</b>	<b>US\$</b>	<b>3,133,763.20</b>