



Instrumentos y Equipos C.A

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
 Caracas, Venezuela 1080
 Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
 Fax: 58-212-977.3613
 E-mail: sales@intech-ie.com
 RIF J-30615033-1

Quote # C-2025-0432
Date: 15/12/2025
Customer ID CHEVRON PETROPIAR

Bill to:
CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY
Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela Att: Rafael Azuaje - Depto de Procura Rafael.Azuaje@chevron.com


Ship to:
CHEVRON PETROPIAR Warehouse Venezuela

Sales Rep.	Your #	Our #	Destiny	Terms	Validity
N. Carricatti	VEN-RFQ-PP-2025-050-XVII	C-2025-0432/PL WIDN-20251203/ QUO00022408 / ...09	Venezuela	DDP Petropiar	30 days

Item	Cant	Description	Unit Price US\$	Total US\$
1	10	THERMOCOUPLE ASSEMBLY WITH FABRICATED FLANGE PROTECTION TUBE MODEL TC10-F DIN, WIKA PN 80076410 Specifications according to data sheet: ATE 65.05 Dual thermocouple Type K Class 2, IEC 60584 Validity limits of class accuracy: -40...+1200 °C Hot junction: Grounded Head / housing: KN4-A, Aluminum, screwed cover Cable entry: Thread (female) Thread size cable entry: 1/2 NPT Transmitter: Without (with terminal block) Connection to neck tube: M24 x 1,5 Protection tube: Straight, flange, form 2F DIN 43772 Protection tube material: Stainless steel 1.4571 Protection tube diameter: 9x1 mm Flange size: ASME 1 inch Pressure rating: 300 lbs Flange face: RF (Raised face) Insertion length [A] : 2032 mm Neck length [MH/N]: 65 mm Insert diameter: 6 mm Sheath material measuring insert: Stainless steel 316L Protection tube total length (spare) [L]: 2112 mm Measuring insert length (spare) [I5]: 2129 mm	\$2.910,00	\$29.100,00
6	12	ULTRASONIC GAS FLOW TRANSMITTER MODEL FLC-UFL, WIKA PN QUO00022409-1 Number of paths: Single path Nominal Pipe Size: 6" Flanges: ANSI 300#	\$120.590,00	\$1.447.080,00

		<p>wall thickness / schedule: schedule 40 Flowbody material: Carbon Steel Option boards Slot 1: None Option boards Slot 2: 4..20mA option board Electrocics case material: SS316 emclosure with display/keypad Cable entry: 1/2" NPT cable glands Ingress protection: NEMA 4X Certificates and Tests: with Certificates and Test Additional ordering information: without Certificate for: Flowmeters Documents and Certificates Language: English Hazardous area Certificate: ATEX II 1 G Ex ia IIC T4 Ga</p>		
7	20	<p>DIFFERENTIAL PRESSURE TRANSMITTER MODEL DPT-20, WIKA PN 80076412</p> <p>Differential Pressure Transmitter DPT-20 Specifications according to data sheet: PE 86.22 Electrical approval: ATEX Ignition protection type: Ex d - explosion proof Zone: Zone 1 gas [2G Ex d IIC T1...T6 Gb] Housing material: Stainless steel cast single chamber enclosure execution: compact / IP66/IP68 (0.2bar); NEMA 6P Digital Display: with integrated indicating/adjustment module (top) Output signal: 4...20 mA, 2-wire, HART Electrical connection: 1/2" NPT female conduit Unit: bar Maximal working pressure: 160 bar (16 MPa / 2400 psi) Pressure range: -3 ... +3 bar Process connection/mounting/material/venting: single side diaphragm seal and 1/4-18 NPT IEC61518 / 7/16-20 UNF / 316L with valve Diaphragm material: 316L Sealing (temperature range): FKM (-20 ... +85 °C) Accuracy: 0.1 % of span Filling of sensor: Silicone oil for regular applications (KN2) Operating modes: Pressure measurement Scaling unit DP-measurement: psi Lower scaling value DP: 15,000 lower scaling prefix: - upper scaling prefix: + Upper scaling value DP: 15,00 Density value: 1 Density unit: kg/dm³ Linearization curve: linear Damping [s]: 1 s (default setting) Output signal low level in %: 0% Output signal low level in %: 100% Displayed value: differential pressure (acc. scaling) Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: 100 mm assembly, horizontal with square tube System fill fluid: KN 2 Silicone oil for general applications Vacuum service: Basic Service according to Technical Information IN 00.25 Process temperature min.: + 69.8°F (room temperature) Process temperature max.: + 266°F Ambient temperature pressure meas. min: + 69.8°F (room temperature) Ambient temperature pressure meas. max: + 86°F Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14)</p>	\$11.060,00	\$221.200,00

	<p>Diaphragm seal: Model 990.10 Threaded connection: 1/2" NPT female Flushing connection: 1 x 1/4 NPT female Nominal pressure rating: PN 100 Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Label: WIKA standard without / with Tag-number</p>												
	<p>Delivery Time Item 1: 13 – 15 Weeks ARAD Item 6, 7: 20 – 22 Weeks ARAD</p> <p>Partial Shipments allowed (WIKA)</p> <p>Payment Terms</p> <ul style="list-style-type: none"> • 50% Prepayment • 50% Net 30 days delivery time <p>Packing Material will be Securely packed in wooden crates suitable for air freight and export.</p> <p>Volume & Weight (to be reconfirmed) To be advised – Aprox 1600 Lbs</p> <p>General Warranty: Brand warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p>Project Cancellation charges:</p> <table border="0"> <tr> <td>15%</td> <td>Up to submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> <tr> <td>75%</td> <td>Within two weeks of production release</td> </tr> <tr> <td>100%</td> <td>Two weeks after production commences</td> </tr> </table>	15%	Up to submittal of Engineering & Design Drawings and Documents	25%	After submittal of Engineering & Design Drawings and Documents	50%	After material order placement and before production commences	75%	Within two weeks of production release	100%	Two weeks after production commences		
15%	Up to submittal of Engineering & Design Drawings and Documents												
25%	After submittal of Engineering & Design Drawings and Documents												
50%	After material order placement and before production commences												
75%	Within two weeks of production release												
100%	Two weeks after production commences												
	<p>NOTAS:</p>												
	<p>CONDICIONES DE PAGO</p> <p><u>COMPONENTE IMPORTADO</u></p> <p><i>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</i></p> <p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134 CUENTA NUMERO 8303790106 BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A. ABA 067010509</p>												

	<p>SWIFT MNBMUS33</p> <p><u>COMPONENTE NACIONAL (IVA)</u></p> <p>En BOLIVARES (Bs.) mediante transferencia bancaria</p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. – 0105-0011-73-1011-50499-5</p>		
	<p>OTRAS CONDICIONES</p> <p>1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos</p> <p>2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y deberá ser cancelado a la tasa oficial del día de pago o de la retención correspondiente</p> <p>3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.</p> <p>4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente</p> <p>5. Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta</p> <p>6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22.</p> <p>In Tech Instrumentos y Equipos, C.A. RIF: J-30615033-1 NIT: 0096996004</p>  <p>Cci: W. Brito – INTECH PLC</p>		

Please Transfer to Account of:
Bank: Amerant Bank
Address: 220 Alhambra Circle, Coral Gables,
Florida 33134, USA
ABA: 067010509
Swift: MNBMUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS
C.A.
Account # 8303790106

Subtotal	US\$	1,697,380.00
Freight	US\$	Incluido
Insurance	US\$	--
IVA 16%	US\$	271,580.80
IGTF 3%	US\$	---
TOTAL	US\$	1,968,960.80