

Instrumentos y Equipos C.A

Visit us at <http://www.intech-ie.com>

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
Caracas, Venezuela 1080
Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
Fax: 58-212-977.3613
E-mail: sales@intech-ie.com
RIF J-30615033-1

Quote # **C-2025-0337**
Date: **26/09/2025**
Customer ID **CHEVRON PETROPIAR**

Bill to:
<p>CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela Att: Diana Carolina Rocha - Depto de Procura Diana.Rocha@chevron.com</p>

Ship to:
<p>CHEVRON PETROPIAR Warehouse Edo Anzoategui, Venezuela</p>

Sales Rep.	Your #	Our #	Destiny	Terms	Validity
L. Zuñiga	VEN-PP-2025-050	C-2025-0337/ QUO00021703-1	Venezuela	DDP Jose complex	30 days

Item	Cant	Description	Unit Price US\$	Total US\$
1	40	<p>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure Model: 233.30 Specifications according to data sheet: PM 02.04 Measuring System: Stainless Steel Case filling: with Nominal size: 2.5" Measuring range: gauge pressure range Scale range: 0/30 psi Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 2/1/2% (ASME B40.100 Grade A) Case surface: bare case / polished ring Material pressure element: Measuring System 316 SS Case filling fluid: Silicone, 1000 cSt Ingress Protection: IP 65 Permissible medium temperature: + 100 °C Permissible ambient temperature: -20 ... +60 °C Pressure Gauge Standard: US-Standard WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial Permissible ambient temperature: -20 ... +60 °C</p>	440.00	17,600.00
2	60	<p>WIKA CAPSULE PROCESS PRESSURE GAUGE SERIES 6X2.34 Type 6X2.34 - Capsule Process Gauges Specifications according to data sheet: PM 06.07 Case: Black Plastic Bezel ring: Threaded Retainer Ring, Plastic, Black Accuracy Class: +/- 2/1/2% (ASME B40.100 Grade A) Measuring System: Stainless Steel</p>	1,280.00	76,800.00

		<p>Case filling: without Nominal size: 4.5" Unit: inH2O Scale range: 0 inH2O...150 inH2O Process Connection: 1/2 NPT Connector location: lower mount Special Design Features: NACE Sour Gas Service Movement: stainless steel Package: Single packing Window: laminated safety glass Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial additional mark for special design: *NACE* *SOUR GAS SERVICE* imprint material on dial: *316 SS wetted parts* inner packages label: Wika USA outside packages label: Wika USA</p>		
3	30	<p>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure with DIAPHRAGM SEAL Process gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: -30 inHg/30 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Silicone, 1000 cSt Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial</p> <p>Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21°C (room temperature) Process temperature max.: + 40°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Diaphragm seal with threaded process connection</p>	2,310.00	69,300.00

		<p>Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 1/2" NPT female Flushing connection: 1 x 1/4 NPT female Nominal pressure rating: 1500 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)</p>		
4	1000	<p>WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure with DIAPHRAGM SEAL Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0/600 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA** CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial</p> <p>Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21°C (room temperature) Process temperature max.: + 40°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 3/4" NPT female Nominal pressure rating: 1500 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)</p>	1,960.00	1,960,000.00

		Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)		
5	100	<p>WIKA DIFFERENTIAL PRESSURE GAUGES SERIES 73X with DIAPHRAGM SEAL Process Gauge Model: 732.51 Specifications according to data sheet: APM 732.51 (APM 07.05) Case: stainless steel Bezel ring: stainless steel Movement: stainless steel Case filling: without Nominal size: 4" Scale range: 0/30 psid Process Connection: Diaphragm Seal Connector location: lower mount Special design features: NACE MR 0175 / ISO 15156-3 Accuracy Class: class 1.6 Maximum Static Pressure: 25 bar Overpressure Safety: 20 bar Ingress Protection: IP 54 Pointer: adjustable pointer Window: laminated safety glass Pressure Gauge Standard: International (standard Europe) CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial case: with pressure blowout disk</p> <p>Diaphragm seal system with 2 diaphragm seals Assembly specification High-Side: Direct assembly Height difference high side: no height difference Assembly specification Low-Side: 2 meter capillary; stainless-steel System fill fluid: KN 2 Silicone oil for general applications Height difference low side: no height difference Process temperature min.: - 10°C Process temperature max.: + 200°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C diameter of capillary: ID 2mm (3x0.5 mm) Version according to NACE: Version according to NACE MR 0175 according to Technical Information IN 00.21 Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) High-/Low-Side: High-Side Diaphragm seal: Model 990.40 Threaded connection: 3/4" NPT female Nominal pressure rating: 200 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14)</p>	8,740.00	874,000.00

	<p>High-/Low-Side: Low-Side Diaphragm seal: Model 990.40 Threaded connection: 3/4" NPT female Nominal pressure rating: 200 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Without</p>												
	<p>Delivery Time Item 1, 3, 4: 14-15 Weeks ARO and Payment 1st Milestone Item 2, 5: 22 Weeks ARO and Payment 1st Milestone</p> <p>Partial Shipments allowed (WIKA)</p> <p>Payment Terms</p> <ul style="list-style-type: none"> • 50% with your Order • Balance Net 30 days delivery time DDP <p>Volume & Weight (to be reconfirmed) To be advised – Aprox 9,000 Lbs</p> <p>General Warranty: WIKA warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p>Project Cancellation charges:</p> <table border="0"> <tr> <td>15%</td> <td>Up to submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> <tr> <td>75%</td> <td>Within two weeks of production release</td> </tr> <tr> <td>100%</td> <td>Two weeks after production commences</td> </tr> </table>	15%	Up to submittal of Engineering & Design Drawings and Documents	25%	After submittal of Engineering & Design Drawings and Documents	50%	After material order placement and before production commences	75%	Within two weeks of production release	100%	Two weeks after production commences		
15%	Up to submittal of Engineering & Design Drawings and Documents												
25%	After submittal of Engineering & Design Drawings and Documents												
50%	After material order placement and before production commences												
75%	Within two weeks of production release												
100%	Two weeks after production commences												
	<p>NOTAS:</p>												
	<p>CONDICIONES DE PAGO</p> <p><u>COMPONENTE IMPORTADO</u></p> <p><i>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</i></p> <p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134 CUENTA NUMERO 8303790106 BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A. ABA 067010509 SWIFT MNBMUS33</p>												

	<p><u>COMPONENTE NACIONAL (IVA)</u></p> <p>En BOLIVARES (Bs.) mediante transferencia bancaria</p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. – 0105-0011-73-1011-50499-5</p>		
	<p>OTRAS CONDICIONES</p> <p>1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos</p> <p>2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y debera ser cancelado a la tasa oficial del día de pago o de la retención correspondiente</p> <p>3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.</p> <p>4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente</p> <p>5. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22.</p> <div style="display: flex; justify-content: space-between; align-items: center;"> <div data-bbox="277 1150 542 1260"> <p>In Tech Instrumentos y Equipos, C.A. RIF: J-30615033-1 NIT: 0096996004</p> </div> <div data-bbox="573 1136 846 1295">  </div> </div> <p>Cci: W. Brito – INTECH PLCRZ</p>		

Please Transfer to Account of:
Bank: Amerant Bank
Address: 220 Alhambra Circle, Coral Gables,
Florida 33134, USA
ABA: 067010509
Swift: MNBMUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS
C.A.
Account # 8303790106

Subtotal	US\$	2,997,700.00
Freight	US\$	Incluido
Insurance	US\$	--
IVA 16%	US\$	479,632.00
IGTF 3%	US\$	---
TOTAL	US\$	3,477,332.00