



Cotizacion

Visit us at <http://www.intech-ie.com>

Instrumentos y Equipos C.A.

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
Caracas, Venezuela 1080
Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
Fax: 58-212-977.3613
E-mail: sales@intech-ie.com
RIF J-30615033-1

Quote # **C-2025-0334**
Date: **22/09/2025**
Customer ID **CHEVRON PETROBOSCAN**

Bill to:
CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela Att: Jorgelis Rincon - Depto de Procura Jorgelis.Rincon1@chevron.com

Ship to:
CHEVRON PETROBOSCAN Warehouse Venezuela

Sales Rep.	Your #	Our #	Destiny	Terms	Validity
N. Carricatti	VEN-RFQ-PB-2025-082-II	C-2025-0324(8&12)/ WIKA@202509-01/QUO00021600-1/ WIKA@202401-02/QUO00015554-1+10%	Venezuela	DDP Petroboscan	30 days

Item	Cant	Description	Unit Price US\$	Total US\$
18	1	<p>THERMAL MASS FLOW SWITCH VERSA-SWITCH® VS5100 Series, DELTAMCORP PN VS514X-C06-S6-OXX.00-24D-LE-XW-FA-TG</p> <p>Product Model: VS51 - VERSASWITCH</p> <p>Ratings: 4X - NEMA 4X</p> <p>Add a Custom Tag: TG - Stainless Steel Tag Tag Etching: FSL-4451</p> <p>Calibration: ∅∅ - Dry/Wet Level Calibration</p> <p>Power Input: 24D - 24VDC</p> <p>Add watchdog circuitry: FA - Failure Alarm</p> <p>Electronic Location: LE - Local (Integral Sensor)</p> <p>Electronic Enviroment: XW - Explosion Proof w/ Window</p> <p>Process Connections:</p>	\$6.060,00	\$6.060,00

		<p>C06-S6 3/4-in NPT Male Stainless 316</p> <p>Insertion Length: > 2.00 Inch Insertion Length</p> <p>Insertion Length in inches: To Be Determined</p>		
19	1	<p>THERMAL MASS FLOW SWITCH VERSA-SWITCH® VS5100 Series, DELTAMCORP PN VS514X-C06-S6-0XX.00-24D-LE-XW-FA-TG</p> <p>Product Model: VS51 - VERSASWITCH</p> <p>Ratings: 4X - NEMA 4X</p> <p>Add a Custom Tag: TG - Stainless Steel Tag Tag Etching: FSL-4461</p> <p>Calibration: ∅∅ - Dry/Wet Level Calibration</p> <p>Power Input: 24D - 24VDC</p> <p>Add watchdog circuitry: FA - Failure Alarm</p> <p>Electronic Location: LE - Local (Integral Sensor)</p> <p>Electronic Enviroment: XW - Explosion Proof w/ Window</p> <p>Process Connections: C06-S6 3/4-in NPT Male Stainless 316</p> <p>Insertion Length: > 2.00 Inch Insertion Length</p> <p>Insertion Length in inches: To Be Determined</p>	\$6.060,00	\$6.060,00
21	1	<p>DIFFERENTIAL PRESSURE (FLOW INDICATOR) TRANSMITTER SERIE DPT-20, WIKA PN 80075081-XX</p> <p>Differential Pressure Transmitter DPT-20 Specifications according to data sheet: PE 86.22 Electrical approval: ATEX, IECEx, Ignition protection type: Ex i - intrinsically safe Zone: Zone 1 attached to zone 0 gas [II 1/2G Ex ia IIC T3...T6 Ga/Gb] Housing material: Plastic single chamber enclosure execution: compact/ IP66/IP67; NEMA 4X Digital Display: with integrated indicating/adjustment module (top) Output signal: 4...20 mA, 2-wire, HART Electrical connection: 1/2" NPT Female</p>	\$7.730,00	\$7.730,00

		<p>Unit: bar Maximal working pressure: 160 bar (16 MPa / 2400 psi) Pressure range: -3 ... +3 bar Process connection/mounting/material/venting: 1/4-18 NPT IEC 61518 / 7/16-20 UNF / 316L / dorsal, incl. 2 valves Diaphragm material: 316L Sealing (temperature range): FKM (-20 ... +85 °C) Accuracy: 0.065 % of span Mounting element: mounting bracket for wall or pipe mounting (max. 2"), stainless steel Additional equipment: with valve manifold / connection adapter Filling of sensor: Silicone oil for regular applications (KN2) Operating modes: Pressure measurement Scaling unit DP-measurement: inH2O Lower scaling value DP: 0 inH2O Upper scaling value DP: 250,0 Density value: 1 Density unit: kg/dm³ Linearization curve: linear Damping [s]: 1 s (default setting) Output signal low level in %: 0% Output signal low level in %: 100% Displayed value: differential pressure (acc. scaling) manifold (version, connection, materials): 5 valve, PN420, IEC 61518 form A - 1/2 NPT female, stainless steel/packing PTFE mounting of the manifold: manifold not fixed enclosed, mounting carried out by user Model: 5-Valve Manifold</p> <p>TAG-1 (SS Tag Plate) UIT-1631</p>		
22	4	<p>DIFFERENTIAL PRESSURE (LEVEL INDICATOR) TRANSMITTER SERIE DPT-20, WIKA PN 80064243-XX-TAG</p> <p>Differential Pressure Transmitter DPT-20 Specifications according to data sheet: PE 86.22 Electrical approval: ATEX Ignition protection type: Ex d - explosion proof Zone: Zone 1 attached to zone 0 gas [II 1/2G Ex db ia IIC T6...T1 Ga/Gb] Housing material: Aluminum single chamber Case version: compact / IP66/IP68 (0.2bar); NEMA 6P Digital Display: with integrated indicating/adjustment module (top) Output signal: 4...20 mA, 2-wire, HART Electrical connection: 1/2" NPT female conduit / plug Unit: bar Maximal working pressure: 160 bar (16 MPa / 2400 psi) Measuring range: -3 ... +3 bar Process connection/mounting/material/venting: for diaphragm seals (accuracy for complete assembly 0.1 % at reference conditions) Diaphragm material: 316L Sealing (temperature range): copper seal ring (-40 ... +85 °C) Accuracy: 0.1 % of span Filling of sensor: Silicone oil for regular applications (KN2) Operating modes: Pressure measurement Scaling unit DP-measurement: inH2O Lower scaling value DP: -250 inH2O Upper scaling value DP: 250,0</p>	\$14.350,00	\$57.400,00

	<p>Density value: 1 Density unit: kg/dm³ Linearization curve: linear Damping [s]: 1 s (default setting) Output signal low level in %: 0% output signal high level in %: 100% Displayed value: differential pressure (acc. scaling) Diaphragm seal system with 2 diaphragm seals Assembly specification High-Side: 20 feet capillary; stainless steel Height difference high side: no height difference Assembly specification Low-Side: 20 feet capillary; stainless steel System fill fluid: KN 2 Silicone oil for general applications Height difference low side: no height difference Servicecategory: Basic Service according to Technical Information IN 00.25 Process temperature min.: + 32°F Process temperature max.: + 752°F Ambient temperature pressure meas. min: + 69,8°F (room temperature) Ambient temperature pressure meas. max: + 104°F Capillary inner diameter: ID 2mm (3x0.5 mm) Diaphragm seal, flange type, flush diaphragm Specifications according to data sheet: DS 99.27 Diaphragm seal: Model 990.27 High-/Low-Side: High-Side Diaphragm seal: Model 990.27 Process connection standard: following ASME B16.5 Process connection: 3" Nominal pressure rating: Class 600 Sealing face: RF 125...250 AA Upper body material / main body material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Sealing face material: Stainless steel 1.4435 (316L); UNS S31603 Diaphragm seal, flange type, flush diaphragm Specifications according to data sheet: DS 99.27 High-/Low-Side: Low-Side Diaphragm seal: Model 990.27 Process connection standard: following ASME B16.5 Process connection: 3" Nominal pressure rating: Class 600 Sealing face: RF 125...250 AA Upper body material / main body material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Sealing face material: Stainless steel 1.4404 (316L); UNS S31603 Label: WIKA standard without / with Tag-number language of the label: English</p> <p>TAG-1 (SS Tag Plate) LIT-1631, LIT-1431, LIT-1411, LIT-1421</p>		
	<p>Delivery Time Item 18, 19: 8 – 12 Weeks ARAD Item 21, 22: 20 – 24 Weeks ARAD</p> <p>Partial Shipments allowed (WIKA, DELTAM CORP)</p> <p>Payment Terms</p> <ul style="list-style-type: none"> • 100% Net 30 days delivery time <p>Packing Material will be Securely packed in wooden crates suitable for air freight and export.</p>		

	<p>Volume & Weight (to be reconfirmed) To be advised – Aprox 155 Lbs</p> <p>General Warranty: Brand warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p>Project Cancellation charges:</p> <table border="0"> <tr> <td>15%</td> <td>Up to submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> <tr> <td>75%</td> <td>Within two weeks of production release</td> </tr> <tr> <td>100%</td> <td>Two weeks after production commences</td> </tr> </table>	15%	Up to submittal of Engineering & Design Drawings and Documents	25%	After submittal of Engineering & Design Drawings and Documents	50%	After material order placement and before production commences	75%	Within two weeks of production release	100%	Two weeks after production commences		
15%	Up to submittal of Engineering & Design Drawings and Documents												
25%	After submittal of Engineering & Design Drawings and Documents												
50%	After material order placement and before production commences												
75%	Within two weeks of production release												
100%	Two weeks after production commences												
NOTAS:													
	<p>CONDICIONES DE PAGO</p> <p><u>COMPONENTE IMPORTADO</u></p> <p><i>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</i></p> <p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134 CUENTA NUMERO 8303790106 BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A. ABA 067010509 SWIFT MNB MUS33</p> <p><u>COMPONENTE NACIONAL (IVA)</u></p> <p><i>En BOLIVARES (Bs.) mediante transferencia bancaria</i></p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. – 0105-0011-73-1011-50499-5</p>												
	<p>OTRAS CONDICIONES</p> <ol style="list-style-type: none"> 1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos 2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y deberá ser cancelado a la tasa oficial del día de pago o de la retención correspondiente 												

	<p>3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.</p> <p>4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente</p> <p>5. Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta</p> <p>6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22.</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <p>In Tech instrumentos y Equipos, C.A. RIF: J-30615033-1 NIT: 0096996004</p> </div> <div style="text-align: center;">  </div> </div> <p>Cci: G. Novoa – INTECH MCBO</p>		
--	---	--	--

Please Transfer to Account of:
 Bank: Amerant Bank
 Address: 220 Alhambra Circle, Coral Gables,
 Florida 33134, USA
 ABA: 067010509
 Swift: MNB MUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS
 C.A.
 Account # 8303790106

Subtotal	US\$	77,250.00
Freight	US\$	Incluido
Insurance	US\$	--
IVA 16%	US\$	12,360.00
IGTF 3%	US\$	---
TOTAL	US\$	89,610.00