

Quote # C-2025-0324
Date: 15/09/2025
Customer ID CHEVRON PETROBOSCAN

Bill to:
<p>CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela Att: Jorgelis Rincon - Depto de Procura Jorgelis.Rincon1@chevron.com</p>

Ship to:
<p>CHEVRON PETROBOSCAN Warehouse Venezuela</p>

Sales Rep.	Your #	Our #	Destiny	Terms	Validity
N. Carricatti	VEN-RFQ-PB-2025-083	C-2025-0324/ WIKA@202509-01/QUO00021600-1	Venezuela	DDP Petroboscan	30 days

Item	Cant	Description	Unit Price US\$	Total US\$
1	6	<p>PRESSURE GAUGE SERIE 232.34 400 PSI, WIKA PN 80052027</p> <p>Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0/400 psi Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock</p> <p>TAG-1 (SS Tag Plate) PI-8761; PI-8764; PI-8641; PI-8651; PI-8761; PI-8764</p>	\$270,00	\$1.620,00
2	6	<p>PRESSURE GAUGE SERIE 232.34 3000 PSI, WIKA PN 4252384</p>	\$290,00	\$1.740,00

		<p>Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0/3000 psi Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock</p> <p>TAG-1 (SS Tag Plate) PI-8762; PI-8763; PI-8760; PI-8762; PI-8763; PI-8760</p>		
3	4	<p>PRESSURE TRANSMITTER SERIE UPT-20 WITH VALVE IV201, WIKA PN 80074917 (1) / 80074918 (3) / 80049208 (4)</p> <p>Universal process pressure transmitter UPT Model: UPT-20 Specifications according to data sheet: PE 86.05 power supply: DC 12...36 V / DC 14...30 V Pressure Range: adjustable with turn down up to 100 : 1 Ingress Protection: IP 66/67 with internal pressure compensation Process connection type: Standard connection with pressure port Electrical approval: ATEX / IECEx Ignition protection type: Ex i - intrinsically safe Zone: Zone 1 attached to zone 0 gas [II 1/2G Ex ia IIC T6...T1 Ga/Gb] Case design: stainless steel cast, IP66/IP67 Digital Display: With Integrated 4 Digit LCD-Display window: plastic window PC Output signal: 4 ... 20 mA with HART protocol, 2-wire Electrical connection: 1/2" NPT female conduit Pressure range: 0 ... 10000 psig Process connection: 1/2 NPT Accuracy: 0.15% of span Unit of outer Scale: psi Scaling lower value: 0 psi Scaling high value: 4000,0 Sensor principle: Thin film</p> <p>Model: IV201 Specifications according to data sheet: AC 09.19 Design: square</p>	\$4.220,00	\$16.880,00

		<p>Valve position: angled Connection process side + instrument side: 1/2 NPT male - 1/2 NPT female Material body: Stainless steel 316/316L Mounting: without bracket hole Vent connection: 1/4" NPT female with plug Nominal pressure: 6000 psi / 420 bar Material packing: PTFE Certificates/Approvals: NACE Sour Gas Service and Inspection certificate 3.1 according to EN 10204,all wetted parts material</p> <p>TAG-1 (SS Tag Plate) PIT-8760</p> <p>Universal process pressure transmitter UPT Model: UPT-20 Specifications according to data sheet: PE 86.05 power supply: DC 12...36 V / DC 14...30 V Pressure Range: adjustable with turn down up to 100 : 1 Ingress Protection: IP 66/67 with internal pressure compensation Process connection type: Standard connection with pressure port Electrical approval: ATEX / IECEx Ignition protection type: Ex i - intrinsically safe Zone: Zone 1 attached to zone 0 gas [II 1/2G Ex ia IIC T6...T1 Ga/Gb] Case design: stainless steel cast, IP66/IP67 Digital Display: With Integrated 4 Digit LCD-Display window: plastic window PC Output signal: 4 ... 20 mA with HART protocol, 2-wire Electrical connection: 1/2" NPT female conduit Pressure range: 0 ... 10000 psig Process connection: 1/2 NPT Accuracy: 0.15% of span Unit of outer Scale: psi Scaling lower value: 0 psi Scaling high value: 300,0 Sensor principle: Thin film</p> <p>Model: IV201 Specifications according to data sheet: AC 09.19 Design: square Valve position: angled Connection process side + instrument side: 1/2 NPT male - 1/2 NPT female Material body: Stainless steel 316/316L Mounting: without bracket hole Vent connection: 1/4" NPT female with plug Nominal pressure: 6000 psi / 420 bar Material packing: PTFE Certificates/Approvals: NACE Sour Gas Service and Inspection certificate 3.1 according to EN 10204,all wetted parts material</p> <p>TAG-1 (SS Tag Plate) PTI-8641; PIT-8651; PIT-8760</p>		
4	2	<p>PRESSURE SWITCH SERIE MW-XXDS 250 PSI, WIKA PN 80074914</p> <p>MW-XXDS - 0...250 psi - Adaptor 1/2 NPT-M - 1/2 -14 NPT-F Diaphragm pressure switch, Stainless steel case, Model MW</p>	\$2.300,00	\$4.600,00

		<p>measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection A electric contacts: 2 x SPDT or 1 x DPDT silver contact, hermetically sealed, argon gas filling setting range: 0...250 psi Standard, working range = 0...250 PSI, proof pressure 400 PSI process connection: Adaptor 1/2 NPT-M electrical connection: 1/2 -14 NPT-F Yoke for 2" pipe mounting Ingress Protection: IP66 Diaphragm: Inconel 718/O-Ring: FPM/Connection: Stainless steel AISI 316L brand: WIKA Instruments Italia Specifications according to data sheet: PV 31.10 Repeatability of set point: ≤ 1% of span set point definition: Set Point customer-specifically configured, one set point 1xDPDT 1. set point: 80,00 psi decreasing, 2. set point: 80,00 psi decreasing Approvals / Certificates IECEx-ATEX Ex ia Certificate Language: English Inspection: 100% Inspection (with calibration values listed each instrument)</p> <p>TAG-1 (SS Tag Plate) PSLL-8761; PSLL-8761</p>		
5	2	<p>PRESSURE SWITCH SERIE MW-GXXDS 4000 PSI, WIKA PN 80074915</p> <p>MWGXDS - 150...4000 psi - Adaptor 1/2 NPT-M - 1/2 -14 NPT-F Diaphragm pressure switch, Stainless steel case, Model MW measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection A electric contacts: 2 x SPDT or 1 x DPDT silver contact, hermetically sealed, argon gas filling setting range: 150...4000 psi Standard, working range = 0...4000 PSI, proof pressure 6000 PSI process connection: Adaptor 1/2 NPT-M electrical connection: 1/2 -14 NPT-F Yoke for 2" pipe mounting Ingress Protection: IP66 Diaphragm: Hastelloy C 276//Connection: Stainless steel AISI 316L brand: WIKA Instruments Italia Specifications according to data sheet: PV 31.10 Repeatability of set point: ≤ 1% of span set point definition: Set Point customer-specifically configured, one set point 1xDPDT 1. set point: 2460,00 psi increasing, 2. set point: 2460,00 psi increasing Approvals / Certificates IECEx-ATEX Ex ia Certificate Language: English Inspection: 100% Inspection (with calibration values listed each instrument)</p> <p>TAG-1 (SS Tag Plate) PSHH-8761; PSHH-8761</p>	\$2.830,00	\$5.660,00
6	2	<p>BIMETAL THERMOMETER, PROEES GRADE, MODEL TG53.5Z WITH THERMOWELL TW15, WIKA PN 80051189-39119068</p> <p>Bimetal thermometer, Proeess grade aeecording to ASME B40.200</p>	\$1.140,00	\$2.280,00


		<p>Model: TG53.5Z Specifications according to data sheet: ATM 53.02 Accuracy Class: +/-1% of Full Scale (ASME B40.3) Nominal size: 5" Connector position: mount, adjustable Design of Connection: standard, male thread Process Connection: 1/2" NPT Seale Range: 30 °F ... 300 °F Stem Diameter: 1/4" Insertion length L 1: 9" Window: laminated safety glass Ingress Protection: IP 66 / NEMA 4X Permissible ambient temperature: -40 ... +70 °C with Serial number Manufacturer logo: *WIKA®* CHEVRON Logo (2 colors)</p> <p>Threaded Thermowell TW15, solid machined Specifications according to data sheet: TW 95.15 Head Design: Hexagon Thermowell Style: Tapered Unit of Measure: Imperial (inch) Process thread [P or E]: 1" NPT Instrument connection [N]: 1/2 NPT female Insertion length [U]: 7.5 inch Head Length: 1.75" Material: Stainless steel 316/316L Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 1.063 inch Tip diameter [V or F3]: 0.750 inch Bore depth / stem length (US): 9.000 inch Tip thickness [Tt]: 0.250 inch (6.4 mm)</p> <p>TAG-1 (SS Tag Plate) TI-8761, TI-8761</p>		
7	2	<p>BIMETAL THERMOMETER, PROCESS GRADE, MODEL TG53.5Z WITH THERMOWELL TW15, WIKA PN 80051189-39119068</p> <p>Bimetal thermometer, Process grade according to ASME B40.200 Model: TG53.5Z Specifications according to data sheet: ATM 53.02 Accuracy Class: +/-1% of Full Scale (ASME B40.3) Nominal size: 5" Connector position: mount, adjustable Design of Connection: standard, male thread Process Connection: 1/2" NPT Seale Range: 30 °F ... 300 °F Stem Diameter: 1/4" Insertion length L 1: 9" Window: laminated safety glass Ingress Protection: IP 66 / NEMA 4X Permissible ambient temperature: -40 ... +70 °C with Serial number Manufacturer logo: *WIKA®* CHEVRON Logo (2 colors)</p> <p>Threaded Thermowell TW15, solid machined</p>	\$1.140,00	\$2.280,00

		<p>Specifications according to data sheet: TW 95.15 Head Design: Hexagon Thermowell Style: Tapered Unit of Measure: Imperial (inch) Process thread [P or E]: 1" NPT Instrument connection [N]: 1/2 NPT female Insertion length [U]: 7.5 inch Head Length: 1.75" Material: Stainless steel 316/316L Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 1.063 inch Tip diameter [V or F3]: 0.750 inch Bore depth / stem length (US): 9.000 inch Tip thickness [Tt]: 0.250 inch (6.4 mm)</p> <p>TAG-1 (SS Tag Plate) TI-8762, TI-8762</p>		
8	4	<p>DIFFERENTIAL PRESSURE TRANSMITTER SERIE DPT-20, WIKA PN 80074929 (2) / 80074930 (2)</p> <p>Differential Pressure Transmitter DPT-20 Specifications according to data sheet: PE 86.22 Electrical approval: ATEX, IECEx, Ignition protection type: Ex i - intrinsically safe Zone: Zone 1 attached to zone 0 gas [II 1/2G Ex ia IIC T3...T6 Ga/Gb] Housing material: Plastic single chamber enclosure execution: compact/ IP66/IP67; NEMA 4X Digital Display: with integrated indicating/adjustment module (top) Output signal: 4...20 mA, 2-wire, HART Electrical connection: M20x1,5 / cable gland PA black (ø5-9mm), standard Unit: bar Maximal working pressure: 160 bar (16 MPa / 2400 psi) Pressure range: -3 ... +3 bar Process connection/mounting/material/venting: 1/4-18 NPT IEC 61518 / 7/16-20 UNF / 316L / dorsal, incl. 2 valves Diaphragm material: 316L Sealing (temperature range): FKM (-20 ... +85 °C) Accuracy: 0.065 % of span Mounting element: mounting bracket for wall or pipe mounting (max. 2"), stainless steel Additional equipment: with valve manifold / connection adapter Filling of sensor: Silicone oil for regular applications (KN2) Operating modes: Pressure measurement Scaling unit DP-measurement: inH2O Lower scaling value DP: 0 inH2O Upper scaling value DP: 200,0 Density value: 1 Density unit: kg/dm³ Linearization curve: linear Damping [s]: 1 s (default setting) Output signal low level in %: 0% Output signal low level in %: 100% Displayed value: differential pressure (acc. scaling) manifold (version, connection, materials): 5 valve, PN420, IEC 61518 form A - 1/2 NPT female, stainless steel/packing PTFE mounting of the manifold: manifold not fixed enclosed, mounting carried out by user Model: 5-Valve Manifold</p>	\$9.250,00	\$37.000,00

		<p>TAG-1 (SS Tag Plate) FIT-8760, FIT-8760</p> <p>Differential Pressure Transmitter DPT-20 Specifications according to data sheet: PE 86.22 Electrical approval: ATEX, IECEx, Ignition protection type: Ex i - intrinsically safe Zone: Zone 1 attached to zone 0 gas [II 1/2G Ex ia IIC T3...T6 Ga/Gb] Housing material: Plastic single chamber enclosure execution: compact/ IP66/IP67; NEMA 4X Digital Display: with integrated indicating/adjustment module (top) Output signal: 4...20 mA, 2-wire, HART Electrical connection: M20x1,5 / cable gland PA black (ø5-9mm), standard Unit: bar Maximal working pressure: 160 bar (16 MPa / 2400 psi) Pressure range: -3 ... +3 bar Process connection/mounting/material/venting: 1/4-18 NPT IEC 61518 / 7/16-20 UNF / 316L / dorsal, incl. 2 valves Diaphragm material: 316L Sealing (temperature range): FKM (-20 ... +85 °C) Accuracy: 0.065 % of span Mounting element: mounting bracket for wall or pipe mounting (max. 2"), stainless steel Additional equipment: with valve manifold / connection adapter Filling of sensor: Silicone oil for regular applications (KN2) Operating modes: Pressure measurement Scaling unit DP-measurement: inH2O Lower scaling value DP: 0 inH2O Upper scaling value DP: 150,0 Density value: 1 Density unit: kg/dm³ Linearization curve: linear Damping [s]: 1 s (default setting) Output signal low level in %: 0% Output signal low level in %: 100% Displayed value: differential pressure (acc. scaling) manifold (version, connection, materials): 5 valve, PN420, IEC 61518 form A - 1/2 NPT female, stainless steel/packing PTFE mounting of the manifold: manifold not fixed enclosed, mounting carried out by user Model: 5-Valve Manifold</p> <p>TAG-1 (SS Tag Plate) FIT-8761, FIT-8761</p>		
12	4	<p>THERMAL MASS FLOW SWITCH VERSA-SWITCH® VS5100 Series, DELTAMCORP PN V5514X-N08-S6-012.00-24D-LE-XW-FA-TG</p> <p>Product Model: VS51 - VERSASWITCH</p> <p>Ratings: 4X - NEMA 4X</p> <p>Add a Custom Tag: TG - Stainless Steel Tag Tag Etching: F5LL-8761</p>	\$7.410,00	\$29.640,00

		<p>FE-8761 FE-8641 FE-8651</p> <p>Calibration: ∅∅ - Dry/Wet Level Calibration</p> <p>Power Input: 24D - 24VDC</p> <p>Add watchdog circuitry: FA - Failure Alarm</p> <p>Electronic Location: LE - Local (Integral Sensor)</p> <p>Electronic Enviroment: XW - Explosion Proof w/ Window</p> <p>Process Connections: N08-S6 1-in NPT Male 3000# Stainless 316</p> <p>Insertion Length: > 2.00 Inch Insertion Length</p> <p>Insertion Length in inches: 12</p>		
18	2	<p>DIFFERENTIAL PRESSURE SWITCH SERIE DW-40DS 15 PSI, WIKA PN 80074916</p> <p>DW-40DS - 0...40 psi - 2x1/4 - 18 NPT-F - 1/2 -14 NPT-F Differential pressure switch, Stainless steel version Model DW 40bar electric contacts: 2 x SPDT or 1 x DPDT silver contact, hermetically sealed, argon gas filling setting range: 0...40 psi process connection: 2x1/4 - 18 NPT-F electrical connection: 1/2 -14 NPT-F Mounting: Yoke for 2" pipe mounting Diaphragm Material: AISI 316 brand: WIKA Instruments Italia Connection: Stainless steel AISI 316L Specifications according to data sheet: SP 08.42 (DW) Repeatability of set point: ≤ 1% of span set point definition: Set Point customer-specifically configured, one set point 1xDPDT 1. set point: 15,00 psi increasing, 2. set point: 15,00 psi increasing Approvals / Certificates IECEX-ATEX Ex ia Certificate Language: English Inspection: 100% Inspection (with calibration values listed each instrument)</p> <p>TAG-1 (SS Tag Plate) PDSH-8761; PDSH-8761</p>	\$4.190,00	\$8.380,00
		<p>Delivery Time Item 1, 2, 12: 8 – 12 Weeks ARAD Item 3+: 12 – 16 Weeks ARAD</p>		

	<p>Partial Shipments allowed (WIKA)</p> <p>Payment Terms</p> <ul style="list-style-type: none"> • 100% Net 30 days delivery time <p>Packing Material will be Securely packed in wooden crates suitable for air freight and export.</p> <p>Volume & Weight (to be reconfirmed) To be advised – Aprox 390 Lbs</p> <p>General Warranty: WIKA warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p>Project Cancellation charges:</p> <table border="0"> <tr> <td>15%</td> <td>Up to submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> <tr> <td>75%</td> <td>Within two weeks of production release</td> </tr> <tr> <td>100%</td> <td>Two weeks after production commences</td> </tr> </table>	15%	Up to submittal of Engineering & Design Drawings and Documents	25%	After submittal of Engineering & Design Drawings and Documents	50%	After material order placement and before production commences	75%	Within two weeks of production release	100%	Two weeks after production commences		
15%	Up to submittal of Engineering & Design Drawings and Documents												
25%	After submittal of Engineering & Design Drawings and Documents												
50%	After material order placement and before production commences												
75%	Within two weeks of production release												
100%	Two weeks after production commences												
NOTAS:													
	<p>CONDICIONES DE PAGO</p> <p><u>COMPONENTE IMPORTADO</u></p> <p><i>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</i></p> <p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134 CUENTA NUMERO 8303790106 BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A. ABA 067010509 SWIFT MNB MUS33</p> <p><u>COMPONENTE NACIONAL (IVA)</u></p> <p><i>En BOLIVARES (Bs.) mediante transferencia bancaria</i></p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. – 0105-0011-73-1011-50499-5</p>												
	<p>OTRAS CONDICIONES</p> <p>1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan</p>												

	<p><i>con Certificados de Conformidad del Fabricante en caso de ser requeridos</i></p> <p>2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y deberá ser cancelado a la tasa oficial del día de pago o de la retención correspondiente</p> <p>3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.</p> <p>4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente</p> <p>5. Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta</p> <p>6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22.</p> <div style="display: flex; justify-content: space-between; align-items: center;"> <div data-bbox="277 842 542 951" style="text-align: center;"> <p>In Tech Instrumentos y Equipos, C.A. RIF: J-30615033-1 NIT: 0096996004</p> </div> <div data-bbox="574 831 847 989" style="text-align: center;">  </div> </div> <p><i>Cci: G. Novoa – INTECH MCBO</i></p>		
--	--	--	--

Please Transfer to Account of:
Bank: Amerant Bank
Address: 220 Alhambra Circle, Coral Gables,
Florida 33134, USA
ABA: 067010509
Swift: MNBMUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS
C.A.
Account # 8303790106

Subtotal	US\$	110,080.00
Freight	US\$	Incluido
Insurance	US\$	--
IVA 16%	US\$	17,612.80
IGTF 3%	US\$	---
TOTAL	US\$	127,692.80