

Quote #

C-2025-0311

Date:

12/09/2025

Customer ID

CHEVRON PETROPIAR

Bill to:

CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY

Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7,
Chua, Caracas 1060, Venezuela
Att: Allen Michael Gamboa - Depto de Procura
AllenMichael.Gamboa@chevron.com

Ship to:

CHEVRON PETROPIAR Warehouse
Edo Anzoategui, Venezuela

| Sales Rep. | Your # | Our # | Destiny | Terms | Validity |
|---------------|---------------------|--|-----------|------------------|----------|
| N. Carricatti | VEN-PP-2025-494-XXI | C-2025-0311/IBI-2025-0136/0139 WIKA@202508-03/QUO00021427-1 | Venezuela | DDP Jose complex | 30 days |

| Item | Cant | Description | Unit Price US\$ | Total US\$ |
|------|------|--|-----------------|------------|
| 1 | 5 | <p>PRESSURE GAUGE SERIE 232.34, WIKA PN 232.34.45-PXXX0PX-N4LM/LSG/LOGO</p> <p>Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX psi - TAGREF 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock</p> <p>TAG - REF: 41-PI-001A: 0 - 1,200 PSIG</p> | \$420,00 | \$2.100,00 |

| | | | | |
|---|---|---|------------|------------|
| | | 41-PI-010: 0 - 1,200 PSIG 41-PI-007: 0 - 1,200 PSIG 41-PI-024: 0 - 1,200 PSIG 41-PI-025: 0 - 1,200 PSIG | | |
| 2 | 1 | <p>PRESSURE GAUGE SERIE 232.34, WIKA PN 232.34.45-PXXX0PX-N4LM/LSG/LOGO</p> <p>Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX psi - TAGREF 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock</p> <p>TAG - REF: 41-PI-006B: 0 - 2,000 PSIG</p> | \$420,00 | \$420,00 |
| 3 | 2 | <p>PRESSURE GAUGE CAPSULE SERIE 6X2.34, WIKA PN 80NG07CV46IN49</p> <p>Type 6X2.34 - Capsule Process Gauges Specifications according to data sheet: PM 06.07 Case: Black Plastic Bezel ring: Threaded Retainer Ring, Plastic, Black Accuracy Class: +/- 2/1/2% (ASME 840.100 Grade A) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Unit: inH2O Scale range: 0 inH2O ... 80 inH2O Process Connection: 1/2 NPT Connector location: lower mount Movement: stainless steel Ingress Protection: IP 65 Case filling fluid: Silicon oil, 50 cSt Package: Single packing Window: laminated safety glass Dial description:</p> | \$2.050,00 | \$4.100,00 |

| | | | | |
|---|---|---|----------|----------|
| | | <p>Pressure Gauge Standard: International (standard Europe) color for 1.scale (outside): black dial background: White Manufacturer logo: *WIKA* Serial number *...* stop pin on dial: at 6 o'clock norm-mark on dial: *EN 837-3* inner packages label: Standard (with Wika Logo) outside packages label: Standard (with Wika Logo) CHEVRON Logo (2 colors)</p> <p>TAG - REF: 41-PI-004A 41-PI-027</p> | | |
| 4 | 1 | <p>PRESSURE GAUGE SERIE 232.34, WIKA PN 232.34.45-PXXX0PX-N4LM/LSG/LOGO</p> <p>Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX psi - TAGREF 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock</p> <p>TAG - REF: 41-PI-0026: 0 - 20 PSIG</p> | \$420,00 | \$420,00 |
| 5 | 2 | <p>PRESSURE GAUGE SERIE 232.34, WIKA PN 232.34.45-PXXX0PX-N4LM/LSG/LOGO</p> <p>Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX psi - TAGREF</p> | \$420,00 | \$840,00 |

| | | | | |
|---|---|--|----------|----------|
| | | <p>2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White Manufacturer logo: *WIKA* Serial number * ... * stop pin on dial: at 6 o'clock norm-mark on dial: *EN 837-3* inner packages label: Standard (with Wika Logo) outside packages label: Standard (with Wika Logo) CHEVRON Logo (2 colors)</p> <p>TAG-1 (SS Tag Plate) 41 PI-004A; 41 PI-027</p> | | |
| 6 | 1 | <p>PRESSURE GAUGE SERIE 232.34, WIKA PN 232.34.45-PXXX0PX-N4LM/LSG/LOGO</p> <p>Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX psi - TAGREF 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number * ... * stop pin on dial: at 6 o'clock</p> <p>TAG - REF: 41-PI-032: 0 - 300 PSIG</p> | \$420,00 | \$420,00 |
| 7 | 1 | <p>PRESSURE GAUGE SERIE 232.34, WIKA</p> | \$420,00 | \$420,00 |

| | | | | |
|---|---|---|----------|----------|
| | | <p>PN 232.34.45-BXXX0PX-N4LM/LSG/LOGO</p> <p>Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX bar - TAGREF 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock</p> <p>TAG - REF: 41-PI-036A: 0 – 3 bar</p> | | |
| 8 | 2 | <p>PRESSURE GAUGE SERIE 232.34, WIKA PN 232.34.45-PXXX0PX-N4LM/LSG/LOGO</p> <p>Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0... XXX psi - TAGREF 2nd Scale / Special Scale: none Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: NONE Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* CHEVRON Logo (2 colors)</p> | \$420,00 | \$840,00 |

| | | | | |
|----|---|--|------------|------------|
| | | <p>serial number on dial: Serial number *...*</p> <p>stop pin on dial: at 6 o'clock</p> <p>TAG - REF: 41-PI-038: 0 - 60 PSIG 41-PI-039: 0 - 60 PSIG</p> | | |
| 9 | 1 | <p>BIMETAL THERMOMETER, PROEESS GRADE, MODEL TG53.5Z WITH THERMOWELL TW15, WIKA PN 56NG05CV00IN88- 39TE119CH06CA8</p> <p>Bimetal thermometer, Proeess grade aeecording to ASME B40.200 Model: TG53.5Z Speeifieations aeecording to data sheet: ATM 53.02 Aeeuraey Class: +/-1% of Full Seale (ASME B40.3) Nominal size: 5" Conneetor position: baek mount, adjustable Design of Conneetion: standard, male thread Proeess Conneetion: 1/2" NPT Seale Range: 0 °C ... 150 °C Stem Diameter: 1/4" Insertion length L 1: 9" Window: laminated safety glass Ingress Proteetion: IP 66 / NEMA 4X Permissible ambient temperature: -40 ... +70 °C with Serial number Manufaeturer logo: *WIKA®* CHEVRON Logo (2 colors)</p> <p>Threaded Thermowell TW15, solid machined Speeifieations aeecording to data sheet: TW 95.15 Head Design: Hexagon Thermowell Style: Tapered Unit of Measure: Imperial (inch) Process thread [P or E]: 1" NPT Instrument connection [N]: 1/2 NPT female Insertion length [U]: 7.5 inch Head Length: 1.75" Material: Stainless steel 316/316L Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 1.063 ineh Tip diameter [V or F3]: 0.750 ineh Bore depth / stem length (US): 9.000 ineh Tip thiekness [Tt]: 0.250 ineh (6.4 mm)</p> <p>TAG-1 (SS Tag Plate) 41-TI-006</p> | \$1.250,00 | \$1.250,00 |
| 10 | 1 | <p>GAS ACTUATED THERMOMETER, MODEL S73.100 WITH THERMOWELL TW15, WIKA PN 80NG07CV46IN48- 39TE10CH80CA40</p> <p>Gas aetuated thermometer, stainless steel series Speeifieations aeecording to data sheet: TM 73.01 Case: stainless steel Stem Material: stainless steel Model: S73.100, nominal size 100, adjustable stem and dial Unit: °F Seale Range: 400 a 1200 °F Design of Conneetion: 4, eompression fitting, sliding on stem</p> | \$2.000,00 | \$2.000,00 |


| | | | | |
|----|---|--|-------------|-------------|
| | | <p>Process Connection: 1/2" NPT Stem Diameter: 6 mm Insertion length L 1: 152 Ignition protection type: without Zone: without Accuracy Class: class 1 per EN 13190 Window: laminated safety glass Connector location: axial Manufacturer logo: *WIKA* with Serial number QR code with extended serial number on dial CHEVRON Logo (2 colors)</p> <p>Threaded Thermowell TW15, solid machined Specifications according to data sheet: TW 95.15 Head Design: Hexagon Thermowell Style: Tapered Unit of Measure: Imperial (inch) Process thread [P or E]: 1" NPT Instrument connection [N]: 1/2 NPT female Insertion length [U]: 4.5 inch Head Length: 1.75" Material: Stainless steel 316/316L Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 1.063 inch Tip diameter [V or F3]: 0.750 inch Bore depth / stem length (US): 6.000 inch Tip thickness [Tt]: 0.250 inch (6.4 mm)</p> <p>TAG-1 (SS Tag Plate) 41-TI-007</p> | | |
| 11 | 1 | <p>WIKA DUAL CHAMBER LEVEL SYSTEM - Redundant BNA/DU-2"/300/RF-M508-L/CS 60x2.77/60x2,77-MRF-ZVSS185/PN25/R48H Tags # 41-LIT-101;</p> <p>Magnetic Level Gauge Type BNA-SD00 Pressure: 100 psi ; Temp.: 14°F...357 °F; Fluid density: 898 -914 kg/m³ Service: TOTAL Level Design code: ASME B31.3 Chamber dimensions: OD 60.3 x 2.77 mm (2" Sch. 10S) Duo stainless steel 316/316L (EN 1.4401/1.4404) Process connection: CS Flange ASME B16.5 2" 300# Form RF Distance C-to-C: 1219 mm Measuring range: 1219 mm Chamber end top: Pipe cap Chamber end bottom: CS Flange ASME B16.5 2" 300# Form RF Vent connection: Butt weld end 3/4" Drain connection: Butt weld end 3/4" Float: ZVSS185/PN25/R48H Dampening element: Dampening spring, bottom, with cover Gasket(s): Spiral wound type, SS 316L/Graphite Bolting: UNC series, carbon steel A193 Gr. B7 HDG / A194 Gr. 2H HDG Top stand-off (T): 100 mm Bottom stand-off (U): 250 mm Nameplate: Stainless steel laser printed Includes Bottom: Mag Trap -316ss/ CS construction -316SS 2" x 2" Tee with 2" CS 300# RFWN Flange -Bottom: CS 2" 300# RFWN with blind mating flange & 1/2" NPT Drain and Plug</p> | \$57.360,00 | \$57.360,00 |

| | | | |
|--|--|--|--|
| | <p>Dual Chamber (DUplus) Sidechamber: OD 60.3 x 2,77 mm (2" Sch. 10S) Location of secondary chamber: 3 o'clock (right side of MLG chamber) Process connection GT: CS Flange ASME B16.5 2" 300# Form RF Distance between chambers center lines: 200 mm Radar connection stand-off: 254 mm Side chamber bottom stand-off: 254 mm Insertion external sensor: With MRF-M1219 Level Indicator for Magnetic Level Gauge Type BMD-FA Measuring range: 1219 mm Housing material: Aluminum anodized Indicating elements: Stainless steel flaps Red & white Graduated scale: Aluminum engraved Graduation unit: inch INCLUDES INSULATION JACKET SS Tag Plate</p> <p>w/ RADAR Transmitter FX81.FADACKHXANAM eID: US34262802 Scope F : USA Approval A : FM (NI) CL I, II, III DIV2, GP ABCDFG Version / Material D : Exchangeable cable (ø2mm) with centering weight / 316 Probe : mounted Length (from seal surface) : 66.000 inch Length of rigid part : 3.937 inch Dimensions centering weight (diameter / height) : 1.77in / 1.18in (for 2" Schedule 40/80 and 3" Schedule 80/160) Process fitting / Material AC : Flange 2" 300lb RF, ASME B16.5 / 316/316L Seal / Second line of defense / Process temperature K : FFKM (Kalrez 6375) / without / -20...+200°C Electronics H : Two-wire 4 ... 20 mA/HART Supplementary electronics X : with Overvoltage protection of the supply cable 24 VDC , Model USB63-48.N Housing / Protection A : Aluminum single chamber / IP66/IP68 (0.2bar) Cable entry / Connection N : ½NPT / Blind plug Display/Adjustment module PLICSCOM A : mounted Certificates M : Yes Certificate / Standard : (C) Material test report – traceable (EN 10204 type 3.1 + NACE MR0175 + NACE MR0103) PMI test : RFA (positive material identification) incl. 3.1 inspection certificate Supply certificates : with goods Measurement loop identification label : of Stainless Steel Customer-specific adjustment : Yes - Unit : inch - 100 % (distance from seal surface) : 10.000 inch - 0 % (distance from seal surface) : 58.000 inch Linearization : No Min. process pressure in bar : -1.000 Max. process pressure in bar : 40.0</p> <p>Technical Notes Included on each System:</p> <ul style="list-style-type: none"> - Approval Drawings - Hydrostatic Pressure Test 1.5x Flange Rating for 10 min @ ambient - NACE MR0175 Certificate - Material Test Reports with Tagging Information on each - Positive Material Identification w/o Carbon Content (10) shots per unit - 100% Xray | | |
|--|--|--|--|

| | | | | |
|----|---|---|-------------|-------------|
| | | <ul style="list-style-type: none"> - Liquid Dye Penetrant - Package/ Handling (per Lot) | | |
| 12 | 1 | <p>WIKA DUAL CHAMBER LEVEL SYSTEM - Redundant BNA/DU-2"/300/RF-M508-L/CS 60x2.77/60x2,77-MRF-ZVSS185/PN25/R48H Tags # 41-LIT-101;</p> <p>Magnetic Level Gauge Type BNA-SD00 Pressure: 100 psi ; Temp.: 14°F...357 °F; Fluid density: 898 -914 kg/m³ Service: TOTAL Level Design code: ASME B31.3 Chamber dimensions: OD 60.3 x 2.77 mm (2" Sch. 10S) Duo stainless steel 316/316L (EN 1.4401/1.4404) Process connection: CS Flange ASME B16.5 2" 300# Form RF Distance C-to-C: 1219 mm Measuring range: 1219 mm Chamber end top: Pipe cap Chamber end bottom: CS Flange ASME B16.5 2" 300# Form RF Vent connection: Butt weld end 3/4" Drain connection: Butt weld end 3/4" Float: ZVSS185/PN25/R48H Dampening element: Dampening spring, bottom, with cover Gasket(s): Spiral wound type, SS 316L/Graphite Bolting: UNC series, carbon steel A193 Gr. B7 HDG / A194 Gr. 2H HDG Top stand-off (T): 100 mm Bottom stand-off (U): 250 mm Nameplate: Stainless steel laser printed Includes Bottom: Mag Trap -316ss/ CS construction -316SS 2" x 2" Tee with 2" CS 300# RFWN Flange -Bottom: CS 2" 300# RFWN with blind mating flange & 1/2" NPT Drain and Plug</p> <p>Dual Chamber (DUplus) Sidechamber: OD 60.3 x 2,77 mm (2" Sch. 10S) Location of secondary chamber: 3 o'clock (right side of MLG chamber) Process connection GT: CS Flange ASME B16.5 2" 300# Form RF Distance between chambers center lines: 200 mm Radar connection stand-off: 254 mm Side chamber bottom stand-off: 254 mm Insertion external sensor: With MRF-M1219 Level Indicator for Magnetic Level Gauge Type BMD-FA Measuring range: 1219 mm Housing material: Aluminum anodized Indicating elements: Stainless steel flaps Red & white Graduated scale: Aluminum engraved Graduation unit: inch INCLUDES INSULATION JACKET SS Tag Plate</p> <p>w/ RADAR Transmitter FX81.FADACKHXANAM eID: US34262802 Scope F : USA Approval A : FM (NI) CL I, II, III DIV2, GP ABCDFG Version / Material D : Exchangeable cable (ø2mm) with centering weight / 316 Probe : mounted Length (from seal surface) : 66.000 inch Length of rigid part : 3.937 inch Dimensions centering weight (diameter / height) : 1.77in / 1.18in (for 2" Schedule 40/80 and 3" Schedule 80/160)</p> | \$57.360,00 | \$57.360,00 |

| | | | | |
|----|---|--|------------|------------|
| | | <p>Process fitting / Material AC : Flange 2" 300lb RF, ASME B16.5 / 316/316L Seal / Second line of defense / Process temperature K : FFKM (Kalrez 6375) / without / -20...+200°C Electronics H : Two-wire 4 ... 20 mA/HART Supplementary electronics X : with Overvoltage protection of the supply cable 24 VDC , Model USB63-48.N Housing / Protection A : Aluminum single chamber / IP66/IP68 (0.2bar) Cable entry / Connection N : ½NPT / Blind plug Display/Adjustment module PLICSCOM A : mounted Certificates M : Yes Certificate / Standard : (C) Material test report – traceable (EN 10204 type 3.1 + NACE MR0175 + NACE MR0103) PMI test : RFA (positive material identification) incl. 3.1 inspection certificate Supply certificates : with goods Measurement loop identification label : of Stainless Steel Customer-specific adjustment : Yes - Unit : inch - 100 % (distance from seal surface) : 10.000 inch - 0 % (distance from seal surface) : 58.000 inch Linearization : No Min. process pressure in bar : -1.000 Max. process pressure in bar : 40.0</p> <p>Technical Notes Included on each System:</p> <ul style="list-style-type: none"> - Approval Drawings - Hydrostatic Pressure Test 1.5x Flange Rating for 10 min @ ambient - NACE MR0175 Certificate - Material Test Reports with Tagging Information on each - Positive Material Identification w/o Carbon Content (10) shots per unit - 100% Xray - Liquid Dye Penetrant - Package/ Handling (per Lot) | | |
| 13 | 4 | <p>BIMETAL THERMOMETER, PROEESS GRADE, MODEL TG53.5Z WITH THERMOWELL TW15, WIKA PN 80NG05CV11IN79-39TE119CH06CA8</p> <p>Bimetal thermometer, Proeess grade aeecording to ASME B40.200 Model: TG53.5Z Speeificatiions aeecording to data sheet: ATM 53.02 Aeecuraey Class: +/-1% of Full Seale (ASME B40.3) Nominal size: 5" Conneetor position: baek mount, adjustable Design of Conneetion: standard, male thread Proeess Conneetion: 1/2" NPT Seale Range: 50 °F ... 550 °F Stem Diameter: 1/4" Insertion length L 1: 9" Window: laminated safety glass Ingress Proteetion: IP 66 / NEMA 4X Permissible ambient temperature: -40 ... +70 °C with Serial number Manufaeturer logo: *WIKA®* CHEVRON Logo (2 colors)</p> <p>Threaded Thermowell TW15, solid machined Specifications according to data sheet: TW 95.15 Head Design: Hexagon Thermowell</p> | \$1.260,00 | \$5.040,00 |

| | | | | | | | | | | | | | |
|------|--|-----|--|-----|--|-----|--|-----|--|------|--------------------------------------|--|--|
| | <p>Style: Tapered Unit of Measure: Imperial (inch) Process thread [P or E]: 1" NPT Instrument connection [N]: 1/2 NPT female Insertion length [U]: 7.5 inch Head Length: 1.75" Material: Stainless steel 316/316L Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 1.063 ineh Tip diameter [V or F3]: 0.750 ineh Bore depth / stem length (US): 9.000 ineh Tip thiekness [Tt]: 0.250 ineh (6.4 mm)</p> <p>TAG-1 (SS Tag Plate) 41-TI-025; 41-TI-026; 41-TI-030; 41-TI-031</p> | | | | | | | | | | | | |
| | <p>Delivery Time Item 1, 2, 4-10, 13: 8 – 12 Weeks ARAD Item 3: 18 – 22 Weeks ARAD Item 11, 12: 14 – 18 Weeks ARAD</p> <p>Partial Shipments allowed (WIKA)</p> <p>Payment Terms</p> <ul style="list-style-type: none"> • 100% Net 30 days delivery time <p>Packing Material will be Securely packed in wooden crates suitable for air freight and export.</p> <p>Volume & Weight (to be reconfirmed) To be advised – Aprox XXX Lbs</p> <p>General Warranty: WIKA warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p>Project Cancellation charges:</p> <table border="0"> <tr> <td>15%</td> <td>Up to submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> <tr> <td>75%</td> <td>Within two weeks of production release</td> </tr> <tr> <td>100%</td> <td>Two weeks after production commences</td> </tr> </table> | 15% | Up to submittal of Engineering & Design Drawings and Documents | 25% | After submittal of Engineering & Design Drawings and Documents | 50% | After material order placement and before production commences | 75% | Within two weeks of production release | 100% | Two weeks after production commences | | |
| 15% | Up to submittal of Engineering & Design Drawings and Documents | | | | | | | | | | | | |
| 25% | After submittal of Engineering & Design Drawings and Documents | | | | | | | | | | | | |
| 50% | After material order placement and before production commences | | | | | | | | | | | | |
| 75% | Within two weeks of production release | | | | | | | | | | | | |
| 100% | Two weeks after production commences | | | | | | | | | | | | |
| | <p>NOTAS:</p> | | | | | | | | | | | | |

| | | | |
|--|--|--|--|
| | <p>CONDICIONES DE PAGO</p> <p><u>COMPONENTE IMPORTADO</u></p> <p>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</p> <p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134 CUENTA NUMERO 8303790106 BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A. ABA 067010509 SWIFT MNB MUS33</p> <p><u>COMPONENTE NACIONAL (IVA)</u></p> <p>En BOLIVARES (Bs.) mediante transferencia bancaria</p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. – 0105-0011-73-1011-50499-5</p> | | |
| | <p>OTRAS CONDICIONES</p> <ol style="list-style-type: none"> 1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos 2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y deberá ser cancelado a la tasa oficial del día de pago o de la retención correspondiente 3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes. 4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente 5. Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta 6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22. <div style="display: flex; justify-content: space-between; align-items: center;"> <div data-bbox="277 1558 542 1667" style="text-align: center;"> <p>In Tech Instrumentos y Equipos, C.A. RIF: J-30615033-1 NIT: 0096996004</p> </div> <div data-bbox="574 1545 847 1705" style="text-align: center;">  </div> </div> <p>Cci: W. Brito – INTECH PLCRZ</p> | | |

Please Transfer to Account of:
Bank: Amerant Bank
Address: 220 Alhambra Circle, Coral Gables,
Florida 33134, USA
ABA: 067010509
Swift: MNB MUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS
C.A.
Account # 8303790106

| | | |
|------------------|-------------|-------------------|
| Subtotal | US\$ | 132,570.00 |
| Freight | US\$ | Incluido |
| Insurance | US\$ | -- |
| IVA 16% | US\$ | 21,211.20 |
| IGTF 3% | US\$ | --- |
| TOTAL | US\$ | 153,781.20 |