



Instrumentos y Equipos C.A

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
 Caracas, Venezuela 1080
 Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
 Fax: 58-212-977.3613
 E-mail: sales@intech-ie.com
 RIF J-30615033-1

Quote # C-2026-0050
Date: 20/02/2026
Customer ID CHEVRON PETROPIAR

Bill to:
CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela Att: Cristian Garcia - Depto de Procura Cristian.Garcia@chevron.com

Ship to:
CHEVRON PETROPIAR Warehouse Venezuela

Sales Rep.	Your #	Our #	Destiny	Terms	Validity
N. Carricatti	6600006931 PP 035 PARTE I	C-2025-0417/PL WIDN-20251102/ QUO00022324	Venezuela	DDP Petropiar	30 days

Item	Cant	Description	Unit Price US\$	Total US\$
7	6	<p>PRESSURE GAUGE MODEL 233.34, WIKA PN 80076234</p> <p>Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: -30 inHg/15 psi 2nd Scale / Special Scale: 2nd scale bar Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Silicone, 1000 cSt Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black color for 2.scale (inside): red dial background: White *WIKA®* serial number on dial: Serial number *...* QR code with extended serial number on dial stop pin on dial: at 6 o'clock LOGO CHEVRON 2 COLOURS INCLUDED</p>	\$530,00	\$3.180,00

57	7	<p>DIAPHRAGM PRESSURE SWITCH MODEL MW, WIKA PN 80077423</p> <p>Diaphragm pressure switch, Stainless steel case, Model MW measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection A electric contacts: 2 x SPDT or 1 x DPDT silver contact, hermetically sealed, argon gas filling setting range: 0...250 psi Standard, working range = 0...250 PSI, proof pressure 400 PSI process connection: Adaptor 1/2 NPT-M electrical connection: 3/4 - NPT-F Enclosure with plate for wall or direct mounting Ingress Protection: IP66 Diaphragm: Inconel 718/O-Ring: FPM/Connection: Stainless steel AISI 316L brand: WIKA Instruments Italia Specifications according to data sheet: PV 31.10 Repeatability of set point: ≤ 1% of span set point definition: Set Point to be defined Approvals / Certificates IECEX-ATEX Ex ia</p>	\$2.580,00	\$18.060,00
58	3	<p>DIAPHRAGM PRESSURE SWITCH MODEL MWGXXDS, WIKA PN 80077424</p> <p>Diaphragm pressure switch, Stainless steel case, Model MW measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection A electric contacts: 2 x SPDT or 1 x DPDT silver contact, hermetically sealed, argon gas filling setting range: 150...1500 psi Standard, working range = 0...1500 PSI, proof pressure 3000 PSI process connection: Adaptor 1/2 NPT-M electrical connection: 3/4 - NPT-F Enclosure with plate for wall or direct mounting Ingress Protection: IP66 Diaphragm: Hastelloy C 276//Connection: Stainless steel AISI 316L brand: WIKA Instruments Italia Specifications according to data sheet: PV 31.10 Repeatability of set point: ≤ 1% of span set point definition: Set Point to be defined Approvals / Certificates IECEX-ATEX Ex ia</p>	\$3.250,00	\$9.750,00
108	4	<p>DIAPHRAGM PRESSURE SWITCH MODEL MW, WIKA PN 80077422</p> <p>Diaphragm pressure switch, Stainless steel case, Model MW measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection A electric contacts: 2 x SPDT or 1 x DPDT silver contact, hermetically sealed, argon gas filling setting range: -15...25 psi Standard, working range = -15...25 PSI, proof pressure 30 PSI process connection: Adaptor 1/2 NPT-M electrical connection: 3/4 -14 NPT-F Enclosure with plate for wall or direct mounting Ingress Protection: IP66 Diaphragm: Stainless Steel AISI 316/O-Ring: FPM/Connection: Stainless steel AISI 316L brand: WIKA Instruments Italia</p>	\$2.580,00	\$10.320,00

		<p>Specifications according to data sheet: PV 31.10 Repeatability of set point: ≤ 1% of span set point definition: Set Point to be defined Approvals / Certificates IECEX-ATEX Ex ia</p>		
109	2	<p>INDUSTRIAL PRESSURE TRANSMITTER MODEL IPT-20, WIKA PN 80077480</p> <p>Industrial process transmitter IPT-2x with metallic sensor element Model: IPT-20 Specifications according to data sheet: PE 86.06 Pressure Range: adjustable with turn down up to 100 : 1 Process connection type: Standard connection with pressure port Electrical approval: ATEX Ignition protection type: Ex d - explosion proof Zone: Zone 1 attached to zone 0 gas [II 1/2G, 2G Ex d IIC T6] Housing material: Stainless steel cast single chamber enclosure execution: compact/ IP66/IP67; NEMA 4X Digital Display: with integrated indicating/adjustment module (top) Output signal: 4...20 mA, 2-wire, HART Electrical connection: M20x1,5 / cable gland brass nickel plated (ø6-12mm) Pressure range: -1 ... +40 bar gauge Accuracy: 0.1 % of span process connection form: Gauge connection open Process connection / wetted parts: Diaphragm seal Sealing: without Clean specification: without Filling of sensor: Silicone oil Certification sterile processes: without wetted parts: stainless steel Unit of outer Scale: psi lower scaling prefix: - Scaling lower value: 14,70 Upper scaling prefix: + Scaling high value: 30,0 Density unit: kg/dm³ Sensor principle: piezoresistiv Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: 4 meter capillary; stainless steel System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: - 30°C Process temperature max.: + 70°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 1/2" NPT female Flushing connection: 1 x 1/4 NPT female Nominal pressure rating: PN 100 Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: PTFE max. 500°F Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)</p>	\$10.800,00	\$21.600,00

	<p>Certificate type: Inspection certificate acc. to EN 10204 3.1 Certificate Language: English and German Certificate for: Diaphragm seal system with process transmitter Accuracy: Calibration values listed (traceable to national standards) Label: WIKA standard without / with Tag-number</p>												
	<p>Delivery Time Item 7: 9 – 11 Weeks ARAD Item 57, 58, 108, 109: 12 – 14 Weeks ARAD</p> <p>Partial Shipments allowed (WIKA)</p> <p>Payment Terms • 100% Net 30 days delivery time</p> <p>Packing Material will be Securely packed in wooden crates suitable for air freight and export.</p> <p>Volume & Weight (to be reconfirmed) To be advised – Aprox 490 Lbs</p> <p>General Warranty: Brand warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p>Project Cancellation charges:</p> <table data-bbox="243 1102 893 1417"> <tr> <td>15%</td> <td>Up to submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering & Design Drawings and Documents</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> <tr> <td>75%</td> <td>Within two weeks of production release</td> </tr> <tr> <td>100%</td> <td>Two weeks after production commences</td> </tr> </table>	15%	Up to submittal of Engineering & Design Drawings and Documents	25%	After submittal of Engineering & Design Drawings and Documents	50%	After material order placement and before production commences	75%	Within two weeks of production release	100%	Two weeks after production commences		
15%	Up to submittal of Engineering & Design Drawings and Documents												
25%	After submittal of Engineering & Design Drawings and Documents												
50%	After material order placement and before production commences												
75%	Within two weeks of production release												
100%	Two weeks after production commences												
	<p>NOTAS:</p>												
	<p>CONDICIONES DE PAGO</p> <p><u>COMPONENTE IMPORTADO</u></p> <p><i>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</i></p> <p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134 CUENTA NUMERO 8303790106 BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A. ABA 067010509 SWIFT MNB MUS33</p> <p><u>COMPONENTE NACIONAL (IVA)</u></p> <p><i>En BOLIVARES (Bs.) mediante transferencia bancaria</i></p>												

	<p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. - 0105-0011-73-1011-50499-5</p>		
	<p>OTRAS CONDICIONES</p> <p>1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos</p> <p>2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y debera ser cancelado a la tasa oficial del día de pago o de la retención correspondiente</p> <p>3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.</p> <p>4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente</p> <p>5. Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta</p> <p>6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22.</p> <div style="display: flex; justify-content: space-between; align-items: center;"> <div data-bbox="277 1073 542 1182" style="text-align: center;"> <p>In Tech instrumentos y Equipos, C.A. RIF: J-30615033-1 NIT: 0096996004</p> </div> <div data-bbox="573 1058 846 1220" style="text-align: center;">  </div> <div data-bbox="844 1194 1114 1222" style="text-align: right;"> <p>Cci: W. Brito – INTECH PLC</p> </div> </div>		

Please Transfer to Account of:
Bank: Amerant Bank
Address: 220 Alhambra Circle, Coral Gables,
Florida 33134, USA
ABA: 067010509
Swift: MNBMUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS
C.A.
Account # 8303790106

Subtotal	US\$	62,910.00
Freight	US\$	Incluido
Insurance	US\$	--
IVA 16%	US\$	10,065.60
IGTF 3%	US\$	---
TOTAL	US\$	72,975.60