



## Instrumentos y Equipos C.A

### INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,  
 Caracas, Venezuela 1080  
 Tel: 58-212-9784430, 9784433, 977.7654, 977.6346  
 Fax: 58-212-977.3613  
 E-mail: sales@intech-ie.com  
 RIF J-30615033-1

**Quote #** C-2026-0065  
**Date:** 02/03/2026  
**Customer ID** CHEVRON PETROPIAR

|   |
|---|
| <b>Bill to:</b>   |
| <b>CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY</b>   |
| Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela<br>Att: Cristian Garcia - Depto de Procura<br>Cristian.Garcia@chevron.com |

|   |
|---|
| <b>Ship to:</b>                                 |
| <b>CHEVRON PETROPIAR Warehouse</b><br>Venezuela |

| Sales Rep.    | Your #                                | Our #   | Destiny   | Terms         | Validity |
|---------------|---------------------------------------|---|-----------|---------------|----------|
| N. Carricatti | REQ0561288<br>PP-2026-168<br>PARTE II | C-2026-0065/PL<br>WIDN-20260204/<br>QUO00023093-1 | Venezuela | DDP Petropiar | 30 days  |

| Item | Cant | Description   | Unit Price<br>US\$ | Total<br>US\$ |
|------|------|---|--------------------|---------------|
| 50   | 5    | <p><b>PRESSURE GAUGE MODEL 233.34 WITH CHEVRON LOGO, WIKA PN 50052632</b></p> <p>Process Gauge<br/>           Model: 233.34<br/>           Specifications according to data sheet: APM 02.10<br/>           Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)<br/>           Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)<br/>           Measuring System: Stainless Steel<br/>           Case filling: with<br/>           Nominal size: 4.5"<br/>           Scale range: 0/2000 psi<br/>           Process Connection: 1/2 NPT<br/>           Connector location: lower mount<br/>           Window: laminated safety glass<br/>           Restrictor: stainless steel, D 0.6<br/>           Pointer: adjustable pointer<br/>           Accuracy Class: +/- .5% (ASME B40.100 2A)<br/>           Material pressure element: Measuring System 316L<br/>           Case filling fluid: Glycerine<br/>           Ingress Protection: IP 65<br/>           Dial description:<br/>           Pressure Gauge Standard: US-Standard<br/>           color for 1.scale (outside): black<br/>           dial background: White<br/>           *WIKA®*<br/>           serial number on dial: Serial number *...*<br/>           stop pin on dial: at 6 o'clock<br/>           LOGO CHEVRON 2 COLOURS INCLUDED</p> | \$500,00           | \$2.500,00    |
| 51   | 3    | <p><b>INDUSTRIAL PRESSURE TRANSMITTER MODEL IPT-20, 4000 PSI, WIKA PN 80077702</b></p> <p>Industrial process transmitter IPT-2x with metallic sensor element</p>  | \$6.920,00         | \$20.760,00   |

|    |   |  |            |             |
|----|---|--|------------|-------------|
|    |   | <p>Model: IPT-20<br/> Specifications according to data sheet: PE 86.06<br/> Pressure Range: adjustable with turn down up to 100 : 1<br/> Process connection type: Standard connection with pressure port<br/> Electrical approval: ATEX<br/> Ignition protection type: Ex d - explosion proof<br/> Zone: Zone 1 attached to zone 0 gas [II 1/2G, 2G Ex d IIC T6]<br/> Housing material: Aluminum double chamber<br/> enclosure execution: compact/ IP66/IP67; NEMA 4X<br/> Digital Display: with integrated indicating/adjustment module (side)<br/> Output signal: 4...20 mA, 2-wire, HART<br/> Electrical connection: M20x1,5 / cable gland brass nickel plated (ø6-12mm)<br/> Pressure range: 0 .. .600 bar gauge<br/> Accuracy: 0.1 % of span<br/> process connection form: Gauge connection open<br/> Process connection / wetted parts: Thread 1/2 NPT PN1000, ASME B1.20.1 / 316L<br/> Sealing: without, -40 ... +105°C<br/> Clean specification: without<br/> Filling of sensor: without<br/> Certification sterile processes: without<br/> wetted parts: stainless steel<br/> Certificates/Approvals: with certificate or approval<br/> Unit of outer Scale: psi<br/> Scaling lower value: 0 psi<br/> Scaling high value: 4000,0<br/> Density unit: kg/dm<sup>3</sup><br/> Mounting accessories: Mounting bracket for wall and pipe mounting (stainless steel) (for 2" pipe)<br/> Sensor principle: Thin film<br/> Inspection certificate 3.1 per EN 10204<br/> Certificate type: Inspection certificate acc. to EN 10204 3.1<br/> Certificate Language: English and German<br/> Certificate for: process pressure transmitter<br/> Accuracy: Calibration values listed (traceable to national standards)</p> |            |             |
| 52 | 3 | <p><b>INDUSTRIAL TEMPERATURE TRANSMITTER MODEL TIF50-F WITH T38, WIKA PN 80077701</b></p> <p>TIF50-F, Field housing, Ex d - gas, ATEX/IECEX<br/> Specifications according to data sheet: TE 62.01<br/> display modul: HART® -Slave/ 4...20 mA (Standard modul)<br/> Design / Approval<br/> Field housing, Ex d - gas<br/> Certifications integrated display module: ATEX/IECEX<br/> Aluminium, Single chamber housing<br/> 3 x thread 1/2 NPT<br/> accessories for pipe mounting: Pipe-Mounting kit 2", stainless steel<br/> Transmitter for TIF: T38, Digitaltransmitter, HART®, universal programmable<br/> Digital temperature transmitter T38<br/> with HART-protocol<br/> Specifications according to data sheet: TE 38.01 TBD<br/> Output signal: 4 ... 20 mA, 2-wire-design<br/> Input: configurable by means of software<br/> Measuring range: configurable by means of software<br/> Design: Head<br/> HART revision: HART® 7<br/> Permissible ambient temperature Transmitter: Standard -40...85°C<br/> Configuration: basic configuration (Pt100, 3-wire, 0 ... 150 °C, signalling down scale &lt; 3,6 mA)</p>  | \$4.170,00 | \$12.510,00 |

|    |   |  |            |            |
|----|---|--|------------|------------|
|    |   | <p>Configuration sensor: Pt100<br/> Input configuration: 3-wire<br/> Sensor Configuration: Sensor 1, sensor 2 not available<br/> Drift Detection / Difference: not active<br/> Unit: °C<br/> Measuring range start value - sign: Plus (incl. 0)<br/> Measuring range start value: 0<br/> Measuring range end value - sign: Plus (incl. 0)<br/> Measuring range end value: 150<br/> Transmitter Signalling of error: Down scale (basically for all kinds of errors)<br/> Certificates: Certificate / certificate combinations<br/> Current value for signalling down scale: 3.5 mA (NAMUR down scale)<br/> Current value for signalling up scale: 21.5 mA (NAMUR up scale)<br/> Inspection certificate acc. to EN 10204 3.1<br/> Certificate Language: English and German<br/> Transmitter<br/> Accuracy: 3 test points (start / middle / end of transmitter range)</p> |            |            |
| 53 | 1 | <p><b>BIMETALLIC THERMOMETER MODEL TG53.5Z, WIKA<br/> PN 52969973</b></p> <p>Bimetal thermometer, Process grade according to ASME B40.200<br/> Model: TG53.5Z<br/> Specifications according to data sheet: ATM 53.02<br/> Accuracy Class: +/- 1% of Full Scale (ASME B40.3)<br/> Nominal size: 5"<br/> Connector position: back mount, adjustable<br/> Design of Connection: standard, male thread<br/> Process Connection: 1/2" NPT<br/> Scale Range: 100 °F ... 800 °F<br/> Stem Diameter: 1/4"<br/> Insertion length L1: 6"<br/> Window: laminated safety glass<br/> Dampening: Dampened movement<br/> Ingress Protection: IP 66 / NEMA 4X<br/> Permissible ambient temperature: -40 ... +70 °C<br/> with Serial number<br/> Manufacturer logo: *WIKA®*</p>   | \$590,00   | \$590,00   |
| 54 | 3 | <p><b>BIMETALLIC THERMOMETER MODEL TG53.5Z WITH TAPERED THERMOWELL TW15, WIKA<br/> PN 52969973</b></p> <p>Bimetal thermometer, Process grade according to ASME B40.200<br/> Model: TG53.5Z<br/> Specifications according to data sheet: ATM 53.02<br/> Accuracy Class: +/- 1% of Full Scale (ASME B40.3)<br/> Nominal size: 5"<br/> Connector position: back mount, adjustable<br/> Design of Connection: standard, male thread<br/> Process Connection: 1/2" NPT<br/> Scale Range: 100 °F ... 800 °F<br/> Stem Diameter: 1/4"<br/> Insertion length L1: 4"<br/> Window: laminated safety glass<br/> Dampening: Dampened movement<br/> Ingress Protection: IP 66 / NEMA 4X<br/> Permissible ambient temperature: -40 ... +70 °C<br/> with Serial number<br/> Manufacturer logo: *WIKA®*</p>  | \$1.070,00 | \$3.210,00 |

|      |   |     |  |     |  |     |  |     |  |      |                                      |  |  |
|------|---|-----|--|-----|--|-----|--|-----|--|------|--------------------------------------|--|--|
|      | <p>Threaded Thermowell TW15, solid machined<br/>Specifications according to data sheet: TW 95.15<br/>Head Design: Hexagon<br/>Thermowell Style: Tapered<br/>Unit of Measure: Imperial (inch)<br/>Process thread [P or E]: 1" NPT<br/>Instrument connection [N]: 1/2 NPT female<br/>Insertion length [U]: 2.5 inch<br/>Head Length: 1.75"<br/>Bar Material: Stainless steel 316/316L<br/>Bore size [B or d1]: 0.260 inch (6.6 mm)<br/>Root diameter [Q]: 1.063 inch<br/>Tip diameter [V or F3]: 0.750 inch<br/>Bore depth / stem length (US): 4,000 inch<br/>Tip thickness [Tt]: 0.250 inch (6.4 mm)</p>   |     |  |     |  |     |  |     |  |      |                                      |  |  |
|      | <p><b>Delivery Time</b><br/><b>Item 50, 53, 54: 8 – 10 Weeks ARAD</b><br/><b>Item 51, 52: 13 – 15 Weeks ARAD</b></p> <p><b>Partial Shipments allowed (WIKA)</b></p> <p><b>Payment Terms</b><br/>• <b>100% Net 30 days delivery time</b></p> <p><b>Packing</b><br/>Material will be Securely packed in wooden crates suitable for air freight and export.</p> <p><b>Volume &amp; Weight (to be reconfirmed)</b><br/><b>To be advised – Aprox 146 Lbs</b></p> <p><b>General Warranty:</b><br/>Brand warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p><b>Project Cancellation charges:</b></p> <table data-bbox="243 1386 893 1711"> <tr> <td>15%</td> <td>Up to submittal of Engineering &amp; Design Drawings and Documents</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering &amp; Design Drawings and Documents</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> <tr> <td>75%</td> <td>Within two weeks of production release</td> </tr> <tr> <td>100%</td> <td>Two weeks after production commences</td> </tr> </table> | 15% | Up to submittal of Engineering & Design Drawings and Documents | 25% | After submittal of Engineering & Design Drawings and Documents | 50% | After material order placement and before production commences | 75% | Within two weeks of production release | 100% | Two weeks after production commences |  |  |
| 15%  | Up to submittal of Engineering & Design Drawings and Documents  |     |  |     |  |     |  |     |  |      |                                      |  |  |
| 25%  | After submittal of Engineering & Design Drawings and Documents  |     |  |     |  |     |  |     |  |      |                                      |  |  |
| 50%  | After material order placement and before production commences  |     |  |     |  |     |  |     |  |      |                                      |  |  |
| 75%  | Within two weeks of production release  |     |  |     |  |     |  |     |  |      |                                      |  |  |
| 100% | Two weeks after production commences  |     |  |     |  |     |  |     |  |      |                                      |  |  |
|      | <p><b>NOTAS:</b></p>  |     |  |     |  |     |  |     |  |      |                                      |  |  |
|      | <p><b>CONDICIONES DE PAGO</b></p> <p><b><u>COMPONENTE IMPORTADO</u></b></p> <p><i>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</i></p>  |     |  |     |  |     |  |     |  |      |                                      |  |  |

|  |   |  |  |
|--|---|--|--|
|  | <p>AMERANT BANK (in US\$)<br/>220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134<br/>CUENTA NUMERO <b>8303790106</b><br/>BENEFICIARIO <b>INTECH INSTRUMENTOS Y EQUIPOS C.A.</b><br/>ABA 067010509<br/>SWIFT MNBMUS33</p> <p><b><u>COMPONENTE NACIONAL (IVA)</u></b></p> <p>En BOLIVARES (Bs.) mediante transferencia bancaria</p> <p>Banco Mercantil<br/>Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A.<br/>- <b>0105-0011-73-1011-50499-5</b></p>   |  |  |
|  | <p><b>OTRAS CONDICIONES</b></p> <ol style="list-style-type: none"> <li>1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos</li> <li>2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web <a href="http://www.bcv.org.ve">www.bcv.org.ve</a> y deberá ser cancelado a la tasa oficial del día de pago o de la retención correspondiente</li> <li>3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.</li> <li>4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente</li> <li>5. Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta</li> <li>6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22.</li> </ol> <p><b>In Tech</b><br/>Instrumentos y Equipos, C.A.<br/>RIF: J-30615033-1<br/>NIT: 0096996004</p>  <p>Cci: W. Brito – INTECH PLC</p> |  |  |

Please Transfer to Account of:  
Bank: Amerant Bank  
Address: 220 Alhambra Circle, Coral Gables,  
Florida 33134, USA  
ABA: 067010509  
Swift: MNBMUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS  
C.A.  
Account # 8303790106

|                  |             |                  |
|------------------|-------------|------------------|
| <b>Subtotal</b>  | <b>US\$</b> | <b>39,570.00</b> |
| <b>Freight</b>   | <b>US\$</b> | <b>Incluido</b>  |
| <b>Insurance</b> | <b>US\$</b> | <b>--</b>        |
| <b>IVA 16%</b>   | <b>US\$</b> | <b>6,331.20</b>  |
| <b>IGTF 3%</b>   | <b>US\$</b> | <b>---</b>       |
| <b>TOTAL</b>     | <b>US\$</b> | <b>45,901.20</b> |