



Instrumentos y Equipos C.A

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
 Caracas, Venezuela 1080
 Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
 Fax: 58-212-977.3613
 E-mail: sales@intech-ie.com
 RIF J-30615033-1

Quote # **C-2024-0317**
 Date: **01/10/2024**
 Customer ID **CHEVRON**
PETROINDEPENDENCIA

Bill to:
CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chuao, Caracas 1060, Venezuela Att: Jorgelis Rincon - Depto de Procura Jorgelis.Rincon1@chevron.com

Ship to:
CHEVRON PETROINDEPENDENCIA Warehouse Edo Anzoategui, Venezuela

Sales Rep.	Your #	Our #	Destiny	Terms	Validity
N. Carricatti	VEN-RFQ-PI053	C-2024-0317/PL-WIDN-202409-01-QUO00017992-1	Venezuela	DDP Jose complex	30 days

Item	Cant	Description	Unit Price US\$	Total US\$
1	16	<p>PRESSURE TRANSMITTER MODEL IPT-20, 0-800 PSI, 4...20 mA, 2-wire, HART, ASME B16.5 1 1/2" – 300# RF, WIKA PN 80068288</p> <p>Industrial process transmitter IPT-2x with metallic sensor element Model: IPT-20 Specifications according to data sheet: PE 86.06 Pressure Range: adjustable with turn down up to 100 : 1 Process connection type: Standard connection with pressure port Electrical approval: ATEX, IECEx, Ignition protection type: Ex d - explosion proof Zone: Zone 1 attached to zone 0 gas [Ex d IIC T1...T6 Ga/Gb] Housing material: Aluminum single chamber enclosure execution: compact/ IP66/IP67; NEMA 4X Digital Display: with integrated indicating/adjustment module (top) Output signal: 4...20 mA, 2-wire, HART Electrical connection: ½NPT / plug Pressure range: 0...100 bar gauge Accuracy: 0.1 % of span process connection form: Gauge connection open Process connection / wetted parts: Diaphragm seal Sealing: without Clean specification: without Filling of sensor: without Certification sterile processes: without wetted parts: stainless steel Unit of outer Scale: psi Scaling lower value: 0 psi Scaling high value: 800,0 Density unit: kg/dm³ Sensor principle: Thin film</p>	\$5.260,00	\$84.160,00

		<p>Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: 10 feet capillary; stainless steel System fill fluid: KN 2 Silicone oil for general applications Vacuum service: Basic Service according to Technical Information IN 00.25 Process temperature min.: + 21°C (room temperature) Process temperature max.: + 90°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C diameter of capillary: ID 2mm (3x0.5 mm) Diaphragm seal, flange type, flush diaphragm Specifications according to data sheet: DS 99.27 Diaphragm seal: Model 990.27 Diaphragm seal: Model 990.27 Process connection standard: following ASME B16.5 Process connection: 1 1/2" Nominal pressure rating: Class 300 Sealing face: RF 125...250 AA Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Sealing face material: Stainless steel 1.4404 (316L); UNS S31603 Label: WIKA standard without / with Tag-number</p>		
2	8	<p>TEMPERATURE TRANSMITTER MODEL TIF50-I, 0-150 C, 4...20 mA, 2-wire, HART, 1/2" NPT, WIKA PN 80068290</p> <p>TIF50-I, Field housing, Ex i - gas/dust, ATEX/IECEX Specifications according to data sheet: TE 62.01 display modul: HART® -Slave/ 4...20 mA (Standard modul) Design / Approval Field housing, Ex i - gas/dust Certifications integrated display module: ATEX/IECEX Aluminium, Single chamber housing 3 x thread 1/2 NPT Transmitter for TIF: T38, Digitaltransmitter, HART®, universal programmable HART® temperature transmitter T38 Specifications according to data sheet: TE 38.01 TBD Output signal: 4 ... 20 mA, 2-wire-design Input: configurable by means of software Measuring range: configurable by means of software Design: Head Explosion protection: ATEX/IECEX Ignition protection type: Ex ia Other approvals / certificates: Without SIL-Statement: suitable for SIL applications (up to SIL2, SIL3 redundant) HART revision: HART® 7 Permissible ambient temperature Transmitter: Standard -40...85°C Configuration: basic configuration (Pt100, 3-wire, 0 ... 150 °C, signalling down scale < 3,6 mA) Configuration sensor: Pt100 Input configuration: 3-wire Sensor Configuration: Sensor 1, sensor 2 not available Drift Detection / Difference: not active Unit: °C Measuring range start value - sign: Plus (incl. 0) Measuring range start value: 0 Measuring range end value - sign: Plus (incl. 0) Measuring range end value: 150 Transmitter Signalling of error: Down scale (basically for all kinds of errors)</p>	\$2.200,00	\$17.600,00

		<p>Current value for signalling down scale: 3.5 mA (NAMUR down scale) Current value for signalling up scale: 21,5 mA (NAMUR up scale) Signaling if ambient temperature is out of range: Down scale Number of Operation Instructions: 1 pcs. per device Standard packaging – head transmitter (6 pcs per unit) – 1 Instruction per device (6x)</p>		
3	34	<p>PRESSURE GAUGE WITH SEAL MODEL 232.34 & 990.34, 0-300 PSI, DIAL 4.5 ", 1/2" NPT SS 316L SEAL MATERIAL, WIKA PN 80068291</p> <p>Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0/300 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: acrylic (PMMA) Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* serial number on dial: Serial number *...* QR code with extended serial number on dial stop pin on dial: at 6 o'clock Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 7 Glycerine; FDA Process temperature min.: + 21°C (room temperature) Process temperature max.: + 80°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Welded design, threaded process connection Specifications according to data sheet: ACS L990.34 (ACS 99.12) Diaphragm seal: Model 990.34 Threaded connection: 1/2" NPT male Nominal pressure rating: PN 160 Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Diaphragm diameter: 2 in (52 mm) Label: WIKA standard without / with Tag-number</p>	\$1.420,00	\$48.280,00
4	9	<p>PRESSURE GAUGE WITH SEAL MODEL 232.34 & 990.34, 0-600 PSI, DIAL 4.5 ", 1/2" NPT SS 316L SEAL MATERIAL, WIKA PN 80068292</p> <p>Process Gauge Model: 232.34</p>	\$1.420,00	\$12.780,00

		<p>Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0/600 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: acrylic (PMMA) Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* serial number on dial: Serial number *...* QR code with extended serial number on dial stop pin on dial: at 6 o'clock Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 7 Glycerine; FDA Process temperature min.: + 21°C (room temperature) Process temperature max.: + 80°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Welded design, threaded process connection Specifications according to data sheet: ACS L990.34 (ACS 99.12) Diaphragm seal: Model 990.34 Threaded connection: 1/2" NPT male Nominal pressure rating: PN 160 Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Diaphragm diameter: 2 in (52 mm) Label: WIKA standard without / with Tag-number</p>		
5	9	<p>BIMETALIC THERMOMETER WITH TAPERED THERMOWELL MODEL TG53.5Z & TW10, 0-250 F, DIAL 5 " , 1/2" NPT, 12" LENGTH, ASME B16.5 1 1/2" – 300# RF (TW) , WIKA PN 52968504-80068293</p> <p>Bimetal thermometer, Process grade according to ASME B40.200 Model: TG53.5Z Specifications according to data sheet: ATM 53.02 Accuracy Class: +/- 1% of Full Scale (ASME B40.3) Nominal size: 5" Connector position: back mount, adjustable Design of Connection: standard, male thread Process Connection: 1/2" NPT Scale Range: 0 °F ... 250 °F Stem Diameter: 1/4" Insertion length L1: 12" Window: laminated safety glass Ingress Protection: IP 66 / NEMA 4X Permissible ambient temperature: -40 ... +70 °C</p>	\$1.880,00	\$16.920,00

		<p>with Serial number Manufacturer logo: *WIKA®*</p> <p>Flanged Thermowell TW10, solid machined Specifications according to data sheet: TW 95.10 Welding Options: Full penetration welded Thermowell Style: Tapered Unit of Measure: Imperial (inch) Flange Size: ASME 1 1/2 inch Pressure Rating: Class 300 Flange Face: RF (Raised face) Instrument connection [N]: 1/2 NPT female Pipe Sched. /Intern.Nozzle Dia.: Schedule 40 (Standard N.A) Insertion length [U]: 10.0 inch Head Length: 2.25 inch Flange Material: Stainless steel 316/316L Bar Material: Stainless steel 316/316L Bar diameter [Bd or F2]: 30 mm Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 1.063 inch Tip diameter [V or F3]: 0.750 inch Bore depth / stem length (US): 12,000 inch Tip thickness [Tt]: 0.250 inch (6.4 mm) Model: TW10</p>		
6	9	<p>RTD THERMOMETER WITH TAPERED THERMOWELL MODEL TR10-B & TW10, 1/2" NPT, -196 TO 600 C, ASME B16.5 1 1/2" – 300# RF (TW) , WIKA PN 80068294</p> <p>TR10-B RTD assembly for additional thermowell Specifications according to data sheet: TE 60.02 1xPt100, 3-wire Class B, IEC 60751 Temperature range of selected class: -196...+600°C Head / housing: KN4-A, Aluminum, screwed cover Cable entry: Thread (female) Thread size cable entry: 1/2 NPT Transmitter: Without (with terminal block) Connection to neck tube: 1/2 NPT Neck tube: Nipple-Union-Nipple Thread size: 1/2 NPT Neck tube material: Stainless steel 316 Neck length [MH/N]: 150 mm (approx. 6 inch) Insertion length [A] : 367 mm Diameter measuring insert: 6 mm Sheath material measuring insert: Stainless steel 316L (1.4404) Gasket: Without Measuring insert length (spare) [I5]: 549 mm Flanged Thermowell TW10, solid machined Specifications according to data sheet: TW 95.10 Welding Options: Full penetration welded Thermowell Style: Tapered Unit of Measure: Metric (mm) Flange Size: ASME 1 1/2 inch Pressure Rating: Class 300 Flange Face: RF (Raised face) Instrument connection [N]: 1/2 NPT female Pipe Sched. /Intern.Nozzle Dia.: WIKA (Standard Germany) Insertion length [U]: 313 mm</p>	\$2.340,00	\$21.060,00

	<p>Head Length: 57 mm Flange Material: Stainless steel 316/316L Bar Material: Stainless steel 316/316L Bar diameter [Bd or F2]: 30 mm Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 25 mm Tip diameter [V or F3]: 19 mm RTD / TC / Thermometer Assembly: TR10-B RTD assembly for additional thermowell Bore depth / stem length (US): 363 mm Tip thickness [Tt]: 0.250 inch (6.4 mm) Model: TW10</p>												
	<p>Delivery Time ARAD/AROC, Item 1: 16 – 19 weeks Item 2,5,6: 10 – 12 weeks Item 3, 4: 15 – 16 weeks</p> <p>Payment Terms 50% Prepayment with P/O 50% 30 days NET</p> <p>Packing Material will be Securely packed in wooden crates suitable for air freight and export. Volume & Weight (to be reconfirmed) To be advised – Aprox 1275 Lbs</p> <p>General Warranty: Our brands warrants its products to be free from defects in material and/or workmanship for a period of 18 months after delivery or 12 months from installation, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall manufacturer's be liable for damages in excess of the amount paid by the purchaser.</p> <p>Project Cancellation charges:</p> <table border="0"> <tr> <td>15%</td> <td>Up to submittal of Engineering & Design Drawings and Documents (when applicable)</td> </tr> <tr> <td>25%</td> <td>After submittal of Engineering & Design Drawings and Documents (when applicable)</td> </tr> <tr> <td>50%</td> <td>After material order placement and before production commences</td> </tr> <tr> <td>75%</td> <td>Within two weeks of production release</td> </tr> <tr> <td>100%</td> <td>Two weeks after production commences</td> </tr> </table>	15%	Up to submittal of Engineering & Design Drawings and Documents (when applicable)	25%	After submittal of Engineering & Design Drawings and Documents (when applicable)	50%	After material order placement and before production commences	75%	Within two weeks of production release	100%	Two weeks after production commences		
15%	Up to submittal of Engineering & Design Drawings and Documents (when applicable)												
25%	After submittal of Engineering & Design Drawings and Documents (when applicable)												
50%	After material order placement and before production commences												
75%	Within two weeks of production release												
100%	Two weeks after production commences												
	<p>NOTAS:</p>												
	<p>CONDICIONES DE PAGO</p> <p><u>COMPONENTE IMPORTADO</u></p> <p><i>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</i></p> <p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134 CUENTA NUMERO 8303790106 BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A.</p>												

	<p>ABA 067010509 SWIFT MNBMUS33</p> <p><u>COMPONENTE NACIONAL (IVA)</u></p> <p>En BOLIVARES (Bs.) mediante transferencia bancaria</p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. – 0105-0011-73-1011-50499-5</p>		
	<p>OTRAS CONDICIONES</p> <ol style="list-style-type: none"> 1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos 2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y debera ser cancelado a la tasa oficial del día de pago o de la retención correspondiente 3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes. 4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente 5. Aporte SOCIAL: Esta Incluido en los precios y forma parte de la Oferta 6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22. 7. En caso de requerirse algún Tipo de Fianza de Anticipo, los Gastos de dicha Fianza serán reembolsables (en la moneda de su contratación) y por cuenta del Cliente CHEVRON, una vez recibidos los materiales en su almacén. <div style="display: flex; justify-content: space-between; align-items: center; margin-top: 20px;"> <div data-bbox="316 1381 581 1491" style="text-align: center;"> <p>In Tech Instrumentos y Equipos, C.A. RIF: J-30615033-1 NIT: 0096996004</p> </div> <div data-bbox="613 1367 889 1528" style="text-align: center;">  </div> </div>		

Please Transfer to Account of:
Bank: Amerant Bank
Address: 220 Alhambra Circle, Coral Gables,
Florida 33134, USA
ABA: 067010509
Swift: MNBMUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS
C.A.
Account # 8303790106

Subtotal	US\$	200,800.00
Freight	US\$	Incluido
Insurance	US\$	--
IVA 16%	US\$	32,128.00
IGTF 3%	US\$	---
TOTAL	US\$	232,928.00