

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
Caracas, Venezuela 1080
Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
Fax: 58-212-977.3613
E-mail: sales@intech-ie.com
RIF J-30615033-1

Quote # **C-2024-0172**
Date: **20/08/24**
Customer ID **CHEVRON PETROPIAR**

Bill to:
<p>CHEVRON GLOBAL TECHNOLOGY SERVICES COMPANY Av. Ppal La Estancia, Centro Banaven, Torre D, Piso 7, Chua, Caracas 1060, Venezuela Att: Javier Hernandez - Procura Javier.Hernandez@chevron.com</p>

Ship to:
<p>CHEVRON PETROPIAR Warehouse Jose Complex, Edo Anzoategui, Venezuela</p>

Sales Rep.	Your #	Our #	Destiny	Terms	Validity
L. Zuniga	Email	C-2024-0172 / PL	Venezuela	DDP Jose complex	30 days

Item	Cant	Description	Unit Price US\$	Total US\$
1	1	<p>WIKA DUAL CHAMBER LEVEL SYSTEM – Redundant BNA/DU-2"/300/RF-M1524-L/CS 60x2.77/60x2,77-MRF-ZTSS50x225mm, SS TAG 10-LIT-322</p> <p>Magnetic Level Gauge Type BNA-SD00 Pressure: 580 psi ; Temp.: -15°F...580 °F; Fluid density: Wter. HC Liquid Design code: ASME B31.3 Chamber dimensions: OD 60.3 x 2.77 mm (2" Sch. 10S) Duo stainless steel 316/316L (EN 1.4401/1.4404) Process connection: 316SS Flange ASME B16.5 2" 300# Form RF Distance C-to-C: 1524 mm Measuring range: 1524 mm Chamber end top: Flat Cap w/ 3/4" NPT Vent & Plug Chamber end bottom: 300# Slip on Flange and Blind Mating Flange w/ 3/4" NPT Drain & Plug Vent connection: Butt weld end 3/4" Drain connection: Butt weld end 3/4" Float: 50 x 225mm, SS Dampening element: Dampening spring, bottom, with cover Gasket(s): Spiral wound type, SS 316L/Graphite Bolting: UNC series, carbon steel A193 Gr. B7 HDG / A194 Gr. 2H HDG Top stand-off (T): 100 mm Bottom stand-off (U): 250 mm Nameplate: Stainless steel laser printed Includes Bottom: Mag Trap -316ss/ CS construction -316SS 2" x 2" Tee with 2" CS 300# RFWN Flange -Bottom: CS 2" 300# RFWN with blind mating flange & 1/2" NPT Drain and Plug</p> <p>Dual Chamber (DUplus) Sidechamber: OD 60.3 x 2,77 mm (2" Sch. 10S) Location of secondary chamber: 3 o'clock (right side of MLG chamber) Process connection GT: CS Flange ASME B16.5 2" 300# Form RF Distance between chambers center lines: 200 mm Radar connection stand-off: 254 mm Side chamber bottom stand-off: 254 mm Insertion external sensor: With MRF-M1524 Level Indicator for Magnetic Level Gauge Type BMD-FA Measuring range: 1524 mm Housing material: Aluminum anodized Indicating elements: Stainless steel flaps Red & white Graduated scale: Aluminum engraved Graduation unit: inch</p>	27,630.00	27,630.00

	<p>W/RADAR Transmitter FX81.FADACDHXANAM eID: US34478045 TDR sensor for continuous level and interface measurement of liquids Scope F : USA Approval A : FM (NI) CL I, II, III DIV2, GP ABCDFG Version / Material D : Exchangeable cable (ø2mm) with centering weight / 316 Probe : mounted Length (from seal surface) : 76.000 inch Length of rigid part : 3.937 inch Dimensions centering weight (diameter / height) 1.77in / 1.18in (for 2" Schedule 40/80 and 3" Schedule 80/160) Process fitting / Material AC : Flange 2" 300lb RF, ASME B16.5 / 316/316L Seal / Second line of defense / Process temperature D : FFKM (Kalrez 6375) / without / -20...+150°C Electronics H : Two-wire 4 ... 20 mA/HART Supplementary electronics X : with Overvoltage protection of the supply cable 24 VDC , Model USB63-48.N Housing / Protection A : Aluminum single chamber / IP66/IP68 (0.2bar) Cable entry / Connection N : ½NPT / Blind plug Display/Adjustment module PLICSCOM A : mounted Certificates M : Yes Certificate / Standard : (C) Material test report – traceable (EN 10204 type 3.1 + NACE MR0175 + NACE MR0103) PMI test : RFA (positive material identification) incl. 3.1 inspection certificate Supply certificates : with goods Operating instructions : EN - English Number of operating instructions : 2 Measurement loop identification label : of Stainless Steel Customer-specific adjustment : Yes - Unit : inch - 100 % (distance from seal surface) : 10.000 inch - 0 % (distance from seal surface) : 79.000 inch Linearization : No Min. process pressure in bar : -1.000 Max. process pressure in bar : 40.0</p>		
	<p>Delivery Time 14 – 16 weeks ARAD (after receive Approval drawings) and payment</p> <p>Payment Terms Net 30 days Delivery DDP Jose Complex</p> <p>Volume & Weight Weight and Volume to be advised IPPC Stamped Sea Freight Export Wood Crate</p>		
	<p>General Warranty: WIKA warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. WIKA's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall WIKA be liable for damages in excess of the amount paid by the purchaser.</p> <p>Project Cancellation charges: valid for individual Tag as well as complete P.O.</p> <p>15% Up to submittal of Engineering & Design Drawings and Documents</p> <p>25% After submittal of Engineering & Design Drawings and Documents</p> <p>50% After material order placement and before production commences</p> <p>75%</p>		

		<p>Within two weeks of production release</p> <p>100% Two weeks after production commences</p>		
		NOTAS:		
		<p>CONDICIONES DE PAGO</p> <p><u>COMPONENTE IMPORTADO</u></p> <p><i>En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a la siguiente cuenta</i></p> <p>AMERANT BANK (in US\$) 220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134 CUENTA NUMERO 8303790106 BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A. ABA 067010509 SWIFT MNBMUS33</p> <p><u>COMPONENTE NACIONAL (IVA)</u></p> <p><i>En BOLIVARES (Bs.) mediante transferencia bancaria</i></p> <p>Banco Mercantil Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A. – 0105-0011-73-1011-50499-5</p>		
		<p>OTRAS CONDICIONES</p> <ol style="list-style-type: none"> 1. Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos 2. El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y deberá ser cancelado a la tasa oficial del día de pago o de la retención correspondiente 3. Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes. 4. INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Equipos de Laboratorio, solo suministrará garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente 5. Aporte SOCIAL 3%: Esta Incluido en los precios y forma parte de la Oferta 6. Las empresas Mixtas no están sujetas a Impuesto a las Grandes Transacciones Financieras (IGTF), Por lo tanto, las facturas donde CHEVRON compra bienes o contrata servicios por cuenta de estas, no están sujetas a la percepción del IGTF. Todo ello con base en el Artículo 9, Numeral 3 de la Ley del IGTF (Gaceta Oficial Nro 6.687 Extraordinario de fecha 25/02/22. Lation charges 7. En caso de requerirse algún Tipo de Fianza de Anticipo, los Gastos de dicha Fianza serán reembolsables (en la moneda de su contratación) y por cuenta del Cliente CHEVRON, una vez recibidos los materiales en su almacén. <p>Cci: W. Brito – INTECH PLCRZ</p>		

--	--	--	--	--

Please Transfer to Account of:
Bank: Amerant Bank
Address: 220 Alhambra Circle, Coral Gables,
Florida 33134, USA
ABA: 067010509
Swift: MNBMUS33

Beneficiary: INTECH INSTRUMENTOS Y EQUIPOS
C.A.
Account # 8303790106

Subtotal	US\$	27,630.00
Freight	US\$	Incluido
Insurance	US\$	--
IVA 16%	US\$	4,420.80
IGTF 3%	US\$	---
TOTAL	US\$	32,050.80