



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
 Suite 130, Sunrise, FL 33323
 Tel: 954-302-3187, 315-4781
 Fax: 954-838-7746
 E-mail: ibicorp@intech-ie.com
 Tax Certificate No. 16-8012998465-1

Quote #

IBI-2025-0032Parte2Rev1

Date:

Oct 28th, 2025

Customer ID

Cerveceria Polar

Bill To:
<p>Cervecería Polar, C.A. RIF: J-00006372-9 Av. 2da De Los Cortijos De Lourdes, Local Planta Polar, Urb. Los Cortijos De Lourdes. Caracas 1071. Atn: Anabella Rueda Telf.: 0412-5870742 Correo: anabella.rueda@empresapolar.com</p>

Ship To:
<p>El material sera retirado por cliente.</p>

Your #	Our #	Sales Rep	Incoterms -EXW	SHIP VIA	Terms	Validity
6004833337	IBI-2024-0077/PL	N. Carricatti	Austria	Pick up	See below	60 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	6	Pc	<p>EVALUATION UNIT mPDS 5 WITH CPU BOARD, ANTON PAAR PN 47839</p> <p>Evaluation unit for multiple Anton Paar Sensors (density, sound velocity, CO2, viscosity, refractive index, ...) Powerful embedded module with color touch screen and comfortable graphical user interface</p> <p>Scope of delivery 1 Pcs. basic unit (Touch screen, housing, mounting kit) 1 Pcs. CPU board 4 Pcs. blind covers 2 Pcs. mounting brackets 1 Pcs. USB flash drive 4 GB 1 Pcs. mPDS 5 instruction manual (DE/EN/FR/SP)</p> <p>Technical specifications CPU board: 2 Pcs. USB, LAN (optional Davis 5), CAN Open for Smart Sensor 999 products with alarms, adjustments, etc. available Graphical and numerical output fields Mount in switch cabinet or stainless steel housing Customized application programs for concentration of numerous liquids stored in the instrument Not for use in hazardous areas</p>	\$7.263,00	\$43.578,00
2	2	Pc	<p>DENSITY SENSOR L-Dens 7500 VERSION HAS, ANTON PAAR PN 178001</p> <p><u>NOTA: Requiere de un adaptador de flujo</u></p> <p>Highly accurate process sensor for density and concentration</p>	\$12.074,00	\$24.148,00



		<p>measurement. The compact design enables inline or bypass installation with minimal integration effort. The robust oscillating U-tube measuring principle has no moving parts and is maintenance-free, with low operating costs.</p> <p>Scope of delivery 1 Pcs. Process density sensor L-Dens 7500 HAS 1 Pcs. Instruction Manual 1 Pcs. Adjustment Report</p> <p>Technical specifications - Process density: max. 2000 kg/m³ - Process temperature: -40 to 125 °C (145 °C for max. 30 min) - Process pressure absolute: max. 50 bar - Flow rate: 100 to 500 L/h - Accuracy density in the adjusted range: 0.05 kg/m³ - Repeatability density: 0.01 kg/m³ - Accuracy temperature in the adjusted range: 0.1 °C - Wetted part: Hastelloy C-276 - Inner diameter of tube: 6.3 mm - Ambient temperature: -40 °C to +70 °C without Pico 3000 -40 °C to +70 °C* with Pico 3000 -20 °C to +60 °C with Pico 3000 and HMI * Pico 3000 PROFINET IO, EtherNet/IP, Modbus TCP: 60 °C - Degree of protection: IP 66 / 67 / NEMA 4X</p>		
		<p>Delivery Time 6-7 weeks after receipt of order and payment (subject to changes)</p> <p>The delivery time of the items offered is subject to changes generated by events outside the company's control, such as:</p> <ol style="list-style-type: none"> 1. Climatic phenomena that do not allow the transport of raw material to the factory, local transport abroad of the manufactured material and/or international transport of the product. 2. Normal functioning of Venezuelan and/or foreign customs. 3. Disruption of public order in the country of origin, country of transit and/or final country. 4. Criminal and/or terrorist acts. 5. Any other event considered major force. <p>Payment terms 100% with purchase order</p> <p>Volume & Weight Weight / Volume to be advised</p>		

PLEASE TRANSFER TO OUR ACCOUNT AT:
 Branch Banking & Trust Co.
 450 North Pine Island
 Plantation, FL 33324
 Account #: 0140953040
 ABA# 053-101-121
 Routing/Transit Number: 2631-9138-7
 Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	67,726.00
Freight	US \$	Included
Insurance	US \$	Included
Docs.	US \$	Included
TOTAL	US \$	67,726.00