



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
 Suite 130, Sunrise, FL 33323
 Tel: 954-302-3187, 315-4781
 Fax: 954-838-7746
 E-mail: ibicorp@intech-ie.com
 Tax Certificate No. 16-8012998465-1

Quote # IBI-2025-0149-CI
Date: Nov 19th, 2025
Customer ID Cerveceria Polar - BCNA

Bill To:
Cervecería Polar, C.A. RIF: J-00006372-9 Av. 2da De Los Cortijos De Lourdes, Local Planta Polar, Urb. Los Cortijos De Lourdes. Caracas 1071. Atn: Gelimar Herrera Telf.: 0212-2028534 Correo: gelimar.herrera@empresaspolar.com

Ship To:
El material sera retirado por broker del cliente en Austria

Your #	Our #	Sales Rep	Incoterms - EXW	SHIP VIA	Terms	Validity
Budgetary	IBI-2024-0077/PL IBI-2025-0032Rev2/3	N. Carricatti	Austria	Pick up	See below	30 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	8	Pc	EVALUATION UNIT mPDS 5 WITH CPU BOARD, ANTON PAAR PN 47839 Evaluation unit for multiple Anton Paar Sensors (density, sound velocity, CO2, viscosity, refractive index, ...) Powerful embedded module with color touch screen and comfortable graphical user interface Scope of delivery 1 Pcs. basic unit (Touch screen, housing, mounting kit) 1 Pcs. CPU board 4 Pcs. blind covers 2 Pcs. mounting brackets 1 Pcs. USB flash drive 4 GB 1 Pcs. mPDS 5 instruction manual (DE/EN/FR/SP) Technical specifications CPU board: 2 Pcs. USB, LAN (optional Davis 5), CAN Open for Smart Sensor 999 products with alarms, adjustments, etc. available Graphical and numerical output fields Mount in switch cabinet or stainless steel housing Customized application programs for concentration of numerous liquids stored in the instrument Not for use in hazardous areas	\$6.930,00	\$55.440,00
2	6	Pc	PROFIBUS DP BOARD mPDS 5, ANTON PAAR PN 97350 Fieldbus board PROFIBUS DP with variable input data block size and output data block size	\$1.040,00	\$6.240,00



			<p>Technical specifications</p> <p>The following functions are available via input - output data blocks of a maximum of 224 bytes each:</p> <p>Read/write product number, measurement values, read/write parameters, status, etc.</p>		
3	5	Pc	<p>DSUB CANopen 9BU CONNECTOR 35°, ANTON PAAR PN 184983</p>	\$97,00	\$485,00
4	2	Pc	<p>DENSITY AND SOUND VELOCITY SENSOR L-Com 5500 Version HAS, ANTON PAAR PN 181263</p> <p><u>NOTA: Requiere de una bomba de adaptacion de flujo</u></p> <p>Combined system for a highly accurate process measurement of density and sound velocity of three-component-mixtures. The compact design enables inline or bypass installation with minimal integration effort.</p> <p>Scope of delivery 1 Pcs. Process-density-sound velocity-sensor L-Com 5500 HAS 1 Pcs. Instruction Manual 1 Pcs. Adjustment Report</p> <p>Technical specifications</p> <ul style="list-style-type: none"> - Process density: max. 2000 kg/m³ - Process temperature: -25 to 125 °C (145 °C for max. 30 min) - Process pressure absolute: max. 50 bar - Flow rate: 100 to 500 L/h - Accuracy density in the adjusted range: 0.05 kg/m³ - Repeatability density: 0.01 kg/m³ - Accuracy temperature in the adjusted range: 0.1 °C - Measurement uncertainty sound velocity: 0.1 m/s - Wetted part: Hastelloy C-276 - Inner diameter of tube: 6.3 mm - Ambient temperature: <ul style="list-style-type: none"> -25 °C to +65 °C without Pico 3000 -25 °C to +55 °C* with Pico 3000 -20 °C to +55 °C* with Pico 3000 and HMI * Pico 3000 PROFINET IO, EtherNet/IP, Modbus TCP: 50 °C - Degree of protection: IP 66 / 67 / NEMA 4X 	\$14.071,00	\$28.142,00
5	4	Pc	<p>L-Sonic 5100 VERSION VG SST L6 CN (CLEANING NOZZLE), ANTON PAAR PN 181501</p> <p>L-Sonic 5100 a highly accurate insertion type sound velocity sensor used for inline concentration measurements or product identification. The sensor is easy to install and continuously monitors the concentration of liquids during production. Smallest deviations are detected immediately.</p> <p>Scope of delivery 1 Pcs. Process sound velocity sensor L-Sonic 5100 VG SST L6 CN 1 Pcs. O-Ring 113x4, EPDM 70</p>	\$10.824,00	\$43.296,00

			1 Pcs. Instruction Manual 1 Pcs. Adjustment Report Technical specifications - Process sound velocity range: 800 to 2500 m/s - Process temperature: -25 to 125 °C (145 °C for max. 30 min) - Process pressure absolute: max. 10 bar - Flange: Varivent G - Flow rate: > 0 to 6 m/s - Repeatability sound velocity: 0.005 m/s - Reproducibility temperature: 0.02 °C - Wetted part: stainless steel 1.4404 - Fork length: 125 mm - Ambient temperature: -25 °C to +65 °C without Pico 3000 -25 °C to +55 °C* with Pico 3000 -20 °C to +55 °C* with Pico 3000 and HMI * Pico 3000 PROFINET IO, EtherNet/IP, Modbus TCP: 50 °C - Degree of protection: IP 66 / 67 / NEMA 4X		
6	80	m	CABLE 2x2x0.22 D7.1 mm PER m FOR CAN BUS PN 94268	\$13,00	\$1.040,00
7	80	m	CABLE 2x2x0.22 D7.1 mm PER m FOR CAN BUS PN 94268	\$13,00	\$1.040,00
8	2	Pc	Inline Pump 300 + adapter VARIVENT® N for L-Dens 7500/L- Com 5500, SST, EPDM PN 244188 Varivent N adapter set with integrated inline pump for easy installation of an L-Dens 7500 or L-Com 5500 process sensor. Scope of delivery 1 Pcs. Inline adapter L-Dens/L-Com with sample pump 1 Pcs. Varivent clamp with nut 2 Pcs. Flat gasket with collar 16.3x6.3 mm EPDM 1 Pcs. O-ring 19.1x1.6 EPDM 70 in adapter 1 Pcs. O-ring 27x1.5 EPDM 70 in adapter 1 Pcs. O-ring 60x3 EPDM 70 in adapter 1 Pcs. O-ring 25x2 EPDM 1 Pcs. Various screws Technical specifications - Connection type: Varivent type N - Wetted parts: 1.4404, WC, SSiC, EPDM - Process temperature: -5 °C to 105 °C (145 °C for max. 30 min) - Process pressure absolute: min. 1 bar; max. 16 bar - Ambient temperature: -5 °C to 60 °C	\$2.915,00	\$5.830,00
			Delivery Time 3-5 weeks after receipt of order and payment (subject to changes) The delivery time of the items offered is subject to changes generated by events outside the company's control, such as:		



INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
 Suite 130, Sunrise, FL 33323
 Tel: 954-302-3187, 315-4781
 Fax: 954-838-7746
 E-mail: ibicorp@intech-ie.com

		<p>1. Climatic phenomena that do not allow the transport of raw material to the factory, local transport abroad of the manufactured material and/or international transport of the product.</p> <p>2. Normal functioning of Venezuelan and/or foreign customs.</p> <p>3. Disruption of public order in the country of origin, country of transit and/or final country.</p> <p>4. Criminal and/or terrorist acts.</p> <p>5. Any other event considered major force.</p> <p>Payment terms 100% with purchase order</p> <p>Volume & Weight Weight / Volume to be advised</p>		
--	--	---	--	--

PLEASE TRANSFER TO OUR ACCOUNT AT:
 Branch Banking & Trust Co.
 450 North Pine Island
 Plantation, FL 33324
 Account #: 0140953040
 ABA# 053-101-121
 Routing/Transit Number: 2631-9138-7
 Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	141,513.00
Freight	US \$	Included
Insurance	US \$	Included
Docs.	US \$	Included
TOTAL	US \$	141,513.00